|INCH-POUND|

MIL-L-29250A(YD)
AMENDMENT 1
9 September 1988
SUPERSEDING
MIL-L-29250A(YD)
28 April 1988

MILITARY SPECIFICATION

LOADING JACK SYSTEM, ISO CONTAINER

This amendment forms a part of MIL-L-29250A(YD), dated 28 April 1988, and is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1 Delete "FED-STD-595 - Colors."

PAGE 4

3.1, line 3: After 8 X 8 X 20, add "and 8'6" X 8 X 20".

PAGE 6

3.9: Delete and substitute:

"3.9 Payload. The ILJS shall transport a 4'3" X 8 X 20, 8 X 8 X 20, or 8'6" X 8 X 20 ISO container with corner fittings conforming to ISO 1161. The payload (container and contents) shall not exceed 25,000 lb gross weight. The center of gravity (CG) of the container may vary longitudinally and laterally as shown in figure 1. The vertical CG shall not exceed 2.5 feet (ft) above the 4'3" X 8 X 20 container floor; 4.0 ft above the 8 X 8 X 20 and 8'6" X 8 X 20 container floor. The design of the ILJS shall be able to accommodate the variable CG. Any test payload shall be in an 8-foot X 20-foot ISO container weighing 25,000 lb with CG located within the cross-hatch area as shown in figure 1."

PAGE 10

3.19.1, line 5: Delete sentences 4 and 5 and substitute "Paint for the finish coat shall conform to MIL-C-46168, Green 383, type IV."

3.21.1, line 2: Delete "No. 37038 in accordance with FED-STD-595" and substitute "37030".

Preparing activity:
Navy - YD

(Project 3950-N022)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:29Z
Check the source to verify that this is the current version before use.