|NOT MEASUREMENT|
|SENSITIVE|

MIL-T-29233A(YD)
5 July 1991
SUPERSEDING
MIL-T-29233
30 November 1984

MILITARY SPECIFICATION

TRAILER, EQUIPMENT, ELEVATING BODY, 4-WHEEL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 4-wheel, 12,000 pound (lb) load capacity, vehicle and equipment transporting trailer with capabilities of lowering and elevating the body (bed) for loading and unloading at ground and loading dock levels.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-V-62038 - Vehicle, Wheeled, Preparation for Shipment and Storage of.

|Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.|

AMSC N/A FSC 2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:23Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-1223 - Nontactical Wheeled Vehicles; Treatment, Painting, Identification Marking, and Data Plate Standards.
MS51336 - Lunette-Coupler, Drawbar, Ring.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which are current on the date of the solicitation (see 6.2).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE J534 - Lubrication Fittings.
SAE J560 - Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
SAE J588 - Turn Signal Lamps.
SAE J1067- Seven Conductor Jacketed Cable for Truck Trailer Connections.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 175 Montrose West Avenue, Coply, OH 44321.)

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:23Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The trailer shall consist essentially of a flatbed surface (body), 4 wheels in tandem with hydraulically operated mechanism that will lower and elevate the body through the wheel spindle center lines to facilitate loading and unloading with a minimum of 12,000 lb capacity. The assembled trailer shall be equipped with electric brakes and a pull type tongue with lunette ring hitch.

3.2 Standard commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3 First article. When specified (see 6.2), the contractor shall furnish a trailer for first article inspection and approval.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification.

3.5 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5.1 System of measurement. The dimensions used in this specification are not intended to preclude the use of the metric system of measurement in the fabrication and production of the material, individual parts, and the finished product, provided form, fit, and function requirements are satisfied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:23Z
Check the source to verify that this is the current version before use.

3.6 Performance. Trailer performance requirements, as specified in 3.6.1 through 3.6.4.1, shall be met by the trailer when fully equipped, with payload distributed over trailer load area, completely serviced, and towed by a towing vehicle over improved and unimproved surfaces (see 6.5).

3.6.1 Towing speed and trailing ability. When transporting the rated payload (see 3.1), while being towed over dry, level, smooth, improved, and prepared hard-surfaced roads at sustained speeds to 55 miles per hour (mph), and over dry unimproved and gravel roads at speeds up to 10 mph, the trailer shall follow the towing vehicle without exceeding the tracking deviations as specified in Federal Motor Carrier Safety Regulation 393.70.

3.6.2 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping. The trailer shall be capable of moving up to an angle of not less than 60 degrees in relation to the towing vehicle without interference between vehicles. The angle shall be measured between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle at the coupling device.

3.6.3 Suspension system. The axles, mounts, accessories, and components of the suspension system shall withstand the imposed loads without evidence of permanent set, part failure, or malfunctioning under the operating conditions specified.

3.6.4 Service brakes. The service brakes of the trailer, in conjunction with the towing vehicle (truck-trailer combination), under all conditions of loading, shall control, decelerate, and stop the vehicle combination in accordance with Federal Motor Carrier Safety Regulation 393.52. Wheel chocks shall be provided for each trailer.

3.6.4.1 Automatic actuation. The trailer shall be equipped with an automatically actuated device to apply the vehicle brakes upon breakaway from the towing vehicle. The breakaway system shall conform to Federal Motor Carrier Safety Regulation 393.43.

3.7 Trailer components.

3.7.1 Suspension. The trailer shall be equipped with an individual wheel suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded as specified in 3.1. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted.

3.7.2 Landing leg. The trailer shall be equipped with a retractable landing leg with cranking handle (rigid or swivel type) permanently installed. The landing leg shall have a vertical range of adjustment. The landing leg shall permit the operator to lower the cargo body to ground level. When the cargo body is in its maximum travel position, the landing leg shall have sufficient vertical adjustment to permit the operator to couple the coupling device to the towing vehicle when the top of the pintle hook of the towing vehicle is 17-3/4 inches above ground level. The landing leg and related parts shall withstand, without permanent deformation, the combined static and dynamic forces due to the proportionate weight of the gross weight and impacts during coupling and uncoupling operations. The landing leg shall operate freely, and

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:23Z
Check the source to verify that this is the current version before use.

shall be protected from malfunctioning by the accumulation of foreign matter. When placed in travel position, the landing leg shall remain positively locked to provide ground clearance in the course of normal towing operations.

3.7.3 Coupling device and towbar. The trailer shall be furnished with a 3-inch lunette ring, in accordance with MS51336 or commercial equivalent. The hitch arm assembly shall permit the trailer body to be lowered to ground level and raised to hauling position without uncoupling the trailer from the towing vehicle. Safety chains shall be provided. Chains shall conform to Federal Motor Carrier Safety Regulation 393.70.

3.7.3.1 Lunette ring height. When specified (see 6.2), the trailer tongue shall be designed to allow for adjustment of lunette ring location for towing vehicle attachment between the range of 16 and 24 inches to top of ring with trailer in level position.

3.7.4 Load leveler. A load leveling system which maintains the trailer body in level position on the transverse plane while being lowered or raised, regardless of weight distribution on the cargo bed, shall be provided.

3.7.5 Dimensions. Trailer dimensions shall be as specified in table I.

TABLE I Dimensions.

Feature	Dimension
Overall length	Minimum practicable
Overall width	96 inches maximum
Body dimensions	
Length (inside)	180 inches minimum
Width (inside)	60 inches minimum
Height (platform to ground)	Minimum practicable
Ground clearance	Maximum practicable

3.7.6 Wheels and tires.

3.7.6.1 Wheels and tires. Trailer shall be equipped with wheels and tires, as specified herein. The wheels and tire ratings shall conform to TRA recommendations for the type and size of tires furnished. Tire and wheel sizes shall be the same for all wheels on the trailer. Tires shall be tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the trailer loaded to specified payload.

3.7.6.2 Spare wheel. A spare wheel or rim shall be mounted on a tire carrier (3.7.6.4).

3.7.6.3 Spare tire. An inflated spare tire shall be mounted on the spare wheel specified in 3.7.6.2. The spare tire shall be of the same size and tread design and of the same ply rating as tires installed on the trailer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:23Z
Check the source to verify that this is the current version before use.

3.7.6.4 Carrier. A carrier for a spare wheel or rim and a tire shall be provided and installed in a readily accessible location. Means shall be provided for securing the tire to the carrier to prevent accidental loss.

3.7.6.5 Tools. Each vehicle shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly and shall include at least a jack, jack handle, and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.7.7 Service brakes. The trailer shall be equipped with a 12-volt (V) direct current (dc), electric brake system wired in accordance with 3.8.2. The systems shall include a manual controller kit for mounting on the dash area of the towing vehicle, a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle, and an emergency breakaway kit. Kits shall be complete with all necessary parts and installation instructions. Unless otherwise specified, the synchronizing controller shall be for use with hydraulic brake system.

3.7.7.1 Parking brakes. Manually applied parking brakes shall be furnished. Parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41. When brake cables are used, the cables shall be corrosion-resistant steel. Provisions shall be made for slack adjustment. Lubrication fittings shall be provided.

3.8 Lighting. The electrical lighting system shall be 12 V dc. All trailer lights, reflectors, and wiring (including electric brakes) shall conform to Federal Motor Carrier Safety Regulations 393.15, 393.19, 393.20, 393.22, 393.23, 393.25, 393.26, and 393.27 through 393.33.

3.8.1 Electrical receptacle. A trailer electrical receptacle with a spring-loaded cover assembly shall be installed on the forward end of the drawbar. The receptacle shall conform to SAE J560, with conductors connected and color-coded as specified in SAE J560.

3.8.2 Brake wiring. Electric brakes shall be wired to the auxiliary circuit of the SAE J560 seven-conductor electrical connector. All wiring shall be properly mounted and secured with clamps. Wiring shall be heavy-wall thermoplastic insulated cable.

3.8.3 Electrical cable. A coiled electrical cable conforming to SAE J1067, with a cable plug at each end conforming to SAE J560, shall be provided. Both plugs shall be equipped with a grip for withdrawing from connector sockets. The cable, when fully extended, shall be not less than 3 feet longer than the distance from the trailer electrical receptacle to the hitch assembly.

3.8.4 Turn signals. Turn signals conforming to SAE J588 shall be furnished.

3.9 Trailer body and frame.

3.9.1 Body and frame construction. The trailer shall be equipped with a body and frame of all steel welded construction, with each main frame member in one

Source: https://assist.dla.mil Downloaded: 20261010-20T22:23Z
Check the source to verify that this is the current version before use.

piece without splices or joints. A sufficient number of full-width crossmembers shall be furnished to assure stability with the trailer fully loaded. All parts of the chassis frame, where welding is required, shall be electrically welded. Body floor and side panels shall be of adequate gage and construction so as to support trailer payload specified without evidence of deformation or permanent set. Tiedown devices shall be welded to the cargo body and located near the center of each side and at each corner.

3.9.2 Tailgate. A tailgate shall be furnished. The tailgate shall be hinged at the floor level of the cargo body. The inside surface of the tailgate shall be covered with safety steel tread plate. The tailgate shall accept a rolling load equal to the specified payload without evidence of deformation or permanent set. The tailgate shall be so constructed that the approach ramp shall be not more than 3/8 inch above the ground surface. The tailgate shall be provided with a latch to hold in an upright or closed position.

3.9.3 Hydraulic pump. The trailer shall be provided with a 12 V dc, electric operated pump hydraulic lift unit. The hydraulic lift unit shall be capable of lowering the cargo body to ground level and raising the cargo body not less than 52 inches with rated payload. The hydraulic lift unit shall elevate the cargo body, with rated payload, from ground level to travel position in not more than 35 seconds. Guards shall be provided to retain the body in travel position. Guards shall be provided to prevent damage to the hydraulic system. The hydraulic pump shall be provided with built-in reservoir and shall be completely sealed to prevent dirt from entering the system. The hydraulic cylinder system shall be provided with external seals to wipe plungers and to clean and keep out foreign matter.

3.9.4 Body mounting. The body (bed) shall be mounted in accordance with manufacturer's standard commercial practice.

3.9.5 Fenders. The vehicle shall have fenders over the wheels. The fenders shall have inside shields and shall have sufficient crown to control mud and water from splashing on the chassis and trailer bed.

3.9.6 Suspension system. The axles, accessories, and components of the suspension system shall exhibit capacity to withstand the imposed loads without evidence of overload, permanent set, part failure or malfunction when the trailer is subjected to the loading and operation conditions specified herein.

3.10 Treatment and painting. Painting and preparation shall be in accordance with MIL-STD-1223. Color shall conform to appropriate color chip of FED-STD-595 (Gloss White No. 17886).

3.10.1 Instruction plates. The trailer shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.10.2 Identification marking. Identification shall be permanently and legibly marked directly on the trailer or on a corrosion-resisting metal plate securely attached to the trailer at the source of manufacturer. Identification

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:23Z
Check the source to verify that this is the current version before use.

shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

3.11 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch (psi) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.12 Servicing and adjusting. Prior to acceptance of the trailer by the Government, the contractor shall service and adjust the trailer for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Proper functioning of all lighting and electrical systems.
c. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

The trailer be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Workmanship.

3.13.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to ensure uniformity of size and shape.

3.13.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.13.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.13.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

Source: https://assist.dla.mil Downloaded: 2026-10-20T22:23Z
Check the source to verify that this is the current version before use.

3.13.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on trailer when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the test of 4.4.1, and the packaging inspection of 4.5.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this document. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. Tests shall be as specified in 4.4.1 through 4.4.5. Failure to pass any of the required tests shall be cause for the Government to refuse acceptance of all trailers until corrective action has been taken. Acceptance shall not constitute a waiver by the Government of its rights under provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 20260410-20T22:23Z
Check the source to verify that this is the current version before use.

4.4.1 Operational test. Each trailer shall be operationally tested to determine compliance with the requirements of this specification.

4.4.2 Road test. The trailer, fully equipped and loaded with rated payload as specified in 3.1, shall be towed at speeds up to 55 mph for a minimum of 50 miles. This distance shall include not less than 10 miles of unimproved or gravel road surfaces within safe operating practices (see 3.6.1).

4.4.3 Turning ability tests. The trailer, with rated payload, shall be tested to verify conformance to the requirements in 3.6.2.

4.4.4 Brake test. With rated payload the trailer shall be subjected to at least two sudden stops from speeds of not less than 20 mph, and retain operating efficiency, to verify conformance to the requirement in 3.6.4.

4.4.5 Function test. The trailer shall be operated through the complete lowering, loading, elevating, unloading cycles, and also in the reverse order, a minimum of 10 complete cycles to verify conformance with 3.9.3. There shall be no minimum time frame for this test.

4.5 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved, packed, and marked in accordance with the requirements of MIL-V-62038 with the level of preservation and packing as specified (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trailer covered by this specification is intended for use loading, transporting and unloading forklifts in areas where there may be no ramps or other facilities to assist. The trailer may be used on improved and unimproved roadways having grades usually found on main and access roads in and about military bases.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first article inspection is required (see 3.3 and 6.4).
d. When adjustable lunette ring hitch is required (see 3.7.3.1).
e. When level of preservation and packing shall be in accordance with MIL-V-62038 is specified (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:23Z
Check the source to verify that this is the currentversion before use.

6.3 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD Federal Acquisition Regulations (FAR) Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract or purchase order requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first article sample, or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Definitions.

6.5.1 Improved road. An improved road is a smooth, hard surfaced road, such as a concrete or asphalt paved highway.

6.5.2 Unimproved road. An unimproved road is an unpaved unstabilized road with an undulating surface, having occasional chuckholes and exposed rocks.

6.6 Subject term (key word) listing.

Cargo
Elevating mechanisms
Equipment

Preparing Activity:

Navy - YD

(Project 2330-N099)

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-29233A(YD)	91-07-05

3. DOCUMENT TITLE

TRAILER, EQUIPMENT, ELEVATING BODY, 4-WHEEL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
A. VILLEGAS	(805) 982-5773	551-5773
c. ADDRESS (Include Zip Code) CIVIL ENGINEERING SUPPORT OFFICE NAVAL CONSTRUCTION BATTALION CENTER PORT HUENEME, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 20260-26122:232
Check the source to verify that this is the current version before use.