| NOT MEASUREMENT |
| SENSITIVE |

MIL-T-29234A(YD)
24 July 1990
SUPERSEDING
MIL-T-29234(YD)
12 November 1984

MILITARY SPECIFICATION

TRUCK, MULTISTOP DELIVERY; WINDOW SERVICE, FOOD, FORWARD CONTROL, 4 BY 2

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of mobile hot and cold food and beverage dispensing truck, powered by a gasoline-engine-driven, four-wheel, two-rear-wheel-drive, forward control chassis, having a gross vehicle weight (gvw) rating of not less than 17,000 pounds (lb).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting, and Starting.

VV-F-800 - Fuel Oil, Diesel.

MILITARY

MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.

MIL-V-62038 - Vehicle Wheeled, Preparation For Shipment and Storage of.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Automotive Vehicles.

MILITARY

MIL-STD-1223 - Nontactical Wheeled Vehicles; Treatment, Painting, Identification Marking and Data Plate Standards.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines: Certification and Test Procedures.
Interstate Motor Carrier Noise Emission Standards.
Motor Vehicle Air Pollution Standards.
Title 40, CFR, Part 204 Subpart B - Noise Emission Standards for Construction Equipment.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852; or CFR, Title 40 should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2. Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which is current on the date of the solicitation (see 6.2).

ASTM

ASTM B 167 - Stainless and Heat Resisting Chromium Nickel Steel, Plate, Sheet, and Strip.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices

SAE J534 - Lubrication Fittings.
SAE J537 - Storage Batteries (DoD adopted).
SAE J551 - Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
SAE J588 - Turn Signal Lamps.
SAE J589 - Turn Signal Switch.
SAE J590 - Turn Signal Flashers.
SAE J688 - Truck Ability Prediction Procedure (DoD adopted).

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

STATE OF CALIFORNIA

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a four-wheel, two-rear-wheel-drive, gasoline-engine-driven, forward control chassis with integral driver's compartment and enclosed body. The truck shall have gvw rating of not less than 17,000 lb. The truck body shall be equipped with canopy type food service windows and rear access door. The body interior shall be provided with equipment for hot and cold food and beverage dispensing, including food warmer, chest type freezer, cooler storage, serving counter, storage facilities, and electrical power supply system.

3.2 First article. When specified (see 6.2), the contractor shall furnish one complete truck for first article inspection and approval (see 4.2.1 and 6.2).

3.3 Standard truck, components, and accessories. Except as specified in 3.3.1 through 3.3.6, the truck, components, and accessories shall be standard or optional items which meet or exceed the requirements of the specification. All items shall be as represented and rated in the manufacturer's technical data including special or mounted equipment. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representative for selection of truck models and components. Technical data and special drawings necessary to identify the herein required truck and components shall be on file in the engineering offices of the procuring activity prior to delivery of the items. Truck, components, assemblies, and accessories to be provided hereunder are standard or optional commercial products for the purpose of this specification. Such items shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

construed as commercial motor vehicle products, complying with all DoT Federal Motor Vehicle Safety Standards and Regulations applicable, on the date of manufacture, to nonmilitary, nonexport motor vehicle products.

3.3.1 Treatment and painting. As specified by the procuring activity for the appropriate service (see 6.2), treatment and painting shall be in accordance with MIL-STD-1223.

3.3.2 Identification marking and data plates. Identification marking and data plates shall be in accordance with MIL-STD-1223, as required for the Navy. Transportation data plates, conforming to MIL-P-514, type III, composition A or C, shall be furnished and shall be inscribed with all pertinent transportation data, including a silhouette of the truck showing the center of gravity.

3.3.3 Electromagnetic interference characteristics. When specified (see 6.2), the truck shall conform to the electromagnetic characteristic requirements and test limits of SAE J551.

3.3.4 Towing devices. Not less than two hooks or loops for towing the truck shall be furnished on the front of the truck. Mounting shall include reinforcement to transfer loads directly to chassis rails.

3.3.5 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to rated gvw, and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (deg F).

3.3.6 Engine hour meter. An engine hour meter, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the driver's compartment instrument panel.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4.1 Stainless steel. Stainless steel shall meet the requirements of ASTM B 167, Stainless Steel type 300 series.

Source: https://assist.dla.mil -- Downloaded: 20260410-20T22:24Z
Check the source to verify that this is the current version before use.

3.5 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 Truck weights, ratings, and dimensions.

3.6.1 Curb weight. Curb weight shall include weight of chassis, with all attachments, accessories, equipment, body, full complement of fuel, lubricants, and coolant.

3.6.2 Weight rating. The gvw rating shall consist of curb weight, operator (weight computed at 175 lb), and payload to provide not less than 17,000 lb gvw.

3.6.3 Weight distribution. The distribution of the gvw for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.6.4 Ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. Minimum gvw shall be 17,000 lb.

3.6.5 Dimensions. The truck, without payload, resting on level ground, shall have the following dimensions:

a. Overall height, not more than 120 inches.
b. Overall width, not more than 96 inches.
c. Overall length, not more than 23 feet
d. Inside height, centerline floor to ceiling, not less than 78 inches.
e. Inside width, not less than 86 inches.

3.7 Performance.

3.7.1 Speeds. High and low speed requirements shall be met with the truck loaded to rated gvw. The truck shall ascend a 2.5 percent grade at 50 miles per hour (mph) when calculated in accordance with SAE J688 (see 6.3). The maximum geared speed of the truck shall be not less than 60 mph. Low speed shall be calculated with engine operating at not less that 35 percent of recommended governed speed and shall not exceed 4 mph.

3.7.2 Brake performance. Service brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52. Service brakes shall control and hold the truck, loaded to the rated gvw, on a 30 percent grade. Parking brake shall hold the truck, loaded to the rated gvw, headed either up or down the grade, without slipping on a 30 percent grade.

3.8 Chassis components.

3.8.1 Gasoline engine. Unless otherwise specified (see 3.8.1.1), The truck engine shall be a liquid cooled, four-stroke cycle, gasoline engine, having horsepower, torque, and speed characteristics to satisfactorily meet all vehicular performance requirements specified herein. The engine furnished shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

produce the required truck performance when operated on unleaded fuel with a research octane of 91 gasoline, at an engine speed of not more than manufacturer's recommended operation speed.

3.8.1.1 Diesel engine. When specified (see 6.2), the truck engine shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than six cylinders. The engine shall demonstrate the performance characteristics specified herein when using diesel fuel conforming to VV-F-800.

3.8.1.1.1 Oil filter. Full flow type oil filter shall be furnished.

3.8.1.1.2 Governor. Engine governor shall be furnished, set, and sealed to limit engine to engine manufacturer's maximum recommended operating speed.

3.8.1.1.3 Air pollution control. Trucks shall comply with the EPA regulations governing control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, trucks destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.8.2 Electrical equipment.

3.8.2.1 Ignition system. The truck shall be equipped with a 12-volt (V) ignition system. An alternator of not less than 42 ampere rated capacity shall be provided, which shall be capable of maintaining an adequate supply of electrical power under all operating conditions for all 12V accessory components of the truck operating simultaneously.

3.8.2.2 Lighting and wiring. The truck lighting and wiring shall conform to and be installed in accordance with DoT Federal Motor Carrier Safety Regulations, sections 393.12, 393.19, 393.20, 393.22 through 393.26(d), 393.27 through 393.31, 393.33, and as specified herein.

3.8.2.3 Turn signals. Turn signal units conforming to SAE J588, class A; with SAE J589, class A operating units mounted on the steering column, shall be furnished, and shall be provided with double faced front signal units and with single faced rear signal units installed in accordance with SAE J588. Turn signal operating units shall be self-canceling type with visible and audible flash indicator conforming tn SAE J590.

3.8.2.4 Battery. The truck shall be equipped with a 12V battery. The total reserve capacity rating shall be not less than 110 minutes. The total cold cranking rating at 0 deg F shall be not less than 450 amperes. Reserve capacity ratings and cold cranking ratings shall be measured in accordance with SAE J537. Battery shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

3.8.3 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.65.

3.8.3.1 Air cleaner. A dry type air cleaner shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

3.8.3.2 Fuel tank(s). Fuel tank(s), with not less than 40 gallon total capacity, shall be provided. When more than one tank is furnished, a selector valve connecting either tank to engine fuel intake shall be provided and means shall be provided to monitor the level of either tank from a single fuel gage.

3.8.4 Exhaust system. The exhaust system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. The exterior sound level produced by the truck shall not exceed the noise limits established by the EPA. The interior sound level shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.94.

3.8.5 Transmission. Unless otherwise specified (see 6.2), an automatic transmission shall be provided. When specified (see 6.2), a manual transmission shall be provided. Input torque capacity of transmission shall be at least equal to the maximum torque delivered by the engine.

3.8.5.1 Automatic or semi-automatic transmission. The vehicle shall be provided with an automatic or semi-automatic transmission. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The transmission furnished shall provide continuous drive. The transmission shall include a hydraulic torque convertor and not less than four forward gear ratios. The normal driving range selector position shall provide not less than four forward gear ratios without movement of the selector.

3.8.5.2 Manually shifted transmission. The manual transmission shall have not less than four forward speeds and one reverse speed. Transmission shall provide for the maximum ease of shifting with synchronized shift for at least the two highest forward speeds.

3.8.6 Clutch. Clutch shall be the largest capacity clutch offered for the truck and engine furnished, with torque capacity exceeding maximum delivered engine torque.

3.8.7 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.8.8 Frame. Chassis frame shall be manufacturer's standard for the truck furnished.

3.8.9 Suspension. Chassis frame shall be equipped with suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with truck loaded to rated gvw. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. Chassis shall be equipped with hydraulic, double-acting, heavy-duty shock absorbers at the front wheels.

3.8.10 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with truck loaded to rated gvw.

3.8.11 Brakes. Brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.43, 393.45 through 393.51, as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:24Z
Check the source to verify that this is the current version before use.

3.8.11.1 Service brakes. Truck shall be equipped with power assisted, hydraulic actuated, four wheel service brakes of the manufacturer's current type.

3.8.11.2 Parking brake. Truck shall be equipped with parking brake which meets performance requirements of 3.7.2.

3.8.12 Wheels, rims, tires, and tubes. Truck shall be equipped with single front and dual rear wheels. Rim and tire ratings shall conform to TRA recommendations, for the type and size of tire furnished. Tire and rim sizes shall be the same for all wheels on each truck.

3.8.12.1 Tires. Tires shall be tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with truck loaded to specified gvw. Tires shall be of domestic make, not less than 100 level quality, and same load range.

3.8.12.2 Tubes. Tubes, when furnished, shall be of heavy-duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided in accordance with TRA recommendations.

3.8.12.3 Spare tire assembly. An inflated spare tire, mounted on a spare wheel or rim, shall be mounted on a carrier and installed in a readily accessible location on the truck. A wheel nut wrench shall be furnished for exchanging mounted tire assembly with the spare assembly.

3.8.13 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by electric motor(s).

3.8.14 Steering. Manufacturer's standard power steering shall be furnished.

3.8.15 Heater and defroster. Hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

3.8.16 Front bumper. Truck shall be provided with a channel type front bumper.

3.8.17 Rear end protection. Rear end of truck shall be protected in accordance with DoT Federal Motor Carrier Safety Regulations, sections 393.86.

3.8.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

3.8.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Outside rearview mirrors, mounted on each side of the driver's compartment, each with at least 80 square inches of reflective area.
b. Key-operated ignition switch.
c. Ammeter or charging indicator.
d. Fuel gage.
e. Oil pressure gage or indicator.
f. Engine temperature gage or indicator.
g. Speedometer with recording odometer.
h. Sunvisor.
i. Manufacturer's standard electric horn.

3.9 Body. The truck shall have an integral driver's compartment and enclosed body built on the forward control chassis. The body shall be designed for a self-contained window service, food and beverage dispensing mobile system, and shall be complete with all equipment and accessories as specified herein.

3.9.1 Exterior construction. Roof assembly shall be standard for the truck, and shall be constructed to insure drainage. The exterior body panels and roof shall be not less than 0.040 inch aluminum alloy, or not less than 0.0359 inch (US revised standard gage number 20) sheet steel. All body and roof seams and joints shall be dust and weather sealed. Body framing shall be of all-steel welded construction. Not less than six full width crossmembers, including end sills, shall be provided on the body subframing. Rain gutters shall be integrated with roof panels at least over driver's door, rear access door, and both canopy service windows. A full width windshield section shall be provided with integral framing to the enclosed body, and shall be of safety glass.

3.9.2 Driver's compartment. Driver's compartment shall be provided with one full size standard truck door located in forward left side of body. The door shall be the side hinged type with external, key-operated lock. The door shall be provided with a safety glass window, and window shall be a sliding type. An individual, adjustable driver's seat shall be provided. Manufacturer's standard fastenings and seat belts shall be furnished and installed for the driver's seat.

3.9.3 Rear access door. An access door shall be provided in the upper, central portion of the rear of the body. The door shall be of the exterior side hinged type, and shall be not less than 28 inches in width and 28 inches in height. The door shall be furnished with a large weathertight, fixed, safety glass window. The door shall be provided with means for locking on the inside of the body, and shall have full perimeter weather stripping.

3.9.4 Canopy service windows. Two canopy, top hinged, service windows shall be provided on the right side of the body. Each service window shall be not less than 78 inches in length and 28 inches in height. Service windows shall be provided with locking support arms on each side for locking service windows in the fully opened position, and shall have interior locking devices for locking in the closed position. Service windows shall have full perimeter weather stripping. The forward service window shall have a weathertight, windows are

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

closed. Service windows shall be insulated as specified in 3.9.5. A suitable device for opening and closing the service windows from the interior of the truck shall be provided.

3.9.5 Interior construction. The interior walls of the body shall be completely lined with not less than 0.0299 inch (US revised standard gage number 22), conforming to ASTM B 167, type 304, bright finish stainless steel. Interior walls shall extend from ceiling to the floor. The ceiling area shall be covered with not less than 0.0299 inch (US revised standard gage number 22), type 304, bright finish stainless steel. All wall and ceiling panels shall be adequately secured to wall framing members and roof support members. All joints and seams shall be sealed. The body sides and rear walls and ceiling shall be insulated with not less than 1-1/2 inch rigid fiberglass, secured in place between the interior and exterior skins.

3.9.6 Floor. Floor shall be of all metal construction, and shall extend wall to wall, including under all equipment. Flooring material shall be sealed at the juncture of floor and wall panels to prevent the intrusion of vermin. Flooring material shall be not less than 0.0747 inch (US revised standard gage number 14) steel safety plate or equivalent aluminum safety plate. An elastomer floor runner shall be provided for the full length of the working area.

3.9.7 Food service equipment electrical power system. An electrical power supply system shall be provided to operate, protect, and control the food and beverage equipment, ventilation equipment, and lighting equipment as specified in 3.9.8 through 3.9.8.9. Electrical power shall be provided by an air cooled gasoline-engine-driven generator unit, with a rated capacity of not less than 12,500 watts at 120/240 V, single phase, 60 Hertz (Hz) alternating current (ac). The power unit shall be mounted on vibration reducing mounts, and installed in a well ventilated, insulated, sound muffled exterior compartment at the rear of the body. A side hinged access door, with provisions for locking, shall be provided for exterior access to the power unit compartment. Power unit shall be complete with air cleaner, battery, starting system, hourmeter, and residential type muffler and exhaust system, with fuel for the engine supplied from the truck chassis fuel tank. The electrical circuits servicing the equipment shall be protected by properly sized circuit breakers, and shall be located in a central panel box. Provisions to accept electrical power from an outside source shall be furnished. An externally located slave receptacle, with cover, and mating female connection shall be provided. A selector switch shall be provided to enable selection of the engine-generator or commercial power for operation of the food warming and refrigerated preserving equipment.

3.9.8 Food and beverage service equipment. All components, designed for direct contact with food or liquid, shall conform to ASTM B 167, type 304 stainless steel. Other materials used in the construction of food handling equipment shall be designed to withstand wear, penetration by vermin, and the corrosive action of foods. All exterior cabinet work shall be finished with type 304, polished stainless steel. The bodies of counters shall be cabinet type with wrap-around unit weld constructions throughout for rigidity. All counters and refrigerated units shall be joined together smoothly and fit flush to the body of the truck, so that food and liquids shall not fall between, behind, or under the equipment. Filler strips may be provided for joining if necessary. The bottom of equipment, wherever possible, shall be sealed off with

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

a kick plate to prevent dust and moisture from entering under the equipment from the center working area. All equipment shall be firmly secured and positioned to preclude movement when truck is operated at required road speeds.

3.9.8.1 Food warmer. An electrically operated food warmer shall be provided, and shall be designed to warm eight individual sections, with each section independently thermostatically controlled. The food warmer shall be capable of maintaining a temperature range form 140 deg F to 180 deg F. The food warmer shall be constructed of type 304 stainless steel, and shall be incorporated into the serving counter. An indicating light shall be furnished for each section control. The food warmer shall be equipped with interchangeable type panels. Three panels shall be capable of accepting 12 by 20 by 6 inch deep (20 quart) stainless steel full pans with stainless steel telescoping lids. Each of the remaining five panels shall be capable of accepting one 10-1/2 inch (11 quart) and one 8-1/2 inch (7 quart) stainless steel insert pans with solid lids. The food warmer shall be furnished with the following pans:

a. Three each - 12 by 20 by 6 inch deep (20 quart) stainless steel full pans with stainless steel telescoping lids.
b. Five each - 10-1/2 inch (11 quart) and one 8-1/2 inch (7 quart) stainless steel insert pans with solid lids.
c. Five each - 8-1/2 inch (7 quart) stainless steel insert pans with solid lids.

The food warmer shall be equipped to operate properly on the 120/240V, 60 Hz, ac electrical power supply system specified in 3.9.7.

3.9.8.2 Freezer. A chest type, electrically operated freezer, with a capacity of not less than 8 cubic feet, shall be provided. The freezer shall be constructed of type 304 stainless steel, externally and internally. The freezer shall be capable of storing ice cream or frozen foods over extended periods of time without requiring defrosting. The freezer shall be equipped with flip type lids. The freezer shall be equipped to operate properly on the 120/240V, 60 Hz, ac electrical power supply system specified in 3.9.7. The freezer shall be capable of maintaining a temperature of 0 deg F at 90 deg F ambient temperature.

3.9.8.3 Cooler(s). Mechanically refrigerated cooler storage shall be provided to accommodate not less than 34 cases of 12-ounce bottles. The cooler(s) shall be constructed of type 304 stainless steel, externally and internally. The cooler(s) shall be equipped with sliding lids which shall remain closed when the truck is in motion. The cooler(s) shall be properly vented to the exterior of the truck. The cooler(s) shall be located on the left side wall of the interior body equipment area. The cooler(s) shall be equipped to operate properly on the 120/240V, 60 Hz, ac electrical power supply system specified in 3.9.7. The cooler(s) shall be capable of maintaining a temperature of 38 deg F to 90 deg F ambient temperature.

3.9.8.4 Beverage dispensers and urn stand. An urn stand counter, constructed of not less than 0.0478 inch (US revised standard gage number 18) type 304 stainless steel, shall be provided in the right rear corner of the interior body equipment area. Two 5-gallon, type 304 stainless steel, insulated vacuum beverage containers, with dispensing faucets, shall be mounted on top of

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

the urn stand counter. The beverage dispenser mounting brackets or devices shall retain the dispensers in place, and shall provide for easy removal of containers for cleaning and refilling. The urn stand counter shall include a no-splash stainless steel drip tray and drain channel. The beverage dispensers shall have sufficient insulation to maintain the temperature of the contents, suitable for serving four, at least a 4-hour period. In addition, two 5-gallon beverage dispensers, as specified herein, shall be furnished and securely mounted in the right side forward section of the body adjacent to the driver's compartment.

3.9.8.5 Serving counter. A serving counter shall be provided, and shall extend over the entire interior length of the body on the right side commencing at the rear of the driver's compartment area. The serving counter shall facilitate the food warmer (see 3.9.8.1), and shall be located at a convenient dispensing height. The serving counter shall be constructed of not less than 0.0478 inch (US revised standard gage number 18) type 304 stainless steel.

3.9.8.6 Storage shelves. All storage shelves shall be constructed of not less the 0.0748 inch (US revised standard gage number 18) type 304 stainless steel, including supporting members. All storage shelves shall be not less that 12 inches deep, and shall have a 1-1/2 inch raised retaining flange to hold contents on the shelves. Storage shelf shall be provided underneath and extend the full length of the serving counter. Storage shelf shall be provided over the serving area, and shall extend from the rear of the driver's compartment to the rear of the body adjacent to the end of the service windows. Two shelves shall be provided along the left side body wall, and shall extend from the rear of the driver's compartment to the rear of the body.

3.9.8.7 Work counter. A work counter shall be provided at the rear of the body enclosing the area between the freezer and the urn stand counter. Construction shall be as specified for the serving counter (see 3.9.8.5).

3.9.8.8 Ventilation equipment. An exhaust fan shall be provided on each side at the rear of the body. Each fan shall be not less than a 20-inch diameter size. Each fan shall be equipped with an automatic shutter system that closes when the fans are not operating. Each fan shall be equipped with an exterior protective screen. Each fan shall have individual operating control.

3.9.8.9 Interior lighting equipment. Fluorescent lighting shall be provided, and shall extend the full length of each side at the ceiling.

3.9.8.9.1 Ceiling mounted lights. Three ceiling mounted emergency 12V, direct current dome lights wired into the truck chassis system, with a single operating switch, shall be provided.

3.10 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:24Z
Check the source to verify that this is the current version before use.

3.11 Rustproofing. When specified (see 6.2), the truck cab, chassis, and chassis underside shall be rustproofed in accordance with FED-STD-297.

3.12 Servicing and adjusting. Prior to acceptance of the truck by the Government, the contractor shall service and adjust the truck and generator unit (see 3.9.7), for immediate operational use as required by the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes (when required).
c. Proper functioning of all lighting and electrical systems.
d. Wheel alignment (when required).
e. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.
f. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The truck shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Workmanship.

3.13.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.13.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.13.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.13.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.13.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as sppecified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete truck when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.3.

4.3 Examination. Each truck shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

4.4 First article tests. When first article is required, the first article shall be tested as specified in 4.4.1 through 4.4.6. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trucks until corrective action has been taken.

4.4.1 Vehicle weight. The first article truck shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle will be computed using the curb weight, the operator weight at 175 pounds, and the payload (see 3.6.2), to provide the specified gvw. The calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, axles, and tires furnished are of adequate capacity to meet requirements of 3.8.9, 3.8.10 and 3.8.12.1.

4.4.2 Service brake test. Service brakes shall be tested to verify conformance to the requirements of 3.7.2.

4.4.3 Parking brake test. Parking brake shall be tested to verify conformance to the requirement of 3.7.2.

4.4.4 Road test. The truck, loaded to the rated gvw, shall be driven at speeds up to 60 mph over improved roads for not less than 20 miles, and at a speed of 20 mph over unimproved roads (see 6.4), for not less than 10 miles. Upon completion of the test, the truck and equipment shall be inspected for leaks, warping, distortion, or malfunction.

4.4.5 Test for electromagnetic interference characteristics. When electromagnetic interference characteristics are required, the truck shall be tested to determine conformance to 3.3.3.

4.4.6 Cooler(s) and freezer test. The empty freezer and cooler(s), with lids in the open position, shall be soaked for not less than 2 hours in an ambient air temperature of 90 deg F. The cooling capability test shall then be performed with the freezer and cooler(s) exposed continuously to the 90 deg F ambient air temperature. The air temperature in the freezer shall be reduced from 90 deg F to 0 deg F in not more than 4 hours. The air temperature in the cooler(s) shall be reduced from 90 deg F to 38 deg F in not more than 3 hours.

4.5 Production unit tests. The contractor's testing system shall, as a minimum, assure that each truck is capable of meeting the performance requirements specified herein.

4.6 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved, packed, and marked in accordance with the mobile requirements of MIL-V-62038 with the level of preservation and packing as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The truck is intended for use as a mobile self-contained system for dispensing hot and cold food and beverages at Naval Shore and Advanced Base Establishments.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first article is required (see 3.2).
d. When appropriate service requirements for treatment and painting are required (see 3.3.1).
e. When conformance to electromagnetic characteristic requirements and test limits of SAE J551 are required (see 3.3.3).
f. When diesel engine is required (see 3.8.1.1.).
g. When manual transmission is required (see 3.8.5).
h. When rustproofing is required (see 3.11).
i. When first article inspection is required (see 4.2.1).
j. When preservations and packing in accordance with MIL-V-62038 is required, and the level of preservation and packing required (see 5.1).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract or purchase order requirements.

6.3 Performance prediction. Completed copies of SAE J688 form and computation for speed requirements for truck model furnished under contract should be submitted as specified in the contract. Unless other conditions are cited in the contract, computation should be made for normal atmospheric pressure, normal ambient air temperature, and still dry air. The SAE Work Sheet Item 1 should include truck model number, wheel base, engine model number, and truck type. The factor to be used in predicting truck ability (see 3.7.1) are established as follows for the corresponding SAE J688 tables:

Table 1	-	Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.	
Table 2	-	Altitude Factor.	1.00
Table 3	-	Rolling Factor.	1.613
Table 4	-	Area Factor.	0.173
Table 5	-	Velocity Factor.	250.0

Source: https://assist.dla.mil -- Downloaded: 20260410-20T22:24Z
Check the source to verify that this is the current version before use.

Table 6 - Altitude Factor. 1.0
Table 7 - Chassis Friction Horsepower. Use applicable power unit gvw (to nearest, high 1,000 lb) and the engine revolutions per minute (rpm) (to nearest 100 rpm) which is required for 50 mph speed.
Table 8 - Grade Factor. 0.75
Table 8A - Correction Factor. Not required.
Table 9 - Road Factor. 0.0

6.4 Definitions.

6.4.1 Improved road. An improved road is a smooth, hard surfaced road, such as a concrete or asphalt paved highway.

6.4.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

6.5 Subject term (key word) listing.

Truck
Food Service
Beverages
Freezer

Custodian:
Navy - YD

Preparing Activity:
Navy - YD

(Project 2320-N445)

☆U.S. GOVERNMENT PRINTING OFFICE: 1990 - 704-034/30760
Source: https://assist.dla.mil -- Downloaded: 20260-20T22:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-29234A(YD)	1990 July 24

3. DOCUMENT TITLE
TURCK, MULTISTOP DELIVERY; WINDOW SERVICE, FOOD, FORWARD CONTROL, 4 BY 2

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
C. R. LEDERER, Director Equipment Criteria Development Division	(1) Commercial (805) 982-5801 x452	(2) AUTOVON 551-5801 x452
c. ADDRESS (Include Zip Code) Commanding Officer (156) Naval Construction Battalion Center Port Hueneme, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:24Z
Check the source to verify that this is the current version before use.