MILITARY SPECIFICATION

# TRACTOR, WHEELED, WITH TELESCOPIC BOOM MOUNTED MOWER, DED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers a four wheel diesel-engine-driven tractor with a long reach boom mounted with a flail mower.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-3351 - Tractor, Full-Tracked, Low-Speed; Tractor Wheeled, Agricultural; and Tractor Wheeled, Industrial: and Their Attachments, Packaging of.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.



Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:24Z
Check the source to verify that this is the current version before use.

2.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

CODE OF FEDERAL REGULATIONS (CFR)

Title 29 CFR, Rollover Protection Structure.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2.1 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. DESCRIPTION

3.1 Description. Tractor wheeled DED with a long reach boom mounted flail mower. Tractor shall consist essentially of a diesel engine, power train, hydraulic operated long reach boom with a 60 inch hydraulic driven flail mower. Mounted on 4 wheels equipped with pneumatic tires. Shipping weight of tractor, boom and mower assembly shall be not less than 8000 pounds (lb).

3.2 First article. When specified (see 6.2), the contractor shall furnish one tractor for first article inspection and approval (see 4.2.1 and 6.2).

3.3 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

3.4 Standard commercial product. The tractor shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the tractor being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.5 Ease of maintenance. Design of the tractor shall permit ready accessibility to all parts of maintenance and repair by the use of conventional general-purpose handtools. Replacement and adjustment of components parts and accessories shall be accomplished with minimum drainage requirements and disturbance to other elements on the tractor. Ease of maintenance provisions shall incorporate features insuring clearances between adjacent components to facilitate maintenance and servicing operation. Accessibility to lubrication fittings shall be provided without the removal or adjustment of accessories or parts.

3.6 Safety. Parts subject to high operating temperatures, moving or rotating mower, hydraulic boom asembly and tractor including rear wheels, and parts energized electrically which are of such a nature or so located as to become a hazard to operating and maintenance personnel shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. Protective devices shall not impair the operating functions. An electric horn shall be furnished. A rollover protection device of the open canopy type conforming to 29 CFR 1926.1000 shall be furnished.

3.7 Performance. The tractor shall have a maximum travel speed of not less than 15 miles per hour (mph). The tractor and mower shall be capable of:

a. Mower shall cut grass, reeds and underbrush from directly along side of tractor to reaches of not less that 28 feet (ft) from center line of tractor, at a speed of not less than 3 mph. Mower shall be capable of cutting grass, reeds and underbrush to a maximum height of not more than 4 inches.

b. Boom shall have a reach of not less than 28 ft from center line of tractor. Boom shall be fully hydraulically operated and shall be capable of mowing on slopes from ground level to not less that 45 degree (°) angles above ground level and 45° below ground level.

3.8 Drawbar pull. The tractor shall have a maximum drawbar pull equivalent to not less than 70 percent of its weight when fully equipped including a 175 lb operator, but without ballast.

3.9 Frame. Frame design may be either farm type or industrial type. The industrial type frame shall be fabricated of structural steel sections or steel plates with members joined using one of the arc-welding processes. To



Source: https://assist.dla.mil -- Downloaded: 20260-20T22:24Z
Check the source to verify that this is the current version before use.

withstand the stresses imposed, and to prevent permanent deformation or damage to the tractor, the frame shall be braced and reinforced wherever necessary. The farm type frame shall consist of the engine housing, transmission case, and the rear differential housing. Design and the method of mating each component shall be such as to assure structural integrity.

3.10 Axles. The tractor shall be equipped with a front located, steering type axle and a rear located axle. Both axles shall be equipped with wheels mounted on heavy-duty ball or roller-type bearings. Rear wheels shall have a width of not more than 96 inches.

3.11 Rims, tires and tubes. Tire and rim sizes shall conform to TRA recommendations for the type and size of tires furnished. Unless otherwise specified (see 6.2), tractor shall be equipped with wide base, rear tires. Rear tires shall be R4 type (with industrial tread) with ply rating of not less than 4. Front tires shall be either I-1 type or F-3 type (Multiple rib tread) with ply rating of not less than 4. Tires shall be of a rated capacity at least equal to the load imposed, measured at each wheel at the ground, when the tractor is fully loaded. When tube-type tires are furnished, tubes shall be of the heavy-duty type and of proper size for the tires furnished.

3.12 Brakes.

3.12.1 Service. Tractor shall be provided with individually operated rear wheel service brakes. Tractor shall also be equipped to provide simultaneous braking of rear wheels. When traveling on a relatively level, hard, smooth surface at a speed of 15 mph, service brakes shall be capable of stopping the tractor within a distance of 60 ft.

3.12.2 Parking. A mechanical parking brake which is part of the main braking system, or an independent mechanical parking brake shall be furnished. Mechanical service brakes which can be locked as parking brakes are acceptable. Parking brake shall be capable of holding the tractor stationary on a 30 percent slope.

3.13 Hitch. Standard drawbar hitch capable of pulling 75 percent of tractor weight without permanent distortion (see 3.8).

3.14 Engine. The tractor shall be powered by a diesel-engine having horsepower, torque and speed characteristics to satisfactorily meet all mowing performance requirements specified herein. The engine shall be equipped with the following:

a. Air cleaner - dry type.
b. Full flow oil filter.
c. Governor. When none adjustable type is furnished it shall be set to limit engine speed to the maximum operating speed recommended by the engine manufacture.



Source: https://assist.dla.mil -- Downloaded: 202610-20T22:24Z
Check the source to verify that this is the current version before use.

d. The operators station shall be equipped with, but not necessarily limited to, the following instruments and controls:

(1) Lubricating oil pressure indicator.
(2) Cooling liquid temperature indicator.
(3) Battery - alternator indicator.
(4) An engine hour meter capable of registering not less than 9,999 hours of engine operation.
(5) A start - stop control.
(6) Throttle control.

3.15 Powerplant systems.

3.15.1 Starting. Engine shall start in any ambient temperature above 20° Fahrenheit (F). The tractor shall have a 12 volt (V) electrical cranking system. Starting aids may be either electric glow plug or ether primer. When an ether priming system is furnished, it shall be of the measured shot type with storage capacity of not less than 12 fluid ounces.

3.15.2 Fuel. Fuel tank shall have sufficient capacity for not less than 8 hours of normal operation. A fuel gage located at the tank or at the operator's station shall be furnished.

3.15.3 Exhaust. Tractor shall be equipped with a muffler and exhaust pipe. The exhaust pipe shall be located to assure expelled gases are directed away from the operator. Verticle exhaust pipes shall be equipped with self-opening and closing rain caps or 90° bend. A spark arrester muffler shall be furnished on tractor and shall have an 80 percent arresting efficiency when rated in accordance with SAE J350.

3.15.4 Cooling. Tractor shall be furnished with a heavy-duty cooling system. The system shall maintain coolant at a temperature below the boiling point when the tractor is operating at 10,000 ft above sea level, or in an ambient temperature of not less 125°F. Radiator core shall be protected against damage by a guard, capable of withstanding damage from brush, hanging tree limbs, or similar ground growth encountered in mowing and general landscape maintenance.

3.16 Power train. The transmission shall have not less than three speed forward and one speed reverse. Transmission shall permit smooth shifting in all gear ranges. Axles and transmission gear ratios shall be matched to provide a progressive shifting pattern through the complete range. Input torque capacity of transmission shall be at least equal to the maximum torque delivered by the engine. Drive line components shall transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction, without sustaining any damage or deformation.

3.17 Power takeoff. Tractor shall be so equipped that there is direct access to the front crankshaft pulley for powering hydraulic pump, for mower and boom operation.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

3.18 Systems.

3.18.1 Electrical. Tractor shall have a 12V electrical system. The battery shall be 12V potential, and have a capacity of not less than 70 ampere-hours at the 20-hour rate. An alternator having not less than a 26-ampere rating shall be furnished. All wiring shall be protected against weathering and wearing, and shall be supported or secured at intervals not exceeding 2 ft.

3.18.2 Lighting. When specified (see 6.2), the tractor shall be furnished with lighting and marking equipment for operation on public roads and rearward directed floodlamp conforming to SAE J598. Instrument panel lamps to illuminate all instruments shall be provided. Head, tail, and instrument panel lamp circuits shall be connected for actuation by a single control switch. Independent control switches shall be furnished for the floodlamp and warning lamp.

3.18.3 Hydraulic. A hydraulic system shall be provided for transmitting engine power to the mechanisms necessary for raising, lowering, extending and retacting of boom and running flail mower. The hydraulic system shall be complete with all operating accessories, including pump, reservoir, valves, filters, hoses, piping, fittings, and pressure relief valve(s). Pump shall have sufficient capacity to energize all hydraulically powered components. The system shall be capable of withstanding a bursting pressure of four times the working pressure and maximum proof pressure of at least two times the working pressure. Hoses shall be suitable for operation at temperatures ranging from -20°F to 240°F. Hoses shall be protected against chafing through utilization of supports and protective devices. A wiper shall be provided on each hydraulic cylinder adjacent to the piston rod seal to prevent dirt and abrasives from damaging the seal or entering the cylinder. System shall be furnished with full flow filter(s) having a micron rating not greater than 25. The reservoir shall have sufficient capacity to allow maximum displacement of all cylinders at the same time, and to aid heat dissipation. Hydraulic reservoir shall be mounted on street side of the tractor to provide counter balance for mowing and boom assembly.

3.18.4 Steering. Tractor shall be equipped for front wheel steering utilizing an automotive type steering mechanism, with gears enclosed in a leakproof housing. Either full power steering or power assisted steering shall be furnished. Unit shall be completely separate from boom and mower hydraulics.

3.19 Operator's station. Operator's station shall be equipped with a seat and backrest, instrument panel, and operating controls for mower and telescopic boom. Seat and backrest shall be padded and covered with weatherproof material. The seat shall be horizontally and vertically adjustable. Instrument panel shall contain the instruments, controls, and switches specified in 3.13 and 3.18.2. All instruments shall be visible and all hand and foot operated controls, including brake, throttle, transmission,



Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:24Z
Check the source to verify that this is the current version before use.

and steering wheel, shall be within easy reach of the operator while sitting in his normal operating position. Instruments, gages, switches, and controls shall be protected against moisture and inclement weather conditions. Each instrument, gage, switch, and control shall be provided with permanently affixed identification markings. Decalcomania shall not be used.

3.20 Flailmower. All structural and wearing parts of the flail mower shall be designed for continous rugged service. All moving parts shall be shielded as required for safety. Mower shall be hydraulically operated with a cutting width of not less than 60 inches. Mower shall be capable of cutting grass, reeds and underbrush to a maximum of 4 inches above ground level. Knife hardness shall range between rockwell hardness C43 and C47. A guard so designed and placed to prevent dangerous ejection of solid objects shall be provided. Mower head shall be of the full floating type.

3.21 Boom. The boom shall be of the hydraulic telescopic type with power extend and retraction capabilities. Boom must have a reach of not less than 28 ft measured from center line of tractor. All controls for the boom and mower assembly shall be located so the operator can reach with ease from his normal operating position. Provisions to stow the boom securely shall be made for normal storage, travel and shipment of the tractor mower. A saddle mounted boom rest shall be provided to support the boom and mower assembly in the stowed position. Tie down or hold down device shall be provided to prevent unactuated movement of the boom when in transit. Boom shall be capable of controlling flail mower for cutting grass, reeds and underbrush at a minimum of a 45° angle above grade or below grade level.

3.22 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.23 Identification plate. An identification plate will be furnished by the contracting officer for each tractor . The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each tractor in a conspicuous place with nonferrous screws, rivets, or bolts not less than 1/8-inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

3.24 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The exterior color finish coat shall be yellow color No. 13538 in accordance with FED-STD-595. Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the



Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:24Z
Check the source to verify that this is the current version before use.

surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.25 Servicing and adjusting. Unless otherwise specified in section 5, prior to acceptance of the tractor by the Government inspector, contractor shall service and adjust each tractor and its mounted equipment for operational use, including at least the following: Focusing of lights; adjustment of engine; adjustment of electrical and brake systems; alignment of front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear, and mounted equipment with grades of lubricants recommended, servicing of the cooling system with a solution of ethylene gylcol type antifreeze and water in equal parts by volum.

3.26 Workmanship.

3.26.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.26.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.26.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.26.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one tractor when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3, the tests of 4.4.1 through 4.4.3 and when specified, the preproduction pack inspection of 4.5. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection includes the examination of 4.3, the tests of 4.4.3, and the packaging inspection of 4.5.

4.3 Examination. Each tractor shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests.

4.4.1. Pretest. Each tractor and mower shall be tested for operation on improved road type terrain for not less than 2 hours and undulating terrain



Source: https://assist.dla.mil -- Downloaded: 20260-20T22:24Z
Check the source to verify that this is the current version before use.

for not less than 1 hour at road speed and moving speed to test for stability. Boom and flail mower shall be operated in all positions from fully retracted to fully extended mowing grass, reeds or underbrush to a maximum height of not more than 4 inches. Boom and mower assembly shall be tested for their cutting from level to 45° above ground level and 45° below ground level. Failure to pass one or more of these test shall be cause for rejections.

4.4.2 Drawbar test. To determine conformance to 3.8, the tractor shall be tested for maximum drawbar pull without ballast in accordance with SAE J708. The test shall be conducted on a clean dry and level concrete surface. Failure to pass any phase of this test shall be cause for rejection.

4.4.3 Performance test. Each tractor shall be completely assembled, properly adjusted, and serviced for operation. Engine shall be started and subjected to a warmup period as recommended by the manufacturer. Tractor shall be driven for not less than 1 hour. All controls and switches shall be operated as many times as necessary to determine ease of operation, effectiveness, responsiveness, and that mechanisms actuated by the controls operate promptly, fully and without restriction, malfunction, or excessive vibration. The power train, power takeoff, hydraulic system, steering system, and other easily accessible moving parts shall be tactually examined for excessive heating or abnormal operation insofar as is practicable. Failure to pass any phase of this test will be cause for rejection.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-T-3351. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required.

## 5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-T-3351 with the level of preservation and the level of packing as specified (see 6.2).

## 6. NOTES

6.1 Intended use. Tractor mower is intended for mowing areas around ammunition magazines with slopes of 45° angles.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When specification shall be other than as specified (see 2.1.1).
c. When a first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
d. When other than wide base type rear tires are required (see 3.11).
e. When a lighting system is required (see 3.18.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

f. When a preproduction pack inspection is required and time frame required for submission (see 4.2.1 and 4.5).
g. Level of preservation and level of packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 52.227-7031 of the Federal Acquisition Regulations (FAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of FAR 52.227-7031 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Custodian:

Navy - YD

Preparing Activity:

Navy - YD

(Project 2420-N046)



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:24Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE NAVY

Commanding Officer
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332-2300

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:24Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-T-29235(YD) | TRACTOR, WHEELED, WITH TELESCOPIC BOOM MOUNTED MOWER, DED |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:24Z
Check the source to verify that this is the current version before use.