| NOT MEASUREMENT |
| SENSITIVE |

MIL-T-29243A(YD)
14 February 1991
SUPERSEDING
MIL-T-29243(YD)
26 July 1985

MILITARY SPECIFICATION

TRUCK, TIRE SERVICING: DIESEL ENGINE DRIVEN, 46,000 POUNDS GVW, 6 X 6

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a diesel engine driven, six-wheel, six-wheel drive, tire servicing truck, having minimum gross vehicle weight (gvw) of 46,000 pounds (lbs) with an articulating hydraulic crane and 16-foot flat bed body.

* 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:27Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage, Vehicular, Ignition, Lighting and Starting.
GG-G-91 - Gage, Tire Pressure, Self Contained and Inflator Gage, Pneumatic Tire.
OO-G-669 - Grinder, Pneumatic, Horizontal and Vertical.

MILITARY

MIL-V-62038 - Vehicle, Wheeled, Preparation for Shipment and Storage of.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions For lifting and Tying Down Military Equipment.
MS51335 - Pintle Assembly, Towing, 18,000 Lbs Capacity Manual Release.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:27Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which is current on the date of the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII, Division I. Pressure Vessels.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

ASTM

ASTM E 380 - Metric Practice, Standard for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices

SAE J318 - Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers-Trucks. Truck-Tractors, and Trailers (DoD adopted).
SAE J534 - lubrication Fittings.
SAE J537 - Storage Batteries (DoD adopted).
SAE J551 - Performance Levels of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
SAE J560 - Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
SAE J588 - Turn Signal Lamps.
SAE J589 - Turn Signal Switch.
SAE J682 - Rear Wheel Splash and Stone Throw Protection (DoD adopted).
SAE J683 - Tire Chain Clearance- Trucks, Buses, and Combination of Vehicles.
SAE J688 - Truck Ability Prediction Procedure (DoD adopted).
SAE J1349 - Engine Power Test Code - Spark Ignition and Diesel.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:27Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

STATE OF CALIFORNIA

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for associated detail specifications, specifications sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a six-wheel, six-wheel drive chassis with cab having a gvw rating of not less than 46,000 lbs. The truck shall be equipped with a diesel-engine-driven air compressor unit located as specified herein. A fully hydraulic, articulated boom type, crane shall be mounted on chassis frame. A flat deck type body shall be located on the rear portion of the chassis frame.

3.2 First production vehicle. The contractor shall furnish a tire truck assembly for first production vehicle inspection.

3.3 Standard truck, components, and accessories. Except as specified herein, the truck, components, and accessories shall be the manufacturer's standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented and rated in the manufacturer's sales information, including special or mounted equipment. Sales information shall be limited to specifications and technical material, identical to that furnished to authorized company representatives for selection of trucks, models, and components. Truck, components, assemblies, and accessories to be provided hereunder are standard or optional commercial products for the purpose of this specification. Such items shall be construed as commercial motor vehicle products, and shall comply with all DoT Federal Motor Vehicle Safety Standards and Regulations applicable, on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:27Z
Check the source to verify that this is the current version before use.

3.3.1 Drain plugs. Drain plugs installed in manual transmission, transfer case, and rear axles shall be of the permanent magnet type.

3.3.2 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded to gvw and operated at an altitude of 10,000 feet above sea level, or in an ambient air temperature of not less than 125 degrees Fahrenheit (^{o}F).

3.3.3 Coolant system and indicators. Coolant system shall include a de-aeration system, a surge tank or a coolant recovery reservoir of not less than 2-quart capacity. A low coolant level or high coolant temperature alarm buzzer and red indicator warning light shall be provided on the cab dash instrument panel.

3.3.4 Towing devices. Not less than two hooks or loops for towing the truck shall be furnished on the front of the truck.

3.3.5 Trailer towing package. When specified (see 6.2), a trailer towing package consisting of a pintle; safety chain attachment devices; a lighting receptacle; and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the type conforming to MS51335. The pintle shall be installed on the chassis frame with reinforcements to transfer pintle loads directly to the chassis rails. The rearmost portion of the pintle shall be forward, but not more than 4 inches forward, of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the gvw of the truck furnished. The lighting receptacle, conforming to SAE J560 with its conductors connected and color coded as specified therein, shall be mounted in a readily accessible location near the pintle. Trailer towing package shall include the brake control system of 3.6.15.2.

3.3.6 Splash guards and shields. Rear wheels shall have rigid splash shields ahead of the wheels and splash guards to the rear. Splash and stone throw protection shall be in accordance with SAE J682.

3.3.7 Engine hour meter. An engine hour meter, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.3.8 Air pollution control. Trucks shall comply with the EPA Regulations governing Control of Air Pollution from New motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, trucks destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the current version before use.

3.3.9 Sound level. The interior sound level shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

* 3.3.10 Radio interference suppression. The truck shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting radiation shall be suppressed to the same level as the truck chassis.

3.4 Truck weights, ratings, and dimensions.

3.4.1 Curb weight. Curb weight shall include weight of chassis and cab, all attachments, accessories, equipment, body, full complement of fuel, lubricant, and coolant.

3.4.2 Weight rating. The gvw rating shall consist of curb weight, operator (weight computed at 175 lbs), and payload, to provide not less than the specified gvw.

3.4.3 Weight distribution. The distribution of the gvw for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.4.4 Ratings. Component and vehicular ratings shall not be raised to the requirements of this specification. Minimum gvw shall be 46,000 lbs.

3.4.5. System of measurement. The dimensions used in this specification are not intended to preclude the use of the metric system of measurement in the fabrication and production of the material, individual parts, and the finished product, provided form, fit, and function requirements are satisfied (see 3.12).

3.5 Performance. Trucks shall meet the following performance requirements. Performance requirements shall be met with front wheel drive disengaged and with front wheel driving hubs unlocked, except that truck equipped with interaxle compensating devices shall meet performance with front wheel drive engaged.

3.5.1 Speeds and gradeability. High and low speed requirements shall be met with truck loaded to specified gvw.

3.5.1.1 High speed gradeability. The truck shall ascend a continuous grade of 1.0 percent at 50 miles per hour (mph). Gradeability requirement shall be met with the transfer case in high range and the main transmission in direct drive. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.4).

3.5.1.2 Low speed. Low speed shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide a truck speed of not more than 3 mph.

3.5.1.3 Maximum geared speed. Maximum geared speed at engine governed

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the currentversion before use.

speed shall be not less than 50 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Engine governed speed}}{\text{Total geared reduction X tire factor}}$$

3.5.2 Brake performance. Service brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulation, section 393.52. Service brakes shall control and hold the truck, loaded to the rated gvw, on a 30 percent grade. Parking brake shall hold the truck, loaded to the rated gvw, headed either up or down the grade, without slipping on a 30 percent grade.

3.6 Chassis components.

3.6.1 Engine. Engine furnished shall be the chassis manufacturer's standard, or optional engine for the commercial model truck which meets or exceeds the requirements of this specification. The truck shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J1349.

3.6.1.1 Oil filter. A full flow type oil filter shall be furnished.

3.6.1.2 Governor. An engine governor shall be furnished and set and sealed to limit engine to engine manufacturer's maximum recommended operating speed.

3.6.2 Electrical systems. Electrical systems shall be in accordance with DoT Federal Motor Carrier System Regulations, sections 393.27 through 393.31 and 393.33.

3.6.2.1 Starting system. A 12- or 24-volt (V) direct current starting system, with 12V lighting system, and not less than 60 ampere (A) alternator, shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type, controlled from the driver's compartment, with a reservoir of not less than 12 fluid ounces, and shall be inoperative with the engine warm.

3.6.2.2 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.12, 393.19, 393.20, 393.22 through 393.26. Lights and reflectors shall not be mounted on vertical surface of rub rails unless recessed and fully protected or mounted on vehicle bumpers.

3.6.2.3 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Vehicle shall be provided with double-faced front signal

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the current version before use.

units and single-faced rear signal units installed in accordance with SAE J588 except that turn signals shall not be mounted on engine compartment hood. Turn signal operating units shall have visible indicator(s) on dash near instrument panel.

3.6.2.5 Batteries. Each battery shall be of 12V potential. The total reserve capacity rating and total cold cranking ampere rating of 0°F, both measured in accordance with SAE J537, shall provide a minimum reserve capacity of 400 minutes at 1,200A. When specified (see 6.2), the battery shall be of the maintenance free type having the characteristics listed in W-B-131.

3.6.3 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.65 and 393.67.

* 3.6.3.1 Air cleaner. Manufacturer's dry type air cleaner shall be furnished.

3.6.3.2 Fuel tanks. Fuel tank shall be manufacturer's standard with a capacity of not less than 40 gallons. When more than one tank is total furnished means shall be provided to assure equalized fuel level in both tanks.

* 3.6.4 Exhaust system. The exhaust system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. Vertical exhaust mufflers capable of being reached easily by personnel entering or leaving either side of the cab shall be provided with a heat shield. Vertical exhaust systems shall be provided with a hinged rain cap, or a 90° vertical to horizontal elbow at the top.

3.6.4.1 Exhaust system safety shield. The exhaust system or hydraulic system shall be shielded so that, in the event of a hydraulic line rupture or hydraulic fluid leak, the hydraulic fluid will not come into contact with any part of the vehicle exhaust system.

3.6.5 Gear train:

3.6.5.1 Transmission. A manually shifted transmission shall be provided on the vehicle. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. Gear ratios in transmission and axles shall be matched to provide a progressive shifting pattern throughout the complete range, and shall provide required vehicle performance (see 3.5). Unless otherwise specified (see 6.2), the transmission shall provide a minimum of 10 forward speeds and one reverse speed. The transmission shall be provided with power takeoff opening(s). The transmission shall provide for maximum ease of shifting in all speeds.

3.6.5.2. Transfer case. A two-speed transfer case shall be provided. Unless the transfer case is equipped with devices which compensate for differential torque and speeds between front and rear axles, transfer case shall provide for driver selection of either rear-wheel or all-wheel drive. When furnished, interaxle compensating devices shall provide for positive transfer of power to all driving axles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

3.6.5.3 Drive hubs. When specified (see 6.2), manually operated drive hub for disengaging front wheels from power train shall be provided, unless the truck is equipped with interaxle compensating devices between front and rear axles.

3.6.5.4 Clutch. The clutch assembly shall be the largest capacity clutch assembly offered for the model and class vehicle and engine furnished with torque capacity exceeding maximum delivered engine torque.

3.6.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.6.7 Frame. Chassis frame shall be manufacturer's standard for the truck furnished. Frame shall have reinforcement extending at least from the front suspension rear hanger bracket to the rear spring front hanger bracket. Reinforcements shall provide sufficient structural strength in the chassis frame through increased bending moment to at least equal the loads imposed. Chassis frame rails shall not project beyond the rear ends of the body.

3.6.8 Suspension. Truck shall be equipped with suspension system with components having a rated capacity at least equal to the loads imposed on each member, measured at the ground, with truck loaded to rated gvw. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. Truck shall be equipped with hydraulic, double-acting, shock absorbers at the front wheels.

3.6.9 Rear bogie. The rear bogie assembly shall be of the four-wheel type, complete with axles, springs, torque rods, and all other necessary parts. The bogie shall be provided with a means of permitting differential action between the two axles and a manually or automatically controlled lockout assuring equal power to each rear axle. The manual lockout control used shall be located in the truck cab.

3.6.10 Axles. Axle rating shall be at least equal to the load imposed on each axle, measured at the ground, with truck loaded to rated gvw. Gear ratio shall provide performance specified in 3.5. Single-reduction drive axles shall be furnished.

3.6.10.1 Traction control. The truck shall be furnished with a traction control on the rear axles. The traction control shall actuate automatically to insure that power is transmitted to the wheels having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

3.6.11 Wheels, rims, tires, and tubes. The truck shall be equipped with single front and single duplex type or dual rear wheels. Rim and tire rating shall conform to TRA recommendations for the type and size of tires furnished to meet specified gvw requirements. Tire and rim sizes shall be the same for all wheels on each truck. Wheels shall be manufacturer's standard disk type.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the current version before use.

3.6.11.1 Tires. Tires shall be tube or tubeless type with nondirectional mud and snow tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with truck loaded to rated gvw.

3.6.11.2 Tubes. Tubes, when furnished, shall be of heavy-duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided in accordance with TRA recommendations.

3.6.12 Tire chain clearance. Clearance shall be provided for installation and use of tire chains in accordance with SAE J683. Allowance for spring deflection shall be included.

3.6.13 Spare wheel assembly. When specified (see 6.2), a spare wheel shall be mounted on a carrier and installed on a readily accessible location on the truck. Carrier design shall enable removal or mounting of spare wheel assembly using only the tools specified in 3.6.20.1.

3.6.14 Spare tire. When specified (see 6.2), an inflated spare tire mounted on the spare wheel shall be furnished. The spare tire shall be of the same size, tread design, and load range as the other tires furnished on the truck.

3.6.15 Brakes. Brakes shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.42, 393.45 through 393.52, and as specified herein.

3.6.15.1 Service brakes. Truck shall be equipped with six-wheel full air brakes. Brakes shall be furnished on all wheels. The braking system, complete with all necessary components, shall include:

a. Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 12 cubic feet per minute (cfm).
b. Air storage reservoir(s) with not less than 2,000 cubic inches total capacity, each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank.
c. Foot control, suspended or treadle type.
d. Air control valves.
e. Air pressure gage, visible to the driver.
f. Low air pressure warning, visible and audible.
g. Service brake stop lamp switch.
h. Alcohol aspirator with unbreakable transparent container.
i. Automatic moisture ejector.
j. When specified (see 6.2), in lieu of subparagraph (h), an air dryer shall be furnished. The air dryer shall be the desiccant type.
k. When specified (see 6.2), automatic slack adjusters.

3.6.15.1.1 Parking brake. Truck shall be equipped with spring applied, air pressure released, parking brake assemblies to meet requirements of 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

3.6.15.2 Trailer brake control system. In addition to components specified in 3.6.15.1, a trailer brake control system shall be furnished when a trailer towing package is required (see 3.3.5 and 6.2). Trailer brake control system shall include:

a. Identification of emergency and service lines.
b. Coincident control of trailer brakes with prime mover foot control.
c. Independent hand control for trailer brakes.
d. Prime mover protection valve with dash control and automatic break-a-way feature.
e. Trailer stoplight operable with foot brake and with hand control for trailer brakes.
f. Two coiled air hoses, not less than 110 inches long when fully extended, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment.
g. Air connectors for trailers with SAE J318 gladhand couplers mounted at the rear of the vehicle, located to preclude interference with trailer hookup.
h. Dummy gladhand couplers with chains.
i. Prime mover only parking brake valve to permit prime mover parking brake to be applied while charging the trailer air brake system.

3.6.15.3 Brake controls for use from a towing vehicle. When specified (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, relay emergency valve with no-bleed-back feature (except when spring applied emergency brake is furnished), additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

3.6.16 Steering. Manufacturer's standard power steering shall be furnished.

3.6.17 Cab. Manufacturer shall furnish a standard full-width cab. Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage, with at least the curb side door equipped with external key-operated lock. Drip rails shall be furnished above cab doors. Cab shall have upholstered, full-width, adjustable seat and back or individual, adjustable driver's seat and individual passenger seat. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be furnished and installed.

3.6.17.1 Accessories and equipment. The cab equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Key-operated ignition switch.
b. Ammeter, charging indicator, or voltmeter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

c. Fuel gage.
d. Oil pressure gage.
e. Speedometer with recording odometer.
f. Engine temperature gage.
g. Dual sunvisors.
h. Front door mounted armrest on driver's side.
i. Driver's compartment ventilator other than window.
j. Manufacturer's standard electric or air operated horn.
k. Tachometer.

3.6.17.2 Windshield wipers and washers. Truck shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by electric or compressed air powered motors.

3.6.17.3 Heater and defroster. Hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct air to floor and to defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver.

3.6.17.4 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.6.17.5 Rearview mirrors. Outside rearview mirrors, each with at least three supporting arms, shall be mounted on each side of the cab. Combinations (flat and convex) mirrors shall be furnished. Each combination mirror shall have at least 50 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area.

3.6.18 Bumper. Unless the bumper is an integral part of the truck cab, a channel type front bumper shall be provided.

3.6.19 Rear end protection. Rear end of truck shall be protected in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.86.

3.6.20 Tool storage. Storage space of sufficient size to accommodate vehicle jack, hand tools, antiskid chains, and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Storage space for these tools may be furnished inside the cab. When storage space for these tools is located outside of cab, it shall be waterproof and shall provide for locking with padlock.

3.6.20.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly, and shall include the minimum of a hydraulic jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point at any wheel with the tire

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:27Z
Check the source to verify that this is the current version before use.

flat. The jack, without blocking, shall be capable of raising any wheel of loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.7 Truck body. A heavy-duty tire service body, open flat-deck type with underslung storage compartments on both sides, shall be furnished. The deck shall be covered with a steel safety tread plate no less than 0.1345-inch (U.S. revised standard gage No. 10) thick. The body components shall include an air compressor unit, crane section, and a flat bed section not less than 16 feet in length. The air compressor, when mounted below bed (see 3.8), shall be protected from the elements with an enclosure providing adequate ventilation. The body shall be not less than 93 inches or more than 96 inches in width. Storage compartments for stowing and securing tools and supplies shall have hinged doors. Hinges shall be continuous rod- or hem-type, with stainless steel hinge pins or sockets. Latches shall have recessed handles. Doors shall have cylinder type locks, with all locks operable by the same key. Inset steps or foldup type steps shall be provided to aid personnel in mounting the rear deck. Inset step openings in the body skirt shall be not less than 6 inches wide, 5 inches high, and 5 inches deep. Steps shall be located, one each side of the body forward of rear wheels and on each side to the rear of rear wheels.

3.8 Air compressor unit. An air compressor unit, consisting of a compressor with diesel engine, receiver, and all the necessary accessories shall be furnished. Compressor may be air or water cooled. The unit shall be mounted at rear of truck cab and may be mounted above or below the bed and shall provide clearance for crane (see 3.9). Operating personnel shall be protected from moving parts by the use of expanded metal guards. The air compressor shall be capable of satisfactory performance in ambient temperatures ranging from +120°F to -20°F, and at any angle up to 15° from the horizontal. The actual air delivery at continuous operating speed shall be not less than 35 cfm at not less than 175 pound-force per square inch gage (psig). Mounting of the air compressor shall be such as to minimize transfer of vibration, and also provide for ease of maintenance for required normal servicing functions.

3.8.1 Compressor engine. A commercial, 4-cycle, diesel engine, of the size and rating recommended by the compressor manufacturer, shall be furnished. Engine shall be furnished complete, including electric cranking system, variable speed governor, and low oil level or high temperature shutoff device. The truck chassis battery may be utilized to start and run the engine providing the systems are the same voltage and polarity. A battery and charging system shall be furnished when chassis battery is not utilized. The engine shall be mounted in conjunction with the air compressor and may be separate from receiver tank.

3.8.2 Pressure control. An adjustable, pressure actuated, mechanical control shall be furnished to stop compression of air and reduce engine speed when pressure reaches 175 $\pm$ 2 psig. Before tank pressure has dropped to 150 psig, the control shall automatically accelerate the engine and start air compression after engine has attained rated operating speed. A manual control shall be provided to override the accelerator control during unload periods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

3.8.3 Fuel tank. A fuel tank with a capacity to assure not less than 5 hours of continuous operation shall be furnished. The truck chassis fuel tank may be utilized when compressor engine fuel system includes manual fuel primer pump and a check valve to prevent fuel drain-back and loss of prime.

3.8.4 Air receiver tank. The receiver tank shall be of sufficient capacity to meet the performance requirements specified herein. The tank shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code, section VIII, Division I. Tank equipment shall include, as a minimum, a pressure relief valve, a discharge valve, a drain valve, and a shock proof pressure gage calibrated from 0 psig to not less than 200 psig in increments no greater than 10 psig.

3.8.5 Compressor accessories. The following accessories shall be furnished:

a. Seventy-five feet of 3/8-inch inside diameter (id) air hose with a burst pressure of not less than 700 psig. Hose shall be provided with 1/4-inch National taper pipe (thread) (NPT), male end fitting.
b. One (1) inflator gage conforming to GG-G-91, type IV, style 3.
c. Seventy-five feet of 1/2-inch id pneumatic tool hose with quick-disconnect automatic valve type couplers.
d. Two 1/4 inch, quick disconnect, automatic valve type coupler halves with 1/4-inch male NPT.
e. Two 3/8 inch, quick disconnect automatic valve type coupler halves with 3/8-inch male NPT threads.
f. Two 3/8 inch, quick disconnect, automatic valve type coupler halves with 1/2-inch male NPT threads.
g. Two self-winding reels, one to accommodate a 3/8-inch hose and one for the 1/2-inch hose.

3.9 Crane. A one man operated, fully hydraulic, articulated boom type crane shall be mounted on the truck frame at the front of the body and shall not interfere with compressor operation (see 3.8). The boom shall be hydraulically operated and extendable not less than 15 feet. Double-acting hydraulic outriggers, independently controlled and integrally mounted to the crane base, shall be furnished. With the outriggers in the down position, the crane shall be capable of lifting the rated maximum capacity at the maximum radius without causing the truck to become unstable. Truck shall be deemed unstable when any one of the truck wheels lifts off the ground. The boom, when fully extended, shall have a minimum vertical reach of 20 feet above ground level and shall rotate through a horizontal arc of not less than 180°. The boom shall fold to a nestable travel height not to exceed top of truck cab roof. Crane controls shall be provided on the passenger side of the truck. Crane and outrigger controls shall be accessible from ground level. Outrigger controls shall be located on both sides of the truck. Each outrigger landing pad shall be not less than 140 square inches.

3.9.1 Lifting capacities. The crane shall be capable of handling a minimum of 8,000 lbs at 8 feet radius and 4,500 lbs at 15 feet radius.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

3.10 Hydraulic system. A hydraulic pump, driven from a power takeoff controlled from inside the truck cab, shall be provided to furnish power for the crane. The pump shall be of the positive displacement type and shall provide a working pressure of not less than 1,800 psig. Controls shall be of self-centering, fail-safe type with hydraulic bypass overload valves, and check valve type locking system in boom and outriggers to prevent load dropping due to hydraulic or power failure. Controls shall have fine metering qualities to provide infinitely variable raising, lowering, and rotating motions of the crane boom. Crane hydraulic system shall contain the following minimum safety features:

a. Check valve system in boom and outrigger system to prevent load drop due to hydraulic system failure.
b. Constant flow valve in hydraulic lines to preclude boom damage due to sudden load lowering stops.
c. Cushioning valves in boom rotating hydraulic system to preclude damage due to sudden stops.
d. Pressure relief valve to preclude loading beyond lifting capacity.
e. Signs with 1-inch lettering visible to the operator at the controls: "OUTRIGGERS MUST BE IN PLACE BEFORE LIFT IS MADE".
f. Device(s) to limit vertical creep of payload to not more than one inch per hour.

3.10.1 Tire grasping device. A device designed to grasp and hold, while lifting or positioning, up to and including off highway tires of 3,000 lbs weight and 100 inches diameter shall be provided. The device shall incorporate the ability to rotate and tilt while loaded to maximum capacity.

3.10.2 Hydraulic fluid. Hydraulic fluid conforming to the manufacturer's standard or recommended requirements, shall be provided in the hydraulic system. A corrosion-resistant caution plate, located near the hydraulic system fill port, stating type of hydraulic fluid required, shall be furnished.

3.11 Jack. When specified (see 6.2), jacking unit of not less than 40-ton lifting capacity shall be furnished. The jacking unit shall consist of a hydraulic jack and an air powered hydraulic pump, with connecting hose lines and operating controls. The pump shall operate at any air pressure from 50 to 200 psig, developing the rated capacity at approximately 100 psig. Pump shall be equipped with a safety valve. The jack shall be manually operated by controls located on the pump. Provisions for securing the jacking unit to the truck deck or in storage areas during travel shall be provided.

3.12 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the machine. When only one system of measurement is acceptable, the particular system required shall be as specified (see 6.2). In this specification, all measurements, dimensions, sizes and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in ASTM E 380.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

3.13 Mounting provision for tire demounter. When specified (see 6.2), provisions shall be made to secure a portable type tire demounter to the deck. Attachment shall be of quick-disconnect type.

3.14 Mounting bracket for grinder. When specified (see 6.2), a detachable bracket to convert a portable pneumatic grinder to a bench grinder shall be furnished. The bracket shall be designed to accommodate a grinder conforming to OO-G-669, type I, size 6 inch. A quick detachable device shall be furnished to mount the bracket near the right rear corner of the body.

3.15 Floodlights. Two sealed-beam floodlights, not less than 4 1/2 inches in diameter, with swivel mounts, shall be mounted, one on each side at rear of cab for illuminating the work area.

3.16 Treatment and painting. Unless otherwise specified (see 6.2), the tire truck shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the truck other than corrosion-resisting steel shall be protected against corrosion and present a neat appearance.

3.17 Identification marking. Identification shall be permanently and legibly marked directly on the truck or on a corrosion-resisting plate securely attached to the truck at the source of manufacturer. Identification shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

3.18 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.19 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type and grade lubricant, specified in the operator's manual, recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

* 3.20 Servicing and adjusting. Prior to acceptance of the truck by the government, the contractor shall service and adjust the truck, air compressor unit, and crane assembly for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Wheel alignment, (when required).
e. Adjustment of engine to include tune-up, (when required).
f. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:27Z
Check the source to verify that this is the current version before use.

g. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The truck and compressor unit, (see 3.8.1.) shall be conspicuously tagged to identify the lubricants and their temperature range.

* 3.21 Lifting and tiedown attachments. When specified (see 6.2), The truck shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the truck. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the truck on the carrier when shipped.

3.22 Workmanship.

3.22.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.22.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.22.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.22.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the current version before use.

of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of government representatives. This inspection shall include the examination of 4.3 and the test of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the government of its right under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.

4.3 Examination. Each truck shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 20261O-20T22:27Z
Check the source to verify that this is the current version before use.

4.4 First production vehicle tests.

4.4.1 Vehicle weight. The first production vehicle shall be weighted to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle shall be computed using the curb weight, the operator weight at 175 lbs, and payload (see 3.4.2 and 3.4.3), to provide the specified gvw. The calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, axles, and tires furnished are of adequate capacity to meet requirements of 3.6.8, 3.6.10, 3.6.11, and 3.6.11.1.

4.4.2 Road test. The tire servicing truck assembled as specified and loaded to rated gvw shall be driven a minimum of 50 miles over improved hard surfaced roadways at speeds up to and including 50 mph. Upon completion of improved road test, the truck shall be driven over unimproved and uneven surfaces with front axle and hubs engaged for a minimum distance of 10 miles. Upon completion of the road test, the crane and compressor shall be operated and the truck with all equipment inspected for malfunction or damage. Compartment doors shall shut tightly without evidence of distortion or racking of the body. Evidence of distortion, cracks, or breaks in frame or body shall cause rejection.

4.4.3 Lift tests. The following shall be performed to determine conformance to 3.9 and 3.10. A load shall be placed on the ground at the side of the truck 15 feet from the centerline of the crane base. The load shall be lifted and lowered onto the deck; lifted again and lowered to the ground. Test shall be repeated with a load placed 8 feet from the centerline of the crane base. The specified tests shall be performed at each radius with the maximum rated capacity at each radius. All hydraulic controls shall be operated and maximum reach movements performed during these tests. Controls shall be tested not less than five times, and at least three simulated hydraulic failures shall be created in each hydraulic circuit during these tests to verify the reliability of the safety stop devices. The tire grasping device shall be tested by grasping a tire of approximately 100 inches in diameter and weighing near 3,000 lbs. The tire shall be held by grasping or squeezing the outer circumference tread surface, lifted from a horizontal plane, tilted to a vertical position and rotated a minimum of 180°. The tire shall be loaded, onto the bed, and unloaded a minimum of three cycles, each time releasing and regrasping the tire.

4.4.4 Compressor test. The compressor unit shall be operated for 1 hour with the truck on level ground, to determine conformance to 3.8 through 3.8.5.

4.4.5 Jack tests. When jack is specified, a compressor hose shall be connected to the air-hydraulic pump of the jacking unit. A load of not less than 40 tons shall be lifted to the maximum height of the jack, held for not less than 5 minutes, and released, to determine conformance to 3.11. Test shall be repeated at least five times. Repeat five cycles of the above lifting tests with the jack raised to one-half of maximum lift height. Compressor and jacking unit shall then be examined for possible defects.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the currentversion before use.

4.4.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the government to refuse acceptance of all vehicles under the contract until corrective action has been taken.

4.4.7 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and may be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.5 Production truck tests. The contractor's testing system shall, as a minimum, assure that the truck is capable of meeting performance requirements contained herein. At the point of final acceptance the contractor shall make available to the government records acceptable to the government indicating that the servicing and adjusting required by 3.20 has been accomplished.

4.6 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

* 5.1 Vehicle processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved, packed, and marked in accordance with MIL-V-62038 with the level of preservation and packing as specified (see 6.2).

* 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The truck is intended for use as a maintenance truck equipped for tire servicing for buses, trucks, and applicable off-road vehicles.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When trailer towing package is required (see 3.3.5 and 3.6.15.2).
d. When battery, of maintenance free characteristics, is required (see 3.6.2.5).
e. When transmission speeds or style varies from specified (see 3.6.5.1).
f. When drive hubs are required (see 3.6.5.3).
g. When spare wheel and carrier are required (see 3.6.13).
h. When spare tire is required (see 3.6.14).
i. When air dryer is required (see 3.6.15.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.

j. When automatic slack adjusters are required (see 3.6.15.1).
k. When towing vehicle brake control facilities required (see 3.6.15.3).
l. When spare wheel assembly tools are required (see 3.6.20.1).
m. When jack is required (see 3.11).
n. When specific measurement system required (see 3.12).
o. When tire demounter attachment is required see 3.13).
p. When mounting bracket to hold portable grinder is required (see 3.14).
q. Color and type of paint required for final coating (see 3.16).
r. When rustproofing is required (see 3.18).
s. When lifting and tiedown is required (see 3.20).
t. When vehicle shall be preserved, packed, and marked in accordance with MIL-V-62038 the level of preservation-packing required (see 5.1).

* 6.3 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract or purchase order requirements.

6.4 Performance prediction. Completed copies of SAE J688 form and computation for speed requirements for each truck model furnished under contract should be submitted as specified in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still dry air. The SAE Work Sheet Item I should include truck model number, wheel base, engine model number, transmission model number, and truck type. The factors to be used in predicting truck ability (see 3.5.1.1) are established as follows for the corresponding SAE J688 tables:

Table 1	- Tire Factor. This factor relates to the size of tires furnished by the contract in accordance with this specification.	
Table 2	- Altitude Factor.	1.00
Table 3	- Rolling Factor.	1.613
Table 4	- Area Factor.	0.173
Table 5	- Velocity Factor.	250.0
Table 6	- Altitude Factor.	1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit gvw (to nearest, higher 1,000 lbs) and the engine revolutions per minute (to nearest 100 revolutions) which is required for 50 mph geared speed. For gvw and engine speed beyond the range of this table, factors shall be extrapolated.	
Table 8	- Grade Factor.	1.75
Table 8A	- Correction Factor.	Not required
Table 9	- Road Factor.	0.0

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:27Z
Check the source to verify that this is the current version before use.

* 6.5 Subject term (key word) listing.

Air compressor
Servicing
Tire truck

Custodian:
Navy - YD

Preparing Activity:
Navy - YD

(Project 2320-N452)

GPO 920-139

Source: https://assist.dla.mil -- Downloaded: 20610-807220277
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-29243A(YD)	2. DOCUMENT DATE (YYMMDD) 14 February 1991

3. DOCUMENT TITLE
TRUCK, TIRE SERVICING: DIESEL ENGINE DRIVEN, 46,000 POUNDS GVW, 6X6

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDING OFFICER NAVAL CONSTRUCTION BATTALION CENTER CODE 156	b. TELEPHONE (Include Area Code) (1) Commercial: (805) 982-5572 (2) AUTOVON: 551-5572
c. ADDRESS (Include Zip Code) PORT HUENEME, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 Previous editions are obsolete. 198

Source: https://assist.dla.mil - Downloaded: 2026-10-20T22:27Z
Check the source to verify that this is the current version before use.