MILITARY SPECIFICATION

TRANSPONDER SET: FORWARD AIR CONTROL, AN/PPN-18

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the general requirements for a Forward Air Control Transponder Set, AN/PPN-18. This equipment is a portable manpack radar transponder designed for field service. The transponder set shall consist of a transponder, antenna, battery, external power cable, and a carrying bag.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-E-485	- Enamel, Semi-Gloss, Rust-Inhibiting.

MILITARY

MIL-T-152	- Treatment, Moisture-And Fungus-Resistance, of Communication, Electronic, And Associated Electrical Equipment.
MIL-T-704	- Treatment And Painting Of Materiel.
MIL-P-15024	- Plate, Tags and Bands For Identification Of Equipment.
MIL-E-16400	- Electronic, Interior Communication and Navigation Equipment, Naval Ship and Shore, General Specification For.
MIL-E-17555	- Electronic And Electrical Equipment, Accessories, And Repair Parts, Packaging And Packing Of.
MIL-M-38510	- Microcircuits, General Specification For.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129	- Marking For Shipment And Storage.
MIL-STD-130	- Identification Marking Of U.S. Military Property.
MIL-STD-454	- Standard General Requirements For Electronic Equipment.
MIL-STD-461	- Electromagnetic Interference Characteristics, Requirements For Equipment.
MIL-STD-462	- Electromagnetic Interference Characteristics, Measurement Of.
MIL-STD-463	- Definition And System Of Units, Electromagnetic Interference Technology.
MIL-STD-749	- Preparation And Submission Of Data For Approval Of Nonstandard Parts.
MIL-STD-781	- Reliability Tests Exponential Distribution.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-883	- Test Methods And Procedures For Microelectronics.

DRAWINGS

U. S. MARINE CORPS

301424G	- Cable Assembly, Power, Electrical, Branched (CX-12430/PPN-18) (Mfr. Code 23115).
301429P	- Antenna (AS-2544A/PPN-18) (Mfr. Code 23115).
DL 400549G 1/	- Data List (Transponder Set, Forward Air Control, AN/PPN-18) (Mfr. Code 23115).
400593G	- Receiver-Transmitter Transponder (RT-999/PPN-18) (Mfr. Code 23115).
76A5116A0000	- Transponder Set, Forward Air Control, AN/PPN-18 (Mfr. Code 01365).
76A5116A0001	- Carrying Bag, Transponder Set (Mfr. Code 01365).

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

1/ Less Drawing No. 400549G (replaced by Drawing No. 76A5116A0000) and Drawing No. 400555P (replaced by Drawing No. 76A5116A0001).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish six first articles in order to determine conformance to this specification. Examinations and tests shall be as specified herein. Approval of first articles by the procuring activity shall not relieve the contractor of compliance with any requirements of this specification. Changes and deviations of production equipments from the approved first articles shall require approval of the contracting officer.

3.2 Parts and materials. The selection of parts and materials shall be in accordance with MIL-E-16400 except as specified herein.

3.2.1 Standard parts. Standard parts shall be as specified in MIL-E-16400.

3.2.2 Nonstandard parts. Nonstandard parts shall be as defined in MIL-E-16400. Request for approval of nonstandard parts shall be submitted in accordance with MIL-STD-749.

3.2.3 Integrated circuits. Maximum use shall be made of microelectronics and integrated circuit design in the construction of electronic equipment. Integrated circuits proposed for use in the transponder set shall be submitted for approval in accordance with MIL-STD-749. Integrated circuits shall be capable of withstanding the examinations and testing requirements of MIL-STD-883 and MIL-M-38510.

3.2.4 Fungus treatment. Parts and materials which may support fungus shall be treated in accordance with MIL-T-152 before installation in the transponder set.

3.3 Design and construction. The transponder set shall consist of a transponder, antenna, battery, external power cable and a carrying bag (see Drawing No. 76A5116A0000). The transponder shall be designed using modular construction and shall be repairable without special tools. Replaceable assemblies shall be of plug-in design and shall permit rapid interchange with spare assemblies. Circuit design and construction shall make use of solid state techniques as much as possible. Transponder sets furnished under this specification shall be designed and constructed to meet the general equipment requirements of MIL-E-16400, DL 400549G and as specified herein.

3.3.1 Transponder. The transponder shall consist of a receiver, transmitter, power supply, video amplifier, coder, modulator, and electronics component assembly (see Drawing No. 400593G). These units shall be contained in a waterproof housing of lightweight, high-strength material. The transponder shall be designed to operate within a voltage range of 24 to 31.1 volts direct current (Vdc) on power supplied from a BB-451/U or BB-626/U battery, or from an external direct current (dc) source with a voltage range of 24 to 31.1 Vdc. Power supplied by the BB-626 battery shall be applied directly to the transponder case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

3.3.1.1 Receiver. The receiver shall meet the following requirements.

3.3.1.1.1 Frequency range. Receiving frequency range and bandwidth shall be from 16.0 to 17.0 gigahertz using a crystal video detector.

3.3.1.1.2 Sensitivity. Transponder shall respond to received signals of 40 decibels (dB) below 1 milliwatt (mW), with a probability of 0.99. This shall be accomplished with an assumed false alarm rate of no greater than one false alarm per ten-second interval.

3.3.1.1.3 Signal input protection. The receiver shall not be damaged by an input signal level of 20 dB above 1 mW.

3.3.1.1.4 Interrogation pulse width. The receiver shall respond to interrogation pulses of 0.2 to 1.0 microsecond in width.

3.3.1.1.5 Interrogation pulse repetition frequency. The receiver shall be capable of multiple aircraft operation.

3.3.1.2 Transmitter. The transmitter shall meet the following requirements.

3.3.1.2.1 Frequency. Transmitter frequency shall be capable of being set to the specified frequency in the J frequency band within a tolerance of ±250 kilohertz measured under standard conditions. The frequency shall be provided by the procuring activity (see 6.2).

3.3.1.2.2 Frequency stability. Transmitter frequency shall not drift more than ±2.5 megahertz from the specified frequency in the J frequency band over entire operating temperature range when the transponder set has reached operating temperature.

3.3.1.2.3 Peak radio frequency (rf) power. Peak rf power shall be a minimum of 600 watts measured at the transponder antenna connector.

3.3.1.2.4 Pulse width. Transmitted pulse shall be 0.2 microsecond in duration with a tolerance of +0.05, -0.00 as measured at the 50-percent waveform point.

3.3.1.2.5 Pulse repetition frequency. Transmitter shall be capable of transmitting 0.2 microsecond coded pulses at a variable rate to 3,000 pulses per second.

3.3.1.3 Delay. Transponder delay shall be 0.3 ±0.05 microsecond between 0 dB and 30 dB below 1 mW received power level from receipt of an interrogation pulse and the first reply pulse transmission. Should any redesign effort be necessary to meet the time delay requirement,

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

design modifications will be held to a minimum due to logistics support considerations.

3.3.1.4 Response. The transponder shall be capable of responding with double or triple pulses within a space of 40 microseconds utilizing one modulator. These pulses shall be capable of providing a radar display in all aircraft radar modes of operation to include automatic moving target indication mode and shall have six distinct permuted codes. Specific codes shall be supplied by the procuring activity.

3.3.1.5 Recovery time. Transponder recovery time shall not exceed 50 microseconds.

3.3.1.6 Warm-up time. For magnetron warm-up considerations, the time required after application of power for the interrogate light to operate and magnetron transmission to occur shall be 1.5 ±0.5 minutes.

3.3.2 Antenna. The antenna shall be designed for horizontal polarization and omnidirectional transmit/receive (see Drawing No. 301429P). The antenna shall be mounted directly on top of the transponder during operational use. A compartment shall be provided inside the transponder housing for storage of the antenna when it is nonoperational. The waterproof integrity of the transponder shall be maintained when the antenna is stowed or is installed for operation. Protection by mechanical means shall be provided to prevent cross polarization upon antenna installation. The antenna shall transmit and receive horizontally polarized signals at the frequencies specified herein. The omnidirectional radiation pattern characteristics shall, while the antenna is mounted upon the transponder, be uniform within ± 2 dB in the horizontal plane. The radiation pattern in the vertical plane shall have a half power beam width of 40 degrees (minimum). The vertical radiation pattern shall range from -10 degrees to +30 degrees from the horizon. The antenna gain between the half power points shall be no less than 0 dB relative to an isotropic radiator. The antenna input voltage standing wave ratio (vswr) shall be less than 2.0:1.

3.3.2.1 Antenna storage cap. A dummy connector shell shall be provided adjacent to the antenna connector for storage of the antenna connector cover when the antenna is installed for operation.

3.3.3 External power cable. An 8-foot-length power cable shall be provided with a connector on one end to mate with the transponder external power connector (see Drawing No. 301424G). The other end shall have alligator clips suitable for attaching to vehicle battery terminals.

3.3.4 Controls and indicators. All controls and indicators shall be operable under blackout conditions with no visible light showing more

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

than 3 meters from the transponder set. All controls and indicators shall be protected against damage during operational conditions and during shipment.

3.3.4.1 Power switch. A three-position toggle switch shall select power source from battery or external power with a center "OFF" position.

3.3.4.2 Code selector. A six-position switch shall select the desired pulse code. Pulse code selections shall be designated by letters A through F.

3.3.4.3 Battery indicator. An indicator lamp shall be provided to indicate when the input voltage is within the normal operating range (24.0 to 31.1 Vdc). The lamp shall glow when the input voltage is 24.0 Vdc or more. The lamp shall not glow (shall be extinguished) when the input voltage is 22.0 Vdc or less.

3.3.4.4 Interrogation indicator. An indicator lamp shall be provided to indicate when the transponder is being interrogated, and shall operate only when the transponder is interrogated.

3.3.4.5 Transmit indicator. An indicator lamp shall be provided to indicate when the transponder set is transmitting, and shall operate only when the transponder is transmitting.

3.3.5 Power source.

3.3.5.1 Voltage. The transponder shall operate from an external dc source with a voltage range of 24.0 to 31.1 Vdc.

3.3.5.2 Current. Quiescent current shall not exceed 500 milliamperes (mA) when the voltage is 28 Vdc. Maximum current drain, when the transponder is replying at 3,000 pulses per second, shall not exceed 800 mA.

3.3.5.3 Power connection. The transponder shall be capable of being mounted directly on a BB-451/U or BB-626/U battery and connected thereto without external devices. Electrical means shall be provided to prevent transponder or battery damage and insure proper operation and there shall be no degradation of performance nor other deleterious effects to the equipment or materials if inserted in either orientation. A connector shall be provided on the top panel for external power operation.

3.3.5.4 Polarity protection. The transponder shall not be damaged by, and shall operate with, reversed polarity of the external power source.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

3.3.5.5 Overvoltage protection. The transponder shall be protected against overvoltages above normal operating voltage levels. The transponder shall operate normally at 35 Vdc for a period of 10 minutes and shall also withstand transient voltage levels up to 50 Vdc maximum for a period not to exceed 1 second.

3.3.6 Carrying bag. A canvas carrying bag shall be provided to hold the transponder, battery and external power cable (see Drawing No. 76A5116A0001). Means shall be provided so that the power cable may be installed without removing the transponder from the carrying bag. The bag shall have adjustable shoulder straps which may also be used as a carrying handle. The carrying bag shall be constructed for heavy duty use and shall be of water repellant material.

3.3.7 Interchangeability. Interchangeability shall be in accordance with requirement 7 of MIL-STD-454.

3.4 Reliability.

3.4.1 Reliability demonstration. Reliability demonstration on equipment shall be performed in accordance with Test Level A-1, Test Plan III of MIL-STD-781.

3.4.2 Mean time between failure (MTBF). The specified MTBF for the transponder set shall be 1,000 hours. One change of the transmitter magnetron will be allowed after 500 hours operation time.

3.5 Performance. Performance requirements of the transponder set shall be as specified herein.

3.5.1 Temperature conditions. The transponder set shall be capable of continuous reliable operation under the temperature range of -25°C to +60°C (both operating and nonoperating). Equipment shall not be damaged, nor shall the operational performance be degraded, when restored to operation after being exposed for long periods (24 hours) in the nonoperating condition.

3.5.2 Humidity. The transponder set shall operate at a minimum relative humidity of 95 percent for both continuous and intermittent periods and over the temperature range to +60°C.

3.5.3 Altitude. The transponder set shall withstand the reduced pressure conditions as encountered during shipment by air and shall operate satisfactorily under the pressure conditions of high ground elevations.

3.5.4 Sunshine. The transponder set shall operate satisfactorily when exposed to solar radiation during service and operation at ground level. There shall be no damage nor deterioration to the equipment or materials such as paints and plastics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

3.5.5 Rain. The transponder set shall operate satisfactorily when exposed to rain under operating service conditions.

3.5.6 Shock. The transponder set shall be designed and constructed to withstand the shock test requirements of MIL-STD-810, method 516.2, procedures, I, II, and V.

3.5.7 Vibration. The transponder set shall withstand the vibration test requirements of MIL-STD-810, method 514.2, procedure X.

3.6 Electromagnetic interference suppression. The transponder set shall meet the electromagnetic interference requirements of MIL-STD-461 in accordance with the criteria cited in MIL-STD-462 and MIL-STD-463; Test Methods CE01, CE03, CE06 in conjunction with Test Methods RE03, CS06 and RS02 shall be performed.

3.7 Dimensions. The transponder shall not exceed 5.5 inches in height, 11.44 inches in length and 4.69 inches in width including the battery skirt. Dimensions include the housing case but exclude protrusions (except battery skirt), battery and mounted antenna.

3.8 Weight. The maximum weight of the transponder set, without battery, shall be 10.3 pounds.

3.9 Treatment and painting. Treatment and painting of the transponder set shall be in accordance with MIL-T-704 with enamel conforming to TT-E-485. Color shall match Marine Corps green No. 23 (see 6.3).

3.10 Marking and identification. Identification marking shall be permanent and legible in accordance with MIL-STD-130. Identification plates shall be in accordance with MIL-P-15024. Request for approval and supporting drawings shall be submitted prior to first article testing.

3.1 Workmanship. Workmanship practices shall be in accordance with requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First Article (see 4.3)

(b) Production (see 4.4)

(c) Sample (see 4.5)

4.3 First article inspection. First article inspection shall consist of all examinations and tests necessary to determine compliance with the requirements specified herein and shall include examinations and tests specified in Table I. First article inspection and testing shall be witnessed by a representative of the contracting officer.

4.4 Production inspection. Production inspection shall be made on every transponder set offered for delivery. This inspection shall comprise examinations and tests which will prove workmanship and manufacturing processes. Functional and performance tests which detect deviations from design shall be performed. Production inspection shall include the examinations and tests specified in Table I.

4.5 Sample inspection. Sample inspection shall cover functional, performance and environmental tests. These tests shall be performed on one transponder set out of each ten offered for delivery. Sample inspection shall include the examinations and tests specified in Table I.

4.6 Test procedures. Detailed procedures for conducting inspection and tests shall be prepared by the contractor and submitted to the procuring activity for review and approval. Inspections and tests shall consist of all examination and testing specified herein to demonstrate that transponder sets submitted for approval meet the requirements of this specification.

4.7 Test reports. The contractor shall prepare test reports and submit them to the contracting officer.

4.8 Approval. Approval of the first article shall be by the contracting officer upon satisfactory completion of all tests.

4.9 Acceptance. With exception of the first articles, acceptance of all transponder sets shall be by the cognizant Government inspector.

4.10 Inspection and tests. All environmental tests shall be conducted in accordance with MIL-STD-810 as specified herein. Standard conditions shall be as specified for standard ambient conditions in MIL-STD-810. The sequence of testing shall be as specified in Table I, Group 1E of MIL-STD-810. Reference measurements shall be taken and considered as

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

Table I. Inspections and Tests

Test	Test Paragraph	First Article	Production Sample	
Surface examinations	4.10.1	X	X	X
Weights and dimensions	4.10.12 4.10.13	X		X
Operating tests	4.10.2	X	X	X
Low temperature	4.10.3	X	X	X
High temperature	4.10.3	X	X	X
Altitude	4.10.4	X		X
Sunshine	4.10.5	X		
Temperature shock	4.10.6	X		
Leakage	4.10.7	X		X
Rain	4.10.8	X		
Humidity	4.10.9	X		
Shock	4.10.10	X		X
Vibration	4.10.11	X		X
Electromagnetic interference	4.10.14	X		
Reliability	4.10.15	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

pretest data before conducting tests to determine satisfactory performance as specified herein. Standard test conditions and test setups shall be established during visual inspection and each test.

4.10.1 Visual inspection. The transponder set shall be examined for the following:

(a) Workmanship, assembly and fit, mechanical safety, and marking.

(b) Materials, parts, and finish.

(c) Treatment for prevention of corrosion.

4.10.2 Operating test. The transponder set shall be energized and subjected to operating tests specified in Table II to insure proper functioning of the transponder set, including all operating controls.

4.10.3 Temperature tests. The transponder set shall be subjected to temperature tests as follows:

(a) First article. The transponder set shall be tested in accordance with the following procedures.

(1) Low temperature: Method 502.1 of MIL-STD-810. Storage time and temperature shall be 24 hours at -25°C. Transponder set shall be turned on and interrogated and data recorded a minimum of four times during the 24-hour operating test.

(2) High temperature: Method 501.1, procedure II, of MIL-STD-810. Storage time and temperature shall be 24 hours at +66°C. Transponder set shall be cycled between +24°C and +60°C for three 12-hour cycles.

(b) Production. The transponder set shall be temperature cycled to the temperature extremes of -25°C and +60°C and shall be temperature stabilized for minimum of 60 minutes at each temperature extreme before electrical test.

(c) Sample. The transponder set shall be tested in accordance with (a) above, except that two 12-hour cycles of high temperature test shall be performed.

4.10.4 Altitude. The transponder set shall be subjected to altitude test in accordance with method 500.1, procedure I, of MIL-STD-810.

4.10.5 Sunshine. The transponder set shall be subjected to sunshine test in accordance with method 505.1, procedure II, of MIL-STD-810. The transponder set shall be operated (uninterrogated) for 30 minutes at 6-hour intervals during each 24-hour cycle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

Table II. Operating tests

Test	Requirement paragraph
Receiver frequency	3.3.1.1.1
Receiver bandwidth	3.3.1.1.2
Receiver sensitivity	3.3.1.1.3
Receiver interrogation pulse width	3.3.1.1.5
Receiver interrogation pulse repetition frequency	3.3.1.1.6
Transmitter frequency	3.3.1.2.1
Transmitter frequency stability	3.3.1.2.2
Transmitter peak power	3.3.1.2.3
Transmitter pulse width	3.3.1.2.4
Transmitter pulse repetition frequency	3.3.1.2.5
Transponder delay	3.3.1.3
Transponder code response	3.3.1.4
Transponder recovery time	3.3.1.5
Antenna beam width	3.3.2
Battery operation and current	3.3.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

4.10.6 Temperature shock. The transponder set shall be subjected to temperature shock test in accordance with method 503.1 of MIL-STD-810. Temperature extremes shall be -25°C and +60°C.

4.10.7 Leakage. The transponder shall be pressure tested (nonoperating) for leakage in accordance with method 512.1, procedure I, of MIL-STD-810. The transponder shall be pressurized to 7.5 pounds-force per square inch and fully immersed in water. All surfaces and internal components shall be carefully examined for any sign of leakage.

4.10.8 Rain. The transponder set shall be subjected to rain test in accordance with method 506.1, procedure I, of MIL-STD-810. The following additional details shall apply during the test:

(a) Amount of rain shall be 10 inches per hour for 10 minutes and 24 inches per hour for 5 minutes reduced to 10 inches for 15 minutes respectively.

(b) Transponder set shall be operated (uninterrogated) during last 10 minutes of each 30-minute cycle.

(c) All sides of transponder set shall be exposed.

4.10.9 Humidity. The transponder set shall be subjected to humidity test in accordance with method 507.1, procedure IV, of MIL-STD-810.

4.10.10 Shock. The transponder set shall be subjected to shock test in accordance with method 516.2, procedures I, II and V, of MIL-STD-810. For procedure I, Figure 516.2-1 (GROUND EQUIPMENT Columns) shall apply. Shock test shall be performed without battery.

4.10.11 Vibration. The transponder set shall be subjected to vibration test in accordance with method 514.2, procedure X, of MIL-STD-810; vibration test curves shall be in accordance with Figure 514.2-7, curve AX.

4.10.12 Dimensions test. The transponder set shall be measured to determine compliance with 3.7.

4.10.13 Weight test. The transponder set shall be weighed to determine compliance with 3.8.

4.10.14 Electromagnetic interference test. The transponder set shall be tested to determine compliance with the requirements of MIL-STD-461, MIL-STD-462, and MIL-STD-463; Test Methods CE01, CE03, CE06 in conjunction with Test Methods RE03, CS06 and RS02 shall be performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

4.10.15 Reliability test. Reliability testing shall be conducted in accordance with Test Level A-1, Test Plan III of MIL-STD-781 with a specified MTBF of 1,000 hours.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. Preservation, packaging and packing shall be the level of shipment specified in the contract or order in accordance with MIL-E-17555 (see 6.2).

5.2 Marking. Marking for shipment and storage shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The transponder set covered by this specification shall serve as a ground locator reference point when used with airborne Radar Systems AN/APQ-92, AN/APQ-112, AN/APQ-126, AN/APQ-148 and similar types of radar systems. The transponder set shall increase the capabilities of these radar systems by receiving pulsed interrogations and transmitting encoded pulsed replies of greater signal strength in the same frequency band.

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.

(b) When first article is not required (see 3.1).

(c) Frequency required (see 3.3.1.2.1).

(d) Levels of preservation, packaging, and packing (see 5.1).

6.2.2 Contract data requirements. Data conforming to Data Item Descriptions DI-T-1902, DI-T-1910, DI-E-4528, DI-E-4542, DI-R-4803, DI-R-4806, DI-T-4901, DI-T-4902, DI-T-4903, DI-T-4904, DI-T-4906, DI-T-4907 and DI-T-4908 will usually be required for delivery in connection with this specification. Data will be specified on a DD Form 1423 included in the contract.

6.3 Color. Color chips for Marine Corps green, No. 23, may be obtained from Commandant of the Marine Corps, Code LMO-1, Headquarters U. S. Marine Corps, Washington, D. C. 20380.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

6.4 First article. First article equipment shall be examined and tested at contractor's plant or an independent commercial testing laboratory acceptable to the Government.

6.5 Supersession data. This specification includes the requirements of Marine Corps Purchase Description 73-1A, Transponder Set: Forward Air Control, AN/PPN-18 dated 22 May 1975.

Preparing Activity:
Navy - MC
Project No. 5895-N253

*U.S. GOVERNMENT PRINTING OFFICE: 1976-703-020/1584

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commandant of the Marine Corps
Headquarters, Marine Corps
ATTN: Code LMO-1
Washington, DC 20380

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:32Z
Check the source to verify that this is the current version before use.