MIL-A-55059C
3 November 1975
SUPERSEDING
MIL-T-55059B
25 April 1968

MILITARY SPECIFICATION

ADAPTER, BATTERY TERMINAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of positive and negative terminal adapters for storage batteries (see 6.1 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-S-698	-	Steel, Sheet and Strip, Low Carbon.

Military

MIL-L-13808	-	Lead Plating (Electrodeposited).
MIL-P-14232	-	Parts, Equipment and Tools for Army, Materiel, Packaging and Packing of.

STANDARDS

Federal

FED-STD-151	-	Metals; Test Methods

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	-	Identification Marking of Military Property.
MIL-STD-129	-	Marking for Shipment Storage.
MS-75004	-	Adapter, Battery Terminal

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing office, Washington, D. C. 20402.)

3. REQUIREMENTS

3.1 Construction. Terminal adapters shall be constructed with a die cast body having a steel insert for reinforcing the core and provisions for bolt and nut for clamping to the battery posts and a bolt and nut for mounting the leads. The insert shall be imbedded in and completely covered by the body alloy and all dimensions shall be in accordance with MS-75004.

3.2 Material.

3.2.1 Body. The body of the terminal adapter shall be a die cast alloy of lead and antimony containing 6 to 7 1/2 percent antimony.

3.2.2 Insert. The insert shall be Steel, sheet or strip HR (pickeled and oiled) or CR commercial quality (temper 2-5), conforming to QQ-S-698.

3.2.3 Bolts and nuts. Bolts and nuts for clamping to the battery post and for the mounting of leads shall be steel having a minimum tensile strength of 55,000 pounds per square inch (psi). Screw threads shall be in accordance with Handbook H28.

3.3 Finish. Bolts and nuts shall be lead plated in accordance with type II, class 2 of MIL-L-13808.

3.4 Assembly. Completed terminal adapters shall have bolts and nuts assembled in place.

3.5 Terminal identification. The letters "P" or "N" and the signs "+" or "-" shall be cast, engraved or stamped on the top face of each terminal adapter for identification of positive or negative terminals as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

3.6 Marking. Marking shall conform to MIL-STD-130 and shall consist of the MS part number and manufacturers identification.

3.7 Workmanship. The workmanship shall be such as to insure a product free of sharp edges, the insert shall be completely covered by the lead alloy and the die cast body shall be free of all voids or pits which would affect its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certification. The supplier is responsible for providing certification for materials and processes used in the manufacture of this item.

4.2 Quality conformance inspection.

4.2.1 Sampling.

4.2.1.1 Lot formation. A lot shall consist of all terminal adapters from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.2.1.2 Sampling for quality conformance examination. Samples for quality conformance examination shall be selected in accordance with MIL-STD-105.

4.2.2 Examination inspection.

4.2.2.1 Acceptable quality level. Each adapter terminal selected in accordance with 4.2.1.2 shall be examined for conformance to the following acceptable quality level (AQL) on the basis of percent defective.

Classification	AQL
Major	2.5
Minor	4.0

4.2.2.2 Classification of defects. For examination purposes, defects shall be classified as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

Table I. Classification of defects

Categories		Method of Inspection
Major		
101	Dimensions affecting interchangeability not within tolerance (see 3.1).	Gage
102	Completeness of assembly (see 3.4).	Visual
103	Terminal identification (see 3.5).	Visual
Minor		
201	Dimensions not affecting interchangeability tolerance (see 3.1).	S.I.E*
202	Improper marking (see 3.6).	Visual
203	Faulty workmanship (see 3.7).	Visual

*Standard Inspection Equipment

4.3 Inspection of preparation for delivery.

4.3.1 Materials and processes. The Government inspector shall at unscheduled intervals, inspect all materials and processes involved in the preparation for delivery, to determine conformance to requirements of Section 5. Any evidence of deviation from specified requirements shall be cause for refusal to conduct further inspection until objective evidence has been provided by the contractor that corrective action has been taken.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. Preservation, packaging and packing shall be level A, B, or C (see 6.2), as specified on the appropriate packaging data sheet or standard.

6. NOTES

6.1 Intended use. Adapter terminals (positive and negative) are used for mounting and fastening of leads to the SAE tapered post of battery terminals by the nuts and bolts provided in the adapter terminals.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Positive or negative terminal (see 1.1).
(c) Selection of applicable level of preservation, packaging, and packing (see 5.1).

Custodian:
Army - AT
Navy - MC
Air Force - 85

Preparing activity:
Army - AT

Project No. 5940-0758

User activities:
Army - EL, ME
Navy - YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:20Z
Check the source to verify that this is the current version before use.