
INCH-POUND
MIL-PRF-55681/5F
24 March 2025
SUPERSEDING
MIL-PRF-55681/5E
10 October 2006

PERFORMANCE SPECIFICATION SHEET


CAPACITOR, CHIP, MULTIPLE LAYER, FIXED, CERAMIC DIELECTRIC, ESTABLISHED RELIABILITY AND NON-ESTABLISHED RELIABILITY, STYLES CDR21, CDR22, CDR23, CDR24, AND CDR25 (HIGH FREQUENCY)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55681.




Style CDR21




Style CDR22

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.




Style CDR23



Style CDR24

FIGURE 1. Dimensions and configuration - continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.



Style CDR25

Inches	mm
.001	0.03
.004	0.10
.005	0.13
.015	0.38
.016	0.41
.020	0.51
.025	0.64

Inches	mm
.030	0.76
.093	2.36
.100	2.54
.110	2.79
.135	3.43
.250	6.35
.500	12.70

Dimensions						
STYLE	L	W	T		L1	F
			Min	Max	Max 1/	Max 2/
CDR21	.135 ± .015	.110 ± .015	.030	.100	.020	---
CDR22	.135 ± .015	.110 ± .015	.030	.100	.020	---
CDR23	.135 ± .015	.110 ± .015	.030	.100	.020	.020
CDR24	.135 ± .015	.110 ± .015	.030	.100	.020	.020
CDR25	.135 ± .015	.110 ± .015	.030	.100	.020	---

1/ Solder buildup over each lead.
2/ Solder fill.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in millimeters and are given for general information only.

FIGURE 1. Dimensions and configuration - continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Terminals: Termination finish S or T. Silver leads, when applicable, are attached with solder having a melting temperature of greater than +200° C.

Inspection conditions: All visual examinations shall be performed using a stereo microscope having a minimum magnification of 20 power.

Capacitance value: See table I.

Capacitance tolerance: See table I.

Rated voltage: See table I.

Operating temperature range: -55° C to +125° C.

Dissipation factor: In accordance with MIL-PRF-55681.

Insulation resistance:

At +25° C ± 5° C: 10^6 megohms, minimum (for 0.1 pF through 470 pF); 10^5 megohms, minimum (for 510 pF through 5,100 pF).

At +125° C ± 5° C: 10^5 megohms, minimum (for 0.1 pF through 470 pF); 10^4 megohms, minimum (for 510 pF through 5,100 pF).

Equivalent series resistance: In accordance with MIL-PRF-55681.

Terminal strength: In accordance with MIL-PRF-55681.

Product level designator: Non-established Reliability - C; Established Reliability - M, P, R, and S.

Marking: In accordance with MIL-PRF-55681.

NOTE: These capacitors are intended for use in RF solid-state circuitry up to and including 25 gigahertz, and cannot be replaced in the field.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.

TABLE I. Styles CDR21, CDR22, CDR23, CDR24, and CDR25 capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	Rated voltage V_{dc}
CDR2-B-0R1EB - -	0.1	B	BG, BP	500
CDR2-B-0R2EB - -	0.2	B	BG, BP	500
CDR2-B-0R3E - - -	0.3	B,C	BG, BP	500
CDR2-B-0R4E - - -	0.4	B,C	BG, BP	500
CDR2-B-0R5E - - -	0.5	B,C,D	BG, BP	500
CDR2-B-0R6E - - -	0.6	B,C,D	BG, BP	500
CDR2-B-0R7E - - -	0.7	B,C,D	BG, BP	500
CDR2-B-0R8E - - -	0.8	B,C,D	BG, BP	500
CDR2-B-0R9E - - -	0.9	B,C,D	BG, BP	500
CDR2-B-1R0E - - -	1.0	B,C,D	BG, BP	500
CDR2-B-1R1E - - -	1.1	B,C,D	BG, BP	500
CDR2-B-1R2E - - -	1.2	B,C,D	BG, BP	500
CDR2-B-1R3E - - -	1.3	B,C,D	BG, BP	500
CDR2-B-1R4E - - -	1.4	B,C,D	BG, BP	500
CDR2-B-1R5E - - -	1.5	B,C,D	BG, BP	500
CDR2-B-1R6E - - -	1.6	B,C,D	BG, BP	500
CDR2-B-1R7E - - -	1.7	B,C,D	BG, BP	500
CDR2-B-1R8E - - -	1.8	B,C,D	BG, BP	500
CDR2-B-1R9E - - -	1.9	B,C,D	BG, BP	500
CDR2-B-2R0E - - -	2.0	B,C,D	BG, BP	500
CDR2-B-2R1E - - -	2.1	B,C,D	BG, BP	500
CDR2-B-2R2E - - -	2.2	B,C,D	BG, BP	500
CDR2-B-2R4E - - -	2.4	B,C,D	BG, BP	500
CDR2-B-2R7E - - -	2.7	B,C,D	BG, BP	500
CDR2-B-3R0E - - -	3.0	B,C,D	BG, BP	500
CDR2-B-3R3E - - -	3.3	B,C,D	BG, BP	500
CDR2-B-3R6E - - -	3.6	B,C,D	BG, BP	500
CDR2-B-3R9E - - -	3.9	B,C,D	BG, BP	500
CDR2-B-4R3E - - -	4.3	B,C,D	BG, BP	500
CDR2-B-4R7E - - -	4.7	B,C,D	BG, BP	500
CDR2-B-5R1E - - -	5.1	B,C,D	BG, BP	500
CDR2-B-5R6E - - -	5.6	B,C,D	BG, BP	500
CDR2-B-6R2E - - -	6.2	B,C,D	BG, BP	500
CDR2-B-6R8E - - -	6.8	B,C,J,K,M	BG, BP	500
CDR2-B-7R5E - - -	7.5	B,C,J,K,M	BG, BP	500
CDR2-B-8R2E - - -	8.2	B,C,J,K,M	BG, BP	500
CDR2-B-9R1E - - -	9.1	B,C,J,K,M	BG, BP	500
CDR2-B-100E - - -	10	F,G,J,K,M	BG, BP	500
CDR2-B-110E - - -	11	F,G,J,K,M	BG, BP	500
CDR2-B-120E - - -	12	F,G,J,K,M	BG, BP	500
CDR2-B-130E - - -	13	F,G,J,K,M	BG, BP	500
CDR2-B-150E - - -	15	F,G,J,K,M	BG, BP	500
CDR2-B-160E - - -	16	F,G,J,K,M	BG, BP	500
CDR2-B-180E - - -	18	F,G,J,K,M	BG, BP	500
CDR2-B-200E - - -	20	F,G,J,K,M	BG, BP	500
CDR2-B-220E - - -	22	F,G,J,K,M	BG, BP	500
CDR2-B-240E - - -	24	F,G,J,K,M	BG, BP	500
CDR2-B-270E - - -	27	F,G,J,K,M	BG, BP	500
CDR2-B-300E - - -	30	F,G,J,K,M	BG, BP	500
CDR2-B-330E - - -	33	F,G,J,K,M	BG, BP	500
CDR2-B-360E - - -	36	F,G,J,K,M	BG, BP	500
CDR2-B-390E - - -	39	F,G,J,K,M	BG, BP	500
CDR2-B-430E - - -	43	F,G,J,K,M	BG, BP	500
CDR2-B-470E - - -	47	F,G,J,K,M	BG, BP	500
CDR2-B-510E - - -	51	F,G,J,K,M	BG, BP	500
CDR2-B-560E - - -	56	F,G,J,K,M	BG, BP	500

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.

TABLE I. Styles CDR21, CDR22, CDR23, CDR24, and CDR25 capacitor characteristics - continued.

PIN 1/	Capacitance pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	Rated voltage V_{dc}
CDR2-B-620E - - -	62	F,G,J,K,M	BG, BP	500
CDR2-B-680E - - -	68	F,G,J,K,M	BG, BP	500
CDR2-B-750E - - -	75	F,G,J,K,M	BG, BP	500
CDR2-B-820E - - -	82	F,G,J,K,M	BG, BP	500
CDR2-B-910E - - -	91	F,G,J,K,M	BG, BP	500
CDR2-B-101E - - -	100	F,G,J,K,M	BG, BP	500
CDR2-B-111D - - -	110	F,G,J,K,M	BG, BP	300
CDR2-B-121D - - -	120	F,G,J,K,M	BG, BP	300
CDR2-B-131D - - -	130	F,G,J,K,M	BG, BP	300
CDR2-B-151D - - -	150	F,G,J,K,M	BG, BP	300
CDR2-B-161D - - -	160	F,G,J,K,M	BG, BP	300
CDR2-B-181D - - -	180	F,G,J,K,M	BG, BP	300
CDR2-B-201D - - -	200	F,G,J,K,M	BG, BP	300
CDR2-B-221C - - -	220	F,G,J,K,M	BG, BP	200
CDR2-B-241C - - -	240	F,G,J,K,M	BG, BP	200
CDR2-B-271C - - -	270	F,G,J,K,M	BG, BP	200
CDR2-B-301C - - -	300	F,G,J,K,M	BG, BP	200
CDR2-B-331C - - -	330	F,G,J,K,M	BG, BP	200
CDR2-B-361C - - -	360	F,G,J,K,M	BG, BP	200
CDR2-B-391C - - -	390	F,G,J,K,M	BG, BP	200
CDR2-B-431C - - -	430	F,G,J,K,M	BG, BP	200
CDR2-B-471C - - -	470	F,G,J,K,M	BG, BP	200
CDR2-B-511B - - -	510	F,G,J,K,M	BG, BP	100
CDR2-B-561B - - -	560	F,G,J,K,M	BG, BP	100
CDR2-B-621B - - -	620	F,G,J,K,M	BG, BP	100
CDR2-B-681A - - -	680	F,G,J,K,M	BG, BP	50
CDR2-B-751A - - -	750	F,G,J,K,M	BG, BP	50
CDR2-B-821A - - -	820	F,G,J,K,M	BG, BP	50
CDR2-B-911A - - -	910	F,G,J,K,M	BG, BP	50
CDR2-B-102A - - -	1,000	F,G,J,K,M	BG, BP	50
CDR2-B-112A - - -	1,100	F,G,J,K,M	BP	50
CDR2-B-122A - - -	1,200	F,G,J,K,M	BP	50
CDR2-B-132A - - -	1,300	F,G,J,K,M	BP	50
CDR2-B-152A - - -	1,500	F,G,J,K,M	BP	50
CDR2-B-162A - - -	1,600	F,G,J,K,M	BP	50
CDR2-B-182A - - -	1,800	F,G,J,K,M	BP	50
CDR2-B-202A - - -	2,000	F,G,J,K,M	BP	50
CDR2-B-222A - - -	2,200	F,G,J,K,M	BP	50
CDR2-B-242A - - -	2,400	F,G,J,K,M	BP	50
CDR2-B-272A - - -	2,700	F,G,J,K,M	BP	50
CDR2-B-302A - - -	3,000	F,G,J,K,M	BP	50
CDR2-B-332A - - -	3,300	F,G,J,K,M	BP	50
CDR2-B-362A - - -	3,600	F,G,J,K,M	BP	50
CDR2-B-392A - - -	3,900	F,G,J,K,M	BP	50
CDR2-B-432A - - -	4,300	F,G,J,K,M	BP	50
CDR2-B-472A - - -	4,700	F,G,J,K,M	BP	50
CDR2-B-502A - - -	5,000	F,G,J,K,M	BP	50
CDR2-B-512A - - -	5,100	F,G,J,K,M	BP	50

1/ Complete PIN will include additional symbols to indicate style, voltage-temperature limits, capacitance tolerance (where applicable), termination finish ("T" for styles CDR21, CDR22, and CDR24, and "S" for styles CDR23 and CDR25), and product level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2025-013)

Review activities:
Navy - AS, MC
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:54Z
Check the source to verify that this is the current version before use.