MIL-T-53023A(ME)
AMENDMENT 2
11 May 1988
SUPERSEDING
AMENDMENT 1
11 May 1987

MILITARY SPECIFICATION

TACTICAL WATER DISTRIBUTION EQUIPMENT SYSTEM (TWDS - SEIS),

10 MILE SEGMENT

This amendment forms a part of MIL-T-53023A(ME), dated 3 April 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defence.

PAGE 2

* 2.1.1, under SPECIFICATIONS, MILITARY, delete MIL-A-8421 in its entirety.

PAGE 3

* 2.2, delete AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), D 3951 in its entirety.

3.7c, delete "2-100 gpm" and substitute "2-350 gpm"; delete "4610-00-880-0154 or 4610-00-937-6862" and substitute "MIL-H-12732".

PAGE 6

4.4.1, line 4, delete "AQL 2.5" and substitute "AQL 1.0".

PAGE 8

* 4.6.1.2.1, lines 1 and 2 (2 places), delete "(see 5.3.1.1)" and substitute "(see 5.3.1)".

* 4.6.1.2.2, lines 1 and 2 (2 places), delete "(see 5.3.1.1)" and substitute "(see 5.3.1)".

* 4.6.2.1, line 2, delete "(see 5.3.1.1 and 5.3.1.2)" and substitute "(see 5.3.1 and 5.3.2)".

AMSC N/A FSC 4320
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:50Z
Check the source to verify that this is the currentversion before use.

* 4.6.2.3, delete in its entirety and substitute:

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following defects. The AQL shall be 1.0 percent defective.

No.	Defect	Level A	Level C
110.	Preservative that adversely affects water applied to surfaces that contact potable water.	5.2	5.2
111.	Components procured by a Federal or Military specification not preserved as specified.	5.2.1	5.2.2
112.	Components not procured by a Federal or Military specification not preserved as specified.	5.2.1	5.2.2
113.	Components not consolidated as specified.	5.2.1.1	5.2.2
114.	Consolidation containers not as specified.	5.2.1.1	5.2.2
115.	Components not formed into groupings as specified.	5.3.1	5.3.1
116.	Crates not as specified.	5.3.2	5.3.3
117.	Level A crates exceed size limitations.	5.3.2	
118.	Marking not as specified.	5.4	5.4"

PAGE 9

* 5.2, delete in its entirety and substitute:

"5.2 Preservation. Preservation shall be level A or C as specified (see 6.2). Preservatives applied to any surface that will contact potable water shall not adversely affect the potability of the water."

* 5.2.1, lines 8 thru 10, delete last sentence in its entirety.

5.2.1.1, line 16, delete last sentence and substitute "Closure for boxes made to comply with PPP-B-601 shall be in accordance with the unnailed closure option specified in section 1 therein. The strapping of boxes made to comply with PPP-B-621 shall not be required. The length of the box shall be limited to that which is required to produce a snug-fitting container around the physical dimensions of the largest component(s) contained therein."

* 5.2.2, delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:50Z
Check the source to verify that this is the current version before use.

"5.2.2 Level C. Components of the set procured by a Federal or Military specification shall be preserved in accordance with either the level C or commercial preservation requirements as contained in the applicable specification. All other components of the set shall be preserved in a manner that will provide protection against deterioration and damage from the contractor to the initial destination. This level may conform to the contractor's standard practice when such meets the requirements of the level. Components so preserved, shall be consolidated together in a manner best suited to accomplish the grouping and packing specified in 5.3."

PAGE 10

* 5.3 thru 5.4, delete in their entirety and substitute the following:

* "5.3 Packing. Packing shall be level A or C as specified (see 6.2).

* "5.3.1 Grouping. Components of the set, preserved as specified in 5.2, shall be formed into eight separate groups as follows: Group 1 shall consist of all components comprising the pumping station except for the 600 GPM pumping assembly. Group 2 shall consist of all components comprising the storage assembly except for the 20,000 gallon collapsible tank. Group 3 shall consist of all components comprising the distribution point except for the 125 GPM pump. Group 4 shall consist of all components comprising the 10 mile segment except for the 6-inch, 500 foot length hose assembly. Group 5 shall consist of the 600 GPM pumping assembly. Group 6 shall consist of the 20,000 gallon collapsible tank. Group 7 shall consist of the 125 GPM pump. Group 8 shall consist of the 6-inch, 500 foot length hose assembly. Components in one group shall not be intermixed with components from another group.

* "5.3.2 Level A. Components of the set, segregated into groups as specified in 5.3.1, shall be packed as follows: Groups 1, 2, 3 and 4 shall be packed in a minimum number of crates conforming to MIL-C-104, type II, class 1 or 2, style A. The outside dimensions of the crates shall be limited to 115 inches in length, 86 inches in width, and 50 inches in height in order to be compatible for shipment in 150 containers. However, the crate length may be increased to accommodate the longest consolidation container length (see 5.2.1.1). The contents of the crate shall be blocked, braced and anchored in accordance with MIL-STD-1186. Groups 5, 6, 7 and 8 shall be packed in accordance with the level A packing requirements of the specification applicable to the item in the group.

* "5.3.3 Level C. Components of the set, segregated into groups as specified in 5.3.1 shall be packed for level C in the following manner: Components of the set, procured by a Federal or Military specification, shall be packed in accordance with either the level C, or commercial requirements as contained in

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:50Z
Check the source to verify that this is the current version before use.

the applicable specification. All other components of the set shall be packed in a manner that will assure arrival at destination in satisfactory condition. This level, as a minimum, shall comply with applicable carrier rules and regulations and may be the contractor's standard practice when such meets the requirements of the level."

* 5.4 Marking. In addition to any special or identification markings required by the contract or purchase order (see 6.2), all markings shall be in accordance with MIL-STD-129. When a package contains a single component or a series of components making up a known set, assembly or group, special care shall be exercised so that each container is marked as specified therein."

PAGE 11

* 6.2, after "g", add: "h. Any special marking (see 5.4)."

PAGE 12

20.1.1, under SPECIFICATIONS, FEDERAL, add:

"WW-N-351 - Nipple, Pipe, Threaded."

* Under MILITARY SPECIFICATIONS, delete MIL-C-10387 in its entirety.

PAGE 13

20.1.1, under SPECIFICATIONS, MILITARY, delete MIL-G-53017 and MIL-R-82184 in their entirety;

and add:

"MIL-P-53054 - Pumping Assembly, Water, Wheel Mounted, Diesel-Engine-Driven, Self-Priming Centrifugal, 6-inch, 600 GPM at 350 Feet Total Head."

Under MILITARY SPECIFICATIONS 12732 delete "Controlled 2 to 100 GPM Flow" and substitute "Controlled 2-350 GPM Flow."

PAGE 15

First item (Coupling, clamp, pipe), delete "(2 coupling halves, 1 gasket for potable water, 2 bolts and nuts; (81349) MIL-C-10387, C10387-1-D-11" and substitute "(includes gasket for potable water), (79154) style 791".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:50Z
Check the source to verify that this is the current version before use.

Delete: "Guard Road Crossing: (81349) MIL-G-53017; (97403) dwg 13226E1576" and substitute:

"Guard Road Crossing: (97403) dwg 13226E1576".

PAGE 16

Under "Skid", line 3, delete "part No. 6"-906-01BV" and substitute "part No. 6"-90G-01BV"; delete fourth line entirely and substitute "(97403) dwg 133225E9090, Find No. 14".

Under Swivel Joint, line 3, delete "dwg 13225E9199" and substitute 13225E9195".

* After tenth item (Swivel joint), add "Tool, Assembly: Coupling, clamp, (79154) style 792, 4 ea".

PAGE 17

* First item (Coupling, clamp, pipe), delete "(2 coupling halves, 1 gasket for potable water 2 bolts and nuts; (81349) MIL-C-10387, C10387-1-D-11" and substitute "(includes gasket for potable water), (79154) style 791".

Delete: "1 ea. Pumping Assembly: 600 gpm @ 350 tdh, DED, wheel mounted, 6 x 6 Victaulic connections, intervehicular connections for 24-volt electric system; (97403) dwg 13225W9180" and substitute:

"1 ea. Pumping Assembly: 600 GPM @ 350 Ft TDH, DED, wheel mounted 6 x 6 Victaulic connections, intervehicular connections for 24-volt electric system; (81349) MIL-P-53054".

* After last item (Relief valve assembly), add "1 ea Tool, Assembly: Coupling, clamp (79154) style 792".

PAGE 18

Under 4730-00-088-9285, delete "4 ea." and substitute "3 ea."

Under 4730-00-938-7997, delete "4 ea." and substitute "3 ea."

Add the following:

"4730-00-088-9286 - 1 ea. Coupling Half, Quick Disconnect: Cam-locking, female, aluminum, class 1, (96906) MS 27024-17

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:50Z
Check the source to verify that this is the current version before use.

"4730-00-840-0797 - 1 ea. Coupling Half, Quick Disconnect: Cam-locking, male, aluminum, class 1, (96906) MS 27022-17

PAGE 19

* Delete the third item in its entirety: "7 ea. Hose Assembly.....dwg 13225E9136-2".

Add: "Meter Assembly, Fluid Flow Indicating, EA, 2, consisting of meter, with flange to quick-disconnect cam-locking fittings and adapter connections. (97403) Dwg 13225E9177 and 13225E9178-1."

PAGE 20

First item (Hypochlorination Unit), delete "4610-00-880-0154" and "4610-00-937-6862"; delete "(09680) 1955-1" and substitute "(09680) 1955-3"; delete "(79172) A-506131".

Under 4730-01-064-0560:

First item (MS49000-17), delete "1 ea." and substitute "2 ea."

Third item (MS49000-19), delete "1 ea." and substitute "2 ea."

Add the following:

"1 ea. Nipple, Brass, 4 inch nom. dia., 6 inch long, type II, std weight, (81348) WW-N-351

"2 ea. Swivel, Hose: Aluminum Body, (97403) Dwg 13225E9139-3".

PAGE 21

* Under TWDS (RDF) Storage Assembly, first item (Coupling, clamp, pipe), delete "(2 coupling halves, 1 gasket for potable water, 2 bolts and nuts; (81349) MIL-C-10387, C10387-1-D-11" and substitute "(includes gasket for potable water), (79154) style 791".

* Under TWDS (RDF) Storage Assembly, second item (Coupling, clamp, pipe), delete "(2 coupling halves, 1 gasket for potable water, 2 bolts and nuts; (81349) MIL-C-10387, C10387-1-D-09" and substitute "(includes gasket for potable water), (79154) style 791".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:50Z
Check the source to verify that this is the current version before use.

PAGE 22

After 5430-01-106-9678, add:

* "1 ea. Tool Assembly: Coupling, clamp, (79154) style 792".

"5430-01-168-0589 1 ea. Chest Water Tank 90598.....20,000".

PAGE 24

Third item (Coupling, clamp, pipe), delete "(2 coupling halves, 1 gasket for potable water, 2 bolts and nuts); (81349) MIL-C-10387, C10387-1-D-11" and substitute "(includes gasket for potable water), (79154) style 791".

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4320-A286

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:50Z
Check the source to verify that this is the current version before use.