MIL-D-21757C
9 June 1978
SUPERSEDING
MIL-D-21757B
6 November 1969

MILITARY SPECIFICATION

DISPENSER, COMPRESSIBLE BOTTLE, CONDIMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of cylindrical plastic condiment dispenser.

1.2 Classification. Plastic condiment dispensers shall be of the following sizes as specified (6.2):

Size 2 - 8 fluid ounces capacity (237 ml)
Size 3 - 12 fluid ounces capacity (355 ml)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATION

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 - Marking for Shipment and Storage

LAWS AND REGULATIONS

US DEPARTMENT OF HEALTH, EDUCATION AND WELFARE

Federal Food, Drug and Comestic Act and Regulations Promulgated Thereunder

21 CFR 121: Subpart F - Food Additives Resulting From Contact with Containers or Equipment and Food Additives Otherwise Affecting Food

(The Code of Federal Regulation (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The condiment dispensers delivered under this specification shall be the manufacturer's commercially current standard product, except for any changes necessary to comply with specification requirements.

3.2 Materials. The dispenser shall be fabricated from a polyethylene plastic material, or other plastic material, which is suitable for condiment dispensers, and is not affected by high water temperature, soap, detergents, and chlorine and will maintain a hard, smooth, and easily cleanable surface. The plastic material shall conform to the requirements of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (see 4.2 and 6.5).

3.3 Design. The dispenser shall consist of two components, the body and cap or cover. The dispenser, when inverted and upon application of hand pressure to the bottle, shall dispense a quantity of condiments through the cap. When the pressure is released the condiment shall not continue coming out of the orifice (see 4.4.4).

3.3.1 Cap. The cap shall be in the shape of a conical spout terminating in a dispensing orifice. The other end shall employ a shoulder utilizing one or two complete female threads designed to engage the male threads of the bottle.

3.3.2 Bottle. The top of the bottle shall include the filling orifice which shall be not less than 3/4 inch (19 mm) inside diameter. The male threaded portion will employ one or two complete threads and shall be designed to engage the female threaded portion of the cap.

3.3.3 Fit. The top of the male threaded portion of the bottle shall seat against the top inside shoulder of the cap. The bottom edge of the female threaded cap shall not seat against the top or shoulder of the bottle.

* 3.4 Capacity. The dispenser shall have a capacity of 8 or 12 fluid ounces (± 0.2 ounce) (237 or 355 ± 6 ml) when tested as described in 4.4.1.

3.5 Permanent deformation. The dispenser shall not be permanently deformed when tested as described in 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

3.6 Color. The color of the dispenser shall be natural (translucent).

3.7 Workmanship. The dispensers shall be free from bubbles, voids, cracks, blemishes, foreign inclusions, cloudy surfaces, discoloration, or any misfit between the threads which would prevent the cover from sealing against the top of bottle.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Certificates of compliance. The contractor shall furnish the contracting officer or his authorized representative a certificate of compliance stating that all materials and processes used in the manufacture of the dispensers comply with all applicable provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. The Government reserves the right to check test the materials when deemed necessary to determine the validity of the certification.

4.3 Quality assurance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.2 Visual examination. Examination of the end item shall be in accordance with the classification of defects in table I. The inspection level shall be level II with an AQL of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:28Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Burrs or slivers, stain, discoloration, bubbles, pits, scratches, crevices (deep enough to hold food particles or dirt) foreign inclusions	X	
Construction, design and workmanship	Part missing	X	
	Part fractured, split, or malformed	X	
	Threads (don't draw tight)	X	
	Fit between top and bottle improper	X	

4.3.3 Dimensional examination. The end item shall be examined to determine compliance with the dimension specified in 3.3.2. If the dimension does not meet the requirement, it shall be classified as a defect. The inspection level shall be level II with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.3.4 End item testing. One sample unit shall be selected at random from each lot and tested in accordance with 4.4.1 to 4.4.4, as applicable.

* 4.3.5 Packaging inspection. An examination shall be made to determine whether the preservation-packaging, packing and marking complies with the section 5 requirements. Defects shall be in accordance with table II. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be level II and the AQL shall be 2.5 defects per hundred units.

TABLE II. Examination of packaging

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; incomplete; illegible; of improper size, location, sequence or method of application.
Materials	Any nonconforming component; component missing, defective, damaged, or not as specified.
Workmanship	Bulged or distorted container.
Contents	Number per container not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

4.3.5.1 Examination of shipping containers. When shipping containers are required to comply with PPP-B-636, examination for defects in closure, waterproofing and reinforcing shall be in accordance with the appendix of the container specification.

4.4 Test methods.

4.4.1 Capacity test. Fill a measuring container with 8 or 12 fluid ounces (237 or 355 ml) of water, as appropriate. Pour the water into the dispenser bottle. Fill the bottle to the shoulder. If the bottle in the sample does not hold at least 8 or 12 fluid ounces (± 0.2 ounce) (237 or 355 ± 6 ml) as appropriate, the entire lot shall be rejected.

4.4.2 Deformation test. Fill the samples with water and completely immerse them in a suitable container. The dispensers shall not be in contact with each other or the container. The water shall be heated to 180°F (82°C) and held at that temperature for 15 minutes. The samples shall then be removed and allowed to cool to room temperature. The samples shall then be examined for evidence of permanent deformation. If any evidence of permanent deformation is apparent, the entire lot shall be rejected.

4.4.3 Detergent test. Repeat 4.4.2 above, except that 2 fluid ounces (59 ml) of common dishwashing detergent and 2 ounces (57 gm) of common chlorine bleach shall be added per gallon of water and heated to 180°F (82°C) and held at that temperature for 15 minutes. The samples shall then be removed and allowed to cool to room temperature. The samples shall be examined for evidence of deformation or reaction with detergent or bleach. If any evidence is apparent, the entire lot shall be rejected.

4.4.4 Dispensing test. The body shall be filled with mustard or ketchup, the cap replaced, the dispenser inverted and pressure applied to the sides of the body. Upon release of the pressure the condiment shall cease flowing from the cap as required in 3.3. If flow continues, the orifice design should be revised.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Twelve dispensers of one size only shall be preserved-packaged in a snug-fitting fiberboard box conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 200. Each box shall be securely closed in accordance with method II as specified in the appendix of PPP-B-636.

5.1.2 Level C. Dispensers shall be preserved-packaged to afford adequate protection against physical damage during shipment from the supplier to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A packing. Forty-eight dispensers (4 boxes) of one type only preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Forty-eight dispensers (4 boxes) of one type only preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be securely closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.2.3 Level C packing. Dispensers preserved-packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Dispensers are intended to be used for the dispensing of mustard, ketchup, and similar condiments.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

(c) Selection of the applicable level of preservation-packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Supersession data. Size 1 - 6 fluid ounces (177 ml) and size 4 - 16 fluid ounces (473 ml) deleted. Size 1, no requirement, size 4, not commercially available.

6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Navy - CG
DLA - GS

Preparing activity:

Army - GL

Project No. 7350-0189

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-D-21757C
DISPENSER, COMPRESSIBLE BOTTLE, CONDIMENT

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-19T10:28Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MA 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

COMMANDER
US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND
ATTN: DRDNA-ES
NATICK, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:28Z
Check the source to verify that this is the current version before use.