MIL-I-21685(AS)
AMENDMENT -- 3
28 March 1979
SUPERSEDING
AMENDMENT - 2
1 November 1961

MILITARY SPECIFICATION

INDICATOR, COMPASS REPEATER, ROTATING DIAL,
TYPE MW-2

This amendment forms a part of Military Specification MIL-I-21685(AER) dated 10 November 1958 and has been approved by the Naval Air Systems Command, Department of the Navy.

By this amendment basic MIL-I-21685(AER) is changed to MIL-I-21685(AS) and throughout the specification Bureau of Aeronautics shall be changed to Naval Air Systems Command.

Page 1

Paragraph 2.1, under SPECIFICATIONS Military: Delete

MIL-D-5028	Drawings and Data Lists: Preparation of Manufacturers (For Production Aeronautical and Associated Equipment)
MIL-L-6880	Lubrication of Aircraft, General Specification for
MII-S-7742	Screw Threads, Standard, Aeronautical
MIL-P-7936	Preparation for Delivery of Naval Aeronautical Equipment; General Specification for

Add

MIL-S-7742	Screw Threads, Standard, Optimum Selected Series; General Specification for
MIL-D-1000	Drawings, Engineering and Associated Lists

FSC 6605

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:19Z
Check the source to verify that this is the current version before use.

Paragraph 2.1, under STANDARDS Military: Delete

MS33586 Metals, Definition of Dissimilar

Add

MIL-STD-143 Specifications and Standards, Order of Precedence for the Selection of

MIL-STD-794 Parts and Equipment, Procedures for Packaging and Packing of

MIL-STD-838 Lubrication of Military Equipment

MIL-STD-889 Dissimilar Metals

MS28105 Window, Dial - Aircraft Instrument Cover, Glass

Delete

Air Force-Navy Aeronautical

AN-5727 Glass-Aircraft Instrument Cover

PUBLICATIONS

Air Force-Navy Aeronautical Bulletin

No. 143 Specifications and Standards, Use of

(When requesting any of the applicable documents refer to both title and number. Copies of this specification and applicable documents may be obtained upon application to the Commanding Officer, Naval Aviation Supply Depot, 700 Robbins Avenue, Philadelphia, Pennsylvania, Attention: Code CDS).

Add

2.1.1 Availability of Documents -

(1) When requesting specifications, standards, drawings, and publications, refer to both title and number. Copies of this specification and applicable specifications required by contractors in connection with specific procurement functions may be obtained upon application to the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:19Z
Check the source to verify that this is the current version before use.

Paragraph 3.2: Delete "ANA Bulletin 143" and substitute "MIL-STD-143"

Page 3

Paragraph 3.3.2.1: Delete "MS33586" and substitute "MIL-STD-889"

Paragraph 3.6.3: Delete "AN5727" and substitute "MS28105"

Page 6

Paragraph 3.11: Delete "MIL-D-5028" and substitute "MIL-D-1000"

Paragraph 3.12.4: Delete "MIL-L-6880" and substitute "MIL-STD-838"

Page 9

Paragraph 4.6.5: Delete and substitute

"4.6.5 Synchro null - Make electrical connections as shown in Figure 3. With switches open, turn the rotor shaft until a minimum voltage is obtained on voltmeter V_1. The rotor will now be in the true electrical zero position or 180 degrees away. With the switches closed, voltmeter V_2 is then used to distinguish between the 15 volts which occur in the true electrical zero and the 38 volts which occur in the false electrical zero. The nose of the airplane on the mark shall indicate "N" on the dial when the synchro is nulled at true electrical zero. To set electrical zero accurately, a sensitive vacuum tube voltmeter must be inserted between the yellow and blue leads, (see Figure 2), the switches opened, and a fine setting made on the rotor position to obtain the minimum voltage, approximately 10 millivolts."

Page 12

Paragraphs 5.1.1, 5.2.1, and 5.3: Delete "MIL-P-7936" and substitute "MIL-STD-794"

Custodian:
Navy - AS

Preparing Activity:
Navy - AS
Project No. 6605-N258

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:19Z
Check the source to verify that this is the current version before use.