MILITARY SPECIFICATION

INDICATOR, AIRSPEED, PITOT STATIC,

MAXIMUM ALLOWABLE SPEED, 40-400 KNOTS

This amendment forms a part of Military Specification MIL-I-21718(Aer) 20 November 1958 and has been approved by the Bureau of Aeronautics, Department of the Navy.

Page 4 Figure 1

Delete: "Lusterless red color no. 31136 of FED-STD-595"

Substitute: "Lusterless white color no. 37875 of FED-STD-595"

Add the following:

Marking	Height or Length	Width of Line or Grad ± .005	Finish
Unshaded portion of the indicated airspeed pointer	- - -	- - -	Lusterless black color no. 37038 of FED-STD-595

Page 5 Paragraph 3.9.1

Delete: "1.5"

Substitute: "1.625"

Page 6 Paragraph 3.10.2 Delete.

Substitute: 3.10.2 Case Connections.- The back of the case adjacent to the applicable connection shall be marked with the letter "P" for the pressure connection and with the word "STATIC" printed twice, forming a ring around the static connection conforming to Standard MS25333. The following shall also be marked on the back of the case:

"CAUTION: DO NOT BLOW IN TUBES.

USE STRAIGHT THREAD FITTINGS ONLY."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:23Z
Check the source to verify that this is the current version before use.