MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, M29A2 ASSEMBLY

This amendment forms a part of Military Specification MIL-C-46615B(MU), dated 7 June 1974, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete: "MIL-E-5272 . . ." in its entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

PAGE 2

3.3 Delete: ". . . MIL-E-5272, Procedure X11 . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5 . . .".

PAGE 13

4.4.1 Delete: ". . . MIL-E-5272, Procedure X11" and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5"

Preparing activity:
Navy - OS
Project No. 1377-N843

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.