INCH-POUND

MIL-DTL-46618C (OS)
01 March 2011
SUPERSEDING
MIL-C-46618B
20 May 1990

DETAIL SPECIFICATION
CARTRIDGE IMPULSE, M73 ASSEMBLY

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M73 Impulse Cartridge (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed..

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-A-2550 Ammunition, General Specification for

MIL-A-8625 Anodic Coatings for Aluminum and Aluminum Alloys

Comments, suggestions, or questions on this document should be addressed to DEPARTMENT OF THE NAVY, Indian Head Division, NSWC, E12AP, Document Control, 4123 Artisans Court, Suite 103, Indian Head, MD 20640-5085 OFFICIAL BUSINESS, or emailed to amanda.penn@navy.mil. Since contact information can change, you may want to verify the currency of this information using the ASSIST Online database at https://assist.daps.dla.mil.

AMSC N/A FSC 1377

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-810 Environmental Engineering Considerations and Laboratory Tests

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

DRAWINGS

NAVAL SEA SYSTEMS COMMAND (CAGE Code 53711)

5184857 Closed Bomb Assembly, M73

NAVAL ORDNANCE STATION (CAGE Code 19200 and 19203)

DL8594157 Cartridge, Impulse, M73 Assembly

8797373 Box, Fiberboard (Inner), Packing, Ammunition, For Cartridge, Impulse M44A1 or M73

8797441 Box, Packing, Ammunition, For Cartridge, Impulse M44A1 or M73

9225380 Box, Fiberboard (Outer), Alternative Packing Ammunition, For Cartridge, Impulse M44A1 or M73

(Application for copies should be addressed to the DEPARTMENT OF THE NAVY, Indian Head Division, NSWC, Code E12P, Document Control, 4123 Artisans Court, Suite 103, Indian Head, Maryland 20640-5085, OFFICIAL BUSINESS.)

2.3 Non-Government publications and drawings. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN NATIONAL STANDARD INSTITUTE (ANSI)/AMERICAN SOCIETY FOR QUALITY (ASQ)

ANSI/ASQ Z1.4 Sampling Procedures and Tables for Inspection by Attributes

ANSI/ASQ Q9000 Quality management systems - Fundamentals and vocabulary

(Copies of these documents are available online at http://webstore.ansi.org/ansidocstore/default.asp, or from the American Society for Quality, PO Box 3005, 600 N. Plankinton Ave., Milwaukee, WI 53203)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 1742/E 1742M Standard Practice for Radiographic Examination

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

(Copies of this document are available online at http://www.astm.org or from the American Society for Testing and Materials Customer Service, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a first article sample shall be subjected to first article inspection (see 4.4, 6.2, and 6.3).

3.2 Conformance to documents. The M73 Impulse Cartridge covered by this specification shall be manufactured in accordance with DL8594157 and all documents listed thereon.

3.3 Materials. All materials used in the manufacture of the cartridges shall conform strictly to the specifications referred to on the respective drawings unless specific approval in writing covering a departure there from has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 Components.

3.4.1 Primary components. For the purpose of this specification, the Ignition Device, igniter charge, and the cartridge propellant charge are considered primary components. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot.

3.4.1.1 Ignition Device. The Ignition Device shall conform to the applicable drawing and reference specification except that the sensitivity of the Ignition Device shall comply with the requirements of 3.4.1.2. Only percussion Ignition Devices from lots manufactured within the last 24 months or recertified within the last 12 months shall be used in these units. Prior to assembly into a cartridge, the Ignition Device shall be visually examined in accordance with 4.6.2 and radiographically examined for defects as specified in 4.7.1.

3.4.1.2 Ignition Device sensitivity of Ignition Device lot. Prior to assembly into a cartridge, the Ignition Device sensitivity of the Ignition Device lot shall be such that the average critical height ($\bar{H}$) plus five standard deviations (5s) shall not exceed 15 inches. The average critical height minus two standard deviations shall not be less than 2-1/2 inches.

3.4.2 Hardness. The hardness of each component part shall be in accordance with the applicable drawing (see 4.7.2).

3.4.3 Protective finish. The finish of each component part shall be in accordance with MIL-A-8625 and the applicable drawing (see 4.7.3).

3.5 Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

3.5.1 Radiographic examination. Each cartridge assembly shall be radiographically examined for defects (see 4.7.4).

3.5.2 Air tightness. Each assembled cartridge shall exhibit no air leakage greater than 1 x 10^{-4} standard cubic centimeters per second (see 4.7.5) at a 14.7 psia pressure differential.

3.5.3 Vibration. The assembled cartridge shall withstand vibration as prescribed in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition 1-3.2.5 without evidence of any disintegration of the Ignition Device, propellant, or igniter, or derangement of any component (see 4.7.6 and 6.2).

3.6 Functional requirements.

3.6.1 Ignition Device sensitivity. The Ignition Device shall fire when drop tested at an energy level of 59 inch-ounces in a sectioned cartridge void of igniter and propellant charge (see 4.7.7.1).

3.6.2 Cartridge performance.

3.6.2.1 Misfires. The cartridge shall not fail to fire.

3.6.2.2 Ballistics. The cartridge, when tested in a closed bomb (Drawing 5184857), shall produce the pressures and ignition delay at temperatures specified in table I (see 4.7.7.2, 6.6.1, and 6.6.2).

TABLE I. Ballistic requirements.

Temperature (°F)	Ignition delay time, max (ms)	Maximum pressure (psig)		Time to Pmax (ms)
		Lower	Upper	
-60 to -70	20	2400	3400	40
65 to 75	20	2400	3400	40
195 to 205	20	2400	3400	40

3.7 Workmanship. Cartridges shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.7.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.7.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter, No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.2 Quality assurance terms and definitions. Reference shall be made to ANSI/ASQ Q9000 to define the quality assurance terms used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

4.2.1 Inspections. Inspections shall be in accordance with MIL-A-2550 and ASTM E 1742/E 1742M.

4.3 Inspection conditions. Unless otherwise specified in the contract or purchase order (see 6.2), inspection conditions shall be as follows:

a. Temperature: Room ambient 20 to 25 °C (68 to 77 °F)
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric: 14.7 psia

4.4 First article inspection. At the beginning of regular production, the supplier shall submit a first article sample to a Government approved facility for evaluation. The sample shall consist of 21 assembled cartridges for ballistics testing including 12 for vibration tests, 5 assembled cartridges for sealant tests, 10 sets of unassembled components for dimensional and visual examination, and a quantity in accordance with 4.4.2, i.e., cartridges assembled without the igniter and propellant charge for Ignition Device sensitivity test. The first article sample shall be manufactured using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. When it becomes necessary to make a change in either the Ignition Device, propellant, or igniter lot after initial production, 12 assembled cartridges from the first production lot thereafter shall be tested in accordance with 4.7.6. The Government reserves the right to require new first article samples until such time as an acceptable sample is submitted (see 6.3).

4.4.1 Examination, tests, and facility. After provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or other such facility specified in the contract (see 6.2).

4.4.2 Sample size for Ignition Device sensitivity. The number of cartridges assembled without igniter or propellant to be submitted for Ignition Device sensitivity tests shall be in accordance with table II.

TABLE II. Ignition Device sensitivity.

Lot Size	Sample Size
3 to 15	3
16 to 25	4
26 to 40	5
41 to 65	7
66 to 110	10
111 to 180	15
181 to 300	25
301 to 500	30
501 to 800	35
801 to 1300	40
Over 1300	50

4.4.3 Temperature conditioning for ballistic test. The sample shall be temperature conditioned and tested to determine compliance with 3.6.2.2. The sample for firing shall be conditioned to table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

TABLE III. Temperature conditioning.

Temperature (°F)	Not vibrated	Vibrated
-60 to -70	3	4
65 to 75	3	4
195 to 205	3	4

4.4.4 First article failure, Failure of the sample to comply with the requirements of the drawings and specifications shall result in first article sample disapproval.

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. The product shall be submitted in accordance with ANSI/ASQ Z1.4.

4.5.1.2 Lot size. Unless otherwise specified (see 6.2), the production lot size shall be not more than 1200 cartridges maximum.
4.5.2 Examination and tests. The quality conformance sample shall be subjected to the examinations of 4.6 and all the test procedures of 4.7 except for 4.7.6.

4.6 Examination. All cartridges and components shall be examined visually and radiographically and characteristics defined in accordance with the applicable drawings. One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4X) magnification may be used in performing visual examination for such defects as burrs and foreign matter. When compliance is in doubt as a result of visual inspection, the characteristic shall be measured or gauged to determine acceptability. All nonconforming items shall be rejected.

4.6.1 Cartridge, Impulse, M73 Assembly, Drawing 859157

Characteristic	Defect	Method of Inspection
Critical		
1	Any part missing	X-ray/Visual
2	Improper assembly	X-ray/Visual
3	Mixed ammunition	Visual
4	Metal Defective	Visual
5	Marking missing, incorrect or illegible	Visual
Major		
101	Cartridge profile failure	Gage
102	Diameter of head, max	Gage
103	Diameter of body, max	Gage
104	Length of datum diameter, max	Gage
105	Protective finish inadequate or defective	Visual
106	Ignition Device crimp missing	Visual
107	Foreign matter present	Visual
108	Burr	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

Minor		
201	Total length, max	Gage
202	Dent	Visual
203	Draw scratch	Visual
204	Fold, wrinkle, buckle, or bulge	Visual
205	Varnish inadequate or missing	Visual
206	Surface Finish improper	Visual

4.6.2 Ignition Device, Percussion, Drawing 851AS500, covering a detail of Drawing 8594157.

Characteristic	Defect	Method of Inspection
Critical		
1	Improper assembly	Visual/X-ray
2	Any part missing	Visual/X-ray
3	Ignition Device pellet broken, cracked or dislodged	Visual
4	Metal defective	Visual
5	Ignition Device sealing paper discolored	Visual
Major		
101	Burr	Visual
102	Foreign matter present	Visual
103	Mixed Ignition Devices	Visual

4.6.3 Case, Cartridge, Drawing 8594158 covering a detail of Drawing 8594157.

Characteristic	Defect	Method of Inspection
Critical		
1	Metal Defective	Visual
Major		
101	Concentricity of large diameter with small diameter	Gage
102	Length to datum diameter	Gage
103	Thickness of base	Gage
104	Thickness of wall	Gage
105	Protective finish inadequate or defective	Visual
106	Foreign matter present	Visual
Minor		
201	Small diameter	Gage
202	Large diameter	Gage
203	Total length	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

204	Flatness of base	Gage
205	Radius missing or incorrect	Visual
206	Surface finish improper	Visual
207	Burr or sharp corner	Visual

4.6.4 Head, Cartridge, Drawing 8594159, covering a detail of Drawing 8594157.

Characteristic	Defect	Method of Inspection
Critical		
1	Perforated Ignition Device vent web	Visual
Major		
101	Concentricity of counterbore, sealing groove diameter, large outside diameter, Ignition Device vent diameter, with Ignition Device pocket	Gage
102	Concentricity of large outside diameter with small outside diameter	Gage
103	Diameter of Ignition Device pocket	Gage
104	Diameter of Ignition Device pocket face counterbore	Gage
105	Diameter of sealing groove	Gage
106	Depth of Ignition Device pocket	Gage
107	Depth of Ignition Device pocket face counterbore	Gage
108	Thickness of Ignition Device vent web	Gage
109	Metal defective	Visual
110	Protective finish inadequate or defective	Visual
111	Surface finish improper	Visual
112	Burr or sharp edge	Visual
113	Foreign matter present	Visual
Minor		
201	Diameter of case crimp counterbore	Gage
202	Diameter of Ignition Device vent	Gage
203	Total length	Gage
204	Depth of external chamfer	Gage
205	Depth of internal chamfer	Gage
206	Angle of internal chamfer incorrect	Visual
207	Radius missing or incorrect	Visual

4.6.5 Box, Fiberboard (Inner), Ammunition, Packing, Drawing 8797373.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
None Defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

Minor

201	Contents loose	Manual/Visual
202	Separator or filler missing	Visual
203	Heat sealer incomplete, loose, or distorted	Visual
204	Cut or damaged through impregnated box	Visual
205	Marking missing, incorrect, or illegible	Visual

4.6.6 Box, Ammunition, Packing, Drawing 8797441

Characteristic	Defect	Method of Inspection

Critical

None defined

Major

None Defined

Minor

201	Contents loose	Manual/Visual
202	Hardware missing, loose, broken, or improperly engaged	Visual
203	Strapping missing, loose, broken, or improperly assembled	Visual
204	Contents of box exposed	Visual
205	Box damaged	Visual
206	Marking missing, incorrect or illegible	Visual
207	Number of cartons incorrect	Visual

4.6.7 Box, Fiberboard (Outer), Alternative, Drawing 9225380

Characteristic	Defect	Method of Inspection

Critical

None defined

Major

None Defined

Minor

201	Contents loose	Manual
202	Box broken or damaged	Visual
203	Number of units contained incorrect	Visual
204	Marking Missing, incorrect or illegible	Visual
205	Tape incomplete	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

4.7 Test methods and procedures.

4.7.1 Ignition Device x-ray. Prior to assembly into the cartridge, the Ignition Device shall be radiographically examined in accordance with ASTM E 1742/E 1742M. Each Ignition Device shall be x-rayed on boards or trays with the cup side perpendicular to the rays. The x-ray negatives shall be identified by item nomenclature and by lot number. Ignition Devices are to be left mounted to the boards or trays until after the x-rays have been reviewed and defects identified to facilitate removal of defective units. After screening, the x-ray negatives with defectives identified, shall be forwarded to the engineering activity designated by the acquiring activity (see 6.2). Interpretation of the radiographic films shall verify the following:

Presence of Ignition Device Charge
No Material Defects

4.7.2 Hardness. Ten units from each heat-treated lot of components shall be tested with a hardness tester. Failure of any unit to comply with the requirements of the drawings shall be cause for rejection of the lot of components.

4.7.3 Protective finish. Sampling plans and procedures in the determination of acceptability of coated parts shall be in accordance with the contract and MIL-A-8625 (see 6.2).

4.7.4 Radiographic examination. All assembled cartridges shall be radiographically examined in accordance with ASTM E 1742/E 1742M. The cartridges shall be positioned on their sides for the most revealing exposure. All cartridges shall be identified with serial numbers prior to examination. The serial numbers shall be in consecutive order beginning with the number 001 in each production lot. The cartridges shall be arranged on trays or boards in consecutive numerical order, and each radiograph shall carry a permanent identification of the cartridges displayed thereon. The radiograph plate identification shall include item nomenclature, the complete lot number as stamped on the cartridges, the span of serial numbers displayed, and the contract number. Cartridges having any observable imperfections in assembly shall be cause for rejection. Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance test. Discontinuities in serial numbers shall be identified on the x-ray negative. Defective cartridges, found by the vendor, shall be clearly identified on the negative and those defectives removed from the production lot. The serial numbers shall be pen or ink stamped on the cartridge with approximately 1/8-inch-high characters. The serial numbers shall be located apart from the other cartridge markings (see 6.2).

4.7.5 Airtightness. Each cartridge shall be subjected to specified pressure differential. The method for determining airtightness shall be with a helium mass spectrometer. The helium leak rate shall be converted to standard cubic inches air. Failure to comply with the requirements of 3.3.2 shall be cause for rejection of the cartridge.

4.7.6 Vibration test. Twelve of the 21 assembled cartridges of the first article sample, x-rayed as directed in 4.7.4, properly identified, shall be subjected to vibration. The method and procedures for performing the vibration test shall be in accordance with MIL-STD-810, Method 514.3, Test Procedure I, Test Condition 1-3.2.5 (see 6.2). Then the 12 vibrated cartridges shall be x-rayed again. Evidence of any disintegration of the Ignition Device, propellant, or igniter, or derangement of any component shall be cause for rejection of the sample.

4.7.7 Functional. The following tests shall be performed by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

4.7.7.1 Ignition Device sensitivity. A quantity of cartridges in accordance with table II, void of igniter and propellant, from the first article sample and each subsequent lot shall be tested for sensitivity. In the event loaded cartridges are selected for test, remove and discard all powder charges from the test cartridge by sectioning the cartridge case around the periphery, 1/2 inch maximum above the base. Drop test at 15 inches (adjusted) using a steel ball l-13/l6-inch in diameter, weighing 3.94 ± 0.02 ounces, in a Ignition Device sensitivity machine with a cartridge holder approved by the acquiring agency. The height of 15 inches shall be adjusted taking into consideration the actual weight of the ball so that the energy level specified in 3.6.1 is achieved. Test shall be made with a drop test firing pin with a pin contour radius of 0.101 ± 0.001. Failure of the sample to comply with the requirements of 3.6.1 shall be cause for rejection of the sample or the lot.

4.7.7.2 Ballistics.

4.7.7.2.1 First article. Thirty cartridges of the first article sample shall be grouped and temperature conditioned as described in table III and 4.8. Following removal from the conditioning chamber, the cartridge shall be tested as required by 3.6.2.2. Failure of any cartridge to comply with the requirements of 3.6.2.2 shall be cause for sample rejection.

4.7.7.2.2 Production lot acceptance, Twenty-one assembled cartridges from each production lot shall be divided into three equal groups, temperature conditioned, and fired in accordance with 3.6.2.2. Failure of any cartridge to comply with 3.6.2.2 shall be cause for rejection of the lot. In addition to the sample of cartridges for the above test, 10 additional cartridges shall be furnished from each production lot for investigative purposes.

4.7.7.2.1 Sealant application. Five cartridges from each production lot shall be selected for this test. The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length of the joining surfaces at the junction of the cartridge head and case sidewall and that the propellant cavity is free of sealant. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot of cartridges.

4.7.7.3 Retest. There shall be no retests.

4.7.7.3.1 Test failure. If a test failure is attributable to an assignable cause, excluding the test cartridge, the original test results shall be discarded and that test reconducted.

4.8 Temperature conditioning. The conditioning chamber shall be preconditioned to the specified temperature. Once the temperature inside the chamber has stabilized, the samples shall be placed inside and maintained at the specified temperature for 4 hours minimum, 24 hours maximum.

4.8.1 Reconditioning. The sample must be tested within five minutes after removal from the conditioning chamber. If this time is exceeded, the cartridge shall be reconditioned in accordance with 4.8.

4.9 Inspection of packaging. The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of material is to be performed by DoD or in-house contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The assembly is used in cartridge actuated devices for Aircrew Emergency Escape Systems. Since the assembly was developed for use on military aircraft, there is no commercial application.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and revision letter of this specification
b. If required, the specific issue of individual documents
c. Whether a first article sample is required (see 3.1, 4.4, and 6.3)
d. Test facility for first article tests (see 4.4.1)
e. Production test activity and lot size (see 4.1 and 4.5.1.2)
f. Any special test conditions (see 4.3)
g. Directions for shipping radiographs of Ignition Devices and of entire lot of cartridge assemblies (see 4.7.1 and 4.7.4)
h. Directions for sampling for protective finish tests (see 4.7.3)
i. Level of preservation and packing (see 5.1 and 6.5)
j. That the safety precaution requirements of the "Contractor's Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M are applicable. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore," OP 5 are applicable.

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the items should be a first article sample or a sample selected from the first production items (see 3.1), and the number of items to be tested as specified in 4.4. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Explosive hazard classification information.

Hazard Classification Division: 1.4
Storage Compatibility Group: S
DOT Class: C

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

DOT Marking - Explosive Power Device - Class C - Handle Carefully - Keep Fire Away

6.5 Packing and marking. Packing and marking should be Level A or B, as specified by the contracting activity (see 6.2). Level A should be in accordance with Drawings 8797373 and 8797441. Level B should be in accordance with Drawings 8797373 and 9225380.

6.6 Hazard notice. The cartridge described herein and certain of its components are flammable or explosive and present hazards in manufacture, handling, storage, and shipment. The contractor should recognize these properties and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling, and electrically induced incidents.

6.7 Definitions.

6.7.1 Ignition delay. Ignition delay is the time between the firing pin striking the Ignition Device or ignition device and the first indication of pressure in the closed bomb. ,

6.7.2 Time to Pmax. Time to Pmax is the time that elapses between the beginning of a continuous pressure rise and the point of maximum pressure on the pressure versus time record.

6.8 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.9 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:
Navy - OS

Preparing activity:
Navy - OS
(Project 1377-2011-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.