MILITARY SPECIFICATION

DETONATOR, STAB, XM58, PARTS FOR

1. SCOPE

1.1 This specification covers the parts for one type of detonator designated as Detonator, Stab, XM58.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition.
MIL-P-10025 - Packing and Marking for Interplant Shipment of Inert Ammunition Components-General Specification for.
MIL-I-45208 - Inspection Requirements, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Inspection Terms and Definitions.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8858412 - Cup, Detonator
8797036-3 - Disc, Detonator Closing
8795797-3 - Disc, Detonator

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes.
IEL-(see 6.3) - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawings (dwgs.) 8797036-3, 8795797-3, and 8858412, as applicable, and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be free of burrs, chips, dirt, grease, corrosion and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.

examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-G-2550 shall apply.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

b. Number of units of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of analysis on all material procured directly by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.

Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 Lot formation.-A lot shall consist of parts produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot number.

4.2.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.3.

4.2.2.1 Disc detonator (see drawing 8795797-3) and Disc Detonator Closing (dwg 8797036-3).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.25 percent	
101.	Thickness	Gage
Minor:	AQL 1.00 percent	
201.	Diameter	Gage
202.	Evidence of poor workmanship (see 3.3)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.

4.2.2.2 Cup, detonator (see dwg. 8858412).

Categories	Defects	Method of inspection
Critical:		
	1. Crack or split	Visual
Major:	AQL 0.25 percent	
	101. Diameter of hole min	Gage
	102. Concentricity of hole with outside diameter	Gage
Minor:	AQL 2.50 percent	
	201. Length	Gage
	202. Inside diameter	Gage
	203. Diameter of hole, max	Gage
	204. Thickness through bottom	Gage
	205. Outside diameter	Gage
	206. Evidence of poor workmanship (see 3.3)	Visual

4.2.3 Inspection equipment.-For the performance of the inspections listed herein, the contractor shall have available and utilize correctly all necessary gages, measuring and testing equipment identified by Index of Inspection Equipment Lists No. (see 6.3), or approved equivalents thereto. Designs of equipment developed by the contractor for use in lieu of that specified in the Index of Inspection Equipment Lists shall be documented and submitted to the Government for approval as equivalent (see 6.2). Approval shall be obtained prior to initiation of production. Supply and maintenance of inspection equipment shall be in accordance with Specification MIL-L-45607.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking shall be in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.

6.2 Submission of contractor equipment designs.-Documentation of contractor developed equipment designs shall be submitted in duplicate to Picatinny Arsenal, Dover, New Jersey, ATTN: ORDBB-ND, for approval. This documentation shall identify all standard devices and set-ups etc., as well as special equipment designs.

6.3 Inspection equipment.-The Index of Inspection Equipment Lists was not available at the time this specification was prepared. Contractor equipment designs developed in lieu of Government designed equipment shall be documented and submitted to the Government for approval prior to the initiation of production (see 6.2).

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing activity:
Army-Ordnance Corps

GPO 815652

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:24Z
Check the source to verify that this is the current version before use.