MIL-W-46611B(MU)
18 August 1966
SUPERSEDI NG
MIL-W-46611A(MU)
18 June 1964

MILITARY SPECIFICATION

WARHEAD SECTI ON, 762 MILLIMETER ROCKET, EMPTY, C4

1. SCOPE

1.1 This specification covers one type of warhead section.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The fol lowing documents of the issue in effect on dote of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-129- Marking for Shipment and Storage.

DRAWINGS

US ARMY EDGEWOOD ARSENAL

DL123-1-293 - Warhead Section, 762 Millimeter Rocket, Empty, C4.

(All drawings referenced in this specification are listed on above draw ing.)

(Copies of specifications, standards, drawing and publications required by suppliers in connection with specific procurement fuctions should be obtained from the procuring activity or as directed by the contr acting officer.)

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:27Z
Check the source to verify that this is the current version before use.

2..2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for propoaL shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Appl ication for copies of these freight classification rules should be addressed to the Uniform Classif ication Committee, 202 Union Station, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL123-1-293 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristic cs set forth on the drawings.

3.1.2 Components. All components of the warhead section shall conform to the specifications and drawings listed on Drawing DL123-1-293 and on subsidiary drawings.

3.2 Assembly. The warhead section shal l be assembled os shown on Drawing E123-1-293.

3.3 Weight. The assembled warhead section shall weigh 332 ± 5 pounds.

3.4 Leakage. The warhead section shall not show a pressure drop of more than 1 pound per square inch gage (psig) when tested in accordance with 4.3.3.

3.5 Identification. Each warhead shall be marked with a serial number on the external surface of each section.

3.6 Preproduction. Prior to the start of regular production, a preproduction sample of warhead sections shall be produced in accordance with this specification for examination and test (see 4.2).

3.7, Workmanship. The warhead shall be free from foreign matter (oil and grease) and damage such as dents, cracks, and sharp edges which could adversely affect its intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unl ess otherwise specified in the contract or purchase order, the suppl ier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Preproduction.

4.2.,1 Lotting. Prior to the start of regul or production, two warhead sect ions shall be produced using the same method, materials and equipment that will be used in regular production.

4.2.2 Examination and test. The preproduction warheads shall be examined and tested for all the requirements listed in this specification.

4.2.3 Acceptance/rejection criteria. The pr eproduction warheads shall meet all the requirements listed in this specification to be acceptable. The supplier shall obtain written approval from the contacting officer prior to proceeding with regular production.

4,3 Regular production.

4.3.1 Inspection previsions for examination and test. Each warhead section shall be examined and tested in accordance with the list of defects. The acceptance number is 0.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:27Z
Check the source to verify that this is the current version before use.

4.3.2 List of defects.

4.3.2.1 Warhead section, 762 mm rocket, empty, C4 (Dwg E1 23-1-293).

1. Leakage (4.3.3)
2. Component missing or incorrectly assembled
3. Configuration incorrect
4. Perpendicularity excessive
5. Skin surface fairing incorrect
6. Gap at assembly joint excessive
7. Rivet or bolt not flush as specified
8. Torque incorrect
9. Hinge pin not staked
10. Detonating cord cavity incorrect or obstructed
11. 1/2-20 UNF-3B hole location incorrect (base assembly)
12. 1/2-20 UNF-3B thread or depth incorrect (base assembly)
13. Detonating block pel let cavity incorrect
14. Fuze retainer locking pin nonfunctioning
15. Nose cone weld not flush as specified
16. Nose cone lock ing device location incorrect
17. Nose cone nonfunctioning
18. Workmanship (3.7)
19. Protective finish missing or incorrect
20. Weight incorrect

4.3.3 Leakage test. The warhead section shall be subjected to 5 ± 1/2 psig for 6 + 1 minute. After the pressure is stabilized, the air supply shall be shut off prior to observ ing the gage.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The empty warhead section and its components shall be cleaned, dried, preserved and packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. The empty warhead section and its components, preserved and packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe del ivery to the first domestic destination. Containers shall comply with Uniform Freight Classification rules or the regulations of other carriers appl icable to the mode of transported ion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This item is used as a component of a chemical rocket.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Preproduction.

(1) Time allowed for supplier's submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

Custodian:

Army - MU

Preparing activity:

Army - MU (EA)

Project No. 1340-A207

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
Attn: SMUPA-DC7
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-W-46611B (MU)

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:27Z
Check the source to verify that this is the current version before use.