MIL-C-50862A (PA)
29 March 1976
SUPERSEDING
MIL-C-50862 (MU)
16 March 1971

MILITARY SPECIFICATION

CARTRIDGE, 40MM, HEDP, M430; LINER FOR METAL PART

This specification is approved for use by Picatinny Arsenal, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal part for one type of liner for Cartridge, 40MM, HEDP, M430.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

PICATINNY ARSENAL

9205397 - Liner

3. REQUIREMENTS

3.1 Material - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Part - The part shall comply with all requirements specified on Drawing (Dwg.) 9205397, all associated drawings, and with all requirements specified in applicable requirements.

3.3 Workmanship - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.4 First Article Inspection - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3 First Article Inspection -

4.3.1 Submission - The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Liner	9205397	25

4.3.2 Inspections to be Performed - See MIL-A-48078 and Table 1 herein.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-50862A(PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
	Liner		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Liner (Dwg. 9205397) Examination for Defects	25	-	3.2	4.4.2.1

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection -

4.4.1 Inspection Lot Formation - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination - See MIL-A-48078.

a. Sampling Plans - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL [illegible]-50632A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Liner		9205397
			NEXT HIGH ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1			
Major					
101	Index angle		0.40%	3.2	Gage
102	Wall thickness at large datum diameter		0.40%	3.2	Gage
103	Wall thickness at small datum diameter		0.40%	3.2	Gage
104	Wall thickness of straight portion, small end		0.40%	3.2	Gage
105	Location of large datum diameter		0.40%	3.2	Gage
106	Location of small datum diameter		0.40%	3.2	Gage
107	Concentricity of outside diameter small end with large outside diameter including perpendicularity		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Large outside diameter, min.		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.4.3 Testing - Testing is described in the First Article Table and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment - The inspection equipment required to perform the examinations and test prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures -

4.5.1 Dimensional Control of Stamped Parts - In place of the normal sampling associated with the Classification of Defects and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he present objective evidence to the Contracting Officer to substantiate the request.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging -

5.1.1 Level C - The liner shall be preserved and packaged in accordance with MIL-STD-1169.

5.2 Packing -

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

5.2.1 Level C - The liner preserved and packaged as specified in 5.1.1 shall be packed for shipment in accordance with MIL-STD-1169.

5.3 Marking - Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping - When components from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing or the lots in transit.

6. NOTES

6.1 Intended Use - The component covered by this specification is intended for use in Cartridge, 40MM, HEDP, M430.

6.2 Ordering Data - See MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval - See MIL-A-48078. Submit equipment designs as required to Commander, Attn: SARPA-QA-T, Picatinny Arsenal, Dover, NJ 07801.

6.4 Submission of Results of Contractor-conducted Examinations and Tests - Data shall be submitted in accordance with data item DI-R-1721 on the DD Form 1423 for the contract.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1310-A090

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.