MIL-C-82582(OS)
17 November 1969

MILITARY SPECIFICATION

CONTAINER, MARK 470 MOD 0

This specification has been approved by the Naval Ordnance Systems Command, Department of the Navy.

1. SCOPE

1.1 Scope - This specification establishes the requirements for one type of container, designated the MARK 470 MOD 0.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-D-3464	Desiccants, Activated, Bagged, Packaging Use and Static Dehumidification

STANDARDS

Federal

Fed. Test Method Std. No. 101	Preservation, Packaging and Packing Materials; Test Procedures

Military

MIL-STD-129	Marking for Shipment and Storage

DRAWINGS AND LISTS

Naval Ordnance Systems Command

DL 2642791	Container, MARK 470 MOD 0

(and all drawings, specifications and standards referenced thereon)

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements -

3.1.1 Construction - The MARK 470 MOD 0 container shall be manufactured in accordance with NAVORD Data List (DL) 2642791 and all documents referenced thereon.

3.1.2 Preproduction sample - Unless otherwise specified in the contract or purchase order (see 6.2), a preproduction sample of the container shall be manufactured using the methods and procedures proposed for production. The sample will be tested as specified in Section 4 herein for the purpose of determining that, prior to starting production, the contractor's production methods are capable of yielding items that comply with the technical requirements of this specification.

3.2 Performance requirements and product characteristics - Containers covered by this specification shall be capable of meeting the following performance requirements and product characteristics.

3.2.1 Rough handling requirements -

3.2.1.1 Rotational drop - There shall be no evidence of structural failure or inability of the container to protect its contents when each corner of the loaded container base is allowed to fall freely onto a rigid steel or concrete surface from a height of 18 inches as described in 4.4.1.

3.2.1.2 Hoisting - The container loaded to a gross weight of 4,300 pounds, shall be capable of being hoisted by a 4-legged sling attached to the four hoisting rings when tested as described in 4.4.2.

3.2.2 Leakage - The container, closed and sealed with all latches properly secured, shall show no leakage when pressurized and tested as described in 4.4.3.

3.3 Data requirement - No data are required by this specification, or by documents referenced in 2.1, unless specified in the contract or purchase order (see 6.2.1).

3.4 Workmanship - Workmanship shall be of sufficiently high quality to assure that completed equipment will comply with all requirements of this specification. Particular attention shall be paid to plating, bonding, painting, welding, marking and freedom of parts from burrs and sharp edges. The assembled containers shall be thoroughly cleaned of all dirt, chips, and other foreign matter. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspections - Inspection of the container shall be classified as follows:

(a) First article inspection (see 4.4).

(b) Quality conformance inspection (see 4.5).

4.3 First article sample - Unless otherwise specified, a preproduction sample of one (1) container, manufactured in accordance with 3.1.1 and 3.1.2, shall be subjected to the preproduction tests detailed in 4.4. Acceptance of the preproduction sample shall be based upon the absence of defects in the sample.

4.4 First article inspection - The preproduction sample, after satisfactorily passing the examinations of 4.5.1 shall be subjected to the Rotational Drop Test of 4.4.1, the Hoisting Test of 4.4.2 and the Leakage Test of 4.4.3. Certified inspection data covering the results of production inspections shall be forwarded to the procuring activity, if required (see 6.2.1).

4.4.1 Rotational drop test - The preproduction sample shall be subjected to the Cornerwise-Drop (Rotational) Test, Method 214, of Fed. Test Method Std. No. 101. The container loaded with a simulated SPARROW III Missile shall be supported at one corner of its base on a block 6 inches in height (see 6.2). A 12 inch high block shall be placed under the other corner of the same end of the container. The lowest point of the opposite end of the container shall be raised to a height of 18 inches, and allowed to fall freely onto a steel or concrete surface of sufficient mass to absorb the shock without deflection. This test shall be applied to all four corners of the container base. Any evidence of structural failure or permanent deformation which would impair the integrity of the container to protect its contents shall be cause for rejection of the preproduction sample. Minor dents, scratches, or paint flaking are not cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

4.4.2 Hoisting test - The container, uniformly overloaded to a total weight of 4,300 pounds shall be suspended for five (5) minutes from a 4-legged sling attached to the four container hoisting rings. There shall be no evidence of over-stressing the hoisting rings or welded areas.

4.4.3 Leakage test - The relief valve and/or humidity indicator shall be replaced with a pressure gauge and valve suitable for air pressurization. When tested at 3.0 +0.50 - 0 PSIG air pressure in accordance with Fed. Test Method Std. No. 101, Method 241, paragraph 6.3, the gauge shall show no pressure loss in 30 minutes minimum time lapse.

4.5 Quality conformance inspection -

4.5.1 Examination - Each container shall be examined for compliance with the requirements of NAVORD Data List (DL) 2642791.

4.5.2 Tests - Each container manufactured shall be subjected to the Leakage Test of 4.4.3 and examined for Workmanship (see 3.4).

5. PREPARATION FOR DELIVERY

5.1 Preservation - Forty-eight (48) units of desiccant, MIL-D-3464, shall be placed in the desiccant tray and the container cover secured.

5.2 Packing - The container requires no packing for delivery. However, all loose interior pieces and all latches shall be tightly secured.

5.3 Marking - In addition to any special marking required by the contract or purchase order, containers shall be marked in accordance with the applicable marking drawing and MIL-STD-129.

6. NOTES

6.1 Intended use - The MARK 470 MOD 0 container is intended for use in shipment, storage, shipboard stowage and handling one complete SPARROW III Missile, AIM-7D, -7E, or -7F. The container is reusable and is compatible with the missile launcher loading sub-system forming a part of Basic Point Defense Surface Missile System.

6.2 Ordering data - Procurement documents shall specify:

(a) Title, number and date of this specification.

(b) If first article inspection is not required (see 3.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

(c) Name and address of activity which will furnish government loaned property (see 4.4.1).

6.2.1 First article inspection - It is expected that first article inspection will normally not be waived. Procurement documents should, therefore, also specify:

(a) First article sample size, if more than one (1) (see 4.3).

(b) Name and address of activity designated to perform first article inspection (see 4.4).

(c) If a government activity is to perform first article inspection, (see 4.4), responsibility for transportation charges to and from the government activity.

(d) If first article inspection is to be performed by the contractor, requirement for first article inspection data (see 4.4), name and address of activity to receive these data, and name and address of activity authorized to approve these data, if different from recipient.

Preparing Activity:
NAVY - OS

Project No. 8140-N067

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof).*

SPI MIL-C-82582(OS) CONTAINER, MARK 470 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED *(Printed or typed name and activity)*	DATE

DD FORM 1 NOV 64 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Weapons Services Office
Attention: Code SSS
Philadelphia, Pennsylvania 19112

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Weapons Services Office
Attention: Code SSS
Philadelphia, Pennsylvania 19112

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:16Z
Check the source to verify that this is the current version before use.