INCH-POUND

MIL-DTL-55302/192A
w/AMENDMENT 2
8 March 2019
SUPERSEDING
MIL-DTL-55302/192A
w/AMENDMENT 1
21 June 2016

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, SOCKET CONTACTS, 122 AND 152 POSITIONS, PRINTED WIRING BOARD (.075 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




FIGURE 1. Connector, receptacle, .075 (1.91 mm) spacing.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.






FIGURE 1. Connector, receptacle, .075 (1.91 mm) spacing - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.



CONNECTOR POLARIZATION WITH "D" SHAPED GUIDE PINS AND SOCKETS. (TYPE "Y")



DETAIL "D" POLARIZATION PINS/SOCKETS



TYPE "N" TURNING HEX JACKSET
DETAIL "E"

TYPE "S" SHORT TURNING HEX JACKSET
DETAIL "F"

FIGURE 1. Connector, receptacle, .075 (1.91 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector receptacle, .075 (1.91 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.

Number of contacts	Dimensions					
	A ± .010	BSC B	BSC C	BSC D	E ± .010	BSC F
122	3.440 (87.38)	3.250 (82.55)	2.925 (74.30)	3.610 (91.69)	3.780 (96.01)	3.000 (76.20)
152	4.190 (106.43)	4.000 (101.60)	3.675 (93.35)	4.360 (110.74)	4.530 (115.06)	3.750 95.25)

Inches	mm	Inches	mm	Inches	mm
.001	0.03	.0375	0.953	.160	4.06
.002	0.05	.0625	1.59	.170	4.32
.005	0.13	.075	1.91	.172	4.37
.006	0.15	.078	1.98	.200	5.08
.008	0.20	.080	2.03	.275	6.99
.010	0.25	.082	2.08	.300	7.62
.014	0.36	.086	2.18	.305	7.75
.017	0.43	.093	2.36	.375	9.53
.018	0.46	.100	2.54	.390	9.91
.020	0.51	.109	2.77	.490	12.45
.0245	0.622	.110	2.79	.500	12.70
.0255	0.648	.125	3.18	.545	13.84
.028	0.71	.140	3.56	.625	15.88
.030	0.76	.141	3.58	.700	17.78
.031	0.79	.150	3.81		
.032	0.81	.156	3.96		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. These connectors mate with connectors specified in MIL-DTL-55302/193 using appropriate hardware.
5. Numbers indicating the first and last position in each row and every fourth contact position in between shall be marked on the side(s) of the connector. As an option to the above, numbers indicating every fourth cavity may be stamped on the side of the connector, with exception that the number one contact shall be marked.
6. Conformal coating clearances shall be .005 (0.13 mm) minimum.

FIGURE 1. Connector, plug, .075 (1.91 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration: See figure 1.

Material: Guide pins, type X guide sockets, jackscrews, and jacksockets shall be made of corrosion resisting stainless steel in accordance with ASTM A581/A581M or ASTM A582/A582M, passivated in accordance with SAE-AMS-2700, or shall be corrosion resistant copper nickel alloy (61± 2 percent copper, 25 ± 2 percent nickel, 2.5 percent maximum other, and the balance zinc) and shall have a brinell hardness of 145 to 175. Type Y guide sockets shall be beryllium copper in accordance with ASTM B196/B196M or ASTM B197/B197M, nickel plated in accordance with SAE-AMS-QQ-N-290, class 2, 50 to 150 microinches.

Plating: The contact plating shall be in accordance with MIL-DTL-55302, or gold in accordance with MIL-DTL-45204 or equivalent as approved by the preparing activities, type II, grade C, class 1, over nickel plating in accordance with SAE-AMS-QQ-N-290, class 2, 50 to 150 microinches in the engaging area and gold in accordance with MIL-DTL-45204 or equivalent as approved by the preparing activities, type II, grade C, class 00 or type III, grade A, class 00, over nickel plating in accordance with SAE-AMS-QQ-N-290, class 2, 50 to 150 microinches in the termination area.

Contact identification: See figure 1.

Oversize pin exclusion: In accordance with MIL-DTL-55302, except that the test for contact size number 23 shall be performed.

Contact engagement and separation forces (number 24 contacts):

Minimum separation: 0.5 ounce with 0.0245 inch diameter test pin, reference SAE-AS31971 for PIN MS31971-24X1.

Maximum engagement: 4.0 ounces with 0.0255 inch diameter test pin, reference SAE-AS31971 for PIN MS31971-24Y1.

Mating and unmating:

Low insertion force contacts: The maximum mating force, in pounds, shall be the number of contacts multiplied by 0.25 and the withdrawal force, in pounds, shall be a minimum of 0.04 times the number of contacts and shall not exceed the measured insertion force.

NOTE: Not applicable when mating and unmating is accomplished through the engaging of jackscrews and jacksockets.

Jackscrews and jacksocket torque: 2 inch pounds max fully mated.

Contact resistance: The average contact resistance of all contacts measured shall not exceed 0.007 ohm, and no individual contact pair shall have a resistance exceeding 0.015 ohm.

Dielectric withstanding voltage:

Sea level: 750 volts rms.

High altitude: 250 volts rms at 70,000 feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.

Current rating: 3.0 amperes maximum per contact.

Polarization: Type X regular, guide pin and socket, full round (see figure 1). Type Y, adjustable “D” shaped guide pin and socket (see figure 1, detail D). All connectors are supplied in the -1 polarized position. For other than OEM use, connectors may be repolarized by using M55302/57-01 spanner wrench and M55302/190-01 guide pin and guide socket kit. When guides are removed and reinstalled in another position, apply Loctite 83-CV or equivalent on the threads. Ordering connectors in other than the -1 polarized position may be done by the OEM’s by placing the desired polarized position in brackets three spaces after the Part or Identifying Number (PIN) on the purchase order. Example: M55302/57-A10Y [-32]. Polarization pins and sockets shall be adjusted to any desired configuration by spanner wrench (M55302/57-01). Ordering connectors in the -1 polarized position without Loctite 83-CV or equivalent applied may be done by placing a “-0” in brackets three spaces after the PIN on the purchase order. Guide sets, as installed, shall withstand 7 ounce-inches backoff torque applied through the guide set mounting nut.

M55302/190-01 kit: Consists of one type Y “D” shaped guide socket and one type Y “D” shaped guide pin and two spanner nuts.

Example of PIN:

M55302/192 L A 152 X

Basic number of specification sheet

Type of contacts

L = low insertion force contacts

Type of terminals (see figure 1)

A = solder cup
B = dip terminal .109 long
C = dip terminal .140 long
D = dip terminal .172 long
E = .093 flexible circuit
F = wire wrap .375 long
G = wire wrap .500 long
H = wire wrap .625 long

Number of contacts (see figure 1)

Type of mounting hardware (see figure 1)

Type X = full round
Type Y = “D” shaped
Type F = fixed jackset
Type S = short turning hex jackset
Type N = turning hex jackset
Type L = turning sloted jackset
Type M = short turning slotted jackset

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-45204
MIL-DTL-55302/193
ASTM A581/A581M
ASTM A582/A582M
ASTM B196/B196M
ASTM B197/B197M
SAE-AMS-QQ-N-290
SAE-AMS-2700
SAE-AS31971

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project: 5935-2019-044)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:56Z
Check the source to verify that this is the current version before use.