INCH-POUND

MIL-P-63430(AR)
AMENDMENT 5
27 July 1991
SUPERSEDING
AMENDMENT 4
30 April 1984

MILITARY SPECIFICATION

PROJECTILE, 155MM, TEST, NON-HAZ, M718/M741 TYPES
LOADING, ASSEMBLING AND PACKING OF

This Amendment forms a part of Military Specification MIL-P-63430(AR), dated 1 December 1980, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Add paragraph 3.12 as follows:

"3.12: Shorting bar resistance. There shall be no more than one (1) ohm resistance to the shorting bar loop when measured between the output terminal to ground.".

PAGE 9

4.4.1: Inspection lot formation. Subparagraph b., change wording to read:

"Expulsion charge assemblies from one lot interfix, from one manufacturer."

Subparagraph e., add:

"-1 and -2 after "Electronic Assemblies".

PAGE 11

4.4.2.2: Electronic and primer assembly (M718). Major defect 102, change to read:

"Bushing missing"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:50Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2.3: Electronic and primer assembly (M741). Major defect 102, change to read:

"Bushing missing".

PAGE 13

4.4.2.4: Battery check and insulator test point installation. Add major defect 104:

"Resistance of shorting bar, improper, 100%, 3.12, 4.5.6".

PAGE 17

4.4.2.7: Mine, test, non-haz (during assembly) (M741). Major defect 113, change to read:

"Retaining ring height improper".

PAGE 18

4.4.2.8: Mine, test, non-haz (during assembly) (M718). Major defect 113, change to read:

"Retaining ring height improper".

PAGE 20

4.4.2.9: Projectile, 155MM, M718/M741 Metal Parts Assy.(Prior to loading mines).

Delete Drawing Number: "9282848".
Add Drawing Number: "10542902".

PAGE 21

4.4.2.10: Projectile, 155MM, test, non-haz, M741 type (prior to inserting mines into projectile).

Critical defect 1, change to read:

"...being assembled into projectile...".

Critical defect 2, change to read:

"...being assembled into projectile...".

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:50Z
Check the source to verify that this is the current version before use.

Critical defect 3, change to read:

"mine color code improper, or HE mine with non-haz color code".

PAGE 22

* 4.4.2.11 Major 104: Change "Sealant" to "Sealing Compound".

PAGE 23

4.4.2.12: Projectile, 155MM, test, non-haz, M741 type (prior to assembling lifting plug).

* Major 102: Change "Gage" to "Gage/4.5.7" under PARAGRAPH REFERENCE/INSPECTION METHOD and add "100%" under AQL.

Major 108: Delete in its entirety.

* Add Minor 202 as follows: "202 Sealant not present between projectile body and base (360°) 0.65% 3.2 Visual".

PAGE 24

4.4.2.13: Projectile, 155MM, test, non-haz, M741 type.

Critical defect 1, change wording

from: "Nomenclature on body, letter in triangle and stamped number on base not consistent"

to: "Nomenclature on body and letter in triangle not consistent".

Major defect 102, change to read:

"Lifting plug missing or improper".

Major defect 103, change as follows:

No. of sample units, delete: "See 4.4.3.5" AQL, add: "0.40%".

Major 104: Delete in its entirety and substitute:

"Major 104, Lifting plug or gasket missing or damaged 100% 3.2 Visual".

Minor defect 201, change to read:

"...1/4 square inch".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:50Z
Check the source to verify that this is the current version before use.

PAGE 26

4.4.2.14: Projectile, 155MM, test, non-haz, M718 type (prior to inserting mines into projectile).

Critical defect 1, change to read:

"...being assembled into projectile...".

Critical defect 2, change to read:

"...being assembled into projectile...".

Critical defect 3, change to read:

"Mine color code improper, or HE mine with non-haz color code".

PAGE 29

4.4.2.17: Projectile, 155MM, test, non-haz, M718 type.

Critical defect 1, change wording

from: "Nomenclature on body, letter in triangle and stamped number on base not consistent"

to: "Nomenclature on body and letter in triangle not consistent".

Major defect 102, change to read:

"Lifting plug missing or improper".

Major defect 103, change as follows:

No. of sample units, delete: "See 4.4.3.5"

AQL, add: "0.40%"

Major 104: Delete in its entirety and substitute:

"Major 104, Lifting plug or gasket missing or damaged 100% 3.2 Visual".

Minor defect 201, change to read:

"...1/4 square inch".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:50Z
Check the source to verify that this is the current version before use.

PAGE 31

4.4.2.18: Pallet (loaded).

Major 106: Add the following:

"Major 106, Cover support missing 100% 3.2 Visual (8 places)".

Major defect 201: Delete in its entirety.

PAGE 33

4.4.3.5: Lifting plug torque. Delete paragraph in its entirety.

4.4.3.7: Expulsion charge assembly. Delete paragraph in its entirety.

PAGE 35

4.5.5: Radiographic examination of test mines. Change title to read:

"Radiographic examination of test mines and projectiles".

Change, "DRDAR-QAT-M" to "DRSMC-QAT-M(D).".

Add paragraph 4.5.6 as follows:

"4.5.6: Shorting bar resistance. The resistance of each shorting bar circuit shall be measured between the test points E3 and TP9, using an approved ohmmeter. Observation shall be made for compliance with the requirement of 3.14."

4.5.7: Add new paragraph:

* "4.5.7 Inspection of gap between projectile body and base. Gap shall be inspected using an approved feeler gage as specified on drawing 9215220. The feeler gage shall be cleaned with a clean dry rag immediately after each inspection such that the gage is free of any base/body gap sealant. No solvent or other substance other than a clean dry rag shall be used to clean the gage. The gap between the projectile body and base shall be inspected within fifteen (15) minutes after the sealant is applied to the shoulder of the base."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:50Z
Check the source to verify that this is the current version before use.

PAGE 36

6.3: Submission of designs for approval.

Change "DRDAR-QAT-I" to "DRSMC-QAT-I(D)".

6.4: Submission of test data and data cards.

Change, "DRDAR-QAT-M" to "DRSMC-QAT-M(D)".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-AC55)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:50Z
Check the source to verify that this is the current version before use.