MIL-S-82567(OS)
AMENDMENT 1
29 June 1971

MILITARY SPECIFICATION

SPEED CONTROL ASSEMBLY

LD 546993

(For Guidance Control Test Set Mk 443 Mod 0 and Mod 1)

This amendment forms a part of Military Specification MIL-S-82567(OS) of 12 September 1968 and has been approved by the Naval Ordnance Systems Command, Department of the Navy.

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command"; also delete "BuWeps" and substitute "NAVORD".

Page 1, paragraph 2.1, under "SPECIFICATIONS, Military": Delete "MIL-S-901" and associated title.

Page 2, paragraph 2.1, under "STANDARDS, Military". Add:
"MIL-STD-202 Test Methods for Electronic and Electrical Component Parts"

Page 3, paragraph 3.3.4, resistance indication between "TP2" and "P1-7": Delete "1,300 max" and substitute "2000 max".

Page 3, paragraph 3.4.2. Delete and substitute:
"3.4.2 Shock (see 6.3.2). The assembly shall be capable of withstanding shock as specified in MIL-STD-202, Method 213A, test condition J."

Page 4, paragraph 4.1. Delete and substitute:
"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 6, paragraph 4.5.2.2. Delete and substitute:
"4.5.2.2 Shock. Subject the assembly to shock tests as specified in MIL-STD-202, Method 213A, test condition J."

Page 11, paragraph 4.7.3.1: Delete "+40 ±5 vdc;" and substitute "+40 ±1.5 vdc;".

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:15Z
Check the source to verify that this is the current version before use.

Page 11, paragraph 4.7.3.2. (a). Delete and substitute:
"(a) Turn on power supply, adjust FREQUENCY control on test fixture for an electronic counter indication of 2000 ± 1 Hz, and observe the following output voltage characteristics after a 3-minute stabilization period.

Waveshape	Sinusoidal with slight distortion (as observed on oscilloscope - ref WD 16233, Figure 2)
Amplitude	28 to 36 vrms (as indicated on digital voltmeter)"

Page 11, paragraph 4.7.3.4, resistance indication between "TP2" and "P1-7": Delete "1,300 max" and substitute "2000 max".

APPENDIX page (2), paragraph 10.3.2.1, under "Limits" column: Delete "+35 to +45 vdc" and substitute "+38.5 to +41.5 vdc".

APPENDIX page (2), paragraph 10.3.2.2, under "Limits" column: Delete "31 to 33 vrms" and substitute "28 to 36 vrms".

APPENDIX page (2) paragraph 10.3.2.4, resistance indication between "TP2" and "P1-7": Delete "1300 ohms max" and substitute "2000 ohms max".

Preparing Activity
Navy - OS
Project No. 1355-N266

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-714-158/2292

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:15Z
Check the source to verify that this is the current version before use.