INCH-POUND

MIL-T-63439 (AR)
AMENDMENT 5
14 March 1990
SUPERSEDING
AMENDMENT 4
12 November 1988

MILITARY SPECIFICATION

TOW 2 FUZE PROBE

This Amendment forms a part of Military Specification MIL-T-63439 (AR), dated 1 July 1982, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Standards, Military - Add the following:

"MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components"

PAGE 2

3.4: Delete paragraph and substitute the following:

"3.4 Angular alignment. The angle formed between a point tangent to the probe at 1.5 probe diameters aft of the probe tip and the warhead centerline shall not exceed 40 minutes total included angle with a load simulating the flight conditions of 22.7 pounds applies to the probe tubes."

PAGE 5

4.4.2.1: Add the following:

"106	Torque of Screw (Black)	1.0%	Gage
107	Torque of Nut (Brown)	1.0%	Gage"

PAGE 6

4.4.2.2: Add the following:

"102	Torque of Nut	1.0%	Gage"

AMSC N/A FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.4: Add the following:

"109	Dimension to Release Mechanism	1.0%	Gage
110	Distance from Mounting Surface to Bottom of elongated slot	1.0%	Gage"

PAGE 14

4.4.2.10: Add to examination of test, category 201, the following: "Surface of spherical end."

PAGE 16

4.4.2.12:

Line 103: Delete "Location of slotted hole in edge" and substitute "Distance from boss hole to side of elongated hole."

Line 202: Delete "Height from hole in boss to bottom flat" and substitute "Length of elongated hole."

Line 203: Delete "Contour" and substitute "width of elongated hole."

PAGE 18

4.4.2.14:

Line 201: Delete "Location of three counterbored holes" and substitute "Location of two counterbored holes."

PAGE 25

4.4.2.21:

Line 203: Delete "Gage" and substitute "Visual."

PAGE 30

4.4.2.26:

Line 101: Delete "Gage" and substitute "Visual"

Examination or Test (category 102): Delete "O.D. Compressed" and substitute "Spring does not compress freely. (see Note 1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

PAGE 30

Add under Notes: "1 Spring shall work freely without binding when compressed to a 2.22 inch max. length in a tube 24 inch min. length and 1.709 max. I.D."

PAGE 33

4.4.2.29: Add the following:

"102 Fit of Spring Carrier in Outer Tube 1.0% Gage."

PAGE 35

4.4.2.31: Delete page 35 in its entirety.

PAGE 37

4.4.2.33:

Line 203: Delete "Visual" and substitute "Gage."

PAGE 43

Delete: Paragraph 4.4.2.39 (Safety Lock Assembly) Substitute: Included page 43 (Safety Knob Assembly - Dwg. 9399710).

PAGE 44

Add: Paragraph 4.4.2.40 "202 Wedge secure 1.0 Visual."

PAGE 46

Delete: Paragraph 4.4.2.42 (Knoab, Safety Lock) substitute: Included page 46 (Knob - Dwg. 9399705).

PAGE 47

Delete: Paragraph 4.4.3.43 (Shaft, Safety Lock) Substitute: Included page 47 (Shaft - Dwg. 9399706).

PAGE 47A

Insert Classification of Defects and Tests, in new Page 47A, included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63439 (AR)
Amendment 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399710
4.4.2.39	Safety Knob Assembly				NEXT HIGHER ASSEMBLY 9342171
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Presence of parts		0.65%	3.2	Visual
202	Pushout force (see note 2 on dwg.)		0.65%	3.2	Gage
203	Workmanship		0.65%	3.23	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63439 (AR)
Amendment 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399705
4.4.2.42	Knob				NEXT HIGHER ASSEMBLY 9399710
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
Minor					
201				3.1	Certification
202	Outside diameter		0.65%	3.2	Gage
203	Length		0.65%	3.2	Gage
204	Workmanship		0.65%	3.23	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.43	Shaft		9399706
			NEXT HIGHER ASSEMBLY 9399710

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Pitch diameter of threads		0.40%	3.2	Gage
103	Major diameter of threads		0.40%	3.2	Gage
104	Diameter of knurled section		0.40%	3.2	Gage
105	Second largest diameter		0.40%	3.2	Gage
106	Largest diameter		0.40%	3.2	Gage
107	Length from stop to end		0.40%	3.2	Gage
Minor					
201	Length from threads to stop		0.65%	3.2	Gage
202	Protective finish		0.65%	3.2	Visual
203	Workmanship		0.65%	3.23	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.44	Tube Lock Pin Assembly				9342183
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Lubrication applied		1.0%		Visual

NOTES:

Source: (AMSA) assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

PAAGE 47B

Add: Paragraph 4.4.2.45 included on page 47B.

PAGE 47C

Add: Paragraph 4.4.2.46 included on page 47C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63439 (AR)
Amendment 2

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.45	Cam				9399707
					NEXT HIGHER ASSEMBLY 9399710
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inner inside diameter		0.40%	3.2	Gage
102	Distance from outside diameter to flat		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
Minor					
201	Material		0.65%	3.1	Certification
202	Small thickness		0.65%	3.2	Gage
203	Workmanship		0.65%	3.23	Visual

NOTES:

Source (SD-6): https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63439 (AR)
Amendment 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399718
4.4.2.46	Washer, Single Wave				NEXT HIGHER ASSEMBLY 9399710
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Workmanship		0.65	3.23	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.

PAGE 50

* 5.1 and 5.2 Delete in their entirety and substitute:

"5.1 Packaging and packing. The parts shall be packaged and packed in accordance with the requirements of MIL-STD-1169.

5.2 Marking. Marking shall be in accordance with requirements of MIL-STD-1169."

PAGE 54

Figure 3, Load: Change "3.6 lbs." to "2.4 lbs."

Bore Rider Angle: Change "30°" to "30°±10°."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendments were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A607)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:51Z
Check the source to verify that this is the current version before use.