INCH-POUND


MS90565H
26 October 2005
SUPERSEDING
MS90565G
20 December 1982

DETAIL SPECIFICATION SHEET

INSERT ARRANGEMENTS, ELECTRICAL CONNECTOR, SIZE 32, CLASS L, 60 AMPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.




Quantity	Contact	Size	Socket SAE-AS39029/49-	Pin SAE-AS39029/48-
1	A	4	331	320
1	N	4N	331 (see note 6)	321

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only. Unless otherwise specified, tolerance is ± .002 (.05 mm).
2. Unless otherwise specified, front face of pin insert pattern is shown. Socket inserts are the reverse.
3. -02-Cable IPCEA 2-NO 6 conductor round, type W.
4. -03-Cable-C0-02-HDF (2/4) 1100 in accordance with MIL-DTL-3432.
5. Mark 32-02 on 32-03 insert. Trademark and 32-( ) shall appear in available space. Contact identifying letter shall be located so as to identify relative contact.
6. Only the pin contact is lengthened and has the N (neutral) designation. The mating socket contact is the same as the power contact.

FIGURE 1. 28 volt DC two wire, -02 and -03 insert arrangements, service D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.




Quantity	Contact	Size	Socket SAE-AS39029/49-	Pin SAE-AS39029/48-
1	A	4	331	320
1	N	4N	331 (see note 6)	321
2	G1, G2	6N	329 (see note 6)	318

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only. Unless otherwise specified, tolerance is ± .002 (.05 mm).
2. Unless otherwise specified, front face of pin insert pattern is shown. Socket inserts are the reverse.
3. -04-Cable IPCEA 2-NO 6 conductor round, type G.
4. -05-Cable-C0-02-HDF (2/6-2/8R) 1100 in accordance with MIL-DTL-3432
5. Mark 32-04 on 32-05 insert. Trademark and 32-( ) shall appear in available space. Contact identifying letter shall be located so as to identify relative contact.
6. Only the pin contact is lengthened and has the N (neutral) designation. The mating socket contact is the same as the power contact.

FIGURE 2. 28 volt AC single phase two wire grounding, -04 and -05 insert arrangements, service D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.




Quantity	Contact	Size	Socket SAE-AS39029/49-	Pin SAE-AS39029/48-
2	A, B	4	331	320
2	N, G	4N	331 (see note 6)	321

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only. Unless otherwise specified, tolerance is ± .002 (.05 mm).
2. Unless otherwise specified, front face of pin insert pattern is shown. Socket inserts are the reverse.
3. -06-Cable IPCEA 3-NO 6 conductor round, type G.
4. -07-Cable-C0-03-HDF (3/4-3/10R) 1210 in accordance with MIL-DTL-3432.
5. Mark 32-06 on 32-07 insert. Trademark and 32-( ) shall appear in available space. Contact identifying letter shall be located so as to identify relative contact.
6. Only the pin contact is lengthened and has the N (neutral) designation. The mating socket contact is the same as the power contact.

FIGURE 3. 28 volt AC single phase three wire grounding, -06 and -07 insert arrangements, service D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



Quantity	Contact	Size	Socket SAE-AS39029/49-	Pin SAE-AS39029/48-
3	A, B, C	4	331	320
1	N	4N	331 (see note 6)	321
1	G	6N	329 (see note 6)	318

NOTES:

1. Dimensions are in inches. Metric equivalents are given for information only. Unless otherwise specified, tolerance is ± .002 (.05 mm).
2. Unless otherwise specified, front face of pin insert pattern is shown. Socket inserts are the reverse.
3. -12-Cable IPCEA 43-NO 6 conductor round, type G.
4. -13-Cable-C0-04-HDF (4/4-4/12R) 1290 in accordance with MIL-DTL-3432.
5. Mark 32-12 on 32-13 insert. Trademark and 32-( ) shall appear in available space. Contact identifying letter shall be located so as to identify relative contact.
6. Only the pin contact is lengthened and has the N (neutral) designation. The mating socket contact is the same as the power contact.


FIGURE 4. 28 volt AC three phase four wire grounding, -12 and -13 insert arrangements, service D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

Insert rotation (degrees from normal)				
Arrangement number	Normal DC or 60 Hz (see figures 6 through 9)	Alternate (see figures 6 through 9) 400 Hz		
		W	X	Y
32 – 02 32 – 03	0 °	---	---	---
32 – 04 32 – 05	0°	---	90°	---
32 – 06 32 – 07	0°	---	---	---
32 – 12 32 – 13	0°	---	---	180°

FIGURE 5. Insert arrangements and rotations.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



NOTES:
1. REF. MS90555******S.
2. REF. MS90557******S.
3. Front face of socket insert shown.

FIGURE 6. Socket contact pattern and polarization, Insert in normal position (60 Hz power only).


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



NOTES:
1. REF. MS90555******SX.
2. REF. MS90557******SX.
3. Front face of socket insert shown.

FIGURE 7. Socket contact pattern and polarization, Insert in alternate position (400 Hz power only).


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



NOTES:
1. REF. MS90556******P.
2. REF. MS90558******P.
3. Front face of pin insert shown.

FIGURE 8. Socket contact pattern and polarization, insert in normal position (60 Hz power only).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.



NOTES:
1. REF. MS90556******PX.
2. REF. MS90558******PX.
3. Front face of pin insert shown.

FIGURE 9. Socket contact pattern and polarization, insert in alternate position (400 Hz power only).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction, see figures 1 through 9, and table I.
Neutral pin (N) is not connected to shell.
Grounding pin (G) is connected to shell.
Applicable SAE-AS33481 crimp bushings shall be supplied with the contacts for insert arrangements as specified.

TABLE I. Accessories.

Insert arrangement	Contacts		Cable conductors MS90556 & MS90557 1/		Contact bushings required	
	Quantity	Size	Quantity	Size	Quantity	PIN SAE-AS33481-
32 – 02	2	4	2	6	2	4-6L
32 – 04	2 2	4 6	2 2	6 10(G)	2 2	4-6L 6-10L
32 – 05	2 2	4 6	2 2	4 8(G)	- 2	- 6-8L
32 – 06	3 1	4 4	3 3	6 12(G)	3 1	4-6L 4-8L
32 – 12	4 1	4 6	4 4	6 12G	4 -	4-6L -

1/ (G) Designates grounding.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-22992, this document references the following:

MIL-DTL-3432
MS90556
MS90557
SAE-AS33481

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Preparing activity:
DLA – CC

Review activities:
Army – AT, AV, CR4, MI
Navy – AS, CG, MC, SH, YD
Air Force – 19

(Project 5935–4719–016)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:39Z
Check the source to verify that this is the current version before use.