MILITARY SPECIFICATION SHEET

DELAY LINES, 14 DIP COMPATIBLE, 5 TAP (5 SECTION MINIMUM)

This amendment forms a part of MIL-D-83532/1, dated 31 March 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "(5 SECTION MINIMUM)".

Requirements, input pulse, delete in its entirety and substitute:

"Input pulse: Delay lines must be capable of passing a minimum input pulse width of 50 percent of total delay time at 50 percent duty cycle (maximum)."

Insert the following requirement between delay times and dc parameters:

"Output rise time (applied to leading edge only): 4 ns maximum for dash numbers -001 through -025; 5 ns maximum for dash numbers -026 through -031. Measurement conditions ($-55^{\circ}C \leq T_C \leq +125^{\circ}C$): V_{CC} = 5.0 V ac; $TR_I \leq 3$ ns; C_L = 50 pF; R_L = 500 ohms."

Add the following requirement after operating temperature:

"Number of sections: Five sections minimum, except for dash numbers -001 through -005 which shall have four sections minimum."

PAGE 4

TABLE III, delete all data for output rise time.

PAGE 5

Supersession data, delete and substitute the following:

"Supersession data: MIL-D-83532/1 supersedes DESC drawings 84087, 85008, and 85013 when a qualified source is available."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 19, 99
DLA - ES

User activities:
Navy - AS, CG, MC, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5999-0269-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:42Z
Check the source to verify that this is the current version before use.