NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-83536/10A
AMENDMENT 4
10 July 1999
SUPERSEDING
AMENDMENT 3
13 May 1999

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED,
ALL WELDED, TRANSIENT SUPPRESSED DC COILS

This amendment forms a part of MIL-PRF-83536/10A, dated 13 May 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, side view: Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS" and "MARKING (EITHER SIDE)".

PAGE 2

FIGURE 1, side view: Delete "MARKING (EITHER SIDE)".

PAGE 3

FIGURE 1, side view: Delete "MARKING (EITHER SIDE)" and substitute "MARKING (SEE NOTES 8 AND 9)".

PAGE 4

* FIGURE 1, delete “SILICONE GASKET (SHORE HARDNESS 30-45)” and substitute “GASKET (SEE NOTE 11)”

PAGE 6

* FIGURE 1, delete “SILICONE GASKET (SHORE HARDNESS 30-45)” and substitute “GASKET (SEE NOTE 11)”

PAGE 8

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:45Z
Check the source to verify that this is the current version before use.

FIGURE 1, delete and substitute:

"



CIRCUIT DIAGRAM
(NO MOUNT, RVFM, AND HFM)



CIRCUIT DIAGRAM (OPTIONAL INTERNAL DIODE CONFIGURATION)



CIRCUIT DIAGRAM (TRACK MOUNT)



CIRCUIT DIAGRAM (TRACK MOUNT)
(OPTIONAL INTERNAL DIODE CONFIGURATION)

FIGURE 1. Dimensions and configurations - Continued."

* NOTE 10, delete and substitute “10. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals and all track mount terminals shall be gold plated. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.”

* NOTE 11, delete and substitute “11. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 30 to 45, thickness .050 ±.005. Gasket material according to AMS 3332 has been considered acceptable.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:45Z
Check the source to verify that this is the current version before use.

PAGE 10

Delete "Contact voltage drop or resistance:" and substitute "Contact voltage drop and resistance:".

PAGE 13

Delete "Maximum leakage current" in its entirety and substitute: "Maximum leakage current for track mount only: 100 microamperes rms."

Vibration (random), first paragraph, line 2: Delete "15 minutes each plane".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA-CC

(Project 5945-1059-23)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:45Z
Check the source to verify that this is the current version before use.