INCH POUND

MIL-R-83536/12
AMENDMENT 1
15 December 1995

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, MAGNETIC LATCH, HERMETICALLY SEALED,
ALL WELDED, DC COIL

This amendment forms a part of MIL-R-83536/12, dated 27 March 1992, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 2

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 3

FIGURE 1 side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 6

Delete "Contact voltage drop or resistance " and substitute "Contact voltage drop and resistance "

PAGE 8

TABLE III, Coil resistance (ohms) minimum column, 28 V dc rated coil voltage (2 places) Delete "400" and substitute "540" (2 places)

TABLE III, column headings Delete "Specified pickup voltage" and substitute "Specified latch/reset voltage" (2 places)

PAGE 9

Vibration (random), line 2 Delete "15 minutes each plane"

Weight Delete "(40 9 g's)" and substitute "(40 9 grams)"

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0964-10)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.