INCH-POUND

MIL-R-83536/20
AMENDMENT 1
15 December 1995

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT, LOW LEVEL TO 10 AMPERES, MAGNETIC LATCH, HERMETICALLY SEALED, ALL WELDED, AC COILS

This amendment forms a part of MIL-R-83536/20 dated 27 March 1992, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

FIGURE 1, side view, dimension 1.025 Add "SQ"

PAGE 2

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 6

Delete "Contact voltage drop or resistance " and substitute "Contact voltage drop and resistance "

PAGE 8

TABLE III Coil current (amperes) heading Add "maximum"

PAGE 9

Vibration (random), line 2 Delete "15 minutes each plane"

Weight Delete "(77.2 g's)" and substitute "(77.2 grams)"

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0964-22)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.