MILITARY SPECIFICATION

BATTERY HOUSING, ASSEMBLY

This specification is mandatory for use by all activities of the Army Munitions Command.

1. SCOPE

1.1 This specification covers special requirements, quality assurance provisions, and the preparation for delivery criteria for one type of battery housing, assembly used on the Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-B-117 - Bags and Sleeves, Interior Packaging
MIL-C-5541 - Chemicals Films and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-W-6858 - Welding, Resistance, Aluminum, Magnesium, Non-Hardening Steels or Alloys, Nickel Alloys, Heat Resisting Alloys, and Titanium Alloys, Spot and Seam

STANDARDS

MILITARY

AN507 - Screw

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components
MS20426 - Rivet

DRAWINGS

ORDNANCE CORPS

8825769 - Battery Housing Assembly
8825770 - Upright Support, Riveting Assembly
8825771 - Cover, Base
8825772 - Upright Support Welding Assembly
8825773 - Block, Clamp
8825774 - Block, Spacer
8825775 - Bracket L.H.
8825776 - Bracket, R.H.
8825777 - Support, Upright, R.H. Assembly
8825778 - Support, Upright, L.H. Assembly
8825779 - Support, Upright Assembly
8825780 - Clamp, Support
8825781 - Spacer, Support
8825782 - Support, Upright, R.H.
8825783 - Support, Upright, L.H.
8825800 - Plage, Spacer
8825801 - Support, Upright
8825872 - Pad
8825873 - Pad
8825874 - Pad
8825927 - Nut, Clinch
8836520 - Stand Off
8861688 - Carton, Packing, Ammunition for Housing, Battery Assembly
ET-8825769 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

3.2 Assembly. The housing assembly shall comply with all requirements specified on the drawing (dwg) 8825769, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purposes of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Table
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristic (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Nut, clinch (see dwg 8825927-10) covering a detail of dwgs 8825777 and 8825778 as applicable.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) for part in accordance with dwg 8825927	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.2 Support, upright, R.H. (see dwg 8825782) covering a detail of dwg 8825777 and support, upright L.H. (see dwg 8825799 covering a detail of dwg 8825778.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of (2) .177 Holes (Left View)	Gage
102.	Diameter of (2) .177 Holes (Left View)	Gage
103.	Width	Gage
104.	Length	Gage
105.	Location of center countersunk hole	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
106.	Diameter of center countersunk hole	Gage
107.	Location of long side holes	Gage
108.	Diameter of .125 holes	Gage
109.	Diameter of .268 holes	Gage
110.	Depth of slot	Gage
111.	Length of slot	Gage
112.	Location of slot	Gage
113.	Location of .125 hole (right view)	Gage
114.	Thickness	Gage
115.	Material (see 3.1)	Visual
116.	Welding in accordance with MIL-W-6858 Class B	Visual/Manual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.3 Support Upright, R.H. assembly (see dwg 8825777) and support Upright L.H. assembly (see dwg 8825778) covering details of dwg 8825772.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Clinch nuts tight	Visual
102.	No damaged thread	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.4 Support upright (see dwg 8825801 covering a detail of dwg 8825779.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of large holes	Gage
102.	Diameter of large holes	Gage
103.	Location of small holes	Gage
104.	Diameter of small holes	Gage
105.	Contour of slot	Gage
106.	Width of formed section	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
107.	Location of formed section	Gage
108.	Depth of formed section	Gage
109.	Total length	Gage
110.	Length of sides	Gage
111.	Location of sides	Gage
112.	Total width	Gage
113.	Material (see 3.1)	Visual/Manual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.5 Plate, spacer (see dwg 8825800) covering a detail of dwg 8825799.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Contour of slot	Gage
102.	Length	Gage
103.	Width	Gage
104.	Thickness	Gage
105.	Material (see 3.1)	Visual
106.	Objective evidence (see 6.2) for finish in accordance with dwg 8825800	Visual
Minor: None defined.		

4.3.2.1.6 Support, upright assembly (see dwg 8825700) covering a detail of dwg 8825772.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Welding in accordance with MIL-W-6858 Class B	Visual/Manual
102.	Contour of slot	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.7 Spacer support (see dwg 8825781) covering a detail of dwg 8825772.

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
101.	Location of small holes	Gage
102.	Diameter of small holes	Gage
103.	Location of large holes	Gage
104.	Diameter of large holes	Gage
105.	Countersink present	Visual
106.	Length	Gage
107.	Width	Gage
108.	Height of formed section	Gage
109.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.8 Clamp support (see dwg 8825780) covering a detail of dwg 8825772.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of 2 end holes	Gage
102.	Diameter of 2 end holes	Gage
103.	Height of formed sections	Gage
104.	Total width	Gage
105.	Total length	Gage
106.	Location of slot	Gage
107.	Depth of slot	Gage
108.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.9 Upright support welding assembly (see dwg 8825772) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Welding in accordance with MIL-W-6858, Class B	Visual/Manual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

4.3.2.1.10 Pad (see dwg 8825873) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of hole	Gage
102.	Diameter of hole	*Measure
103.	Length	*Measure
104.	Width	*Measure
105.	Material (see 3.1)	Visual/Measure
106.	No crack, split or hole present	Visual

*Measure with suitable scale

Minor: None defined.

4.3.2.1.11 Block, spacer (see dwg 8825774) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Pitch diameter of threaded holes	Gage
102.	Minor diameter of threaded holes	Gage
103.	Location of threaded holes	Gage
104.	Length	Gage
105.	Width	Gage
106.	Thickness	Gage
107.	Material (see 3.1)	Visual/Manual
108.	Objective evidence (see 6.2) for finish in accordance with dwg 8825774	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.12 Pad (see dwg 8825874) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of hole	Gage
102.	Diameter of hole	*Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
103.	Length	*Measure
104.	Width	*Measure
105.	Material (see 3.1)	Visual/Manual
106.	No crack, split or hole	Visual

*Measure with suitable scale

Minor: None defined.

4.3.2.1.13 Rivet (see MS20426A3-7 and MS20426A-12) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Objective evidence (see 6.2) for part in accordance with applicable standard	Visual

Minor: None defined.

4.3.2.1.14 Block, clamp (see dwg 8825773) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Pitch diameter of threaded hole	Gage
102.	Minor diameter of threaded hole	Gage
103.	Location of threaded holes	Gage
104.	Length	Gage
105.	Width	Gage
106.	Thickness	Gage
107.	Material (see 3.1 SQAP-Appendix I)	Visual
108.	Objective evidence (see 6.2) for finish in accordance with dwg 8825773	Visual

Minor:

201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.15 Bracket, R.H. (see dwg 8825776) and bracket L.H. (see dwg 8825775) covering details of dwg 8825770.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
101.	Pitch diameter of threaded hole	Gage
102.	Minor diameter of threaded hole	Gage
103.	Location of threaded hole	Gage
104.	Total width	Gage
105.	Total length	Gage
106.	Width of projection	Gage
107.	Width of tapered side projection	Gage
108.	Taper (top view)	Gage
109.	Thickness of side projection	Gage
110.	Total thickness	Gage
111.	Diameter of large hole	Gage
112.	Location of large hole	Gage
113.	Taper (bottom view)	Gage
114.	Material (see 3.1)	Visual
115.	Objective evidence (see 6.2) for finish in accordance with dwgs 8825775 or 8825776 as applicable	Visual
116.	Surface finish	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.16 Pad (see dwg 8825872) covering a detail of dwg 8825770.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Length	*Measure
102.	Width	*Measure
103.	Material (see 3.1)	Visual
104.	No crack split, gouge or hole	Visual

Minor: None defined.

*Measure with suitable scale

4.3.2.1.17 Upright support assembly (see dwg 8825770 covering a detail of dwg 8825769.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	No part loose	Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
102.	Location of threaded holes	Gage
103.	Rivets flush both ends	Visual/Manual
104.	Objective evidence (see 6.2) for finish in accordance with dwg 8825770	Visual
105.	Pads cemented with adhesive specified on dwg 8825770	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.18 Stand off (see dwg 8836520) covering a detail of dwg 8825769.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Pitch diameter of thread	Gage
102.	Minor diameter of thread	Gage
103.	Length	Gage
104.	Chamfer present	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.19 Cover, base (see dwg 8825771) covering a detail of dwg 8825769.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Diameter	Gage
102.	Location of 2 holes	Gage
103.	Diameter of 2 holes	Gage
104.	Contour of cover	Visual
105.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.20 Battery housing assembly (see dwg 8825769.

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
101.	Objective evidence (see 6.2) for screw in accordance with AN507C632-6	Visual
102.	Welding in accordance with MIL-W-6858, Class B	Visual/Manual
103.	Finish spot welds in accordance with MIL-C-5541	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual/Manual

4.3.2.1.21 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual/Manual
Minor: None defined.		

4.3.2.1.21 Carton, packing, ammunition, for housing, battery assembly (see dwg 8861688 and 5.2).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Housing tight in carton	Manual
102.	Corners blunted on carton	Visual/Manual
103.	Heat seal of bag complies with MIL-B-117	Visual
104.	Marking	Visual
Minor: None defined.		

4.3.2.1.22 Packing and Marking for Storage and Shipments (see dwg 8808362 and 5.2).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Gross load weight, max	*Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Package material (see 3.1)	Visual

*Determine weight with a suitable scale

Minor:

201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual/Manual

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET-8825769. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The housing assembly shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The housing assembly shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The housing assembly shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The housing assembly shall be packaged in accordance with dwg 8861688 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The housing assembly shall be packaged in accordance with dwg 8861688 and 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The housing assembly shall be packed in accordance with dwg 8861688 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwg 8861886 and 8808362 as applicable.

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing Activity
Army - MU

Project No. 1125-A074

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-B-50896(MU) Battery, Housing, Assembly

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.