MILITARY SPECIFICATION

CASE, FUZE SETTER SET: M178

1. SCOPE

1.1 This specification covers requirements, related quality assurance provisions, and packaging data for a water-vaporproof carrying case which provides a means of storing and transporting a fuze setter set (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-4150	Case, Carrying, Water-vaporproof
MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel, Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army, Frankford Arsenal

F8614057	Case, Fuze Setter Set: M178

PACKAGING DATA SHEET

MIL-P-14232/P8614057	Packaging of Case, Fuze Setter Set: M178

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The case shall be manufactured in accordance with Drawing F8614057 and drawings pertaining thereto.

3.2 General specification.- The contractor shall be responsible for adherence to the following requirements of MIL-F-13926:

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Part identification and marking
(e) Workmanship

3.3 Environmental service conditions.

3.3.1 Standard ambient temperature.- The case shall meet the requirements of 3.4 to 3.7.2 inclusive at a standard ambient temperature between +60° and +90° Fahrenheit (F).

3.3.2 Extreme operating temperatures.- The case shall meet the requirements of 3.6 to 3.7.2 inclusive while exposed to, and thermally stabilized at, ambient temperatures of -40° and +150°F.

3.4 Shock.- The case shall meet this requirement with the cover closed and the catches in the locked position. With a dummy load contained within it to simulate the fuze setter set in weight and distribution, the case shall be capable of sustaining two drops onto a concrete floor from a height of 36 inches. One drop shall be on a corner of the body; the other drop shall be on a corner of the cover. Subsequent to the two drops, the case shall show no evidence of damage which will affect its operability, and the case shall meet the requirements of 3.5 to 3.7.2 inclusive.

3.5 Sealing.- The closed and locked case shall meet the immersion requirement specified in MIL-C-4150.

3.6 Inserts.- The inserts shall be securely bonded to the cover or body, as applicable, and shall show no evidence of looseness.

3.7 Operability.

3.7.1 Cover.- With the case unlocked, it shall be possible to open and close the cover easily without restriction or binding.

3.7.2 Catches.- The catches shall function without interference and, when secured, they shall lock the cover to the body and show no evidence of looseness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examination and tests.- Components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with the "Classification of Defects" specified in Table I below and the inspection level and sampling plans specified in MIL-STD-105. Examinations and tests for packaging, packing, and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement, and to reject individual non-conforming items.

TABLE I - CLASSIFICATION OF DEFECTS

	REQUIREMENTS	TEST PROCEDURES
CRITICAL: NONE		
MAJOR: AQL 2.5 percent defective		
101. Inserts	3.6	4.5.2
102. Cover	3.7.1	4.5.3.1
103. Catches	3.7.2	4.5.3.2
MINOR: None defined		

4.2.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.3 Special sampling.

4.3.1 General.- One case shall be selected at random by a Government representative as a sample from each 100 produced. The sample shall meet the requirements and tests in Table II.

TABLE II

CHARACTERISTICS	REQUIREMENTS	TEST PROCEDURES
301. Fabrication	3.1	Applicable drawings - visual
302. General specifications	3.2	MIL-F-13926 - visual

4.3.2 Environmental.- Three units shall be selected at random by a Government representative as samples from each 50 produced or from each month's production, whichever occurs first. The samples shall have met the requirements and tests in Table I and shall then meet the requirements and tests in Table III.

TABLE III

CHARACTERISTICS	REQUIREMENTS	TEST PROCEDURES
303. Performance at extreme temperatures	3.3.2	4.5.1.1
304. Shock	3.4	4.5.1.2
305. Sealing	3.5	4.5.1.3

4.3.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented production lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.2.3).

4.4 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply equipment in accordance with the applicable requirements of MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:24Z
Check the source to verify that this is the currentversion before use.

4.4.2 Contractor furnished inspection equipment.

4.4.2.1 Government design.- All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the requirements of 4.4.

4.4.2.2 Contractor design.- The contractor shall provide inspection equipment compatible with the "Test methods and procedures" specified in 4.5 and with the "Component inspection" and "Test facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5 Test methods and procedures.

4.5.1 Environmental.

4.5.1.1 Operating temperatures.- The operating temperature test consists of exposing the case to the temperatures indicated in 3.3.2 by means of equipment complying with the requirements specified under "Test facilities" outlined in MIL-F-13926. The test shall be conducted in accordance with Procedure II of MIL-F-13926, and the temperatures specified in 3.3.2 shall apply. While thermally stabilized at these temperatures, the case shall meet the performance requirements specified in 3.3.2.

4.5.1.2 Shock.- The case, with a dummy load, shall be dropped on the specified corners and from the height specified in 3.4. Upon completion of each of the drops, the case and inserts shall be examined for evidence of damage or looseness and shall then meet the performance requirements specified in 3.5 to 3.7.2 as required by 3.4.

4.5.1.3 Water immersion.- This test shall be accomplished in accordance with Test Procedures in MIL-C-4150 to determine compliance with 3.5.

4.5.2 Inserts.- Inserts shall be examined by tactile and visual means to determine accessibility, secureness, and looseness to insure compliance with 3.6.

4.5.3 Performance.

4.5.3.1 Ease of Operation.- Using tactile means, the cover shall be examined to determine compliance with 3.7.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.5.3.2 Catch operability.- Catch operability shall be inspected by a tactile examination of the catch when engaged to the cover to determine compliance with 3.7.2.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking.- Packaging, packing, and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P8614057. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The case is primarily a protective device intended to house and carry Fuze Setter Set: M63 which is used to hand-set various fuzes.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation, packaging, and packing.
(c) Applicable stock number.
(d) Applicable packaging data sheet (see 5.1).

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A162Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT

$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.