MIL-I-51072C(EA)
21 May 1979
SUPERSEDING
MIL-I-51072B(MU)
24 July 1967

MILITARY SPECIFICATION

INSTALLATION KIT, GAS-PARTICULATE FILTER UNIT, ARMORED VEHICLE, M20A1

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of filter unit installation kit.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed and Lock Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-C-843 - Cushioning Material, Cellulosic.

FSC 4240

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation-Packaging, Methods of.
MIL-B-117 - Bags, Sleeves and Tubing- Interior Packaging.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-46506 - Boxes, Ammunition Packing, Wood, Wirebound.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL 5-19-1777 - Installation Kit, Armored Vehicle, Gas-Particulate Filter Unit, M20A1.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on TDPL 5-19-1777 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the installation kit shall conform to the specifications and drawings listed on TDPL 5-19-1777 and subsidiary drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

3.2 Manufacture and assembly. All components of the installation kit shall be manufactured and assembled in accordance with their respective assembly drawings listed on TDPL 5-19-1777. Electrical components shall function properly and have electrical continuity, as applicable, when tested as specified in 4.2.4.1.

3.3 Workmanship. All metal parts of the installation kit shall be free of burrs and sharp edges and defects such as bent, broken, or cracked members. All rubber parts shall be smooth, of uniform thickness, and free of cuts, breaks, abrasions, and molding defects. Wiring shall be free of kinks and cuts, breaks, and abrasions of the insulating surface. All parts shall be free of contamination such as dirt and foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the installation kits produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection.

4.2.3.1 Examination and tests. Sample installation kits shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects.

(a) Metal support assemblies (Dwgs B5-19-1063, bracket; D5-19-1754, frame; D5-19-1769, shock mount).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Component missing or incorrect
102		Component incorrectly assembled
103		Hardware components inoperative
104		Welding not as specified
105		Mounting holes for component assemblies not as specified
106		Workmanship (3.3)
Minor:	AQL 2.5 percent defective	
201		Protective finish missing

(b) Electrical system assemblies (Dwgs B5-19-1663, ground wire; B5-19-1767 and B5-19-1768, cable assemblies; C5-19-1757, circuit breaker and switch assembly).

Categories		Defects	Acceptance standards
Critical:		None defined	
Major:	AQL 0.65 percent defective		
101		Electrical continuity	4.2.4.1
102		Switch or circuit breaker nonfunctioning	4.2.4.1
	AQL 1.0 percent defective		
103		Component missing	
104		Component incorrectly assembled	
105		Electrical connectors not as specified	
106		Workmanship (3.3)	
Minor	AQL 2.5 percent defective		
201		Protective finish missing	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects (continued).

(c) Packaging inspection.

Categories	Defects
Critical;	None defined
Major:	AQL 2.5 percent defective
101	Item not cleaned as specified
102	Preservation missing where specified
103	Packaging method incorrect
104	Quantity per bag or per container incorrect
105	Container incorrect
106	Container closure incorrect
107	Container or package damaged (broken, crushed, torn, punctured, or cracked)
108	Marking incorrect, missing, or illegible
Minor:	AQL 4.0 percent defective
201	Bag incorrect
202	Insufficient cushioning or blocking to insure a tight package
203	Unlike items put together in Grade A greaseproof bag

4.2.4 Test.

4.2.4.1 Electrical continuity and circuit breaker/switch functioning test. The electrical continuity of the cables and functioning of the circuit breaker and switch shall be determined using a test lamp.

5. PACKAGING

5.1 Preservation (level A and commercial).

5.1.1 Level A.

5.1.1.1 Cleaning and drying. The components of the installation kit shall be cleaned in accordance with cleaning process C-1 of MIL-P-116. Drying shall be accomplished using any process of MIL-P-116, providing the selected process is not harmful to the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

5.1.1.2 Unit packing.

5.1.1.2.1 The components of the kit shall be prepared for placement in the unit pack using the methods and procedures of MIL-P-116 as follows:

(1) Frame Assembly [5-19-1754 (1 ea)]. The frame assembly shall be packaged method III. Secure the mounting bracket to the frame with tape or twine

(2) Shock mount assembly [5-19-1769 (1 ea)]. The shock mount shall be packaged method III by wrapping in MIL-B-121 barrier material, type II, grade A, class 2, size 18 inches by 24 inches and securing with tape.

(3) Supports [5-19-1667 (2 ea)]. The supports shall be packaged method III by wrapping in MIL-B-121 barrier material, type II, grade A, class 2, size 14 inches by 14 inches and securing with tape.

(4) Bracket [5-19-1063-2 (1 ea)]. The bracket shall be packaged method III by wrapping in MIL-B-121 barrier material, type II, grade A, class 2, size 6 inches by 8 inches and securing with tape.

(5) Wire and cable assemblies [5-19-1663 (1 ea) and 5-19-1768 (1 ea)]. Package method 1A-8 by wrapping both items in one piece of MIL-B-121 barrier material, type II, grade A, class 2, size 6 inches by 8 inches and placing in a MIL-B-117 barrier bag, style 1, type I, class E, size 4 inches by 6 inches and heat sealing.

(6) Cable assembly [5-19-1767 (1 ea)]. Package method 1A-8 by coiling assembly to minimum safe diameter, then wrap in MIL-B-121 barri material, type II, grade A, class 2, size 10 inches by 10 inches and secur with tape. Place wrapped item in a MIL-B-117 bag, style 1, type I, class size 6 inches by 8 inches and heat seal.

(7) Circuit breaker and switch assembly [5-19-1757 (1 ea)]. Package method 1A-8 by wrapping in MIL-B-121 barrier material, type II, grade A, class 2, size 12 inches by 12 inches and secure with tape. Place wrapped item in a MIL-B-117 bag, style 1, type I, class E and heat seal.

(8) Miscellaneous items.

(a) Nonmetallic and nonferrous items. Package like items together method III in MIL-B-117 class C bags. Close by heat sealing, stapling or taping.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

(b) Ferrous items. Package like items together, method IC-1. Apply P-7 preservative to all bare surfaces. Wrap in MIL-B-121 type II, grade A, class 2 barrier material and secure with tape. Place wrapped items in a MIL-B-117 class C bag and heat seal.

5.1.1.2.2 Place the frame assembly [5.1.1.2.1(1)] in a PPP-B-636 fiberboard box, style RSC, grade W5c, size 14-1/2 inches by 7 inches by 8-3/4 inches inside dimensions. Place the remaining components [5.1.1.2.1 (2) thru (8)] inside the frame assembly. Use PPP-C-843 cushioning material to fill all voids. Closure of the box shall be in accordance with PPP-B-636, appendix.

5.1.2 Commercial. The kit shall be packaged in accordance with MIL-STD-1188.

5.2 Packing (levels A, B and commercial).

5.2.1 Level A. A quantity of kits, not to exceed 10 per box, shall be packed in PPP-B-621 or MIL-B-46506 boxes for overseas shipment. Boxes shall meet size and weight limitations of their respective specifications and shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.2.2 Level B. A quantity of kits, not to exceed 10 per box, shall be packed in a PPP-B-636 fiberboard box, style RSC, grade V3c. Boxes shall meet size and weight limitations of PPP-B-636 and shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.2.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.3 Marking (levels A, B and commercial).

5.3.1 Levels A and B. Each separately wrapped item (5.1.1.2) shall be identified by part number and item nomenclature. When more than one item is placed in a wrap or bag, the quantity shall be included in the marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129. Packing list shall be provided as specified in MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This specification covers one type of installation kit designed to facilitate installation of the M8A3 filter unit in various armored vehicles.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packing and marking required.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A533

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-I-5072C

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD-314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament Research
and Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:49Z
Check the source to verify that this is the currentversion before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-I-51072C(EA)
NOTICE 1
5 March 1996

MILITARY SPECIFICATION

INSTALLATION KIT, GAS-PARTICULATE FILTER UNIT, ARMORED VEHICLE, M20A1

This notice should be filed in front of MIL-I-51072C(EA), dated 21 May 1979.

MIL-I-51072C(EA) is inactive for new design and is no longer used except for replacement purposes.

Custodian:

Army - EA

Preparing activity:

Army - EA

(Project 4240-A181)

Review Activities:

DLA - GS

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.