MIL-I-63259A(AR)
6 April 1982
SUPERSEDING
MIL-I-63259(AR)
26 January 1978

MILITARY SPECIFICATION

INTERFACE MODULE
FOR
SAFETY AND ARMING DEVICE, M100

This specification is approved for use by the U. S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Quality Assurance Provisions and special requirements for the fabrication of the Interface Module for the Improved HAWK M100 Safety and Arming Device.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

2.1.1 Specifications and standards

SPECIFICATIONS

MILITARY

MIL-E-5272	-	Environmental Testing, Aeronautical and Associated Equipment, General Specification For.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-130	-	Identification Marking of U.S. Military Property

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

MIL-STD-454	-	Electronic Equipment Standard, General Requirements For
MIL-STD-1460	-	Soldering of Electrical Connections and Printed Wiring Assemblies, Procedures For

2.1.2 Other Government documents, drawings, and publications.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting office.)

DRAWINGS (see 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

5423441	-	S and A Interface Module
9324896	-	Packing and Marking for Box, Packing
10292831	-	S & A Interface Module, Electronic Components, Assembly, Potted

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENT

3.1 Materials. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. - The components and assemblies shall comply with all requirements specified on drawings (dwgs) 5423441 and 10292831 and associated drawings and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

3.2.1 Marking. - All components and assemblies shall be permanently and legibly marked in accordance with MIL-STD-130 as specified on the applicable drawing.

3.2.2 Electronic components assembly (Dwg 10292831).

3.2.2.1 Continuity. - The resistance shall not exceed 0.2 ohm when measured between the following points:

J1 - Pin	1	and	J2 - Pin 1
J1 - Pin	6	and	J2 - Pin 6
J1 - Pin	9	and	J2 - Pin 9
J1 - Pin	11	and	J2 - Pin 11
J1 - Pin	13	and	J2 - Pin 13
J1 - Pin	4	and	J1 - Pin 5
J2 - Pin	4	and	J2 - Pin 5

3.2.2.2 Resistance

3.2.2.2.1 25°C ± 5°C. The resistance shall be 5760 ohms ± 1.5% when measured between the following points and observing the indicated polarity:

J1 - Pin 5 (+) and J2 - Pin 5 (-)
J2 - Pin 5 (+) and J1 - Pin 5 (-)

3.2.2.2.2 71°C ± 5°C and -32°C ± 5°C. The resistance shall be 5760 ohms ± 3.0% when measured between the following points and observing the indicated polarity:

J1 - Pin 5 (+) and J2 - Pin 5 (-)
J2 - Pin 5 (+) and J1 - Pin 5 (-)

3.2.2.3 Insulation resistance. - The resistance between the following points with 100 volts DC, min. applied shall be 1000 megohms, min.:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

J1 - Pin 1 and J1 - Pins 2,3,5,6,9,10,11,12,13,14,15 and Case
J1 - Pin 2 and J1 - Pins 3,5,6,9,10,11,12,13,14,15 and Case
J1 - Pin 3 and J1 - Pins 5,6,9,10,11,12,13,14,15 and Case
J1 - Pin 5 and J1 - Pins 6,9,10,11,12,13,14,15 and Case
J1 - Pin 6 and J1 - Pins 9,10,11,12,13,14,15 and Case
J1 - Pin 9 and J1 - Pins 10,11,12,13,14,15 and Case
J1 - Pin 10 and J1- Pins 11,12,13,14,15 and Case
J1 - Pin 11 and J1- Pins 12,13,14,15 and Case
J1 - Pin 12 and J1- Pins 13,14,15 and Case
J1 - Pin 13 and J1- Pins 14,15 and Case
J1 - Pin 14 and J1- Pins 15 and Case
J1 - Pin 15 and Case

3.2.2.4 Forward voltage drop

3.2.2.4.1 25°C ± 5°C.

a. Voltage A. - The voltage A when tested for as specified in the detail drawing, shall be 4.0 volts direct current (VDC) min.

b. Voltage B. - The voltage B when tested for as specified in the detail drawing shall be 1.1 ± 0.4 VDC plus the voltage A result.

3.2.2.4.2 71°C ± 5°C and -32°C ± 5°C

a. Voltage A. - The voltage A when tested for as specified in the detail drawing shall be 3.8 VDC min.

b. Voltage B. - The voltage B when tested for as specified in the detail drawing shall be 1.1 ± 0.6 VDC plus the voltage A result.

3.2.2.5 Reverse leakage current

3.2.2.5.1 25°C ± 5°C. - The reverse leakage current when tested for as specified in the detail drawing shall be 11.0 microamps DC min. to 12.4 microamps DC max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

3.2.2.5.2 71°C + 5°C and -32°C + 5°C. - The reverse leakage current when tested for as specified in the detail drawing, shall be 10.8 microamps DC min. to 17.0 microamps DC max.

3.2.2.6 Flight shock (25°C + 5°C). - Electronic components assemblies shall not exhibit discontinuity or shorts when subjected to flight shock as specifed in the detail drawings.

3.2.2.7 Flight vibration. - Electronic components assemblies shall not exhibit discontinuity or shorts when subjected to flight vibration as specified in the detail drawing.

3.2.2.8 Transport shock (25°C + 5°C). - Electronic components assemblies shall meet the 25°C end point requirments after having been subjected to transport shock as specified in the detail drawing.

3.2.2.9 Transport vibration (25°C + 5°C). - Electronic components assemblies shall meet the 25°C end point requirements after having been subjected to transport vibration as specified in the detail drawing.

3.2.2.10 Thermal cycling. - Electronic components assemblies shall not exhibit discontinuity or shorts when monitored during the last cycle of thermal cycling and shall meet the 25°C end point requirements following thermal cycling as specified in the detail drawing.

3.2.2.11 Humidity. - Electronic components assemblies, when tested in accordance with MIL-E-5272 procedure I for ten days, shall meet the insulation resistance requirements of the detail drawing after one and ten days of exposure and shall meet the 25°C end point requirements of the detail drawing.

3.2.2.12 High temperature storage. - Electronic components assemblies shall meet the 71°C end point

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

3.2.2.13 Low temperature storage. - Electronic components assemblies shall meet the -32°C end point requirements after having been subjected to low temperature storage as specified in the detail drawing.

3.2.2.14 Operating temperature. - Unless otherwise specified, all requirements shall apply at all temperatures between -32°C and +71°C.

3.3 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples shall be as specified in the contract.

3.4 Workmanship. - Interface modules shall be manufactured, processed and tested in a careful and workmanlike manner in accordance with good engineering practice, and in accordance with the requirments of the applicable drawings, standards and specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2.

a. The electronic components assembly first article sample shall be selected from parts that have passed the tests of 4.4.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

b. The first article sample shall consist of the following items in sample quantities as indicated:

PART NUMBER	DESCRIPTION	QUANTITY
10292831	Electronic Components Assy(Potted)	24
9341725	Electronic Components Assy	10
9341724	Frame	10
10292866	Spacer	10
10676125-2	Gasket	10
9341720	Insulator	10
9341723	Connector, Receptacle J2	10
9341722	Connector, Receptacle J1	10
9341718	Component Board	10

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table 1 specified herein. All inspections listed in Table 1 shall be classifed Major unless otherwise specified.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259 (AR)

PARAGRAPH CATEGORY	TITLE: Interface Module for Safety and Arming Device, M100 and Components		SHEET 1 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Electronic Components Assembly, Potted (Dwg 10292831)				
	Examination for Defects	24		3.2	4.4.2.1
	Flight Shock	3		3.2.2.6	Dwg 10292831
	Flight Vibration	3		3.2.2.7	Dwg 10292331
	Transport Shock	3		3.2.2.8	Dwg 10292831
	Transport Vibration	3		3.2.2.9	Dwg 10292831
	Thermal Cycling	3		3.2.2.10	Dwg 10292831
	Humidity	3		3.2.2.11	Dwg 10292831
	71°C				
	High Temperature Storage	3		3.2.2.12	Dwg 10292831
	Insulation Resistance	3		3.2.2.3	Test

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	Interface Module for Safety and Arming Device, M100 and Components - Continued				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	-32°C				
	Low Temperature Storage	3		3.2.2.13	Dwg 10292831
	Insulation Resistance	3		3.2.2.3	Test
	Electronic Components Assy (Dwg 9341725)				
	Examination for Defects	10		3.2	4.4.2.2
	Spacer (Dwg 10292866)				
	Examination for Defects	10		3.2	4.4.2.3
	Gasket (Dwg. 10676125-2)				
	Examination for Defects	10		3.2	4.4.2.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-6325[illegible] AR)

PARAGRAPH	TITLE		SHEET [illegible] OF [illegible]		DRAWING NUMBER
	Interface Module for Safety and Arming Device, M100 and Components - Continued				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	FRAME (Dwg. 9341724)	10		3.2	4.4.2.5
	Examination for Defects				
	Insulator (Dwg 9341720)	10		3.2	4.4.2.6
	Examination for Defects				
	Connector; Receptacle J2 (Dwg 9341723)	10		3.2	4.4.2.7
	Examination for Defects				
	Connector; Receptacle J1 (Dwg 9341722)	10		3.2	4.4.2.8
	Examination for Defects				
	Component Board (Dwg 9341718)	10		3.2	4.4.2.9
	Examination for Defects				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. - Unless otherwise specified in the Classification of Defects and Tests tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63[illegible]9A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	S&A INTERFACE MODULE Electronics Components, Assembly, Potted	1 OF 1	10292831 NEXT HIGHER ASSEMBLY 5423441

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Continuity		100%	3.2.2.1	Test
102	Resistance, 25°C		100%	3.2.2.2.1	Test
103	Insulation Resistance		100%	3.2.2.3	Test
104	Forward Voltage drop A, 25°C		100%	3.2.2.4.1a	Test, Dwg 10292831
105	Forward Voltage drop B, 25°C		100%	3.2.2.4.1b	Test, Dwg 10292831
106	Reverse Leakage Current, 25°C		100%	3.2.2.5.1	Test, Dwg 10292831
107	Resistance, -32°C		0.4%	3.2.2.2.2	Test
108	Resistance, 71°C		0.4%	3.2.2.2.2	Test
109	Forward Voltage Drop A, -32°C		0.4%	3.2.2.4.2a	Test, Dwg 10292831
110	Forward Voltage Drop A, 71°C		0.4%	3.2.2.4.2a	Test, Dwg 10292831
111	Forward Voltage Drop B, -32°C		0.4%	3.2.2.4.2b	Test, Dwg 10292831
112	Forward Voltage Drop B, 71°C		0.4%	3.2.2.4.2b	Test, Dwg 10292831
113	Reverse Leakage Current, -32°C		0.4%	3.2.2.5.2	Test, Dwg 10292831
114	Reverse Leakage Current, 71°C		0.4%	3.2.2.5.2	Test, Dwg 10293831
115	Not GO Pitch Diameter Plug Enters More Than 1 Turn Before Encountering Perceptible Drag (2 Places)		0.4%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	S&A INTERFACE MODULE Electronics Components, Assembly, Potted - Continued	2 OF 2	10292831
			NEXT HIGHER ASSEMBLY 5423441

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR cont'd					
116	Thickness of Potting, Min, over Cups and Wire		0.4%	3.2	Gage
117	Missing or Improper Position of Washers on Connector J1 (2 Places)		0.4%	3.2	Visual
MINOR					
201	Marking Incomplete or Incorrect		0.65%	3.2.1	MIL-STD-130
202	Evidence of Poor Workmanship		1.0%	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-6325[illegible](AF)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	S&A INTERFACE MODULE Electronic Components Assembly	[illegible] OF [illegible]	9341725
			NEXT HIGHER ASSEMBLY 10292831

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Lack of Preformed Wires on Pin 1, 9, 14 and 15 on J1 Connector		0.4%	3.2	Visual
102	Soldering		0.4%	3.2	MIL-STD-[illegible]460
103	Missing Strain Relief (5 Places)		0.4%	3.2	Visual
104	Missing Rivets (2 Places)		0.4%	3.2	Visual
105	Missing Insulator		0.4%	3.2	Visual
MINOR					
201	Evidence of Poor Workmanship		1.0	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Spacer				10292866
					NEXT HIGHER ASSEMBLY
					5423441
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Thickness		0.4%	3.2	Gage
102	Inside diameter, min.		0.4%	3.2	Gage
103	Outside diameter, max.		0.4%	3.2	Gage
MINOR					
201	Identification Incomplete or Incorrect		0.65%	3.2	MIL-STD-130
202	Evidence of Poor Workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.4	Gasket			10676125-2
				NEXT HIGHER ASSEMBLY: 5423441

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Thickness		0.4%	3.2	Gage
102	Length, A		0.4%	3.2	Gage
103	Width, B		0.4%	3.2	Gage
104	Angle		0.4%	3.2	Gage
MINOR					
201	Marking Incomplete or Incorrect		0.65%	3.2.1	MIL-STD-130
202	Evidence or Poor Workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Frame				9341724
					NEXT HIGHER ASSEMBLY 9341725
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Location of Connector Holes on J1 End (2 Places)		0.4%	3.2	Gage
102	Location of Connector Holes on J2 End (2 Places)		0.4%	3.2	Gage
103	Diameter of Connector Holes on J1 End (2 Places)		0.4%	3.2	Gage
104	Diameter of Connector Holes on J2 End (2 Places)		0.4%	3.2	Gage
105	Location of Length of Slots (2 Places)		0.4%	3.2	Gage
106	Location of Width of Slots (2 Places)		0.4%	3.2	Gage
107	Length of Slots (2 Places)		0.4%	3.2	Gage
108	Width of Slots (2 Places)		0.4%	3.2	Gage
109	Length of Frame, Max.		0.4%	3.2	Gage
110	Width of Frame, Max.		0.4%	3.2	Gage
111	Height of Frame, Max.		0.4%	3.2	Gage
112	Location of Component Board Mounting Holes (2 Places)		0.4%	3.2	Gage
113	Counter Sink Missing (2 Places)		0.4%	3.2	Visual
MINOR					
201	Evidence of Poor Workmanship		1.0	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-6325[illegible](AR)

PARAGRAPH	TITLE		SHEET [illegible] OF [illegible]		DRAWING NUMBER
4.4.2.6	INSULATOR				9341720
					NEXT HIGHER ASSEMBLY 9341725
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Thickness of Insulator, Min.		0.4%	3.2	Gage
102	Location of Holes (2 Places)		0.4%	3.2	Gage
MINOR					
201	Evidence of Poor Workmanship		1.0%	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE	SHEET 2 OF 3	DRAWING NUMBER
4.4.2.7	CONNECTOR, RECEPTABLE, J2		9341723
			NEXT HIGHER ASSEMBLY
			9341725

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Size of Hole (2 Places)		0.4%	3.2	Gage
MINOR					
201	Evidence of Poor Workmanship		1.0%	3.4	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.8	CONNECTOR, RECEPTABLE, JI			9341722
				NEXT HIGHER ASSEMBLY
				9341725

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Size of Hole (2 Places)		0.4%	3.2	Gage
MINOR					
201	Evidence of Poor Workmanship		1.0%	3.4	MIL-STD-454

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	COMPONENT BOARD	1 OF 1	9341718
			NEXT HIGHER ASSEMBLY: 9341717

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Location of Mounting Holes (2 Places)		0.4%	3.2	Gage
102	Diamater of Mounting Holes (2 Places)		0.4%	3.2	Gage
103	Location of Terminal Holes (6 Places)		0.4%	3.2	Gage
104	Diameter of Terminal Holes (6 Places)		0.4%	3.2	Gage
105	Counter Bores Missing		0.4%	3.2	Visual
106	Depth of Counter Bore, Max.		0.4%	3.2	Gage
MINOR					
201	Evidence of Poor Workmanship		1.0%	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-63259. (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	TERMINAL			9341719
				NEXT HIGHER ASSEMBLY
				9341717

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Missing Finish		0.4%	3.2	MIL-STD-171
MINOR					
201	Evidence of Poor Workmanship		1.0%	3.4	MIL-STD-454

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment.- The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

5. PACKAGING.

5.1 Packaging. - Packaging shall be as specified on drawings (Dwg 9324896).

5.2 Packing and marking. - Packing and marking shall be as specified on applicable drawings.

6. NOTES

6.1 Intended use. - The components covered by this specification are intended for use on the Safety and Arming Device, M100 for Improved HAWK.

6.2 Ordering data. - In addition to the requirements of MIL-A-48078, one copy of the lot acceptance data for each lot of Interface Modules manufactured, shall be submitted to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Drawings. - Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings identified as Redstone Arsenal, or Picatinny Arsenal drawings.

Custodian:
Army-AR

Preparing Activity
Army-AR

PROJECT NUMBER: 1336-A420

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-I-63259A Interface Module for Safety and Arming Device, M100

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:29Z
Check the source to verify that this is the current version before use.