MILITARY SPECIFICATION

MINE ANTI-PERSONNEL M86: CLASSROOM MODEL FOR

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Classroom Model for use in training personnel.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to tie extent specified herein. Unless-otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition Standard Quality Assurance Provisions, General Specification For.
MIL-A-70780	Arming Assembly for Mine, Anti Personnel, M86

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of inert Ammunition Components.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to. Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications . The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation ,

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9366675	Mine, Antipersonnel, Assembly, Classroom Model .
12910124	Classroom Model with Bandoleer, for M86 APERS Mine.
12910120	Bag Assembly, Classroom Model for M86.

(Copies of specifications, standards, drawings, publications and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer .)

2.3 Order of precedence . In the event of a conflict between the text of this specification anti the references cited herein (except for associated detail specifications, specification sheets or MS standards) , the texts of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained .

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Mine, classroom model. The classroom model shall comply with all requirements specified on Drawing 9366675, and with all requirements specified in applicable specifications- including MIL-A-70780 and MIL-STD-1169.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts and assemblies shall be fabricated, loaded and assembled in a thorough workmanlike manner; and all manufacturing, processing, and assembling operations shall be correctly performed. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent(s). Exterior surface coating shall be continuous except for a few light scratches not exposed base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein, or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor' s overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of three (3) consecutively produced classroom models from each cavity of each mold. (The total quantity shall be three times the number of cavities) . Fifteen (15) classroom models shall be submitted if not produced by a molding process.

4.3.2 Inspections to be performed . See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-M-70763(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Mine Antipersonnel Assembly Classroom Model		SHEET 1 OF 1		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Mine Antipersonnel Assembly Classroom Model (Dwg. 9366675) Examination of defects	1/		3.2	4.4.2.1

NOTES:
1/ Three (3) consecutively produced parts from each cavity or fifteen (15) parts if a molding process is not used.

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-04-0-23T03:58Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection .

4. 4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inpection lots of classroom models shall contain molding compound from one manufacturer's batch. (See 4.4.1.1)

4.4.1.1 Molding compound batch. A molding compound batch is herein defined as material from one manufacturer's lot, produced in one continuous unchanged process using raw materials from one homogeneous lot.

4.4.1.2 Classroom model batch. A batch of classroom models is herein defined as mines molded and cured in one unchanging process using molding compound from one batch (See 4.4.1.1) . The-mines in the batch shall consist of material mixed and cured at one time l

If a continuous type process is used, a batch of classroom models shall consist of that quantity of mines molded and cured within a four (4) hour period or portion thereof using molding compound from one batch .

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in-the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Insert Housing	1	1	9366676
				NEXT HIGHER ASSEMBLY 9366674

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material		---	3.2	Certification
102	Finish		0.40%	3.2	Gage
103	Incorrect hole(s)		0.40%	3.2	Gage
104	Position of slot(s)		0.40%	3.2	Gage
105	Depth of slot(s)		0.40%	3.2	Gage
106	Height of housing		0.40%	3.2	Gage
107	Depth of housing		0.40%	3.2	Gage
108	Width of housing		0.40%	3.2	Gage
109	Position of holes		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Wire, Housing		9366686
			NEXT HIGHER ASSEMBLY 9366674

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material		---	3.2	Certification
102	Finish		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Diameter		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -7- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Housing Assembly	1 OF 1	9366674
			NEXT HIGHER ASSEMBLY: 9366675

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect color		100%	3.2	Visual
102	Distance between screw holes		0.40%	3.2	Gage
103	Distance between screw holes and apex		0.40%	3.2	Gage
104	Screw holes incorrect		0.40%	3.2	Gage
105	Height of housing from bottom of mine		0.40%	3.2	Gage
106	Depth(s) of insert housing		0.40%	3.2	Gage
107	Distance of insert housing from top		0.40%	3.2	Gage
108	Height of insert housing		0.40%	3.2	Gage
109	Position(s) of insert housing		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Mine Antipersonnel Assembly Classroom Model	1 OF 1	9366675
			NEXT HIGHER ASSEMBLY: 12910120

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sealant missing		0.40%	3.2	Visual
102	Screws improper or missing		0.40%	3.2	Visual
103	Nose protector missing		0.40%	3.2	Visual
104	Improper tightening of screws		0.40%	3.2	Visual
105	Warning label missing		0.40%	3.2	Visual
106	Proper position of tape		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Bag Assembly, Classroom Model for M86				12910120
					NEXT HIGHER ASSEMBLY
					12910124
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Wrong model mine used		100%	3.2	Visual
Major					
101	Mine loaded incorrectly		0.40%	3.2	Visual
102	Heat Seal test failed	25-0-1	--	3.2	Visual
103	Heat Seal positioned incorrectly		0.40%	3.2	Gage
104	Notches missing		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Classroom Model with Bandoleer for M86 APERS mine				12910124
					NEXT HIGHER ASSEMBLY: Final
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Bandoleer marked incorrectly		0.40%	3.2	Visual
102	The bandoleer loaded incorrectly		0.40%	3.2	Visual
103	Positioning of marking incorrect		0.40%	3.2	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Packing and Marking for Shipping & Storage Container, PA19 for Mine, Apers M86, Classroom Model, Special Test Mine, Demonstration Mine	1 OF 1	9366709
			NEXT HIGHER ASSEMBLY: 9366710

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
1	Marking on PA19 container incorrect		100%	3.2	Visual
Major					
101	Packing material(s) incorrect sizes		0.40%	3.2	Visual
102	Moisture in packing material above max.		0.40%	3.2	Visual
103	Outer barrier bag marked incorrectly		0.40%	3.2	Visual
104	Outer bag loaded incorrectly		0.40%	3.2	Visual
105	Outer bag sealed incorrectly		0.40%	3.2	Visual
106	Pull tabs missing from outer bag		0.40%	3.2	Visual
107	PA19 container not loaded correctly		0.40%	3.2	Visual
108	Marking for outer bag incorrectly		0.40%	3.2	Visual
109	Marking for PA19 container incorrect		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Box, Wire bound	1 OF 1	9366708
			NEXT HIGHER ASSEMBLY: 9366710

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect material		0.40%	3.2	Visual
102	Inside tolerances incorrect		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.40%	3.4	Visual

NOTES:

Replaces DPSMC QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70763(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.9	Packing and Marking for Box, Wirebound for Mine, Apers M86, Classroom Model, Special Test Mine or Demonstration Mine	1	1	9366710
				NEXT HIGHER ASSEMBLY: 9366711

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Packing material missing		0.40%	3.2	Visual
102	Incorrect packing material used		0.40%	3.2	Visual
103	Moisture content of packing materials over max.		0.40%	3.2	Visual
104	Packing material installed incorrectly		0.40%	3.2	Visual
105	Marking incorrect or missing		0.40%	3.2	Visual
106	Wirebound box closed incorrectly		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.40%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.4.5 Heat seal test. The contractor shall develop a heat seal test to detect any air leakage into the sealed bag assemblies. As a minimum the test shall be in accordance with the applicable test specified in MIL-P-116. Any test plan used shall be submitted to: ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, NJ 07806-5000 for approval.

4.5.1 Dimensional control of molded or plastic parts. In place of the normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (See Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in 4.4.2.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting officer to substantiate the request for a change of inspection frequency. Contractor designs of gages and test equipment required to perform the inspections listed herein shall be forwarded to ARDEC, ATTN: AMSMC-QAT-M (D) , for approval prior to manufacture of equipment. The noted sub-paragraphs identify those items and minimum inspections subject to the requirements of this paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60 etc reins) until dimensional stability is attained. The curing time will be from the time the parts comes out of the mold until " dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARDEC, ATTN: AMSMC-QAT-M (D). If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

5* PACKING

5.1 Unit packaging.

5.1.1 Level A. Level A unit packaging shall be in accordance with Dwg. 9366709.

5.1.2 Level B. Level B unit packaging shall have the same requirements as for Level A.

5.1.3 Level C. Level C unit packaging shall have the same requirements as for Level A.

5.2 Packing.

5.2.1 Level A. Level A packing shall be in accordance with Dwg. 9366710.

5.2.2 Level B. Level B packing shall have the same requirements as for Level A.

5.2.3 Level C. Level C packing shall have the same requirements as for Level A.

5.3 Marking.

5.3.1 Level A. Level A marking shall be in accordance with Dwg. 9366709 and Dwg. 9366710.

5.3.2 Level B. Level B marking shall have the same requirements as for Level A.

5.3.3 Level C. Level C marking shall have the same requirements as for Level A.

5.4 Shipping. When shipments of units from more than one lot are made at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit. The Pursuit Deterrent Classroom Model shall be shipped Category IV munitions of Arms, Ammunition, and Explosives (AA&E) .

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The classroom models covered by this specification is intended for use in training personnel.

6.2 ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806-5000.

6.5 Drawings. Drawings in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as ARRADCOM, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under cognizance of ARDEC.

6.7 Submission of results from contractor conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations and tests to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806-5000.

6.8 Subject (key word) listing.
Anti-Personnel
Classroom Model
Molded Assembly

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A517)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-70763	MINE, ANTI-PERSONNEL M86 CLASSROOM MODEL FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to pro suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:58Z
Check the source to verify that this is the current version before use.