MILITARY SPECIFICATION

PRIMER, STAB, PA515

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the PA515 Stab Primer.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-A-250	Aluminum - Alloy Plate and Sheet, General Specification for

MILITARY

MIL-E-5272	Environmental Testing, Aeronautical and associated equipment, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

MIL-A-48078 Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-129 Marking for Shipment and Storage
MIL-STD-331 Fuze and Fuze Components, Environment and Performance Tests for
MIL-STD-650 Explosive: Sampling, Inspection and Testing

DRAWINGS

US Army Armament Research and Development Command (ARRADCOM)

9298743 - Primer, Stab, PA515
9298744 - Cup, Primer
9298745 - Disc, Closure.
9298746 - Primary, Mixture.
9258182 - Box, Set-up, Packing, Ammunition, Inner, for Small Explosive Components.
9258183 - Box, Set-up, Packing, Ammunition, Outer, for Small Explosive Components.
9258184 - Box, Packing, Ammunition, for Small Explosive Components.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:33Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General Requirements

3.1.1 Construction Materials and Composition - Construction, materials and composition of the primer shall comply with this specification and applicable specifications and drawings (See 2.1).

3.2 Detail Requirements

3.2.1 Function and Energy Output - The primers shall function satisfactorily as evidenced by a depression in the aluminum block within the limits of .030 to .056 centimeter (.012 to .022 inch) when tested as specified in 4.5.2. The primer must function on the first attempt. The two ounce steel ball shall be dropped from a height of four inches, measured from the top of the firing pin to the bottom of the ball.

3.2.2 Moisture Content

3.2.2.1 Lead Azide: The moisture content of the lead azide at the loading station at the time of loading the primers shall not exceed 0.30 percent when determined as specified in 4.5.3.

3.2.2.2 Primer Mixture: The moisture content of the primer mixture at the loading station at the time of loading the primer shall not exceed 0.30 percent when determined as specified in 4.5.3.

3.3 Workmanship: The manufacturer shall employ procedures which provide controls that preclude conditions which may adversely affect the safety or reliability of the primer (i.e. contamination, damage in handling, etc.).

3.4 First Article Inspection: This specification contains provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

3.5 Data Requirements: The contractor shall generate data in accordance with the requirements of the data item description cited in 4.5.4 (See 6.3).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility For Inspection and Standard Quality Assurance Provisions: Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections: The following types of inspection shall be conducted on the item:

a. First Article Inspection (See 4.3)
b. Quality Conformance Inspection (see 4.4)

4.3 First Article Inspection

4.3.1 Submission: The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article shall consist of 125 primers obtained by sampling as described in 4.4.2.1. The samples shall be obtained from a production lot which has been produced by the contractor using the same production processes, procedures and equipment as will be used in fulfilling the contract. All materials shall be obtained from the same sources of supply as will be used in regular production.

4.3.2 Inspections to be Performed: See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection: See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

TABLE 1-FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AP)

PARAGRAPH	TITLE		SHEET 1 of		DRAWING NUMBER
	Primer, Stab, PA 515				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major 101	Function and Energy Output	125	a	3.2.1	4.5.2
Minor	None Defined				
	(a) If two (2) or more primers fail to comply with the applicable requirements, the first article shall be rejected.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026/10 23T01:33Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection:

4.4.1 Inspection Lot Formation: Inspection lots shall comply with the lot provisions of MIL-A-48078. In addition, lots of primers shall:

a. Consist of units produced during a continuous period where no significant changes in process or formulation of raw indredients have occurred.

b. The number of primers in a lot shall be as determined by the contract, but shall not exceed 10,000 units.

c. Contain only metal parts of one interfix number from one manufacturer.

d. Primer mixture consisting of batches blended by the same process. Each batch shall be composed of the same ingredients, each of which is to be from one interfix lot from one manufacturer.

4.4.2 Examination: See MIL-A-48078.

4.4.2.1 Sampling Plans: Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

4.4.2.2 Sampling for Moisture and Composition Determinations: Two (2) independent representative samples of approximately 4g. shall be withdrawn from each batch of lead azide and primer mix. Sampling shall be performed at the operation table immediately prior to consolidation in the cup. If either of the replicate samples fail to meet the test requirement given in 3.2.2.1, 3.2.2.2 or DWG 9298746 the batch involved shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Primer, Stab, PA 515	1 of 1	9298743
			NEXT HIGHER ASSEMBLY: 9239418 or 9327657

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Outside Diameter		0.40%	3.1.1	Gage
102	Outside Height		0.40%	3.1.1	Gage
103	Crimp Angle		0.40%	3.1.1	Gage
Minor					
201	Poor Workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF	DRAWING NUMBER
4.4.2.4	Cup, Primer		9298744
			NEXT HIGHER ASSEMBLY 9298743

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Inside Cup Diameter		0.40%	3.1.1	Gage
102	Outside Cup Diameter		0.40%	3.1.1	Gage
103	Thickness of Cup Bottom		0.40%	3.1.1	Gage
Minor					
201	Radius, Maximum		0.65%	3.1.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-04-02T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET 1 OF	DRAWING NUMBER
.4.2.5	Disc Closure		9298745
			NEXT HIGHER ASSEMBLY 9298743

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Diameter of Disc		0.65%	3.1.1	Gage
202	Thickness of Disc		0.65%	3.1.1	Gage
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-02-23T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET 1 OF	DRAWING NUMBER
4.4.2.6	Primer, Stab, PA 515		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Function and Engery Output		1.0%	3.2.1	4.5.2
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-25T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Primer Mixture	1 OF 1	9298746
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Moisture Content	See 4.4.2.2	See 4.4.2.2	3.2.2	4.5.3
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2024-04-21T02:40:07
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Lead Azide		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Moisture Content	4 See 4.4.2.2	See 4.4.2.2	3.3.1	4.5.3
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

QUALITY · CONFORMANCE · INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
.4.2.9	NOL #130 Priming Mixture	1 OF 1	9298746
			NEXT HIGHER ASSEMBLY 9298743

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Priming Mixture	See 4.4.2.2	See 4.4.2.2	DWG	4.5.4
Minor	None Defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23 10:23:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Box, Set-up, Inner, After Loading and Prior to Closing Slide Cover	of 1	9258182
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Filler and cushion assembly missing		100.0%	3.1.1	Visual
2	Filler and cushion assembly improperly assembled		100.0%	3.1.1	Visual
3	Stiffener missing		100.0%	3.1.1	Visual
4	Slide cover assembled reversed		100.0%	3.1.1	Visual
Major					
101	Release paper missing		0.40%	3.1.1	Visual
Minor					
201	Marking missing, Incomplete or Illegible		0.65%	3.1.1	Visual
202	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260...
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Box, Set-up, Outer, with Inner Set-up Boxes Assembled and Prior to Assembling Top	1 of 1	9258183
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up boxes		100.0%	3.1.1	Visual
2	Stiffeners not facing one direction		100.0%	3.1.1	Visual
Major	None Defined				
Minor					
201	Marking missing, incomplete or illegible		0.65%	3.1.1	Visual
202	Box improperly taped		0.65%	3.1.1	Visual
203	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:33:2
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Sealed Packed Barrier Bag, Prior to Packing in Box	1 OF 1	9258183
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.1.1	Visual
102	Evidence of crushed box		0.40%	3.1.1	Visual
NOTE:	Package should be opened if there is evidence of crushing				
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.1.1	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.1.1	Visual
203	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-0-T02:33Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Box, Packing, Ammunition, Prior to Assembling Cover and Strapping	1 OF 1	9258184
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Bags containing set-up boxes damaged		0.40%	3.1.1	Visual
102	Cushioning material incomplete or missing from around outer set-up boxes		0.40%	3.1.1	Visual
103	Marking missing, misleading or unidentifiable		0.40%	3.1.1	Visual
104	Contents loose within box		0.40	3.1.1	Visual/Manual
Minor					
201	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2020-10-29T02:00Z
Check the source to verify that this is the current version before use.

QUALITY · CONFORMANCE · INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63297 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9258184
4.4.2.14	Box, Packing, Ammunition				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Strapping missing, broken, loose or improperly fastened		0.40%	3.1.1	Visual/Manual
102	Box damaged		0.40%	3.1.1	Visual
103	Marking missing, Incomplete or unidentifiable		0.40%	3.1.1	Visual
104	Wooden box cover nailed to box		0.40%	3.1.1	Visual
105	Metallic seal missing		0.40%	3.1.1	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20261 02:33Z
Check the source to verify that this is the current version before use.

4.4.3 Testing: PRECAUTION. This specification covers sampling and testing toxic or hazardous materials. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

Testing is described in the Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment: The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.3. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.4 herein.

4.5 Test Method and Procedures

4.5.1 Materials, Components and Processes: Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and Mechanical Inspections: The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein.

4.5.2 Functioning and Output

4.5.2.1 Functioning: A 2-ounce steel ball shall be dropped on the firing pin. Materials, hardness and point configuration shall be identical to that shown on firing pin 8797250 shown in Test No 302 of MIL-STD-331. The remainder of the firing-pin detail may be any practical configuration compatible with the test equipment and consistent with test requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

4.5.2.2 Output Test: This test may be conducted at the same time as the functioning test (4.5.2.1). The maximum depth of indentation produced in each sample disc shall be measured and recorded to the nearest 0.0025 centimeter (0.001 inch). To measure the depth of indentation, mount a dial indicator over a horizontal surface plate in such a manner that the indicator stem is perpendicular to the surface plate. The indicator stem shall be approximately .0025 cm (.001 inch) diameter, with a conical tip of 30 degrees included angle terminating in a rounded point having a sperical radius of .064 centimeter (.025 inch) maximum. Place the disc, indented side up, in a ring type holder so arranged that the periphery of the bottom face of the aluminum disc is parallel to the surface plate. Lower the indicator tip to the bottom of the indentation in the disc and set the dial to zero. Take readings at four equidistant points near the periphery of the upper face of the disc. The arithmetical average of these four measurements shall be considered the depth of indentation for that disc.

4.5.2.3 Aluminum Sample Disc: The aluminum sample disc shall have the following characteristics:

a. Diameter 3.10 - .025 centimeters (1.22 - .01 inch)
b. Thickness 0.318 ± .013 centimeter (0.125 ± .005 inch)
c. Material Aluminum, Alloy, Sheet, 2024 - T3, QQ-A-250/4

4.5.3 Moisture Content (See 6.6): Perform the moisture determination in accordance with Method 101.6 of MIL-STD-650 except that a 2g sample shall be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

4.5.4 Primer Mix Composition (See 6.6): The analysis of the composition shall be performed as follows:

4.5.4.1 Barium nitrate: Transfer an accurately weighed portion of approximately 0.5 grams of the dried sample (dried as described in 4.5.3) to a tared medium porosity fritted glass crucible of 30 milliliter (ml.) capacity. Record the weight of crucible and sample as Weight A. Add 3 ml. of distilled water saturated with lead azide at a temperature of 5° ± 2°C. Swirl for 30 seconds, then apply suction. Repeat this procedure two times, making a total of three extractions. Using an eye dropper, transfer to the crucible enough alcohol to thoroughly wet the sample and wash the crucible walls. Aspirate until the odor of alcohol is no longer detectable and dry the crucible in an oven for 30 minutes at 60° + 5°C. Cool in a desiccator and weigh. Record this weight as Weight B. Reserve the crucible and residue for the basic lead styphnate determination. Correct for the percentage of basic lead styphnate in the water extract as follows: Transfer the filtrate and washings quantitatively to a 100 ml. calibrated volumetric flask, washing the beaker thoroughly with distilled water and dilute to the mark. Using a calibrated pipette, transfer a 10 ml. aliquot of this solution to a second 100 ml. calibrated volumetric flask and dilute to the mark with distilled water. Transfer a portion of this solution to a corex glass spectrophotometric cell having a width of approximately 1 centimeter (cm) and determine its optical density at a wave length of 410 millimicrons. Use as reference a similar cell containing the same proportion of water saturated with lead azide and alcohol as in the sample solution. Since the cell which holds the lead styphnate solution is not identical with the reference cell, correct the optical density obtained as described above for the difference in the amount of light which the two cells scatter and absorb. To do this, fill both cells with a solution of water and alcohol, and measure at a wave length of 410 millimicrons, the optical density of the cell which originally contained the basic lead styphnate solution. Caluculate the percentage of basic lead styphnate in the filtrate on a dry basis as follows:

Basic lead styphnate found in barium nitrate filtrate, Percentage $P_b = \frac{4.48\ (A-B)}{WD}$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

where:

A = Optical density of normal lead styphnate solution.
B = Optical density of water and alcohol solution.
D = Width of corox cell, cm.
W = Weight of dried sample, g,

Calculate the percentage of barium nitrate in the sample as follows:

$$\text{Barium nitrate, percent} = \frac{100 \cdot (A-B)}{W} - (P_b)$$

where:

W = Weight of the dried sample, g.
A = Weight of crucible and sample, g.
B = Weight of the crucible and sample after extractions with water saturated with lead azide, g.
P_b = Percentage of basic lead styphnate found in barium nitrate filtrate.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:33Z
Check the source to verify that this is the current version before use.

4.5.4.2 Basic Lead Styphnate: Using the residue obtained in the determination of barium nitrate (See 4.5.4.1), determine the basis lead styphnate content of the sample in accordance with Method 408.1 of MILSTD-650 except use the following calculation:

$$\text{Percentage basic lead styphnate} = 28\ \frac{(A-B)}{WD} + P_b$$

where:

A = Optical density of basic lead styphnate.
B = Optical density of ammonium acetate solution.
D = Width of corex cell, cm.
W = Weight of dried specimen.
P_b = Percent basic lead styphnate found in barium nitrate filtrate.

4.5.4.3. Tetracene: The wet residue obtained in the determination of basic lead styphnate shall be washed three times with alcohol, dried in an oven maintained at 60 + 5°C, for 30 minutes, cooled in a desiccator and weighed. The dried residue in the crucible shall be transferred to a 125 ml. beaker with a stream of water; 25ml. of water shall be added, and the contents of the beaker boiled on a hot plate for 5 minutes. The contents of the beaker shall be quantitatively transferred into the same crucible, and the residue in the crucible washed three times with boiling water and finally with alcohol. The crucible and contents shall be dried in an oven maintained at 60 + 5°C for 30 minutes, cooled in a desiccator and weighed. The percentage of tetracene in the specimen shall be calculated as follows:

$$\text{Tetracene, percent} = \frac{(C-D)\ 100}{W}$$

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:33Z
Check the source to verify that this is the current version before use.

where:

C = Weight of crucible and residue after extraction with saturated ammonium acetate solution, g.
D = Weight of crucible and residue after treating with hot water, g.
W = Weight of the dried specimen, g.

4.5.4.4 Antimony sulfide: The weight of the residue shall be calculated from the determination of tetracene as percentage antimony sulfide in the specimen as follows:

$$\text{Antimony sulfide, percent} = \frac{(D-E)\ 100}{W}$$

where:

D = Weight of crucible and specimen after treating with hot water, g.
E = Weight of crucible, g.
W = Weight of dried specimen, g.

4.5.4.5 Lead azide: The lead azide content in the specimen shall be determined by subtracting from 100 the combined percentage of barium nitrate, basic lead styphnate, tetracene and antimony sulfide.

4.5.5 Data Items: The contractor shall submit a quality inspection test, demonstration and evaluation report in accordance with Data Item Description DI-R-1721 and DI-R-1724 giving the detailed test results.

5. PACKAGING

5.1 Preservation and Packaging

5.1.1 Level B: Packaging shall be as specified on dwgs 9258182 and 9258183.

5.2 Packing

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:33Z
Check the source to verify that this is the currentversion before use.

5.2.1 Level B: Packing shall be as specified on dwg 9258184.

5.3 Marking: Marking of all packaging and packing shall comply with dwgs 9258182, 9258183, and 9258184 and MIL-STD-129.

6. NOTES

6.1 Intended Use: The primer covered by this specification is intended for use in the 2.75 Inch Rocket.

6.2 Ordering Data: See MIL-A-48078.

6.3 Data Requirements: Deliverable data required by this specification is cited in the following paragraphs:

PARAGRAPHS	DATA REQUIREMENT	APPLICABLE DID
4.5.5	Quality Inspection Defect Report	DI-R-1721
4.5.5	Quality Inspection Test, Demonstration and Evaluation Report	DI-R-1724

(Copies of data item descriptions required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

6.4 Submission of Inspection Equipment for Design Approvals: See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.5 Drawings: Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

6.6 Equivalent Test Methods: Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted thru the Contracting Officer to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QA, Dover, New Jersey 07801. This description should include but not be limited to the procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision, and drawings of any special equipment required.

Custodian
Army-AR

Preparing Activity
Army-AR

Project Number: 1375-A226

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-63297 PRIMER, STAB, PA515

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:33Z
Check the source to verify that this is the current version before use.