MILITARY SPECIFICATION

BREAD PUDDING, IMITATION MAPLE FLAVORED, WITH SMOKED SAUSAGE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers bread pudding, maple flavored with pork sausage tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistance Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of specifications, standards and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59)

(Copies may be obtained from the Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

Meat and Poultry Inspection Regulations

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Standards for Condition of Food Containers

(Copies may be obtained from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 0610, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies may be obtained from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Copies should be obtained from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Copies should be obtained from the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to the first article inspection (see 4.3, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, off-odors, off-flavors, and off-colors.

3.2.1 Sausage Links, smoked, cooked. Cooked, smoked sausage links shall be commercially cured in accordance with USDA Meat and Poultry Inspection Regulations. The sausage links shall contain not more than 90 percent pork and not less than 10 percent beef based on raw meat weight. Added water shall not exceed 4 times the protein content plus 10 percent as determined by USDA methodology. The cooked, smoked sausage links shall not contain more than 2.2 percent corn syrup or corn syrup liquid equivalent. The cooked, smoked sausage links shall have a fat content of not greater than 30 percent and a salt content not greater than 2.7 percent. Each sausage link shall be approximately 2 inches (± 1/8 inch) in length and the count per pound shall be 46 to 52. The cooked, smoked sausage links shall have a uniform brown surface color and shall possess a heavy smoke flavor. Packaged, sausage links shall be maintained at an internal temperature of 28° to 40°F for not more than 15 days prior to tray pack can filling. If destined for freezing, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

packaged sausage links shall be frozen to an internal temperature of 0°F or below withn 72 hours after packaging and shall be held for not more than 30 days prior to tray pack can filling and sealing.

3.2.2 Whole, eggs, liquid or frozen. Whole eggs may be liquid or frozen and shall have been processed and labeled in accordance with Regulations Governing the Inspection of Eggs and Egg Products (7 CFR 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell eggs as evidenced by a USDA Egg Products Inspection Certificate. For liquid whole eggs, the certificate shall state the date and the time of pasteurization. Liquid whole eggs shall be held at an internal temperature of 28° to 40°F for not more than 72 hours from the time of pasteurization until the start of formulation of the product in which they are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days from the date of production. The whole eggs shall be free from off-odors, off-flavors, or foreign odors and flavors, such as metallic, musty, sour, fruity, or sulfide like and shall be free from foreign material.

3.2.3 Sugar, granulated. Sugar shall be white, refined, sucrose, granulated cane or beet, or a combination of both and shall comply with MIL-STD-900.

3.2.4 Water. Water used for formulation, ice making and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.5 Bread, white, enriched. Bread shall be commercial, soft crumb, enriched, white bread. The bread shall possess a flavor, aroma and texture that is typical of soft crumb, white bread. The commercial white bread shall have a moisture content of 38.0 percent; however, if this moisture requirement is not met, the moisture can be adjusted to 38.0 percent requirement as described in 3.3.2, footnote 1. The bread shall have a protein content of not less than 8.0 percent, fat content of not less than 1.4 percent, and carbohydrate content of not less than 50.0 percent.

3.2.6 Oil, vegetable. Vegetable oil shall possess a clean, bland flavor and shall have a minimum stability of 15 hours (A.O.M), a free fatty acid value not to exceed 0.05 percent, a moisture/volatile matter content not to exceed 0.06 percent and pass a cold test of 5.5 hours (minimum).

3.2.7 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.8 Cream, dry. Dry cream shall comply with FDA Standards of Identity for dry cream and shall contain 60 to 65 percent, by weight, of milk fat. The product shall contain no added nutritive sweeteners.

3.2.9 Flavoring, maple, imitation. Imitation maple flavoring shall be a double strength product that possesses a color, flavor and odor characteristic of maple flavoring (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of frozen whole eggs. Frozen whole eggs shall be tempered/thawed to an internal temperature of 28° to 40°F and held for not more than 24 hours prior to product preparation.

3.3.2 Preparation of bread pudding. The bread pudding shall be formulated as follows:

Ingredient	Percent by Weight
Water	29.17
Eggs, whole	28.18
Bread 1/	27.37
Sugar	11.69
Vegetable oil	2.03
Imitation maple flavor, double strength	0.52
Cream, dry	0.78
Lecithin	0.26

1/ The moisture content of the bread used in the formula shall be determined before combining with the above ingredients. If the moisture content is determined to be greater than 38 percent, that amount in excess shall be deducted from the percent water in the formulations. If the moisture content is less than 38 percent, adjust the formulation with the required amount of water.

a. The dry cream shall be rehydrated in the formula water.

b. The balance of ingredients (except the bread) shall be combined with the rehydrated cream and mixed until the sugar is completely dissolved.

c. The bread shall be added and coarsely mixed to produce small but recognizable particles of bread.

3.3.3 Product preparation. The Bread Pudding, Maple Flavored, with Sausage shall be formulated and prepared as follows:

Ingredients	Percent by Weight
Bread pudding mixture	77.0
Sausage links	23.0

a. The sausage shall be added to the bread pudding mixture and mixed only for sufficient time to uniformly distribute the sausages throughout the pudding.

b. Filling of the product into Tray Pack cans shall be a continuous operation. Filling shall be completed within one hour after product

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

preparation. The time allowed from product preparation to tray can filling may be extended to four hours provided the product is held under refrigeration at an internal temperature of 28° to 40°F during this time. In addition, the mixture shall be periodically stirred during can filling to prevent settling.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product so as to conform to the finished product requirements and to the following requirements.

a. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirement (see 3.6r).

b. The filled and sealed tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (Fo) of not less than 6.0 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material, such as, but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as, but not limited to rancid, scorched, burnt, stale, sour, musty, moldy, or sulfurous.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 104 ounces.

e. No individual can shall contain less than 102 ounces of product.

f. The product shall have a tan surface with a uniform creamy-tan interior.

g. The product shall be uniformly interspersed with discernable sausages.

h. The product shall possess a slightly sweet maple flavor, and moderate sausage flavor.

i. The product shall have a smooth surface with a moist, dense grainy, spongy texture.

j. The sausage links shall have a moderately uniform brown surface color with no pink or red color throughout.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

k. No individual can shall have a fat content greater than 23.0 percent.

l. The average fat content shall be not greater than 21.5 percent.

m. No individual can of product shall have a salt content greater than 1.5 percent or less than 0.5 percent.

n. Texture of the sausage shall not be dry or rubbery.

o. Total weight of bone, cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in any individual can shall be not more than 1 ounce.

p. There shall be no bone measuring greater than 0.3 inch in any dimension.

q. The product shall show no evidence of excessive heating (materially darkened, scorched).

r. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The meat component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to any identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 104 ounces or if the net weight of any individual can is less than 102 ounces, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/ 3/

Category	Defect
Major	
101	Product does not have a uniform tan surface and a uniform creamy-tan interior.
102	Sausage links not uniformly interspersed throughout the product.
103	Total weight of bone, cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in a can weighs more than 1 ounce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ 3/ (cont'd)

Category	Defect
Major	
104	Presence of bone greater than 0.3 inch in any dimension.
105	Texture of sausages, dry or rubbery.
106	Product does not possess a slight sweet maple flavor, and moderate sausage flavor.
107	Product not uniform in appearance and does not possess a smooth surface with a moist, dense grainy, spongy texture.
108	Sausage links do not have a moderately uniform brown surface color or has a pink or red color throughout.
109	Evidence of excessive heating (materially darkened or scorched).

1/ The presence of any foreign material (e.g., dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal, etc.) foreign odor or flavor (e.g., rancid, burnt, scorched, moldy, sour, stale, musty, or sulfurous, etc.) or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall only be performed when deemed necessary by an AMS agent.)

3/ The product shall be divided into ten approximately equal portions and each portion shall be examined for appearance and texture characteristics.

4.5.3.3 Fat and salt content. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by the AMS agent as reserve samples.

The three Tray Packs for laboratory analyses shall be individually tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Cereal Foods, except that

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

preparation of the samples shall be as follows: The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. Test results shall be reported to the nearest 0.1 percent. Any test failure is a major defect. The lot shall be rejected if the following defects occur:

a. The fat content of any individual Tray Pack is greater than 23.0 percent.

b. The average fat content of the three tray packs is greater than 21.5 percent.

c. The salt content of any individual Tray Pack is less than 0.5 percent or greater than 1.5 percent.

Analysis of reserved samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers except that inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a critical defect and shall be cause for rejection of the lot:

Evidence of buffing causing damage (i.e. scratches or scuffing) to exterior can coating.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4) except that, for self-adhering labels, the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, i.e., label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and CFR 21, Part 113, Subpart D, or CFR 9, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns is a major defect and shall be cause for rejection of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, only lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance is a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. One hundred and four ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. Buffing of the can causing damage to the exterior can coating is not permitted (see 4.5.4).

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans also with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., EST 38) or a three letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four-digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987 would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

"Tray cans may be heated prior to serving or served at ambient temperatures without heating. When heated, the following heating directions shall apply:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently 35 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven 35 - 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions cut 3 rows by 6 rows."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

As an alternate labeling method, a pre-printed self-adhering 0.002 inch thick clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When self-adhering label is used, the tray pack can shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters, larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of packing required (see 5.2).
e. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

6.4 Flavoring maple, imitation. It has been found that Durkee's Standard Imitation Maple Flavoring (Durkee Industrial Foods, 925 Euclid Avenue, Cleveland, OH 44155) and Cunningham Imitation Maple Flavor #S-L-102 (Dirigo Corporation, P.O. Box E4 141 W. second street, So. Boston, MA 02127) satisfactorily colors and flavors the product such as to meet the requirements in 3.6f and h.

6.5 Sausage links, smoked, cooked. It has been found that Oscar Mayer's "Little Smokies" (Oscar Mayer, P.O. Box 7188, Madison, WI 53707), Armour's "Cocktail Smokies" manufactured by Armour Food Company, 1230 East Diehl Road, Naperville, IL. 60540, and Kahns' "Lit'l Smokies" (Kahns and Company, 3241 Spring Grove Avenue, Cincinnati, OH 45225) meet the requirements of 3.2.1 and performed satisfactorily during development of this product.

6.6 Subject term (key word) listing.

Bread pudding
Canned foods
Rations
Sausage
Tray pack

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8940-0663

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44351	Bread Pudding, Imitation Maple Flavored, with Smoked Sausage, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to pro suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.