MILITARY SPECIFICATION

CONDIMENTS, PLASTIC COLLAPSIBLE TUBE PACK

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers plastic collapsible tube pack condiments as a component of operational rations.

1.2 Classification. The product shall be of the following types, as specified (see 6.1).

Type I - Mustard
Type II - Catsup
Type III - Sweet Pickle Relish

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-20036 - Mustard
L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
Q-A-1876 - Aluminum Foil

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies may be obtained from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Catsup

(Copies may be obtained from the Standardization Section, Fresh Products Branch, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2056, South Building, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

F 88 - Seal Strength of Flexible Barrier Materials

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Copies should be obtained from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Copies should be obtained from the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.2).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Mustard, prepared. The prepared mustard shall meet the requirements of Commercial Item Description (CID) A-A-20036. In addition, the viscosity of the mustard shall be not less than 1.5 cm per 15 seconds or greater than 3.0 cm per 15 seconds when determined by a Bostwick consistometer.

3.2.2 Catsup. The catsup shall be U.S. Grade A or U.S. Fancy of the U.S. Standards for Grades of Tomato Catsup.

3.2.3 Relish, sweet pickle. Sweet pickle relish shall consist of cured, finely cut or finely chopped cucumbers packed in vinegar solution with suitable nutritive sweetening ingredients. The sweet pickle relish may contain other finely cut or chopped vegetable ingredients such as cabbage, onions, green and red peppers.

3.2.4 Xanthan gum. Xanthan gum shall comply with the Food Chemicals Codex.

3.2.5 Glycerol. Glycerol shall comply with the Food Chemicals Codex.

3.2.6 Water. Water used for formulation, ice making, and washing shall conform to the National Primary Water Regulations.

3.3 Preparation and processing. Preparation shall be on a continuous basis.

3.3.1 Product preparation. The product shall be prepared as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

3.3.2 Preparation of mustard, (Type I).

The prepared mustard shall be handled in a manner to prevent discoloration and filled into the tubes at ambient room temperature.

3.3.3 Preparation of catsup, (Type II).

a. The catsup shall be heated to 165°F to 170°F and held in this temperature range for approximately 3 minutes.

b. The heated catsup shall be handled in a manner to prevent discoloration and shall be filled into the tubes immediately after heating.

3.3.4 Preparation of sweet pickle relish, (type III).

Ingredient	Percent by weight
Sweet pickle relish	99.40
Xanthan gum	.30
Glycerol	.30

a. The sweet pickle relish shall be milled once through a 1/4 inch sieve size screen.

b. A slurry shall be prepared by mixing the Xanthan gum with the glycerol.

c. The slurry shall be added to the milled relish and blended on low speed to form a homogeneous mixture. The viscosity of the combined slurry and relish shall be not less than 0.3 cm per 60 seconds or greater than 0.7 cm per 60 seconds when determined by a Bostwick consistometer.

d. The relish mixture shall be handled in a manner to prevent discoloration and shall be filled into the tubes at ambient room temperature.

3.4 Filling and sealing. Each tube (see 5.1.1) shall be filled with product that conforms to the finished product requirements and to the following requirements:

a. A net weight of 207 grams of type I product shall be filled in each tube.

b. A net weight of 223 grams of type II product shall be filled into each tube.

c. The temperature of the catsup at time of filling shall be in the temperature range of 165°F to 170°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

d. A net weight of 218 grams of type III product shall be filled into each tube.

e. Each tube of product shall be heat sealed immediately after filling.

f. Tube seals shall be free from entrapped matter.

3.5 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to dirt,. insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to burnt, scorched, stale, sour, rancid, moldy, or sulfurous.

c. There shall be no color foreign to the product.

d. The type II and type III product shall not be rubbery.

e. The product shall be smooth, without lumps, and shall not be excessively thick or thin.

f. The type II product shall show no evidence of excessive heating (materially darkened or scorched).

g. The average net weight of the type I product shall be not less than 207 grams, no individual tube shall contain less than 202 grams.

h. The average net weight of the type II product shall be not less than 223 grams, no individual tube shall contain less than 218 grams.

i. The average net weight of the type III product shall be not less than 218 grams, no individual tube shall contain less than 213 grams.

3.5.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample in palatability and overall appearance (see 4.4, 6.1, and 6.2).

3.6 Plant qualifications. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods," and the plant sanitation requirements of the appropriate Government inspection agency.

3.7 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all the requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance of palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document, or applicable purchase document.

4.5.2 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to any identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.5.3 Laminated barrier bag material certification. Material listed below shall be accepted on the basis of a contractor's certification of conformance to the indicated requirements. Thickness tolerance as specified in L-P-378 and QQ-A-1876, as applicable, shall apply:

Material requirement	Requirement paragraph	Test procedure
Ionomer or polyethylene film thickness	5.1.1.1	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirement of L-P-378.
Polyester film thickness	5.1.1.1	As above
Aluminum foil thickness	5.1.1.1	As specified in QQ-A-1876.
Laminated material construction	5.1.1.1	Laboratory evaluation
Color of laminated material	5.1.1.1	Visual examination

4.5.4 Tube seal integrity test. Test apparatus shall be a manually operated press or electrical operated compression machine fitted with a gauge or recording device to measure pressure in pounds exerted on the sample tube. Apparatus or machine shall be fitted or equipped with a pressure disc 2-1/2 inch in diameter and gauge, dial or recording device with a range of 1-125 pound pressure. Test shall be conducted by applying the force of the pressure of the disc down on the center of the tube at approximately 5 inches per minute until the gauge or device reads 40 pounds. The pressure is released after approximately 1 second and the tube removed and examined for leakage. The sample size shall be the number of filled and sealed tubes indicated by inspection level S-1. Any test specimen showing leakage shall be scored as a major defect and shall be cause for rejection of the lot.

4.5.5 Unfilled preformed barrier bag seal strength testing. The unfilled preformed bags shall be tested for seal strength in accordance with method B of ASTM F 88, except that testing speed may be 10 or 12 inches per minute. Machines that apply tensile load to the specimen by movement of the upper or lower clamp may be used. The lot size shall be expressed in bags. The sample size shall be the number of bags indicated by inspection level S-1. Three adjacent specimens shall be cut from each of the three sealed sides of each bag in the sample. The results shall be reported to the nearest 0.1 pound. The average seal strength of each seal shall be calculated by averaging the strengths of the three test specimens cut from that seal. Any test specimen

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

failing to meet the individual test specimen seal strength requirement specified in 5.1.1.1 or any seal failing to meet the average seal strength requirement specified in 5.1.1.1 shall be cause for rejection of the lot.

4.5.6 In-process examination. In-process examination shall be performed to determine conformance to the preparation and processing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation, or of other valid documents shall be cause for rejection of the involved product.

4.5.7 Net weight inspection. The net weight of the filled and sealed tubes and barrier bags shall be determined by weighing each sample unit on a suitable scale tared with a representative empty tube and barrier bag. Any individual net weight not meeting the finished product requirement (see 3.5) shall be scored as a minor defect. The lot size shall be expressed in units of tubes and barrier bags. The sample unit shall be one filled and sealed tube and barrier bag. The inspection level shall be S-3 and the (AQL), expressed in terms of defects per hundred units, shall be 2.5. Results shall be reported to the nearest gram. In addition, the lot shall be rejected if the sample average net weight is more than specified (see 3.5).

4.5.8 Barrier bag vacuum examination. The filled and sealed barrier bag shall be visually examined for a proper vacuum level not less than 96 hours after filling and sealing. The sealed bag shall continue to exhibit tight adherence to the surface contours of the contents when a pulling force is applied at the center of each side seal. This force shall be applied by holding each side seal between thumb and forefinger of each hand, simultaneously exerting a slight pull with both hands. Any evidence of loss of vacuum shall be considered a major defect. The lot size shall be expressed in barrier bags. The sample unit shall be one filled and sealed bag. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65.

4.5.9 Barrier bag closure seal strength testing. The filled and sealed bags shall be tested in accordance with method B of ASTM F 88, except that the specimen holding clamps shall be spaced two inches apart prior to testing and the testing speed shall be 10 or 12 inches per minute. Machines that apply tensile load to the specimen by movement of the upper or lower clamp may be used. The test specimens shall be cut to a length suitable for proper mounting. Three adjacent specimens, 1/2 or 1 inch wide shall be cut from the closure seal of each bag in the sample. The average seal strength of the closure seal shall be calculated by averaging the test results of the three test specimens cut from that seal. The results shall be reported to the nearest 0.1 pound per inch of width. Any test specimen or average seal strength failing to meet the requirements of 5.1.1.1 shall be scored as a major defect. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The sample size shall be the number of bags indicated by inspection level S-1 and the AQL, expressed in terms of defects per hundred units shall be 1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.5.10 Filled and sealed barrier bag examination. The filled and sealed barrier bags shall be examined for the defects listed in table I. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The inspection level shall be S-4 and AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 4.0 for minor defects.

TABLE I. Filled and sealed barrier bag defects

Category		Defect
Major	Minor	
101		Not formed as specified
102		Inside dimensions of bag not as specified
103		Side, end, or closure seal width not as specified
104		An impression or design on seal which conceals or impairs visual detection of seal defects 1/
105		Distance between inside edge of tear nick or notch and inside edge of seal is less than 1/8 inch
106		Color not as specified
107		Required labeling missing, incorrect, illegible, or smudged
108		Bag has odor not associated with material
109		Closure seal width not as specified
	201	Tear nick or notch missing
	202	Tear nick or notch not loaded as specified
	203	Depth of tear nick or notch not as specified

1/ If doubt exists as to whether or not the sealing equipment leaves an impression or design on the seal surface that could conceal or impair visual detection of seal defects, samples shall be furnished to the contracting officer for a determination as to acceptability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

4.5.11 Filled and sealed tube inspection. Filled and sealed tubes shall be inspected for defects indicated in table II. The lot size shall be expressed in tubes. The sample unit shall be one filled and sealed tube. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects.

TABLE II. Filled tube defects 1/

Category	Defect
Major	
101	Dimensions of tubes not as specified
102	Snip tip missing or not closed
103	Neck not threaded
104	Compatible screw cap missing
105	Not heat sealed as specified
106	Presence of entrapped matter in tube seal area
107	Outside surface of tube unclean 2/
108	Date of pack missing from tube closure seal

1/ Any evidence of leakage of product from the tube shall be cause for rejection of the lot.

2/ Scale or dust on the outside of tubes caused by pastuerization may be removed by washing. The following shall not be scored as defects for unclean:

a. Water spots.

b. Any foreign matter which presents no health hazard or no potential tube damage and which readily falls off when pouch is lifted and shaken lightly.

c. Very thin film of grease, oil, or product residue which is discernible to touch, but not readily discernible by visual examination.

4.5.12 Product inspection. The filled and sealed sample tubes shall be opened and inspected for the defects indicated in table III. The lot size shall be expressed in tubes. The sample unit shall be the contents of one tube. The inspection level shall be S-3 and the (AQL), expressed in terms of defects per hundred units, shall be 1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

TABLE III. Product defects 1/ 2/

Category	Defect
Major	
101	Type II and III product is rubbery
102	Product is not smooth
103	Product is excessively thick or thin
104	Product is lumpy
105	Product shows evidence of excessive heating (materially darkened or scorched.)

1/ The presence of any foreign material (e.g. dirt, insects, insect parts, hair, wood, paper, paint, glass, metal, etc), foreign odor or flavor (e.g. burnt, scorched, stale, sour rancid, moldy, sulfurous, etc), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

4.5.13 Viscosity testing. Samples of the type I and type III product shall be individually tested for viscosity as specified in 4.5.13.1 (see 6.4). Any sample unit not meeting the viscosity requirement shall be scored as a major defect. The lot size shall be expressed in tubes. The sample unit shall be one filled and sealed tube. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.13.1 Bostwick consistometer method.

Instrument: Bostwick Consistometer

Catalog Number: 23270-004
VWR Scientific Company
P.O. Box 7900
San Francisco, CA 94120

or

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

Catalog Number: 15-347-50
Fisher Scientific
585 Alpha Drive
Pittsburgh, PA 15238

Method:

a. Level the instrument.
b. Bring filled and sealed tube of product to 100° ± 1°F in a water bath.
c. Open the tube and fill the Bostwick cavity.
d. Scrape product evenly across upper edge of cavity.
e. Release product and time product flow to the nearest 1 second and distance traveled to the nearest 0.1 cm.

4.5.14 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: - National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible

- Tube partitions not full height of shipping container

- Less than required number of tubes packed in shipping container

- Type II product not packed as specified

Minor: - Other required marking missing, incorrect or illegible

4.5.15 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation.

5.1.1 Unit pack. The product of the type specified (see 1.2) shall be filled into one piece collapsible plastic tubes. The net weight of product shall be as specified in 3.4. The tubes shall have a length of 8 inches (± 1/16 inch) and a diameter of 1-1/2 inches (± 1/16 inch) one end of the tube shall be fitted with a blind orifice 0.300 inch (±0.0005 inch) and a 0.340 inch (±0.005 inch) snip tip 0.172 inches high (±0.005 inch). The neck shall project 0.407 inch (±0.015 inch), including snip tip, above the shoulder of the tube and shall be provided with screw threads and a compatable screw cap. After filling, the open bottom of the tubes shall be closed by heat sealing. Sealed tubes shall not leak when tested in accordance with 4.5.4. The filled and sealed tubes shall be inserted in tri-laminate barrier bags fabricated in accordance with 5.1.1.1 and the bags shall be sealed under a vacuum of approximately 23 inches of mercury (see 4.5.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

5.1.1.1 Barrier bag. The tri-laminate barrier bags shall be fabricated from material made by hot-extruding or laminating not less than 0.001 inch thick polyethylene on 0.00035 inch thick aluminum foil (± 10 percent) and laminating the plain side of the foil to 0.0005 inch thick polyester (± 20 percent) (see 4.5.3). The exterior of the laminated material shall have a color in the range from 34079 through 34078 or 24052 through 24087 or 30045 through 30118 (except that 30109 may not be used), or 10045 of FED-STD-595. The inside dimensions of the bag shall be 9-7/8 inches by 3-1/8 inches (± 1/8 inch). The bag shall be heat sealed on three edges with 3/8 inch (± 1/8 inch) wide seals. A tear nick or notch shall be made in one or both side seals, 1 to 1-1/4 inch from the open end of the bag, and a 1/8 inch (± 1/16 inch) lip shall be incorporated into the open end of the bag. At least one of the nicks or notches shall be at least 1/16 inch deep and neither shall extend into the seal to a depth that results in less than 1/8 inch between the inside edge of the notch or nick and the inside edge of the seal. The closure seal shall be not less than 1/8 inch wide located above the nick or notch. Sealing equipment shall not leave an impression or design on the seal surface that would conceal or impair visual detection of seal defects. The average seal strength of the seals shall be not less than 3.5 pounds per inch of width and no individual specimen shall have a seal strength of less than 3.0 pounds per inch of width when tested in accordance with 4.5.4 and 4.5.9.

5.2 Packing. Forty-eight tubes of product preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V3c of PPP-B-636. The tubes shall be arranged eight in length by six in width and individually separated by full height partitions. The partitions shall be fabricated from weather-resistant grade fiberboard conforming to W5c or V3c of PPP-F-320 and shall be approximately 1-1/8 inch square. The inside dimensions of the shipping container shall be 17-1/4 inches in length, by 12-3/4 inches in width by 9-3/8 inches in depth. The type I and type III product shall be packed on end with the screw cap down and the type II product shall be packed with the screw cap up. Shipping containers shall be closed in accordance with method III of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), shipping containers shall be arranged in unit loads in accordance with MIL-L-35078. When unit loads are strapped, strapping shall be limited to nometallic strapping except for type II, class F loads.

5.4 Labeling.

5.4.1 Barrier bag labeling. Each bag shall be clearly printed or stamped, in a manner that does not damage the bag, with permanent black ink which is free of carcinogenic elements or ingredients. The following information shall be located on the body of the bag not closer than 1/16 inch to any seal and shall be of the height indicated:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

Product name: (letters not less than 7/32 inch high)
Date markings: (Date of Pack) (letters not less than 1/4 inch high)
Net weight: (letters not less than 1/8 inch high)
Name and address of producers: (letters not less than 1/8 inch high)

5.4.2 Tube labeling. The date of pack shall be embossed on the tube closure seal.

5.5 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of product required (see 1.2).
c. When a first article is specified (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction sample (see 3.5.1 and 6.2).
e. Type and class of unit load when unit loading is required (see 5.2).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Subject term (key word) listing.

Catsup
Condiments
Mustard
Relish
36 - Person Meal/Module

6.4 The contracting officer may authorize an alternative contractor recommended method of viscosity testing if the alternative method is approved by the U.S. Army Natick Research, Development and Engineering Center.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 8940-A659

Review activities:

Army - MD, TS
Navy - MC, SA
Air Force - 50
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44352(GL)	Condiments, Plastic Collapsible Tube Pack

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:46Z
Check the source to verify that this is the current version before use.