INCH-POUND

MIL-C-44364
10 April 1989
SUPERSEDING
PP-C-002200(Army-GL)
28 June 1984

MILITARY SPECIFICATION

CHICKEN AND NOODLES, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers chicken and noodles thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Cothing, Personal Equipment and Equipage; General Specification for
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Products Inspection Regulations

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Standards for Grades of Canned Mushrooms

(Copies are available from the Director, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2077, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, Room 0610, South Building, P.O. Box 96456, Department of Agriculture, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

U.S. Standards of Identity for Enriched Egg Noodles

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Chicken. The chicken shall be prepared from chilled or frozen ready-to-cook fowl (mature female chicken) which has been processed in accordance with USDA Poultry Products Inspection Regulations. All chicken (raw or cooked) shipped between plants shall be accompanied by a USDA Poultry Grading Certificate to certify class and condition of the product and either the initial chilling date or initial freezing (in-storage) date.

3.2.1.1 Chicken, chilled. Raw bone-in or boneless chicken received in the chilled state shall not have been previously frozen and shall have been held at a temperature not to exceed 40°F for a period of time not to exceed 6 days following initial chilling and prior to preparation and further processing (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.2.1.2 Chicken, frozen. Raw bone-in or boneless chicken received in the frozen state shall have been held at a temperature not to exceed 0°F for a period of time not to exceed 120 days following initial freezing and prior to preparation and further processing (see 3.3).

3.2.1.3 Chicken, cooked, frozen. Frozen cooked chicken shall be prepared from chilled chicken that complies with 3.2.1 and 3.2.1.1. Chicken shall be processed in accordance with 3.3.1 and 3.3.1.1 or 3.3.1.2. Cooked chicken, in log or dice form, shall be packaged and vacuum-sealed in water-impermeable material having an oxygen permeability rate of not more than 10cc of oxygen per square meter per 24 hours at 73°F and 0 percent relative humidity and shall be frozen to an internal temperature of 0°F or below within 72 hours. The packaged, frozen cooked chicken shall have been held at 0°F or below for a period not to exceed 60 days prior to can filling (see 3.4). The initial freezing (in-storage) date and processing and packaging requirements shall be certified by a USDA Agricultural Marketing Service (AMS) Poultry Products Agent. Alternatively, chicken dices produced from cooked chicken logs may be packaged in suitable material other than that described above and placed in a freezer immediately after dicing and frozen to 0°F or below within 24 hours after placement in the freezer. Cooked, frozen chicken dices packaged in other than impermeable material shall be held at an internal temperature of 0°F or below for a period of time not to exceed 30 days. If other than impermeable packaging material is used, the type of material shall be approved by USDA.

3.2.2 Broth, chicken. Chicken broth may be frozen or canned (thermostabilized). The broth shall be inspected in accordance with USDA Poultry Products Inspection Regulations. It shall be free from extraneous material and cracklings. If frozen, broth shall have been held at an internal temperature of 0°F or below for a period not to exceed 75 days prior to use in product formulation. The broth shall be clear, essentially fat free, and concentrated to a soluble solids level sufficient to comply with the solids requirement in the product formulation. The broth shall have a characteristic mild chicken broth odor and flavor and may contain flavor enhancers approved by FDA.

3.2.3 Mushrooms, canned, pieces and stems. The canned pieces and stems shall be U.S. Grade B or better, in accordance with the U.S. Standards for Grades of Canned Mushrooms. The mushrooms shall be drained prior to use in the sauce formulation. The brine shall be retained for inclusion into the sauce. The canned mushrooms shall be from the latest date of pack.

3.2.4 Mushrooms, frozen, sliced. Frozen mushrooms shall be prepared from fresh, sound, properly trimmed and washed mushrooms possessing the characteristics of the species Agaricus (Psalliota) bisporus or Agaricus bitorguis. The mushrooms shall be of the white or cream color type and shall be a randomly sliced style and approximately 1/8 inch slices. The frozen mushrooms shall be of the latest season's pack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.2.5 Cheese, cheddar, sharp, dehydrated, uncolored. Dehydrated cheddar cheese shall be derived from aged cheddar cheese. The dehydrated cheese shall be uncolored, uniform in composition and appearance, and free from burnt specks and from lumps that do not fall apart under light finger pressure. The cheese shall possess a characteristic flavor and odor. The dehydrated cheese shall contain not more than 4.0 percent moisture, not more than 5.0 percent salt, and not less than 50.0 percent milkfat.

3.2.6 Starch, food, modified, high opacity. The high opacity starch shall be white, odorless, finely pulverized modified maize food starch for use in canned foods and shall comply with MIL-STD-900. The modified starch shall demonstrate initial viscosity development in the temperature range 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The cooked slurry prepared from the starch shall be bland with essentially no cereal or starch taste.

3.2.7 Shortening, vegetable, powdered. The powdered vegetable shortening shall consist of components which, when combined, will serve as a product whitening agent. The powdered shortening, when used as an ingredient in this product, shall withstand the conditions of thermoprocessing specified in this document without browning. A typical analysis of the powdered shortening follows:

Fat	75.00 percent ± 1.50 percent
Protein	5.50 percent ± 0.50 percent
Carbohydrates	15.00 percent ± 1.00 percent
Moisture	2.00 percent maximum

3.2.8 Fat, chicken, rendered, frozen. Frozen rendered chicken fat shall have a clear, yellow color and a characteristic mild chicken-fat odor and flavor. The fat may contain USDA approved antioxidants. The chicken fat shall have a peroxide value not to exceed 6 meq./kg, a free fatty acid value not to exceed 0.50 percent (expressed as oleic acid), and a moisture content not to exceed 0.25 percent. The chicken fat shall be produced in accordance with USDA regulations and shall have been held at an internal temperature of 0°F or lower for a period not to exceed 75 days prior to sauce formulation (see 3.3.3).

3.2.9 Sugar, white, granulated. Sugar shall be white, refined, granulated cane or beet sugar, or a combination thereof, and shall comply with MIL-STD-900.

3.2.10 Onions, dehydrated, chopped. The dehydrated chopped onions shall be Fancy Grade as defined in the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.11 Monosodium glutamate (MSG). Monosodium glutamate (MSG) shall comply with the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.2.12 Celery, soluble. Soluble celery flavoring shall be prepared by blending and dispersing a minimum of 4 percent of total extractives of the dried fruit of Apium graveolens L. and soluble, dry, edible carrier. The flavoring shall possess a clean, celery-like aroma with a slightly bitter taste. The flavoring shall be free-flowing, yellowish-gray in color, and free of caking.

3.2.13 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner coverings have been removed. The pepper shall have a characteristic penetrating odor, a hot biting pungent flavor, and a light color. The white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.14 Garlic powder. Garlic powder shall be Fancy Grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.15 Bay leaves, ground. Ground bay leaves shall be derived from the dried leaves of Laurus nobilis L. The bay leaves shall possess a pleasant aromatic odor and a pungent, mildly bitter flavor and a pale green to yellow green color. A minimum of 95 percent shall pass through a U.S. Standard No. 30 sieve. Volatile oil content shall be not less than 1.0 mL of volatile oil per 100 grams of ground bay leaves.

3.2.16 Noodles, egg (fettuccini), enriched. Egg noodles shall comply with FDA Standard of Identity for Enriched Egg Noodles. The egg noodles shall be dried with no checking or cracking and shall comply with the following dimensions and analytical requirements:

Length:	4.0 inches (± 0.5 inch)
Width:	0.25 inch (± 0.00625 inch)
Thickness:	0.040 inch (± 0.003 inch)
Moisture:	Not greater than 12.00 percent
Ash:	Not greater than 0.98 percent (moisture-free basis)
Protein:	Not less than 13.00 percent (moisture-free basis)
Egg solids:	Not less than 5.50 percent by weight.
Lipid phosphorous:	Not less than 0.136 percent if prepared with egg yolk solids; not less than 0.101 percent if prepared with whole eggs.

The egg noodles shall comply with MIL-STD-900.

3.2.17 Sodium tripolyphosphate. Sodium tripolyphosphate shall comply with the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.2.18 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.2.19 Water. Water used for ice-making, formulation, rehydration, blanching and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation and further processing. Processing shall be on a continuous basis.

3.3.1 Chicken preparation. The chicken shall be made boneless and skinless. The wing tips, giblets, neck, feet, and viscera shall be excluded. The boned meat shall be free of pin feathers, skin, blood clots, bruises, blemishes, ligaments, tendons, coarse connective tissue, cartilage, and bone greater than 0.3 inch in any dimension. The boneless chicken meat shall be comprised of at least 50 percent white meat. Cooked chicken dices shall be prepared in accordance with 3.3.1.1 or 3.3.1.2.

3.3.1.1 Preparation of individually quick frozen (IQF) chicken dices. The IQF chicken dices shall be prepared as follows:

a. The chicken shall be cooked either before or after deboning by any commercially acceptable cook method in accordance with USDA Poultry Products Inspection Regulations.

b. The cooked chicken meat shall be cooled to an internal temperature of 28° to 40°F within 4 hours following the cooking process and shall be held not more than 48 hours at this temperature prior to dicing.

c. The cooked chicken meat shall be mechanically diced with dicer settings at 3/4 by 3/4 by 3/4 inch dimensions. The diced meat shall not be held longer than 4 hours at an internal temperature of 28°to 40°F from time of dicing to the beginning of the IQF process.

d. Immediately after the IQF process, the frozen chicken dices shall be screened to eliminate fines. The frozen and screened chicken dices shall be packaged and vacuum sealed in water-impermeable material having an oxygen permeability rate of not more than 10 cc of O_2 per square meter per 24 hours at 73°F and zero percent relative humidity (see 3.2.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.3.1.2 Chicken log preparation and processing. The chicken logs shall be prepared and processed as follows:

Ingredient	Percent by weight
Chicken meat	95.75
Ice or ice water	3.00
Salt	1.00
Sodium tripolyphosphate	0.25

a. Fresh chilled chicken meat processed on the day of boning shall be coarse ground within 24 hours following boning. If fresh-chilled (not previously frozen) chicken meat is transported between plants, it shall be maintained at an internal temperature of 28° to 40°F and coarse ground within 6 days following initial chilling. Frozen chicken meat shall be maintained at 0°F or lower until further processing and be coarse ground within 120 days after boning. The meat shall be mechanically coarse ground through a grinder plate having kidney-shaped openings measuring not less than 2 inches in the shortest dimension. The grinder shall be equipped with a 2-blade knife.

b. The coarse ground (chunked) chicken meat shall be mechanically mixed with the salt and sodium tripolyphosphate. The mixing shall continue until the mixture exhibits a sticky (tacky) consistency. The ground chicken meat shall be maintained at an internal temperature of 28° to 40°F during this time period.

c. The mixed meat shall immediately be mechanically stuffed tightly into prestuck, regenerated cellulose casings. The stuffed meat logs shall be in the cooking process within 4 hours after being stuffed. (This period of time may be extended up to 24 hours, provided the meat logs are maintained at an internal temperature of 28° to 40°F.)

d. The chicken logs shall be cooked in a cook house (smoke house without smoke) or by other commercially acceptable cook methods to provide a product meeting the finished product drained weight and other requirements.

e. Immediately after completion of the cooking process, the cooked meat logs shall be placed in an ice water bath, or cooled by other commercially acceptable cooling method, and rapidly cooled to 130°F or below. The chicken logs shall be further cooled from 130° to 80°F or below within 2 hours and further cooled from 80° to 40°F or below within 4 hours. The cooled logs shall be held for not more than 48 hours at an internal temperature of 28° to 40°F prior to dicing or packaging for frozen storage (see 3.2.1.3).

f. The cooked chicken logs shall be mechanically diced with dicer settings at 3/4 by 3/4 by 3/4 inch dimensions. After dicing, the meat shall be screened to eliminate fines. The diced meat shall be held not longer than 4 hours in the temperature range of 28° to 40°F until preparation of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

finished product or, if stored in frozen form, until packaged and vacuum-sealed (see 3.2.1.3). Dices prepared from previously frozen logs shall not be frozen.

3.3.3 Sauce formulation and preparation. The sauce shall be formulated and prepared as follows:

Ingredient	Percent by weight
Broth chicken 1/	78.06
Mushrooms, sliced, frozen or canned, drained	6.95
Cheddar cheese (dehydrated)	5.55
Starch, modified, high opacity	4.10
Powdered vegetable shortening	2.10
Chicken fat	2.00
Sugar, white	0.50
Onion, chopped, dehydrated	0.40
Monosodium glutamate	0.15
Celery, soluble	0.09
Pepper, white, ground	0.05
Garlic powder	0.04
Bay leaf, ground	0.01

1/ The chicken broth shall be adjusted to 3.0 to 3.5 percent solids.

a. A slurry shall be made using part of the chicken broth, the starch, and the powdered vegetable shortening.

b. An emulsion shall be made by mixing the remainder of the chicken broth and the chicken fat. The emulsion shall be heated to a boil in a steam jacketed kettle with continous and vigorous agitation to attain maximum emulsification of the fat.

c. The emulsion shall be cooled to 180°F or lower and the remaining ingredients added. The emulsion shall be stirred to assure that the salt is dissovled, the dehydrated vegetables are rehydrated, and the spices are uniformly dispersed.

d. The slurry shall be added to the emulsion and final mixture heated to 180° to 190°F and held in this temperature range for 5 minutes.

e. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating and holding.

f. The sauce shall be filled within 4 hours after cooking. If a continuous fill method is used, the prepared sauce shall be held in the temperature range of 150°F to 180°F at all times prior to filling into the sauce. If a continuous method is not used, the prepared sauce shall be cooled immediately and held at a temperature not to exceed 45°F at all times prior to filling into the tray pack can.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.3.4 Preparation of noodles. The noodles shall be blanched in hot water until doubled in weight. If the blanched noodles are not filled into a can immediately after blanching, they shall be cooled rapidly to 45°F or lower by washing with cold water immediately following blanching, and held at a temperature of 45°F or below for not longer than 4 hours after blanching.

3.3.5 Preparation of the finished product. The chicken, noodles and sauce shall be combined in the following proportions, using either a single stage or multi-stage filling operation:

Ingredient	Percent by weight 1/
Chicken	34.0
Noodles, blanched	9.0
Sauce	57.0

1/ The percent by weight of ingredients may be adjusted if necessary to assure compliance with finished product drained weight requirements.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product such as to conform to the finished product requirements and to the following requirements:

a. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with finished product requirement (see 3.6u).

b. The filled and sealed tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at 240°F or below until a sterilization value (F_o) of not less than 6.0 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odors or flavors such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. No individual can shall contain a bone piece measuring more than 0.3 inch in any dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

e. The total weight of skin, cartilage, coarse connective tissue, section of tendons or ligaments, and discolored meat, collectively, in a can shall be not more than 1 ounce.

f. There shall be no feathers or feather parts.

g. The average net weight shall be not less than 106 ounces.

h. No individual can shall contain less than 104 ounces of product.

i. The average drained weight of whole intact chicken pieces, mushrooms, and noodles (combined) shall be not less than 47.0 ounces.

j. No individual can shall contain less than 43.0 ounces of drained, whole intact chicken pieces, mushrooms, and noodles (combined).

k. Of the 43.0 ounces drained weight of product, not less than 27.0 ounces shall be whole intact chicken pieces.

l. Texture of chicken pieces shall not be dry, rubbery, or mushy.

m. Texture of mushrooms shall not be mushy, hard, fibrous, or tough.

n. The noodles shall not be dry, rubbery, mushy, or crumbly.

o. Sauce consistency shall be smooth, without lumps, and shall not be excessively thick or thin.

p. The average fat content shall be not greater than 8.0 percent.

q. The fat content of an individual tray pack shall be not greater than 10.0 percent.

r. The salt content of an individual tray pack shall be not greater than 1.0 percent nor less than 0.5 percent.

s. The chicken pieces, noodles, and sauce shall be uniformly distributed.

t. The product shall show no evidence of excessive heating (materially darkened or scorched).

u. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.7 Plant qualification. The poultry component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Products Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection service necessary to assure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance be verified by examination of pertinent labels, markings, U.S. Grade certificates, certificates of analysis, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated 40 - 45 minutes in boiling water, opened and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Presence of bone measuring more than 0.3 inch in any dimension.
102	Presence of feathers or feather parts.
103	Total weight of skin, cartilage, coarse connective tissue, section of tendons or ligaments, and discolored meat, collectively, is more than 1 ounce.
104	Drained weight of whole intact chicken pieces, mushrooms and noodles (combined) in a can is less than 43.0 ounces. 3/ 4/
105	Of the 43.0 ounces drained weight of product, less than 27.0 ounces are whole intact chicken pices. 5/
106	Texture of chicken pieces dry, rubbery, or mushy. 6/
107	Sauce consistency lumpy or excessively thick or thin.
108	Texture of mushrooms mushy, hard, fibrous, or tough. 6/
109	Noodles texture dry, rubbery, mushy, or crumbly. 6/
110	Chicken pieces, noodles, and sauce not uniformly distributed.
111	Product shows evidence of excess heating (materially darkened or scorched).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

1/ The presence of foreign material (for example, glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (for example, burnt, scorched, stale, sour, rancid, moldy), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparision shall be performed only when deemed necessary by an AMS agent.)

3/ To determine drained weight, the free liquid in the can shall be poured off and the remaining contents shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be gently agitated such as to liquify rendered fat and to remove the sauce without breaking the chicken pieces, mushrooms, or noodles. The contents shall then be poured into a U.S. Standard 1/4-inch sieve in a manner that will distribute the product over the sieve without breaking the chicken pieces, mushrooms, or noodles. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at an approximate 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4/ The lot shall be rejected if the sample average drained weight of the whole intact chicken pieces, mushrooms, and noodles is less than 47.0 ounces.

5/ For purpose of this examination, the definition of a whole intact chicken piece is one that measures not less than 3/8 inch in each of two separate dimensions.

6/ Examination for appearance and texture conformance of the chicken, mushrooms, and noodles shall be made of representative pieces immediately following the determination of drained weight.

4.5.3.3 Fat and salt content testing. Nine tray packs shall be selected at random from the lot and distributed as follows:

-Three for laboratory analysis.
-Three for submission to the contractor.
-Three for retention by the AMS agent as reserve samples.

The three tray packs for laboratory analysis shall individually be tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The test results shall be reported to the nearest 0.1 percent. Any test failure shall be classified as a major defect. The lot shall be rejected if any of the following major defects occur:

a. The average fat content of the three tray packs is greater than 8.0 percent.

b. The fat content of any individual tray pack is greater than 10 percent.

c. The salt content of any individual tray pack is less than 0.5 percent or greater than 1.0 percent

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a critical defect and shall be cause for rejection of the lot:

Evidence of buffing causing scratches or scuffing of exterior can coating.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except, for self-adhering labels, the following additional defects shall apply:

Major: Labels torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closure shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and CFR 21, Part 113, Subpart D, or CFR 9, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. One measurement shall be made when examining a ribbed lid; lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. One hundred and six ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. Buffing of the can causing damage to the exterior can coating is not permitted (see 4.5.4).

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987 would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.5.4 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT IN WATER: Submerge unopened can in boiling water. Simmer gently for 40-45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

TO HEAT IN OVEN: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven 35-40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 12 portions of 1 cup each.

As an alternative labeling method, a pre-printed, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When a self-adhering labels are used, the tray pack cans shall be labeled with the Julian code and a product code prior to retorting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE. UNLESS PALLET RACKS ARE USED

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Level of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing.

Canned foods
Food processing
Operational ration

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Preparing activity:

Army - GL

(Project 8940-0658)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44364	Chicken and Noodles, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22101:49Z
Check the source to verify that the content is current before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.