INCH-POUND

MIL-H-44357(GL)
29 June 1989

MILITARY SPECIFICATION

HEATER, RATION, INDIVIDUAL MOUNTED TROOPS

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a fabric covered lightweight ration heater for use by mounted troops (see 6.1).

1.2 Classification. The heater shall be of the following types as specified (see 6.2).

Type I - Heater with bayonet plug
Type II - Heater with pin type plug
Type III - Heater with adapter plug

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U. S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-P-44073 - Packaging and Thermoprocessing of Foods in Flexible Pouches

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-13-4000 - Heater, Ration, Individual

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Guide sample. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from this specification may appear in the sample in which case this document shall govern.

3.3 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this specification. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.4 Design and construction. The design and construction of the heater shall be as specified herein, and as shown on Drawing 5-13-4000 and all subsidiary drawings and parts lists. The dimensions of the heater during operation are 9-1/2 inches by 6 inches by 4-1/2 inches. Each heater has four compartments, each compartment is capable of heating one MRE pouch. Water is heated by inserting a disposable water pouch in a compartment. There are five heating elements, so that each pouch is heated from both sides. The heater is equipped with a power cord and plug. Since the auxiliary/utility receptacles vary by vehicle type, a plug of the applicable type (see below) compatible with the vehicle shall be attached to the heater. The heater shall operate off available vehicle electrical power inside the vehicle while it is moving or stationary and shall be collapsible for storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

3.4.1 Type I heater. The type I heater shall have a bayonet plug and be in accordance with Drawing 5-13-4000-1.

3.4.2 Type II heater. The type II heater shall have a pin type plug and be in accordance with Drawing 5-13-4000-2.

3.4.3 Type III heater. The type III heater shall have an adapter plug and be in accordance with Drawing 5-13-4000-3.

3.4.4 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of stitching, and stitches per inch shall be as referenced on drawings. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams occur.

3.4.4.1 Type 301 and 304 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.4.4.1.1 Repairs of type 301 and 304 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box or box-x stitching) and continue a minimum of 1 inch beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.4.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, size, and type of thread are met, and at least three or more tying, overlapping, or backstitches are used to secure the ends of the stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

3.4.4.3 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4 inch.

3.4.4.4 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.4.5 Cutting and fusing of webbing ends. All cut ends of webbings shall be hot cut. The apparatus used to heat cut the webbing ends shall be capable of providing sufficient heat to provide a smooth edge and with the cut ends of the webbing all fused together.

3.4.6 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32 inch in width.

3.4.7 Repairs. Repairs, such as mends, darns, patches, or splices are not permitted on the heater.

3.4.8 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.4.9 Setting of grommets. Holes prepunched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so the barrel must be forced through the hole. The grommet shall be securely clinched without cutting the adjacent material.

3.5 Electrical. The heater shall draw 8 amperes $\pm$ 0.2 percent at 24 volts dc (see 4.4.4.1).

3.6 Thermostat. The thermostat in the heater shall be UL listed and rated for 175°F to 185°F $\pm$ 5°F. The thermostats will be conducted to a 24 volt dc power supply and placed in a temperature controlled environment. The temperature shall be raised from ambient to 185°F. The resistance on the power supply shall change from 0 $\pm$ 5 percent to 100 percent within 30 seconds after reaching 185°F (see 4.4.1.1).

3.7 Temperature.

3.7.1 Initial temperature. On initial heating, each heating element in the heater shall have an initial minimum temperature of 170°F and a maximum temperature of 210°F (see 4.4.4.2).

3.7.2 Steady state temperature. During operation the average steady state temperature in the heater shall be in the temperature range from 170°F to 185°F with no individual thermocouple temperature exceeding 190°F (see 4.4.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

3.8 Climate design. The heater shall be operable, transportable, and storable in the temperatures ranging from -25°F to 160°F (see 4.4.4.4).

3.9 Workmanship. The heater shall conform to the quality of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.4.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of reference documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the components and materials conform to the requirements specified in 3.4.4.4 and 3.6.

4.4.2 End item visual examination. The end items shall be examined for the defects listed below. The lot size shall be expressed in units of heaters. The sample unit shall be one heater. The inspection level shall be S-2 (see 6.6)

Examine	Defect	Classification Major	Minor
Cloth, laminated nylon	Any smash, multiple float or loose slub	101	
	Cut, tear, mend, burn, needle chew, or hole	102	
Webbing	Any hole, cut, tear, or smash,	103	
	Not firmly and tightly woven, edges frayed or scalloped	104	
	Multiple floats		201
	Abrasion mark, slub, broken end or pick	105	
	Cut ends of webbing not fused as specified		202
Cleanliness	Any spot, streak, or stain of a permanent nature on outside of the heater	106	
	Removable spot, streak, or stain on outside of the heater		203
	Threads not trimmed		204

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Hardware	Broken or malformed, failing to serve intended purpose, corroded area, burr or sharp edge	107	
	Any required component improperly installed causing failure to serve intended purpose	108	
	Not assembled as specified	109	
	Size or type not as specified	110	
	Fuse not secure	111	
	Does not collapse for storage	112	
	Cover does not velcro properly		205
Clamp, cord	Reversed		206
Grommets and eyelets	Clinched excessively tight, cutting adjacent material	113	
	Insecurely clinched to a degree that grommet or eyelet may be detached from material	114	
	Washer installed on incorrect side of material		207
	Eyelet barrel split		208
Component and assembly	Any defective assembly	115	
	Any component part omitted	116	
	Any required operation omitted or improperly performed	117	
Open seam	1/2 inch or less		209
	More than 1/2 inch	118	

NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Classification Minor
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching		210
NOTE:	Raw edges not securely caught in stitching shall be classified as an open seam.		
Seam and stitch type	Wrong seam or stitch type	119	
	Seam badly twisted, pleated or puckered	120	
	Gage of stitching not as specified		211
Run-off (see open seam)			
Stitch tension	Loose, resulting in loose bobbin or top thread		212
	Excessively tight, resulting in puckering of material		213
Stitches per inch	Up to two stitches less than minimum specified		214
	Three of more stitches less than minimum specified	121	
	One or more stitches in excess of minimum specified.		215
NOTE:	Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corner shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		
Stitching ends	Not secured as specified		216
Thread breaks, skipped stitches or run-offs	Not overstitched as specified		217

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

Examine		Defect	Classification Major	Minor
Thread breaks, skipped stitches or run-offs (cont'd)	NOTE:	Thread breaks or two or more consecutive skipped or run-off stitches overstitched shall be classified as open seams.		
Location markings		Drilled	122	
		Printed marking more than 1/32 inch width or not covered by component part.		218
Markings		Omitted, incorrect, illegible, misplaced or size of characters not as specified	123	

4.4.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated on the end items without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of heaters. The sample unit shall be one heater. The inspection level shall be level S-2 (see 6.6).

4.4.4 End item testing. The end items shall be tested as specified in 4.4.4.1, 4.4.4.2, 4.4.4.3, and 4.4.4.4 for characteristics in 3.5, 3.7 and 3.8. The lot size shall be expressed in units of heaters. The sample unit shall be one heater. The inspection level shall be S-1 (see 6.6).

4.4.4.1 Current draw. The heater shall be connected to a 24 volt dc power supply and operated for 20 seconds, the current shall be 8 amperes $\pm$ 0.2 percent (see 3.5). Any test failure shall be cause for rejection.

4.4.4.2 Initial heating test. Test blanks shall be fabricated with five thermocouples placed on each side of a 4 inch by 8 inch by 0.5 inch styrofoam pad. The thermocouples shall be located to maximize the distance between themselves. Four blanks shall be placed in the heater so that each element is in contact with a thermocouple array. The heater shall be connected to a 24 volt dc power supply, and operated for 15 minutes. A temperature reading of the thermocouples shall be taken every 10 seconds by a temperature recording device capable of producing a hardcopy output. If any thermocouple reading is not in the temperature range from 170°F to 210°F, it shall be classified as a test failure (see 3.7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

4.4.4.3 Steady state heating test. Four test blanks shall be fabricated using 8-ounce size retort pouches conforming to MIL-P-44073 (see 6.5). Five thermocouples shall be placed in each pouch and 8 ounces of a 5 percent Betonite solution shall be added. The thermocouples shall be spaced evenly in the pouch, and the pouch sealed with the thermocouple wires remaining exposed. The four blanks shall be placed in the heater, one between each two heating elements. The heater shall be connected to a 24 volt dc power supply and operated for 2 hours. Once a temperature of 170°F has been obtained a temperature reading of the thermocouples shall be taken every minute by a temperature recording device capable of producing a hardcopy output. If any thermocouple reading is not in the temperature range from 170°F to 190°F, or the average steady state temperature exceeds 185°F, it shall be classified as a test failure (see 3.7.2).

4.4.4.4 Extreme temperature. The tests in 4.4.4.2 and 4.4.4.3 shall be repeated in a temperature controlled environment of -25°F and 160°F (see 3.8).

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 (see 6.6).

Examine	Defect
Marking (exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Contents	Number of unit packs per intermediate pack or packs per shipping container is more or less than specified.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each ration heater shall be unit packaged in a clear 0.003 inch thick (± 10 percent) polyethylene bag. The bag may be fabricated from film tubing or sheeting and shall measure approximately 18 inches long and 9 inches wide. Closure shall be by folding excess material onto the body of the package. Each bagged heater shall be placed into a snug-fitting style FOL intermediate fiberboard box conforming to grade V3c of PPP-B-636. When stitching is used in the assembly of the box, stitches shall be covered with tape to prevent contact with the heater fabric. Each intermediate box shall be taped closed in accordance with method IV of the appendix of PPP-B-636.

5.1.2 Level B preservation. Each heater, bagged as specified in 5.1.1, shall be placed into the same style and size box as specified in 5.1.1 (taped stitches) except the fiberboard shall conform to type CF, class domestic, grade 275 of PPP-B-636. Each intermediate box shall be taped closed in accordance with method IV of the appendix of PPP-B-636.

5.1.3 Commercial packing. Each heater shall be preserved and packaged in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Six heaters, preserved as specified in 5.1, shall be packed on edge in a fiberboard shipping container. The intermediate boxes shall be arranged in one row of six boxes each. The fiberboard container shall conform to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of each shipping container shall approximate 19-3/4 inches in length, 13-3/8 inches in width, and 7 inches in depth. Approximate dimensions are furnished as a guide only. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, class SW, grade V3c of PPP-B-636. Each container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that inspection shall be in accordance with 4.4.6.

5.2.2 Level B packing. Six heaters, preserved as specified in 5.1, shall be packed as specified in 5.2.1 in a style RSC-L, type V3c fiberboard box, fabricated in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Heaters, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 alletization. When specified (see 6.2), heaters of one type only, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 102 in accordance with appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, intermediate boxes, shipping containers and palletized loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The heater is intended for heating MRE food pouches and disposable water pouches for mounted troops on the following vehicles; M1, M3, M48, M109, M113 family, M551, M728, M992, F1SV, M1-AVLB, and M60-AVLB.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Type, of heater (see 1.2 and 3.4).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

6.4 Guide samples. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 MRE suppliers. The retort pouch material is available from one of the following suppliers:

American National Can Co.
1915 Marathon Ave.
Neenah, WI 54956
POC: Roger Genske
(414) 729-3816

Ludlow Packaging Inc.
Mt. Vernon, OH 43050
POC: Florren Long
(614) 397-0222
Cincinnati, Oh 45203
POC: Orren Freshour
(513) 421-5222

6.6 Acceptance criteria. The acceptance criteria below are recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in acceptance with MIL-STD-105.

6.6.1 For end item visual examination. An acceptance quality level (AQL), expressed in terms of defects per hundred units, of 1.0 for major defects and 6.5 for minor defects is recommended.

6.6.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 4.0 is recommended.

6.6.3 For end item testing. An AQL, expressed in terms of defects per hundred units, of 1.0 is recommended.

6.6.4 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.6.5 For palletization examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.7 Subject term (key word) listing.

Bag
Eat
Food
Meal
Warmer

Custodian:
Army - GL

Preparing activity:
Army - GL

Review activity:
Army - MD

(Project 7310-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-44357(GL)	HEATER, RATION, INDIVIDUAL MOUNTED TROOPS

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.