INCH-POUND

MIL-P-44365
31 March 1989
SUPERSEDING
EE-P-002191A(Army-GL)
26 December 1985

MILITARY SPECIFICATION

PUDDING, CHOCOLATE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers chocolate pudding thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-44340 - Can, Tray Pack

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Condition of Food Containers

(Copies are available from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 0608, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Creamer, nondairy, dry. The dry nondairy creamer shall be white to light cream colored, free-flowing powder that possesses the capability of rapid and complete solubility. The creamer shall contain corn syrup solids, partially hydrogenated vegetable oils, and other safe and suitable ingredients. The creamer shall contain not more than 4.9 percent moisture, not less than 31 percent fat, and not less than 95 percent shall pass through a U.S. Standard No. 10 sieve.

3.2.2 Sugar. Sugar shall be white, refined, granulated, cane or beet sugar or a combination thereof, and shall comply with MIL-STD-900.

3.2.3 Starch, waxy maize, modified. The starch shall be white, odorless, finely pulverized, modified waxy maize starch for use in thermostabilized canned puddings and shall comply with MIL-STD-900. The starch shall be non-gelling and shall demonstrate a low hot viscosity (190°F) but shall thicken to the desired consistency upon cooling. The starch shall be non-pH sensitive, be shear resistant, and be stable to varying storage conditions. The cooked starch shall be bland with essentially no cereal or starch taste. (see 6.4)

3.2.4 Cocoa, powder. The cocoa powder shall conform to the Standard of Identity for medium fat cocoa of the "Food and Drug Administration". The cocoa shall be non-dutched. Not less than 98 percent, by weight, shall pass through a U.S. Standard No. 200 sieve.

3.2.5 Salt. Salt shall be noniodized, white, refined, sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.6 Sodium stearoyl-2-lactylate. Sodium stearoyl-2-lactylate shall comply with the requirements of the Food Chemicals Codex.

3.2.7 Vanilla flavor, artificial. The artificial vanilla flavor shall be Hercules Artificial Vanilla Flavor FLAV-O-LOK 650204U or an equivalent artificial vanilla flavor which imparts a like-flavor and odor in the finished chocolate pudding product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.2.8 Water. Water used for formulation, ice making and washing shall conform to the National Primary Drinking Water Regulations.

3.3 Preparation. The pudding shall be formulated and prepared as follows:

Ingredient	Percent by weight
Water	58.08
Creamer, non-dairy, dry	17.00
Sugar	16.60
Starch, waxy maize, modified	4.50
Cocoa	3.50
Salt	0.20
Sodium stearoyl-2-lactylate	0.10
Vanilla flavor, artificial	0.02

a. Approximately 75 to 80 percent of the water shall be added to a steam-jacketed kettle.

b. The sodium stearoyl-2-lactylate and either a portion of the sugar or of the non-dairy creamer shall be preblended. The mixture shall be added to the kettle.

c. The remaining sugar, the non-dairy creamer, and the salt; or the remaining non-dairy creamer, the sugar and the salt shall be added to the above mixture.

d. The cocoa shall be sifted to remove any lumps and shall be added to the above mixture.

e. The entire contents of the kettle shall be heated without scorching, and with continous agitation, to a temperature of 185° to 190°F.

f. A thin slurry shall be prepared with the starch and the remaining cold water. The slurry shall be added to the above mixture and the resultant mixture heated to 185° to 190°F. Add the artificial vanilla flavoring and thoroughly blend into the mixture.

g. The volume of the final mixture shall be adjusted with water to compensate for evaporation losses during heating.

h. The prepared mixture shall be filled into the tray pack cans within 4 hours after cooking. The temperature of the mixture shall be held at 150° to 180°F until filling into the tray cans.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with pudding to conform to the finished product requirements and to the following requirements:

a. The temperature of the product shall be not less than 150°F at the time of filling.

b. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirement (see 3.61).

c. The filled and sealed tray pack cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting at 240°F until a sterilization value (Fo) of not less than 8.5 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for sterility as specified in 4.5.3.4.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, glass, dirt, insect parts, hair, wood, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. Texture of the finished product shall be smooth and free from lumps.

e. The chocolate pudding shall be evenly cooked with no ungelatinized or watery portions.

f. Product viscosity shall be not less than 0.5 cm per 10 seconds nor greater than 1.5 cm per 10 seconds when determined by a Bostwick Consistometer.

g. The product shall be a uniform medium brown color.

h. The product shall possess a characteristic chocolate flavor with a slight vanilla flavor note.

i. The average net weight shall be not less than 110 ounces.

j. No individual can shall contain less than 108 ounces of product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

k. The product shall show no evidence of excessive heating (materially darkened or scorched).

l. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Packing or Holding of Human Food", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all the requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 110 ounces or if the net weight of any individual can is less than 108 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be opened and inspected for the defects listed in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

National Primary Drinking Water Regulations

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3,200	8	-	0	2
	8	16	1	2
3,201 to 35,000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and, if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Presence of ungelatinized or watery portions.
102	Presence of lumps.
103	Product not uniformly medium brown in color.
104	Product does not possess a characteristic chocolate flavor with a slight vanilla flavor note.
105	Product shows evidence of excessive heating (materially darkened or scorched).

1/ The presence of foreign material (for example, glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparision shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

4.5.3.3 Viscosity testing. Each of the cans in the first sample of cans selected for product inspection (see 4.5.3.2) shall be individually tested for viscosity as specified below:

Bostwick Consistometer method.

Instrument: Bostwick Consistometer
Catalog number: 23270-004
VWR Scientific Company
P.O. Box 7900
San Francisco, CA 94120

or Catalog Number: 15-347-50
Fisher Scientific
585 Alpha Drive
Pittsburgh, PA 15238

Method:

a. Level the instrument.
b. Bring pudding to 70° ± 1°F in a water bath in a covered container.
c. Stir pudding thoroughly before filling the Bostwick cavity.
d. Scrape pudding evenly across upper edge of cavity.
e. Release pudding and time pudding flow to the nearest 1 second and measure distance traveled to the nearest 0.1 cm.

If the Bostwick viscosity value of the pudding from any can in the sample is less than 0.5 cm per 10 seconds or greater than 1.5 cm per 10 seconds, it shall be classified as a major defect and the lot shall be rejected.

4.5.3.4 Commercial sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The sample cans shall be tested for sterility by incubating the cans at 95° ± 5°F for 10 days. Any evidence of can swelling shall be classified as a critical defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the U.S. Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with 4.5.4.1. In addition, the following defect shall be classified as a critical defect and shall be cause for rejection of the lot:

Bare metal exposed on exterior of can (see 5.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4) except, for self-adhering labels; the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, for example, label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closure shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns shall be classified as a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to $75^{o} \pm 5^{o}F$, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. One measurement shall be made when examining a ribbed lid; lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A.

5.1.1 Level A. One hundred and ten ounces of food product shall be filled into a tray pack can conforming to MIL-C-44340 and sealed and thermoprocessed as specified in 3.4 and 3.5. There shall be no evidence of denting, scuffing, scratching, or abrasion of exterior can coating resulting in exposure of bare metal (see 4.5.4).

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 or 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified, except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (for example, EST 38) or a three-letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four-digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987, would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four-digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4. Paper labels are not permitted. Cans shall show the following statements:

DO NOT HEAT

YIELD: For Army Field Feeding serves 18 portions of 3/4 cup each. For other uses serves 25 portions of 1/2 cup each.

As an alternate labeling method, a preprinted self-adhering 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. When a self-adhering label is used, the tray pack can shall be labeled with the Julian code and a product code prior to retorting.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT
OR MORE THAN TWO HIGH IN STORAGE,
UNLESS PALLET RACKS ARE USED

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
e. Level of packing required (see 5.2).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

6.4 Starch, waxy maize, modified (for use in thermostabilized canned pudding). It has been found that Therm Tex Starch manufactured by National Starch and Chemical Corp., Bridgewater, N.J. and Thin-n-Thik 99 Starch manufactured by A.E. Staley Manufacturing Co., Decatur, IL, meet the requirements of 3.2.3 and perform satisfactorily in this product.

6.5 Subject term (key word) listing.

Canned food
Dessert
Combat field feeding
Food processing
Operational ration
Shelf stable

Custodians:
Army - GL
Navy - SA
Air Force - 50

Review activities:
Army - MD, TS
Navy - MC
DP - SS

Preparing activity:
Army - GL

(Project 8940-0662)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-44365	Pudding, Chocolate, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1 Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T01:49Z
Check the source to verify that this is the current version before use.