INCH-POUND

MIL-S-44344
28 June 1989

MILITARY SPECIFICATION

STOVE, MULTIFUEL SQUAD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements including drawings for the multifuel squad stove, with case, which will be used for groups of 2 to 5 personnel engaged in combat operations. The stove has been designed to burn any available liquid fuel including diesel, kerosene, JP 4/5/8 and gasoline (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic, Sheet and Strip, Thin Gauge, Polyolefin
VV-F-800	-	Fuel Oil, Diesel
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-T-704	-	Treatment and Painting of Material

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality Of Wood for Containers and Pallets
MIL-STD-970	-	Standards and Specifications, Order of Preference for the Selection of

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

6-1-8823	-	Stove Assembly, Multifuel, Squad; with Case
6-1-8825	-	Case
6-1-8826	-	Lid
6-1-8827	-	Stove Assembly
6-1-8828	-	Pump Assembly
6-1-8829	-	Cylinder, Pump
6-1-8834	-	Handle
6-1-8840	-	Wrench

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

6-1-8842	-	Hook, Retaining
6-1-8843	-	Tank Assembly
6-1-8848	-	Preheater Assembly
6-1-8849	-	Fuel Cap Assembly
6-1-8850	-	Labels, Identification and Instruction

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

3.2 Materials and components. The materials and components shall be as specified herein and on the applicable drawings. Materials and components not specified shall be selected by the contractor in accordance with MIL-STD-970. Materials and components specified in accordance with MIL-STD-970 shall not degrade the operational suitability or effectiveness of the stove. It is encouraged that recycled material be used when practical providing the requirements of the specification are met.

3.3 Design and construction. The design and construction shall be as specified herein and as shown on Drawing 6-1-8823 and all subsidiary drawings and parts lists pertaining thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

3.4 Performance.

3.4.1 Tank leakage. Prior to attachment of grill and finishing, the tank shall not leak when tested as specified in 4.5.2.

3.4.2 Stove assembly leakage. The stove assembly shall not leak when tested as specified in 4.4.5.

3.4.3 Tank capacity. The tank shall hold 10 ounces minimum and 10.5 ounces maximum of fuel when tested as specified in 4.4.5.

3.4.4 Stove operation and performance. When tested as specified in 4.4.5, the stove shall meet the following requirements.

3.4.4.1 Preheater. The preheater shall light on the first attempt while using only one match and require no more than one additional match to re-light during the time required to preheat.

3.4.4.2 Burner.

3.4.4.2.1 Control knob rotation. The control knob (valve spindle) shall rotate 135 $\pm$ 22.5° before and after the lighting test.

3.4.4.2.2 Burner ignition. The burner shall light automatically from the flame of the preheater.

3.4.4.2.3 Burner flame. With the control knob fully open, the flame shall be symmetrical and blue around the entire outer cap with no traces of yellow and shall heat the two uppermost bars of the grill equally resulting in equal red patterns. With the control knob partially open, the heating shall be symmetrical with the outer cap becoming red uniformly all around. (NOTE: Partially open is the amount required for the outer cap to be heated to a red glow.)

3.4.4.2.4 Valve spindle leakage. There shall be no flame or vapor leaking around the valve spindle.

3.4.4.2.5 Residual fuel. When the stove is operated with the control knob fully open and allowed to run out of fuel, there shall be no more than .5 ounces of unconsumed fuel in the tank.

3.4.5 Pressure relief valve. The pressure relief valve shall open at no more than 25 PSIG and close at no less than 20 PSIG when tested as specified in 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T01:35Z
Check the source to verify that this is the currentversion before use.

3.5 Labels. The labels shall conform to Drawing 6-1-8850. The contents of the labels shall be clearly legible and shall be firmly affixed to the stove in the required locations with no areas of poor or no adhesion. The labels shall be free of tears and scratches.

3.6 Workmanship. The stove assembly shall conform to the quality of product established by this specification.

3.6.1 Surface Defects. The stove assembly shall be free from fractures, splits, punctures, dents, creases and bows. There shall be no burrs, slivers, sharp edges or sharp corners.

3.6.2 Welds. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease and other foreign matter. Welds shall be sound, continuous, smooth and free from pits, burn holes, cracks, fissures, incomplete fusion and deformation of material. All scale, flux deposits and excess metal shall be removed from the finished welds. The welds shall be finished to blend smoothly with the adjacent surfaces.

3.6.3 Brazing. The surface of parts to be brazed shall be free from oxide, scale, paint, grease and other foreign matter. Brazing shall be smooth, continuous, sound and free of embedded foreign matter. All flux shall be removed.

3.6.4 Threaded fittings. Threads shall not be missing, broken, stripped or fractured. Threads shall be protected during welding, brazing, cleaning and painting from being distorted, damaged or coated. When a thread sealing compound is required, it shall be applied uniformly on all threads and any excess after tightening shall be removed.

3.6.5 Finishing. Coatings shall level out to an adherent, continuous and uniform film without runs, streaks, embedded foreign material or areas of no film. The finish after baking shall be free of blistering, crinkling, peeling or chipping.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 3.1 and 6. 2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.4.5.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.2.1 Visual examination of operations. Inspection shall be made of the following operations to establish conformance to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

Whenever nonconformance is noted, correction shall be made to the items affected and to the operation. Items which cannot be corrected shall be removed from production.

a. Welding and brazing of tank conforms to 3.6.2, 3.6.3 and Drawing 6-1-8843.

b. Application of sealing compound to threads conforms to 3.6.4 and Drawings 6-1-8827, 6-1-8848 and 6-1-8849.

c. Cleaning and priming of components prior to final coat of paint conforms to MIL-T-704.

d. Temperature of oven and time period for baking final finish coat conforms to Drawings 6-1-8829, 6-1-8834, 6-1-8840, 6-1-8842 and 6-1-8843.

e. Gasket used when installing preheater assembly to tank in compliance with Drawing 6-1-8827.

f. Siphon tube on preheater assembly is orientated vertically into tank when trigger is orientated in specified position in compliance with Drawings 6-1-8827 and 6-1-8848.

g. Filters are properly rolled and installed in burner assembly fitting in compliance with Drawing 6-1-8827.

h. O-Ring is installed on gland in pump in compliance with Drawing 6-1-8828.

i. Fittings are protected from being distorted during brazing and welding in compliance with 3.6.4 and Drawing 6-1-8843.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of stoves. The sample unit shall be one stove. The inspection level shall be II (see 6.5).

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Blistered, crinkled, peeling, chipping, or not adherent	101	
	Permanently stained, tacky, uncoated areas, runs, streaks or embedded foreign matter	102	
	Color not as specified	103	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Welding	Any weld missing, incomplete, cracked, fractured, has burn holes or fusion incomplete	104	
	Not smooth, scale or flux deposits, excess metal not removed		201
Brazing	Any Braze missing, not smooth or not continuous	105	
	Flux not removed		202
Threaded components	Threads broken, stripped, fractured or missing	106	
	Components not securely tightened		203
	Excess sealing compound not removed		204
Design, construction and workmanship (applicable to all components and assemblies)	Any component missing or not as specified	107	
	Fractured, split, punctured torn, dented, creased, bowed or otherwise malformed	108	
	Any component misplaced or not in proper alignment		205
	Any burr, sliver or sharp edge		206
	Any loose particles inside tank (as noted when shaking)		207
	Any operation omitted or not performed as specified	109	
	Any functioning component that is inoperative or will not operate as intended	110	
	Lid does not fit on case or does not fit snugly on case	111	
Lanyards, wrench and funnel	Chain improperly attached		208
Labels	Any missing, incorrect, incomplete, scratched, torn, not legible or not in proper location	112	
	Any area not securely adhered to tank		209

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Instruction sheet or not legible	Missing, incorrect, incomplete,	210	

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on Drawings 6-1-8825, 6-1-8826, 6-1-8827 and 6-1-8843 that are annotated with an asterisk (see 4.1.2). Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of stoves. The sample unit shall be one stove. The inspection level shall be S-3 (see 6.5).

4.4.5 End item testing. The stoves shall be tested for the characteristics listed in table II. The lot size for all tests shall be expressed in units of stoves. The sample unit shall be one stove. The inspection level for stove leakage and the stove operation and performance tests shall be II and for all other tests, S-2 (see 6.5).

TABLE II. End item tests

Characteristic	Specification reference: Requirement	Specification reference: Test method	Number determinations per sample unit	Results reported as: Pass or Fail
Stove leakage	3.4.2	4.5.3	1	X
Tank capacity	3.4.3	4.5.4	1	X
Stove operation and performance	3.4.4	4.5.1	8	X
Pressure relief valve performance	3.4.5	4.5.3	1	X

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 (see 6.5).

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Stove operation and performance tests. The stove operation and performance tests shall be performed as specified below. Pressurizing and lighting of stove shall be in accordance with the instructions on the instruction label.

Fill tank with summer grade diesel fuel conforming to grade DF-2 of VV-F-800 and pressurize tank.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

b. With burner control knob in full off position (rotate clockwise to shut off) rotate to full open position and measure amount of rotation. Failure to meet requirement in 3.4.4.2.1 shall constitute failure of the test. Return control knob to off position.

c. Light preheater. Failure to be able to light the preheater with a single match or relight using one additional match as specified in 3.4.4.1 shall constitute failure of the test.

d. Light burner and observe performance with control knob in the full open position and the partial open position. Failure to provide the flame and heating required as specified in 3.4.4.2.3 shall constitute failure of the test.

e. During the burner performance test, inspect for flame or vapor leakage around the valve spindle. If there is any flame or vapor leakage, tighten the valve spindle nut and let the stove burn for an additional five minutes minimum and again inspect for flame or vapor leakage around the valve spindle. Failure to meet the requirements in 3.4.4.2.4 for no leakage shall constitute failure of the test.

f. Operate the stove until the flame dies out. Shut burner off and repeat control knob rotation test required in b. above.

g. Drain completely and measure the residual fuel in the tank. Any fuel in excess of the amount specified in 3.4.4.2.5 shall constitute failure of the test.

4.5.2 Tank leakage test. The burner, preheater, and safety relief valve fittings in the unfinished tank shall be securely capped and the fuel cap shall be securely closed. An air pressure of 30 ± 2 PSIG shall be applied and maintained through the fuel cap. Submerge the tank completely in clear water maintained at room temperature (70° ± 2°F) for a minimum of 30 seconds. In accordance with 3.4.1, any steady stream of air bubbles shall be considered evidence of leakage and failure of the test. Any test failure shall be cause for rejection of the tank and correction of the affected process. Successfully tested tanks shall be fully dried prior to being put back into the production lot.

4.5.3 Pressure relief valve performance and stove assembly leakage tests. With the tank empty, the burner assembly, preheater trigger and fuel cap shall be securely closed. A pressure gauge and a means of pressurizing the stove shall be attached to the fuel cap. Submerge the stove (without pump) completely in clear water maintained at room temperature (70 ± 2°F) for a minimum of 30 seconds. An air pressure of not less than 25 PSIG shall be applied through the fuel cap. A steady stream of bubbles should be released from the pressure relief valve. Slowly allow the pressure to reduce and observe when bubbles are no longer being emitted from the relief valve. There should be no bubbles being emitted when the pressure drops to 20 PSIG. In accordance with 3.4.5 if there

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

are no bubbles being emitted at a pressure of 25 PSIG or there are bubbles being emitted at a pressure of 20 PSIG, the test shall be considered a failure. In accordance with 3.4.2, any steady stream of air bubbles (except coming from the pressure relief valve) shall be considered evidence of stove leakage and failure of the leakage test. Successfully tested stoves shall be fully dried prior to being put back into the production lot.

4.5.4 Tank capacity test. Assure that the tank is empty. Securely close the burner valve and preheater trigger and place stove on a level surface. Measure out 10.5 ounces of any one of the fuels used in the stove. The fuel shall be at room temperature (70 ± 2°F). Using the stove funnel, pour the fuel into the tank. The tank is full when the fuel level reaches the top of the filler fitting. In accordance with 3.4.3, if the tank is not full or if there is more than .5 ounces of residual fuel, the test shall be considered a failure.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Each stove, before being placed in its case, shall be packaged in a clear polyethylene film bag of 0.004 inch thickness conforming to type I, class 2 of L-P-378. The bag shall be of adequate size to completely enclose the stove and prevent movement and abrasion within its case. Each complete stove and case shall be placed in a snug-fitting intermediate box conforming to style RSC, type CF (variety SW), class domestic, grade 200 of PPP-B-636. Inside dimensions shall approximate 7-1/8 inches in length, 4-5/8 inches in width, and 5-3/8 inches in depth. Approximate dimensions are furnished as a guide only. Each intermediate box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.1.2 Commercial preservation. Each stove with case shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6. 2).

5.2.1 Level A packing. Twenty-four stoves with cases, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type, style A or J, grade A, type 2 load of PPP-B-601. Level A intermediate boxes shall be packed upright, three in length, four in width and two in depth within a shipping container. Inside dimensions of each container shall approximate 23 inches in length, 20-1/2 inches in width and 12 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and reinforced in accordance with the appendix of PPP-B-601.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:35Z
Check the source to verify that this is the currentversion before use.

5.2.2 Level B packing. Twenty-four stoves with cases, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V3c, V3s or V4s of PPP-B-636. Level A intermediate boxes shall be packed upright, three in length, four in width and two in depth within a shipping container. Inside dimensions of each container shall approximate 23 inches in length, 20-1/2 inches in width and 12 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Stoves with cases, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), stoves with cases, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia of MIL-STD-147, as applicable. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 90 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase or order, intermediate boxes, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The stove covered by this specification is intended for use in the field for cooking rations, heating water and melting snow for groups of 2 to 5 personnel.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issues of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3 and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. When palletization is required (see 5.3).
f. Acceptance criteria required (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Sources of Supply. The following listed manufacturers parts have been found to meet the requirements of the items listed with minor alterations to some of the items.

a. Franz Heinze KG
Postfach 131314
D-5600 Wuppertol 13
W. Germany

Item	Part No.	Franz Heinze Part No.
Burner Assembly	6-1-8847	6215
Preheater Assembly	6-1-8848	6217
Seal Assembly	6-1-8857	6219
Jet, Burner	6-1-8856	6250
Needle Assembly	6-1-8852	6251

b. Optimus International
P.O. Box 1950
1100 Boston Avenue
Bridgeport, CT 06601

Item	Part No.	Optimus Part No.
Fuel Cap Assembly	6-1-8849	2912
Tube, Restrictor	6-1-8858	5163

6.5 Acceptance criteria. The acceptance criteria below is recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.5.1 For end item visual examination. An AQL, expressed in terms of defects per hundred units, of 2.5 for major defects and 4.0 for minor defects is recommended.

6.5.2 For end item dimensional examination. An AQL, expressed in defects per hundred units, of 4.0 is recommended.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:35Z
Check the source to verify that this is the current version before use.

6.5.3 For end item testing. An AQL, expressed in terms of defects per hundred units, of 1.0 is recommended.

6.5.4 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.5.5 For palletization examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.6 Subject term (key word) listing.

Burner
Field equipment
Food cooking equipment

Custodians:
Army - GL
Navy - YD

Review activities:
Army - MD, TS
DLA - GS

User activity:
Navy - MC

Preparing activity:
Army - GL

(Project 7310-A755)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-44344	STOVE, MULTIFUEL, SQUAD

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
3b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil – Downloaded: 2026/6-22701.352
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:35Z
Check the source to verify that this is the current version before use.