INCH-POUND

MIL-S-44355(GL)
28 October 1988

MILITARY SPECIFICATION

SIGN MAKING KIT, PORTABLE

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This documents covers a portable sign making kit.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| L-S-300 | - | Sheeting and Tape, Reflective |
| FF-N-105 | - | Nails, Brads, Staples, Spikes, Wire, Cut and Wrought |
| GG-G-531 | - | Goggles, Industrial and Spectacles, Plastic |
| QQ-A-200 | - | Aluminum Alloy, Bar, Rod, Shapes, and Tubes |
| TT-C-490 | - | Cleaning Method of Ferous Surfaces |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 9905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

GGG-H-86 - Hammer, Hand, (Forged Steel Head)
GGG-S-278 - Shears and Scissors
PPP-B-26 - Bag, Plastic (General Purpose)
PPP-B-566 - Box, Folding, Paperboard
PPP-B-601 - Boxes, Wood, Cleated Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-T-43702 - Tie, Ribbon, Twist
MIL-T-60394 - Tape, Pressure Sensitive Adhesive Film Foam, Double Coated

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MS-9549 - Washer, Flat-AMS5510

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this speci-fication to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-7-190 - Portable Sign Making Kit
5-7-191 - Case Assembly
5-7-192 - Cover, Assembly
5-7-193 - Bag, Storage, Assembly
5-7-194 - Strap, Shoulder Assembly
5-7-195 - Handle, Assembly
5-7-196 - Latch, Cover Assembly
5-7-197 - Latch, Front Assembly
5-7-198 - Cover, Panel
5-7-199 - Front, Panel
5-7-200 - Back, Panel



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:47Z
Check the source to verify that this is the current version before use.

5-7-201 - Bottom, Panel
5-7-202 - Side, Panel Left
5-7-203 - Side, Panel Right
5-7-204 - Holder, Letters, and Arrows
5-7-205 - Holder, Marker
5-7-206 - Holder, Tape, Foam
5-7-207 - Holder, Tape, Reflective
5-7-208 - Holder, Bag
5-7-209 - Holder, Number
5-7-210 - Brace, Corner
5-7-211 - Bag, Pattern
5-7-213 - Letters and Numbers, Sign Kit
5-7-214 - Arrow
5-7-215 - Markers
5-7-216 - Sign Board
5-7-217 - Anchor Stakes

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials. The materials used in the construction of the sign making kit shall conform to the applicable referenced specifications, standards, drawings, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this document (see 6.5).

3.3 Components. The sign making kit shall consist of the items listed in table I.

TABLE I. Sign making kit components

| Component | Requirement paragraph | Quantity | Notes |
|---|---|---|---|
| Case, wood | 3.4 herein | 1 | |
| Bag, storage | 3.5 herein | 1 | |
| Goggles, type I, style B | GG-G-531 | 1 | 1/ |
| Twist ties, green, 15 inch lengths | MIL-T-43702 | 50 | 1/ 2/ |
| Nails, 2 inches long, 98/pound, type II style 17 | FF-N-105 | 1 pound | 1/ 2/ |
| Nails, zinc coated, barbed shank, 1/2 inch long, 80/pound, type II, style 20 | FF-N-105 | 1/2 pound | 1/ 2/ |
| Hammer, hand, type I, class I, style A | GGG-H-86 | 1 | 1/ |
| Shears, type I, class I, style B | GGG-S-278 | 1 | 1/ |
| Anchor stakes | Dwg. 5-7-217 | 40 | 1/ 2/ |
| Anchor tubes, 1/4 inch, 0.035 inch wall, 8 inches long, 6063-T52, type I or II | QQ-A-200 | 40 | 1/ 2/ |
| Flat washer | MS-9549-10 | 100 | 1/ 2/ |
| Letters (5 per card) | | | |
| A, E, I, L, N, O, R | Dwg. 5-7-213 | 4 cards each | 2/ |
| Remaining letters | Dwg. 5-7-213 | 2 cards each | 2/ |
| Numbers 0-9 | Dwg. 5-7-213 | 4 cards each | 2/ |
| Arrows | Dwg. 5-7-214 | 50 cards | 2/ |
| Markers: | | | |
| Black | Dwg. 5-7-215 | 2 | 2/ |
| Red | Dwg. 5-7-215 | 1 | 2/ |
| Blue | Dwg. 5-7-215 | 1 | 2/ |
| Green | Dwg. 5-7-215 | 1 | 2/ |
| Reflective tape, 25 foot length, 2 inch, inside diameter spool, reflectivity 1, color orange, type II, class 4 | L-S-300 | 1 roll | 2/ |
| Sign boards | Dwg. 5-7-216 | 30 | 2/ |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE I. Sign making kit components (cont'd)

| Component | Requirement paragraph | Quantity | Notes |
|---|---|---|---|
| Double-sided foam tape, 1 inch wide, 25 foot lengths, 2.5 inch inside diameter spool, type I, class I | MIL-T-60394 | 1 roll | 2/ |
| Instructions | 3.6 herein | 1 set | |

1/ This item shall be located in the storage bag.

2/ This item, when used up, may be restocked in the kit from separate replacement supplies (see 5.1.1.1).

3.4 Case. The case for the kit shall be constructed in accordance with the applicable drawings listed in 2.1.2 and as specified herein.

3.4.1 Design and construction. The individual panels of the case shall be made of one piece of plywood. All exposed surface edges shall be sanded smooth. The cover, when closed, with the flaps secured, shall set evenly on the case edges and shall align with the sides within 1/16 inch. The space between the closed lid and the sides shall not exceed 1/16 inch. All hardware and corner braces shall be secured evenly on the wood and be firmly attached in accordance with the drawing.

3.4.2 Finish.

3.4.2.1 Metal surface preparation. Prior to priming, and before assembly, the hinges, rivets, bolts, wing nuts, and washers shall have their surfaces cleaned of rust, oil, paraffin, lubricants or other foreign matter and conditioned for painting in accordance with any method of type I or II of TT-C-490.

3.4.2.2 Plywood surface preparation. Before priming, exposed voids in the core of the plywood components shall be filled with a commercial wood filler and sanded smooth. Knots on plywood faces shall be coated with commercial knot sealer and sanded smooth. Plywood surfaces shall be cleaned of dust, sawdust, chips, glue runs and other foreign matter.

3.4.2.3 Priming.

3.4.2.3.1 Plywood. After all hardware has been attached to the case, all interior and exterior surfaces shall be painted with primer specified in all drawings of components made of plywood. The primer shall be thoroughly dry before any necessary sanding is done.



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:47Z
Check the source to verify that this is the current version before use.

3.4.2.3.2 Sanding of primer. The primed exterior surfaces of the case shall be scuff sanded with 80 grit (minimum coarseness) garnet paper but without sanding through the primer to expose bare wood. After sanding, all surfaces shall be cleaned of sanding residue and foreign matter.

3.4.2.4 Topcoat. After assembly and priming, the exterior and interior surfaces of the case with assembled hardware, excluding plastic components, shall be coated with enamel specified in all plywood component drawings. All surfaces shall be thoroughly dry before packing and stacking. Forced drying is permitted, provided that a surface temperature of 140°F is not exceeded and the relative humidity of surrounding air is maintained at 30 percent minimum. When tested as specified in 4.5.1, the top shall not stick to the body, and there shall be no wet or tacky paint.

3.4.2.5 Case. The completely fabricated case (with components) shall be tested as specified in 4.5.2. The cover of the case shall not bind, there shall be no splintering of wood, and the case shall open freely. Parting agents, such as beeswax, may be applied to contact surfaces to assist in meeting the requirements.

3.4.2.6 Marking for identification. The letters "US" in solid face characters, 3-1/2 inches by 5-1/2 inches minimum, shall be stamped or stenciled with black water-resistant ink in the location shown on Drawing 5-7-190.

3.5 Bag, storage. The storage bag shall be constructed in accordance with the applicable drawings listed in 2.1.2.

3.6 Instructions. An instruction pamphlet shall be furnished by the contractor with each sign marking kit. The pamphlet shall be placed in the compartment along with the signboards. The printing and collation of the pamphlet shall be in accordance with the standard sample (see 6.3).

3.7 Workmanship. All components and assemblies of the portable sign making kit shall be free from dirt and other harmful extraneous material, burrs, slivers, rough die, tool and grind marks, dents and other cracks. Castings, molded parts, and stampings, if used, shall be free of sand, fins, pits, blow holes, and sprues. External surfaces shall be free from sharp edges and corners, except when corners are required.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in table III and tested for the characteristics specified in 4.5.1 and 4.5.2. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the following requirements, operations, and assemblies to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts which cannot be corrected shall be removed from production.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE II. In-process examination

| Characteristic | Requirement/Drawing |
|---|---|
| Gluing of all wood joints | Dwg. 5-7-191 |
| Spacing of nails | Dwg. 5-7-191 |
| Metal surface preparation | 3.4.2.1 |
| Holes drilled, pierced or punched for tubular rivets | Dwg. 5-7-190 thru Dwg. 5-7-192 |
| Exposed voids in core of plywood filled with synthetic filler and sanded smooth | 3.4.2.2 |
| Knots on plywood faces coated with knot sealer | 3.4.2.2 |
| Priming of interior and exterior | 3.4.2.3.1 |
| Grit of garnet paper | 3.4.2.3.2 |
| Sanding of primed surfaces of case | 3.4.2.3.2 |
| Temperature and humidity when forced drying is used | 3.4.2.4 |

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in units of sign making kits. The sample unit shall be one sign making kit completely assembled. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 10.0 for major defects and 25.0 for total (major and minor combined) defects.

TABLE III. End item visual defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Fabric, coated | Any hole, cut or tear | X | |
| | Any abrasion mark or scratch which extends through the coating to a point where base fabric yarns or fabric weave can be seen | X | |
| | Any uncoated area | X | |
| | Blister, tunnel or delamination of coating | X | |
| Webbing and tape | Any hole, cut or tear | X | |
| | Frayed or scalloped edges, not firmly or tightly woven | | X |
| | Any needle chews | | X |
| | Ends not turned under or not fused as specified | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Hardware - general | Broken or malformed; corroded area; burrs or sharp edge | X | |
| | Finish omitted or not as specified | X | |
| | Any required component improperly installed causing failure to serve intended purpose | X | |
| Seams and stitching machine 1/ | Open seams: | | |
| | - 1/2 inch or less | | X |
| | - More than 1/2 inch | X | |
| Raw edge (on edge of fabric required to be finished) 2/ | More than 1/2 inch in length when securely caught in stitching | | X |
| Stitch tension | Any loose tension | | X |
| | Tension tight, resulting in puckering of material | | X |
| Thread breaks, skipped stitches or runoffs 3/ | On stitching other than box stitching, overstitched less than 1 inch in each direction beyond defective stitching area | | X |
| | On box stitching, overstitched less than 1/2 inch in each direction beyond the defective stitching area | | X |
| Stitching ends | Not secured as specified | | X |
| Rows of stitching | One or more required rows of stitching omitted | | X |
| Finish of painted surfaces | Color not as specified | | X |
| | Finish not smooth or uniform e.g., has run, sag, tear drop, or areas of no film | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Plywood | Individual panels made of more than one piece of plywood | X | |
| | Direction of grain on plywood panels not as specified | | X |
| | Delamination veneer | | X |
| | Sanded through face or back veneer | | X |
| | Torn grain, chip or splinter in veneer | | X |
| | Breaks on end or edges | X | |
| Construction and workmanship | Any component missing unless otherwise classified herein | X | |
| | Any component wrong size or type | X | |
| | Any component broken, cracked, malformed, or split: | | |
| | - affecting serviceability seriously | X | |
| | - not seriously affecting serviceability | | X |
| | Any operation not properly performed unless otherwise specified herein: | | |
| | - seriously affecting appearance or serviceability | X | |
| | - not affecting appearance or serviceability seriously | | X |
| | Burr, rough edges, sharp edges or surfaces | X | |
| | Slivers, gouges, torn grain, dents, hammer marks, machine marks or bruises | | X |
| | Cover binds in closing operation | | X |
| | Cover more than 1/16 inch from sides and/or ends with cover in closed position | X | |
| | More than three nails or rivets omitted throughout | X | |
| | One nail or rivet missing on any one joint | X | |
| | Nail place more than 1 inch from specified location | | X |
| | Nail head not flush with surface or improperly driven | | X |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Construction and workmanship (cont'd) | "T" nail or oval head machine rivet not drawn tight | | X |
| | Rivet not peened, star, or roll clinched | | X |
| | Any rivet head reversed or incorrectly set | | X |
| Marking | Missing, illegible, incorrect type or size, or wrong location | | X |

1/ A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur.

2/ Raw edge not securely caught in stitching shall be classified as an open seam.

3/ Thread breaks or two or more consecutively skipped or runoff stitches not overstitched shall be classified as open seams.

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on applicable drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of sign making kits. The sample unit shall be one sign making kit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.5 End item testing. The end items shall be tested as specified in 4.5.1 and 4.5.2. Any nonconformance with 3.4.2.4 and 3.4.2.5 shall constitute a defect. The lot size shall be expressed in units of sign making kits. The sample unit for each test shall be one sign making kit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper location, sequence, or method of application. |
| Materials | Any component missing, damaged, or not as specified. |
| Workmanship | Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container. |
| Content | Number per container is more or less than required. |

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement. |
| Palletization | Pallet pattern not as specified.<br>Interlocking of loads not as specified.<br>Load not bonded with required straps as specified. |
| Weight | Exceeds maximum load limits. |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application. |

4.5 Methods of inspection.

4.5.1 Paint sticking test. A closed sign making kit shall be allowed to stand a minimum of 8 hours in an area with the temperature at 70° to 50°F. Any nonconformance to the requirements of 3.4.2.4 shall constitute failure of this test.

4.5.2 Case opening test. Sign making kit shall rest on a solid surface on its bottom panel. With hook and loop fasteners released, the cover shall be opened until it is aligned with the back panel. The cover shall then be placed in a closed position, resting on the edges of the case. The open and closing procedure shall be repeated 10 times consecutively. Any nonconformance with the drawings on 2.1.2 or the requirements of 3.4.2.5 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. The components of each sign making kit shall be preserved in the following manner. All numbers, letters, arrows, markers, reflective tape, double-sided foam tape, safety goggles, wire ties, anchor stakes, anchor tubes and sign boards shall be individually enclosed, in the quantities specified in table IV, in close-fitting clear polyethylene bags conforming to type I or II, style 1 of PPP-B-26. Flat washers, masonry nails, and roofing nails shall be individually preserved, in quantities specified in table IV, in close-fitting paperboard boxes conforming to PPP-B-566, with style, type, and class optional. The storage bag, with components (see table IV) inside, shall be placed in its compartment within the plywood case. The sign boards, arrows, letters, and instructions shall be placed in their appropriate compartments within the body of the plywood case. The double-sided foam tape, and reflective tape shall be secured to the lid of the plywood case by piercing the screw through the plastic bag and attaching the rolls of tape with the bolts and wing nuts. The numbers shall be placed in the compartment on the lid of the plywood case.

5.1.1.1 Replacement consumable components. The consumable components, in quantities specified in table IV, shall be preserved as specified in 5.1.1. All replacement supplies shall be placed in an intermediate pack conforming to style RSC, class domestic, grade 200 of PPP-B-636. Approximate inside container dimensions shall be 26 inches by 17 inches by 6-1/2 inches.

5.1.2 Commercial. Each portable sign making kit and its components in the quantities specified in table IV. shall be preserved in accordance with ASTM D 3951.

TABLE IV. Component quantities per each sign making kit

| Components | Quantity | Notes |
|---|---|---|
| Case | 1 | |
| Storage bag | 1 | |
| Twist ties | 50 | 1/ 2/ |
| Anchor stakes | 40 | 1/ 2/ |
| Anchor tubes | 40 | 1/ 2/ |
| Flat washers | 100 | 1/ 2/ |



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:47Z
Check the source to verify that this is the current version before use.

TABLE IV. Component quantities per each sign making kit (cont'd)

| Components | Quantity | Notes |
|---|---|---|
| Masonry nails | 1 pound | 1/ 2/ |
| Roofing nails | 1/2 pound | 1/ 2/ |
| Safety goggles | 1 pair | 1/ |
| Hammer | 1 pair | 1/ |
| Shears | 1 pair | 1/ |
| Letters (5 per card): | | |
| A, E, I, L, N, O, R | 4 cards each | 2/ |
| Remaining letters | 2 cards each | 2/ |
| Numbers, 0-9 | 4 cards each | 2/ |
| Arrows | 50 cards | 2/ |
| Markers: | | |
| Black | 2 | 2/ |
| Red | 1 | 2/ |
| Blue | 1 | 2/ |
| Green | 1 | 2/ |
| Sign boards | 30 | 2/ |
| Reflective tape | 1 roll | 2/ |
| Double-sided foam tape | 1 roll | 2/ |
| Instructions | 1 set | |

1/ This item shall be located in the storage bag.

2/ This item, when used up, may be restocked in the kit from separate replacement supplies (see 5.1.1.1).

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (See 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Ten portable sign making kits, preserved as specified in 5.1, shall be packed two in length, five in width, and one in depth within a snug-fitting plywood box conforming to overseas type, style A or I, grade A of PPP-B-601. Each shipping container shall be provided with skids, closed, and strapped in accordance with the appendix of PPP-B-601.

5.2.1.1 Replacement consumable components. Three intermediate packs, preserved as specified in 5.1.1.1, shall be packed flat into a plywood box conforming to overseas type, style A or I, grade A of PPP-B-601. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601.

5.2.2 Level B. Each portable sign making kit, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to type CF, variety SW, grade 275 of PPP-B-636. The shipping container shall be closed in accordance with method II and reinforced as specified in the appendix of PPP-B-636.

5.2.2.1 Replacement consumable components. Three intermediate packs, preserved as specified in 5.1.1.1, shall be packed flat into a fiberboard shipping container conforming to type CF, variety SW, grade 275 of PPP-B-636. The shipping container shall be closed in accordance with method II and reinforced as specified in the appendix of PPP-B-636.

5.2.2.2 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be grade V3c fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.3 Commercial. Each portable sign making kit preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization.

5.3.1 Kits. When specified, portable sign making kits packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 55 in accordance with the appendix of MIL-STD-147.

5.3.2 Replacement consumable components. When specified, replacement components packed as specified in 5.2.1.1 or 5.2.2.1, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 90 in accordance with the appendix of MIL-STD-147.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, interior packages, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The portable sign making kit is intended to provide a portable means of expediently fabricating temporary signs in combat, combat support, and combat services support operations.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.2).
e. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

6.6 Subject term (key word) listing.

Combat support
Temporary signs

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 9905-A297



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:47Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-S-44355(GL) | SIGN MAKING KIT, PORTABLE |

**3a. NAME OF SUBMITTING ORGANIZATION**

**b. ADDRESS** *(Street, City, State, ZIP Code)*

**4. TYPE OF ORGANIZATION** *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

**5. PROBLEM AREAS**

**a. Paragraph Number and Wording:**

**b. Recommended Wording:**

**c. Reason/Rationale for Recommendation:**

**6. REMARKS**

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

Source: https://assist.dla.mil — Downloaded: 2026-10-23T01:47Z
Check the source to verify that this is the current version before use.