INCH-POUND

MIL-T-44372
INTERIM AMENDMENT 2 (GL)
23 October 1990
SUPERSEDING
INTERIM AMENDMENT 1 (GL)
2 August 1990

MILITARY SPECIFICATION

TROUSERS, AIRCREW, CAMOUFLAGE PATTERN, COMBAT

This interim amendment is approved for use within the Department of the Army, with MIL-T-44372 dated 5 June 1989.

PAGE 1

1.1, line 1: Delete "camouflage pattern,".

* 1.2, lines 1 and 2: Delete and substitute:

"1.2 Classification. The trousers shall be in the following classes and sizes (see 6.2):

Class 1 - Woodland Camouflage
Class 2 - Tan 380"

PAGE 2

2.1.1, under "SPECIFICATIONS, FEDERAL": Delete "V-T-280" and its title.

Under "SPECIFICATIONS, FEDERAL": Add the following:

"A-A-50195 - Thread, Aramid
A-A-50198 - Thread, Gimp, Cotton, Buttonhole
A-A-50199 - Thread, Polyester Core, Cotton- or Polyester-Covered"

Under SPECIFICATIONS, MILITARY": Delete "MIL-T-43548" and "MIL-T-43636" and their titles.

* Under "STANDARDS FEDERAL": Add "FED-STD-595 - Colors Used in Government Procurement".

Under "STANDARDS MILITARY": Delete the last paragraph and substitute:

"(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

PAGE 3

* 2.2, after line 18: Add "Department of Defense Standard Shades for Buttons".

PAGE 4

* 3.3.1, line 1, after "material": Add "for the class 1 trousers".

* At the end of the paragraph: Add "The basic material for the class 2 trousers shall be plain weave aramid conforming to type II, class 6 of MIL-C-83429. The color for class 2 shall be Tan 380."

3.3.2, paragraph identifier, line 1: Delete "facing".

Line 2: Delete "and thigh pocket facing".

Line 3: Delete "right fly facing, left fly, and thigh pocket facing" and substitute "right fly and left fly".

* Line 4: Delete "camouflage pattern".

* Delete the second sentence and substitute "The cloth shall be colored to a ground shade conforming to class 5 of MIL-C-83429 prior to overprinting of the camouflage pattern.".

* Line 10, after "MIL-C-83429.": Delete the period and add "for class 1 trousers.".

* 3.3.3: Delete the second sentence and substitute "The color for class 1 shall be Olive Drab 106 and for class 2 shall be Tan 380."

* Add the following new paragraph:

"3.3.3.1 Tape, textile, aramid. The tape for the leg drawcords shall be 1/4 inch wide and shall conform to MIL-T-43709. The color for class 1 shall be Olive Green 106 and for class 2 shall be Tan 380. Ends of the drawcords shall be seared or dipped in a colorless, non-combustible resin (see 6.6)."

* 3.3.5, line 2, after "class 1": Delete remainder of sentence and substitute "of MIL-F-21840. The color for class 1 shall be Green 3421 and for class 2 shall be Khaki 384.".

PAGE 5

* 3.3.6.1, line 2, after "wide": Delete ", Olive Green 106 in color and the tape shall" and substitute "and".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

* Line 3, after "operation.": Add "The color for class 1 shall be Olive Green 106 and for class 2 shall be Tan 380.".

Line 6: Delete "20" and substitute "6".

* 3.3.6.2, line 3, after "wide": Delete ", color Olive Green 106".

* Line 4, after "MIL-T-43709.": Add "The color for class 1 shall be Olive Green 106 and for class 2 shall be Tan 380.".

* 3.3.7: Delete and substitute:

"3.3.7 Button. The button for the waist closure shall conform to type II, class D, style 26, 30-line of V-B-871. The button shall have a dull finish. The color for class 1 shall be Olive Green BP, Cable No. 62016 and for class 2 shall be Tan AJ, Cable No. 62028."

3.3.8, line 2: Delete "V-T-280" and substitute "A-A-50198".

* Delete the last sentence and substitute "The color for class 1 shall be Camouflage Green 483 matching color chip 34094 of FED-STD-595 and for class 2 shall be Tan 380."

* 3.3.9.1: Delete and substitute:

"3.3.9.1 Aramid and para-aramid. The thread shall be aramid, 40 and 60 tex conforming to A-A-50195. Para-aramid spun staple thread, size T-35 conforming to MIL-T-44100 may be used as an alternate to aramid sizes B and E. The color of the thread for class 1 shall be Camouflage Green 483 matching color chip 34094 of FED-STD-595 and for class 2 shall be Tan 380. The thread shall show fastness to laundering equal to or better than the standard sample. When no standard sample is available, the thread shall show "good" fastness to laundering."

3.3.9.2, line 2: Delete "MIL-T-43548" and substitute "A-A-50199".

* Delete the second sentence and substitute "The color of the thread for class 1 shall be Camouflage Green 483 matching color chip 34094 of FED-STD-595 and for class 2 shall be Tan 380 and shall show fastness to laundering equal to or better than the standard sample."

* 3.3.10: Add the following to the end of the paragraph: "The color of the label for class 1 shall be Medium Green, Cable No. 70034, 70130 or 70131 and for class 2 shall be Khaki, Cable No. 70188. The fastness to laundering requirements of DDD-L-20 shall apply."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

* 3.3.10.1, line 2, after "DDD-L-20.": Delete the remainder of paragraph.

* 3.3.10.2: Delete the second and third sentences.

PAGE 7

* 3.3.10.3, line 2, after "DDD-L-20.": Delete the remainder of paragraph.

* 3.3.10.4: Delete the second and third sentences.

PAGE 8

3.4, line 2: Delete "thigh patch pockets" and substitute "cargo pockets".

3.6.1, under "Nomenclature" and "Cut parts", lines 1 through 3: Delete and substitute:

"Cargo pocket	2
Cargo pocket flap	2"

Under "Nomenclature" and "Cut parts", lines 9 and 10: Delete and substitute:

"Left fly	1
Right fly	2"

Under "Nomenclature", line 12, after "Hip pocket facing": Add "4/".

Line 13, after "Hip pocket bearer": Add "4/".

PAGE 9

3.6.1, under "Nomenclature", line 8: Delete "Right fly lining" and substitute "Right fly".

After the table: Add the following new footnote:

"4/ Hip pocket facing and bearer are cut from the same pattern part."

PAGE 12

Table I, operation 1.b, line 4: Delete "thigh pocket facing,".

Operation 1.d(1), line 1: Delete "Thigh" and substitute "Cargo".

Operation 1.d(1), line 2: Delete "9-3/8 ± 1/8" and substitute "7 ± 1/8".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

Operation 1.d(3), line 2: Delete "7-5/8 ± 1/8" and substitute "8-1/4 ± 1/8".

PAGE 13

Table I, operation 1.d, line 1: Delete "facing" and substitute "lining".

Line 3: Delete "facing" and substitute "lining".

Line 7: Delete "facing" and substitute "lining".

Table I, after operation 1.h: Add the following new subparagraph:

"i. Cut the tape for the leg drawcords (cut two) 32 ± 1 inches long for all sizes."

PAGE 17

Table I, operation 9, paragraph identifier: Delete ", thigh, and calf".

PAGES 18 and 19

Table I, operation 9, paragraph identifier: Delete ", thigh, and calf".

Operations 10 and 11: Delete and substitute:

"10. Make cargo pockets and flaps.					
a. Fold cargo pocket flap in half, with fabric face to face, and raw edges even and stitch sides leaving the top raw edges open. Turn flap, work out edges and corners.	301	SSa-1	10-14	E	E
b. Fold the cargo pocket pleats at marks indicated on pattern. Stitch along the two folds 1/8 ± 1/16 inch from the edge. The pleats shall finish facing the back of the trousers.	301	OSf	10-14	E	E
c. Hem front edge of pocket as indicated on pattern. Stitch 1/16 to 1/8 inch from folded edge. The hem shall finish 1-5/8 ± 1/8 inches wide.	301	EFb-1	10-14	E	E

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

d. Position hook portion of fastener tape on pocket as indicated by marks on pattern. Stitch on all four sides 1/16 to 3/32 inch from edge of tape.	301	LSbj-1	10-14	E	E
e. Position face of cargo pocket flap on back of cargo pocket and with top raw edges even, overedge stitch the pocket and pocket flap together.	503 or 504	EFd-1	6-10	E	E
f. Turn flap over pocket and stitch flap to pocket 1/4 ± 1/16 inch from the side and bottom edges.	301	LSd-1	10-14	E	E
11. Make calf pockets and flaps.					
a. Fold calf pocket flap in half, with fabric face to face, and raw edges even and stitch sides leaving the top raw edges open. Turn flap, work out edges and corners.	301	SSa-1	10-14	E	E
b. Position face of calf pocket flap on back of calf pocket, with top raw edges even and side edges of pocket turned in, overedge stitch the pocket and pocket flap together.	503 or 504	EFd-1	6-10	E	E
c. Position hook portion of fastener tape to back of pocket as indicated by marks on pattern. Stitch on all four sides 1/16 to 3/32 inch from edge of tape through pocket only.	301	LSbj-1	10-14	E	E
d. Turn flap over pocket and stitch flap to pocket 1/4 ± 1/16 inch from the side and bottom edges."	301	LSd-1	10-14	E	E

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

Table I, operations 18 and 19: Delete and substitute:

"18.	Attach cargo pockets and flaps.					
	Finished appearance. The pleats of the cargo pocket shall finish toward the back of the trousers. Pockets shall be uniformly stitched and properly positioned.					
	a. Mark the position of the cargo pockets as indicated on pattern. Position loop portion of the fastener tape to the trouser front as indicated by marks on pattern. Stitch on all four sides 1/16 to 3/32 inch from edge of tape.	301	LSbj-1	10-14	E	E
	b. Turn in seam allowance of the pocket. Position pocket as marked and with fastener tapes aligned, stitch to trousers with one row of stitching 3/16 to 1/4 inch from edge.	301	LSd-1	10-14	E	E
	c. Bartack top and bottom of pocket opening with horizontal bartacks in line with ends of fastener tape through pocket and trousers.	Bartack		28 per bartack	E	E
19.	Attach calf pockets and flaps.					
	Finished appearance. The pockets shall be uniformly stitched and properly positioned with the top edge of the pocket covering the fastener tape.					
	a. Mark the position of the calf pockets as indicated on pattern. Position loop portion of the fastener tape to the trouser leg as indicated by marks on pattern. Stitch on all four sides 1/16 to 3/32 inch from edge of tape.	301	LSbj-1	10-14	E	E

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

PAGES 18 and 19 (cont'd)

b. Turn in raw edges of pockets 3/8 inch, if not prehemmed. Stitch pocket to trousers, positioned as marked and fastener tapes aligned, with one row of stitching 3/16 to 1/4 inch from edge. Stitching shall superimpose prehemming stitching when this option is selected."	301	LSd-1	10-14	E	E

PAGE 36

Table I, operation 26, paragraph identifier: Delete "hem drawtapes." and substitute "hem drawcords.".

Operation 26.a, line 7: Delete "drawtape" and substitute "drawcord".

Line 9: Delete "drawtape" and substitute "drawcord".

Operation 26.d, line 1: Delete "tape" and substitute "leg drawcord".

Operation 26.e, line 1: Delete "leg hem tape" and substitute "leg drawcord".

PAGE 37

* Table I, operation 28, under "Seam and stitching type": Delete "52-56".

* Under "Stitches per inch": Delete "E" and substitute "52-56".

* Under "Thread, Needle": Delete "B" and substitute "E".

* Under "Thread, Bobbin/Looper": Add "B".

PAGE 40

4.4.3, under "Defect", line 4: Delete "Interlocking of loads not as specified."

Line 5: Delete "with required straps".

PAGE 41

* 5.2.1, line 1, after "one": Add "class and".

* 5.2.2, line 1, after "one": Add "class and".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.

PAGE 42

5.3, lines 6 and 7: Delete "K and L or film bonding means O or P." and substitute "C and D or film bonding means F or G.".

* 6.2.b: Delete and substitute:

"b. Class and size required (see 1.2)."

PAGE 43

* 6.6: Delete and substitute:

"6.6 Suggested resin. A suggested resin for dipping ends of drawcords (see 3.3.3.1) and slide fastener thongs (see 3.3.6.2) is "No Fray No. 64", Champion Packaged Products, Inc., 4939 South Austin Avenue, Chicago, IL 60638."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:

Army - GL

(Project 8415-A803)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:50Z
Check the source to verify that this is the current version before use.