INCH-POUND

MIL-V-44362(GL)
9 March 1989

MILITARY SPECIFICATION

VEST, GRENADE, CARRIER (FOR 40-mm GRENADES)

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of nylon duck vest intended for carrying 40-mm grenades.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-50083	-	Bag, Plastic, Folded Garment
DDD-L-20	-	Label: for Clothing, Equipage and Tentage, (General Use)
PPP-B-26	-	Bag, Plastic (General Purpose)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U. S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for
MIL-B-43826 - Belt, Individual Equipment

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-1-2143 - Vest, Grenade, Assembly, 40-mm
2-1-2170 - Vest, Back, Pattern
2-6-103 - Cord Lock, Double Cord
5-10-47 - Fastener, 1-Inch

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (6.3) in accordance with 4.3.

3.2 Guide samples. Guide samples, when furnished, are solely for guidance and information (see 6.4). Variations from the document may appear in the sample, in which case the document shall govern.

3.3 Materials. The materials shall be as specified on Drawing 2-1-2143 and all subsidiary drawings and parts lists pertaining thereto. It is encouraged that recycled material be used when practical and as long it meets the requirements of this specification.

3.4 Design and construction. The design and construction of the vest shall be as specified herein and as shown on Drawing 2-1-2143 and all subsidiary drawings and parts lists (PLS) pertaining thereto.

3.4.1 Stitches, seams and stitches. All seams and stitchings shall be as specified on Drawing 2-1-2143 and subsidiary drawings pertaining thereto.

3.4.1 Automatic stitching. Automatic machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying, overlapping, or backstitches are used to secure the ends of the stitching.

3.4.1.2 Lubrication of thread. Thread lubrication is permitted providing it does not stain the materials used to fabricate the vest. Only nonwicking lubricants shall be used (see 4.4.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

3.4.1.3 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched as specified on the drawings except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.4.1.3.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (3/8 inch for box and box-x stitching) back of the end of the stitching.

b. Thread breaks, or two or more consecutive skipped or runoff stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (3/8 inch on box and box-x stitching), continue over the defective area, and continue a minimum of 1 inch (3/8 inch on box and box-x stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner.

(When making the above repairs in a. and b. above, the ends of the stitching are not required to be backstitched.)

3.4.1.4 Bartacking. Bartacking shall be 3/4 ± 1/16 inch in length and 1/8 ± 1/32 inch in width and shall contain 42 stitches. Bartacking shall be free from thread breaks and loose or tight stitching.

3.4.1.5 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.2 Fusing of ends of nylon webbing, cord, and material. Ends of webbing, including bias cuts, cord and raw edges of nylon material shall be fused smooth. Fusing of the webbing ends and nylon material shall be accomplished prior to assembling for stitching. The apparatus used to fuse the webbing and cord ends, and material shall be capable of providing sufficient heat to provide a smooth edge with the cut ends of the yarns fused together to prevent separation.

3.4.3 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32-inch in width.

3.4.4 Repairs. Repairs such as mends, darns, patches,or splices are not permitted on the vests.

3.4.5 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3, shall be removed from production and replaced with non-defective and properly matched components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

3.4.6 Setting of eyelets. Holes shall be prepunched or drilled to receive the eyelets. Holes prepunched to receive the eyelets shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole.

3.4.6.1 Eyelets, with washer, brass. The brass eyelets with washer shall be securely clinched in a manner that will prevent detachment from or cutting of the surrounding material. The eyelets shall be clinched without splitting.

3.4.7 Setting of grommets. Holes shall be prepunched or drilled to receive the grommets. Holes prepunched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommet shall be securely clinched without cutting the adjacent material.

3.4.8 Setting of snap fasteners. A hole shall be prepunched or drilled to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

3.5 Marking. The letters "US" shall be applied in the size characters and in the location indicated on Drawing 2-1-2143 and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.6 Combination identification and instruction label. A combination identification and instruction label shall be applied on the inside of the back part as indicated on Drawing 2-1-2170. The label shall conform to type VI, class 15 of DDD-L-20. The label color shall be medium green, cable number 70034, 70130 or 70131. The legend shall be located on the label so that no part of the legend will be obscured by stitching or binding when sewn on the vest back part. The instructions shall be as follows:

HAND WASHING

Scrape dirt/dust from the vest using a brush or flat stick which will not cut fabric/webbing.
Wash vest in a pail of warm water using mild detergent or soap.
Rinse thoroughly in clean water.
Do not use Chlorine Bleach, Yellow Soap, Cleaning Fluids or Solvents as these will discolor/deteriorate the item.
Dry item in shade or indoors.
Do not launder or dry item in Fixed/Commercial/Home Type Laundry Equipment.
Do not attempt to dye item or repair it. Turn in for repair/replacement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

Use considerations:

1. During high combat stress situations, the easiest to reach rounds are to be extracted first.
2. During low combat stress situations, the rear most rounds are to be extracted first.
3. The vest should be worn with the chest straps and equipment belt unfastened during water borne or water crossing operations.

3.6.1 Component cutting and marking. Cut all parts of the vest out of one piece of material except for pocket reinforcement material which may be cut from ends or printed seconds. Printed seconds shall be cloth which has been rejected only for defects pertaining to color, infrared reflectance, or camouflage printed pattern as specified in MIL-C-43734. In addition, the cloth for pocket reinforcing material may be dyed Olive Green 106, water repellent treated, conforming to all other requirements of MIL-C-43734. The component parts of the vest shall be cut, marked and bundled to insure uniform size and shade throughout the vest. The following marking methods shall not be used:

a. Corrosive metal fastening device
b. Sew-on type ticket
c. Adhesive type ticket which leave an impression or traces of paper or adhesive on the material upon removal of the ticket.

3.7 Patterns. Standard pattern drawings for textile components other than tape or webbing are shown full scale on drawings and provide allowances for all seams and shall be used for making working patterns. The standard pattern shall not be altered in any way.

3.8 Workmanship. The vest shall conform to the quality of product established by this specification and occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.2 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3, 4.4.4 and 4.4.5. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the thread lubrication conforms to the requirements specified in 3.4.1.2, and also for the fastener requirement on Drawing 5-10-47 and for the cord lock on Drawing 2-6-103.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, fabricated parts before assembly, and marking for location of components, are in accordance with specified requirements for dimensions and that operations and assemblies are accomplished as specified. In addition, inspection shall be made during the manufacturing process to ensure that holes for receiving hardware are prepunched smaller than the outside diameter of the tube. Whenever nonconformance is noted, corrections shall be made to the items and lot in-process. Items which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of vests. The sample unit shall be one completely fabricated vest. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Nylon duck cloth	Any hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet).	101	
	Shade bar or abrasion mark.		201
Webbing or tape, nylon	Any hole, cut, tear, or smash.	102	
	Not firmly and tightly woven, edges frayed or scalloped.	103	
	Multiple floats.		202
	Abrasion mark, slub, broken end or pick.	104	
	Cut ends of webbing not fused as specified.	105	
Side drawstrings	Cut, chafed, or abraded.	106	
	Ends not fused.		203
	Not threaded through eyelets or knotted as specified.		204
	Omitted.	107	
Fastener tape	Any hole, cut, or tear.	108	
	Hooks flattened, broken, or missing, impairing function.	109	
Hardware	Broken or malformed, failing to serve intended purpose, corroded area, burr, or sharp edge.	110	
	Finish omitted or not as specified: - on brass components		205
	Area of partial or no finish.		206
	Any required component improperly installed causing failure to serve intended purpose.	111	
	Not assembled as specified.	112	
	Size or type not as specified.	113	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Snap fasteners	Any fastener not functioning properly i.e., fails to snap closed, to provide a secure closure, or to open freely.	114	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material.	115	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use.		207
	Clinched loosely to the degree that components can be expected to become detached during use.	116	
	NOTE: Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
	Incorrect style.	117	
	More than three splits in eyelet or button barrels.		208
Brass grommets and eyelets	Clinched excessively tight, cutting adjacent material.	118	
	Insecurely clinched to a degree that grommet or eyelet may be detached from material.	119	
	Washer installed on incorrect side of material.		209
	Eyelet barrel split:		
	- more than two		210
	- more than four	120	
Cord lock	Reversed.		211

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Buckle, side release (plastic)	Color not as specified.		212
	Color not molded in.		213
	Broken, cracked, chipped, or malformed, failing to serve intended purpose.	121	
	Any sink mark.		214
	Any burr, sharp edge, or flash.	122	
	Gates not trimmed as specified.		215
	Surface not smooth.		216
	Not functioning properly, failing to effect a secure closure or to open freely.	123	
Seams and stitching:			
Open seam	1/2 inch or less.		217
	More than 1/2 inch.	124	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching.		218
NOTE:	Raw edge not securely caught in stitching shall be classified as an open seam.		
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type.	125	
Bartacks	Any bartack omitted.	126	
	Any bartack not as specified or not in specified location.	127	
	Loose, incomplete, or broken stitches.	128	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Seams and stitching: (cont'd)			
Stitch tension	Loose, resulting in loose bobbin or top thread.		219
	Excessively tight, resulting in puckering of material.		220
Stitches per inch	Up to two stitches less than minimum specified.		221
	Three or more stitches less than minimum specified.	129	
	One or more stitches in excess of maximum specified.		222
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corners shall be classified as follows: (a) Within the minor defect classification - no defect (b) Within the major defect classification - minor defect.		
Stitching ends	Not secured as specified.		223
Thread breaks, skipped stitches, or runoffs	Not overstitched as specified.		224
	NOTE: Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as an open seam.		
Rows of stitching	Any row missing except on box and box-x stitching.	130	
	On box and box-x stitching: - one row of stitching omitted		225
	- two or more rows of stitching omitted.	131	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Components and assembly	Any component part omitted or not as specified or any operation omitted or not as specified (unless otherwise classified herein).	132	
	Any needle chew: - up to 1/8 inch in length		226
	- over 1/8 inch in length.	133	
	Any mend, darn, patch, splice, or other unauthorized repair.	134	
	Any material pleated or caught in stitching where not specified.		227
Binding	Loosely applied but not exposing raw edge of material.		228
	Loosely applied exposing raw edge of material.	135	
	Ends of binding on pocket flap and on grenade pockets not caught in seams.		229
Grenade pocket and tabs	Pocket or tab not formed as specified.		230
	Tabs improperly set or distorted failing to effect a full and smooth closure.	136	
	Binding tape not securely attached.		231
Cleanness	Grease, oil, dirt or ink stains clearly noticeable.		232
	Thread ends not trimmed as specified.		233
Location markings	Drilled.	137	
	Printed marking more than 1/32 inch in width and not covered by component part.		234
Markings: US, identification and instructions	Omitted, incorrect, illegible, misplaced, or size of characters not as specified.		235
Label	Omitted, or not as specified	138	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of vests. The sample unit shall be one vest. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5 for major defects and 15 for total (major and minor combined) defects.

TABLE II. End item dimensional defects 1/

Examine	Defect	Classification Major	Classification Minor
Dimensions (overall)	Smaller than nominal dimensions less applicable minus tolerance indicated on drawings, but not smaller than nominal dimensions less twice the applicable minus tolerance.		201
	Smaller than nominal dimensions less twice the applicable minus tolerance.	101	
	Larger than nominal dimensions and applicable plus tolerance.		202
Component and location dimensions	Not within specified tolerance.		203
Stitch margin or gage	Not within specified tolerance.		204
Box and box-x stitching	Dimensions not as specified.		205
Brass eyelets	Not spaced on vest panels and vest back within specified dimensions.		206
Pocket and tabs	Not parallel (vertically) to each other by more than 1/4 inch.		207

1/ Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined.

4.4.5 End item fit examination. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in units of vests. The sample unit shall be one vest. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

TABLE III. End item fit defects

Examine	Defect
Fit of grenade into pockets and closure of tab	Pocket(s) too small, i.e., grenades fail to fit properly within the pocket. Pocket(s) too large, i.e., grenades slide through pocket opening, extending out of the pocket bottom by more than 1/2 inch.
NOTE:	The 40-mm grenade fit examination shall be performed with the grenades (or grenade fit gauges) to be furnished by the contracting activity (see 6.4). (The grenades shall be inserted into each pocket.) The flat ends of the grenades shall face toward the tab of the pockets. A defect shall be scored if any grenade must be forced into the pocket(s), or if it extends outward beyond the bottom of the pocket by more than 1/2 inch.
Securing of grenade retainer tab	Grenade retaining tab too short, causing inability to secure snap fastener without applying excessive force.
NOTE:	With the grenade in the pocket(s) it shall be possible to secure the grenade retaining webbing tab without having to put excessive force on the webbing to the degree that the webbing is under tension after being secured.
Fit of equipment belt into belt loops	Belt does not fit into belt loops as specified.
NOTE:	The belt used in the belt loop fit test shall conform to MIL-B-43826, and is to be furnished by the contracting activity (see 6.4). With the vest placed flat on a table, camouflage side up, place the equipment belt between the two portions of the ten belt loops. First, fold each upper portion under the belt to secure the hook and pile fasteners. Next, fold each lower loop up to join the snap fasteners. The hook and pile and snap fasteners shall meet and allow the belt to fit into the loops with enough ease to allow freedom of movement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and unit pack)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than specified.

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each vest shall be folded to the approximate dimensions of 16 inches in length, 8 inches in width, and 3-1/2 inches in depth. The vest shall then be placed in a clear polyethylene bag conforming to type I or II, style 1 or 2 of PPP-B-26, or a plastic bag conforming to A-A-50083. Style 1 bags shall have a 1/4 inch hole located near a bottom corner to allow air to escape.

5.1.2 Commercial. Each vest shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Twelve vests preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of the shipping container shall be approximately 17 inches in length, 16 inches in width, and 20 inches in depth. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twelve vests preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, style CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Inside dimensions of the shipping container shall be approximately 17 inches in length, 16 inches in width, and 20 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.3 Commercial packing. Vests, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), vests, packed as specified in 5.2.2 and 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV , or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 95 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The vest is intended for use by Military personnel as an outer garment for the purpose of carrying eighteen 40-mm grenades. The vest is also compatible with the standard equipment belt, and the large field pack with frame and combat "patrol Pack".

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article sample is required (see 3.2, 4.3, and 6.3).
d. Levels of preservation, and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples. For access to samples of the vest and 40-mm grenades or fit test items or gages required for the fit examination in 4.4.5, address the contracting activity issuing the invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Ammunition carrier
Combat

Custodian:
Army - GL

Review activities:
Army - MD
DLA - CT

Preparing activity:
Army - GL

(Project 8415-A693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-V-44362(GL)	Vest, Grenade, Carrier (For 40-mm Grenades)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 #2 MAR — PREVIOUS EDITION IS OBSOLETE. NATIONAL F-H-PC

Source: https://assist.dla.mil - Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:48Z
Check the source to verify that this is the current version before use.