NOT MEASUREMENT SENSITIVE

MIL-T-45305C(AT)
25 April 1991
SUPERSEDING
MIL-T-45305B(AT)
9 May 1980

MILITARY SPECIFICATION

* TRUCK, BOOKMOBILE: DIESEL OR GASOLINE ENGINE DRIVEN, 16,000 POUNDS GVW, 4x2, MODIFIED COMMERCIAL

This specification is approved for use by the US Army Tank Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a bookmobile mounted on a forward control chassis. The vehicle is a four wheel, two-wheel-drive truck having a gross vehicle weight (GVW) of not less than 16,000 pounds. Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS
FEDERAL

* A-A-393 - Extinguisher, Fire, Dry Chemical (Portable).
W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.

STANDARDS
FEDERAL
FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either form the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DOT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)
NFPA-70 - National Electrical Code.

(Application for copies of NFPA publications should be addressed to the National Fire Protection Association, Batterymarch, Park, Quincy, MA 02269.)

STATE OF CALIFORNIA
Vehicle Code of California

(Application for copies of State of California publications should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, California 95809.)

SOCIETY AUTOMOTIVE ENGINEERS, INC. (SAE)
SAE Standards and Recommended Practices

J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation From Vehicles and Devices (30-1000 MHz).
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J688	- Truck Ability Prediction Procedure (DoD adopted).
* J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

* (Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.8, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. Except as specified in 3.1.1 through 3.1.1.8, no removal, substitution or alteration of the chassis manufactuer's standard or optional chassis model components shall be made. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate military service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Markings and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

* 3.1.1.4 Drain plugs. Drain plugs installed in the rear axle shall be of the permanent magnet type.

* 3.1.1.5 Wood treatment. As specified herein (see 3.5.9), wood shall be treated in accordance with MIL-STD-1223.

* 3.1.1.6 Towing devices. Towing devices consisting of two hooks, loops, eyes or pins or the chassis manufacturer's standard single center mounted eye or pin shall be mounted on the front of the vehicle. All towing devices shall be frame rail mounted or reinforced back to each frame rail.

* 3.1.1.7 Splash and stone throw protection. Rear wheel splash and stone throw protection in accordance with SAE J682 shall be furnished. Rubber mud flaps or fenders shall be provided to the rear of the front wheels and shall extend down to at least the centerline of the front axle. A metal strip not less than 0.125 inch thick and not less than 1 inch wide, extending the entire width of the mudflap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. As an alternate method of attaching the mud flaps, tabs or clips with minimum surface contact dimensions of 1 inch high by 1.250 inch wide by 0.094 inch thick shall be furnished at each bolt.

* 3.1.1.8 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher or the two systems shall be independent of each other. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. Vehicles shall comply with Environmental Protection Agency Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 3.2.3 Sound level. The interior sound level shall not exceed 84 db(A). The vehicle exterior sound level shall conform to the Environmental Protection Agency Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis, with all attachments, accessories, and equipment; body; full complement of fuel, lubricants and coolant.

3.2.5 Gross vehicle weight. The gross vehicle weight (GVW) shall consist of the curb weight, operator weight (computed at 175 pounds) and a payload to provide not less than the specified GVW.

3.2.6 Weight distribution. The distribution of gross vehicle weight shall be determined with the payload uniformly distributed over the load area.

3.2.7 Wheelbase. The wheelbase shall be not less than 150 inches.

* 3.2.8 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. Minimum GVW rating shall be not less than 16,000 pounds.

* 3.2.9 Overall width. The overall width of the vehicle, exclusive of tires and safety related items such as mirrors, lights, and reflectors, shall be not more than 96 inches. The width over the tires shall be not more than 100 inches.

* 3.2.10 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.11 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with vehicle loaded to specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend a 2.0 percent continuous grade at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive, and when multispeed axle is furnished, with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

3.3.1.2 Low speed. Low speed for vehicles with a manual transmission shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide not more than 4.5 miles per hour.

* 3.3.1.3 Maximum geared speed. Maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction X tire factor (see 6.3).}}$$

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

* 3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke, or four-stroke cycle diesel engine, with not less than four cylinders. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. Unless otherwise required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil filter. A full flow or combination full flow and bypass oil filter with replacement element shall be furnished.

* 3.4.1.4 Cooling system. The cooling system shall maintain the engine coolant at a temperature below the boiling point with the vehicle loaded to specified GVW and operated at an altitude of 10,000 feet above sea level or

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

in an ambient air temperature of not less than 125 degrees Fahrenheit (°F). The coolant system shall include a surge tank or a coolant recovery reservoir of not less than two-quart capacity.

* 3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include complete thermostatic control of all coolant flow through the radiator.

* 3.4.1.6 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

* 3.4.1.7 Silicone rubber hoses. When specified (see 6.2), silicone rubber radiator and heater hoses shall be furnished.

* 3.4.1.8 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Heaters shall operate on 110 volt alternating current (ac), and shall be wired through a junction block, including a fuse or circuit breaker, to a single three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). The electrical insulation of the connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1,000-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed.

* (b) An oil pan heater of the permanent external surface mount, permanent in-pan mount, or immersion type that meets the following requirements, shall be installed:
  (1) Not less than 22 watts per quart heating capacity
  (2) Not more than 18 watts per square inch heating capacity
  (3) Thermal balance design or thermostat control providing for uninterrupted operation
  (4) Provision for mounting below minimum service oil level.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

(c) A fuel warmer or pre-heater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a fuel flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

* 3.4.1.9 Fuel fired engine preheater. When specified (see 6.2), for diesel engine driven vehicles, a diesel fuel fired engine water heater shall be furnished to preheat the engine. The heater shall include a timer, a thermostat and a circulating pump and shall be connected to the engine coolant system. The heater shall be capable of starting and operating at minus 60°F and shall heat the engine to plus 40°F from minus 60°F in not more than 1 hour. The system shall be equipped with a light, visible to the driver, to indicate that the preheater is operating.

3.4.2 Electrical systems. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system, with a 12-volt dc lighting system shall be furnished. Engine starting equipment shall include an ether starting system, glow plug or electric grid heater. If an ether system is furnished in lieu of a glow plug or grid heater, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

* 3.4.2.2 Ignition system. For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished.

* 3.4.2.3 Alternator. Unless otherwise specified (see 6.2) on diesel engine driven vehicles, a minimum 65-ampere alternator shall be furnished. The alternator output with the engine at engine idle speed shall be not less than 45 amperes. Unless otherwise specified (see 6.2) on gasoline engines driven vehicles, an alternator of not less than 85 amperes rated capacity, and which provides not less than 45 amperes dc output at normal engine idle speed, shall be furnished.

* 3.4.2.4 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.13, 393.19, 393.20 and 393.22 through 393.26(d).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

Positioning and guarding shall permit normal replacement of the bulbs and lenses. Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers. When right hand drive is specified by acquisition documents, left-dip headlights shall be provided. Left-dip headlights may be provided as a replacement set, stowed in the cab for shipment.

* 3.4.2.5 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Turn signal units shall be installed in accordance with SAE J588. Turn signal operating units shall be self-cancelling type with a visible and audible type flash indicator.

* 3.4.2.6 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity rating and the total cold cranking rating at °F, both measured in accordance with SAE J537, shall be not less than as specified in table I. Batteries shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

TABLE I. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Gasoline	100	450
Diesel	230	1,100

* 3.4.2.7 Radio interference suppression. The vehicle shall be suppressed for radio interference in accordance with SAE J551. Any body equipment emitting radio interference shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

* 3.4.3.1 Air cleaner. An air cleaner shall be furnished.

* 3.4.3.2 Fuel tank. The fuel tank shall be the manufacturer's standard for the vehicle furnished with a capacity of not less than 30 gallons. When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve, connecting either tank to the engine fuel intake, shall be provided and means shall be provided to monitor the fuel level of either tank from a single fuel gage; or an equalizing pump shall be used to maintain the same fuel level in both tanks.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. The exhaust system shall discharge at the rear of the vehicle or to the side behind the rear wheels.

* 3.4.5 Automatic transmission. An automatic transmission shall be furnished. The transmission shall include a hydraulic torque convertor and not less than three forward gear ratios. Normal driving range selector position shall provide not less than three gear ratios without movement of the selector. The driving range selector shall provide a normal drive position and a second, low speed, high power position. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.6 Driveline components. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be manufacturer's standard for the vehicle furnished.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW. When the suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW.

* 3.4.10 Wheels, rims, tires, and tubes. The vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished. Tire load ratings shall be in accordance with Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.10.1 Tires. Tires shall be tubeless type with highway tread. Tires shall be of the steel belted radial ply type. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW. Tires and tire size designation systems shall conform to Tire and Rim Association or to The European Tyre and Rim Technical Organisation recommendations.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

3.4.10.2 Inner tubes. When tube type tires are specified in procurement documents, inner tubes shall be of heavy duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.4.10.3 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier design shall enable removal or mounting of a spare wheel assembly using only the tools specified in 3.4.15. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished.

* 3.4.10.5 Spare tire assembly. When specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the front axle of the vehicle.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.51.

* 3.4.11.1 Power-hydraulic type. The vehicle shall be equipped with power assisted, hydraulic actuated, four-wheel, service brakes.

3.4.12 Steering. Power steering shall be provided.

3.4.13 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by either air, vacuum with booster, or electric motor(s).

3.4.14 Bumpers. A standard front bumper shall be provided. A rear bumper shall be provided and shall conform to Federal Motor Carrier Safety Regulation 393.86.

3.4.15 Tools. When specified (see 6.2), the vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly (see 3.4.10.5), and shall include at least a jack, jack handle and wheel nut wrench. The jack shall be of such closed height as to permit its location under an axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

3.4.16 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.17 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.4.17.1 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

* (a) Outside rearview mirrors, mounted on each side of body; each with not less than 50 square inches of reflective area
(b) Key-operated ignition switch
(c) Ammeter, voltmeter or charging indicator
(d) Fuel gage
* (e) Oil pressure gage or red indicator warning light
* (f) Engine temperature gage or high coolant temperature or low coolant level red indicator light
* (g) High coolant temperature or low coolant level alarm buzzer
(h) Speedometer with recording odometer
(i) Ash receptacle
(j) Dual sunvisors
(k) Driver's compartment ventilator other than window.
(l) Tachometer (for diesel engine driven vehicles).

3.4.18 Horn. Manufacturer's standard electric horn shall be furnished.

* 3.5 Body. The body shall be an integral driver's compartment and enclosed body. The front section shall be the forward control type with cowl, windshield and side windows or of the walk-in multi-stop type with short hood, fenders and windshield. Manufacturer's standard fiberglass sections may be incorporated.

3.5.1 Body construction. The body shall be constructed of sheet metal having a minimum gage thickness specified for carbon steel; high tensile steel utilized may be 2 gages lighter weight in accordance with U.S. Standard gages. All exterior panels shall be removable to facilitate body repair. Aluminum or magnesium alloys of equal strength may be furnished. Both sides of the body shall be protected with an all steel rub-rail located at the lower edge of the exterior panels. The rear of the body shall be protected with a full width bumper with wrap around ends.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

3.5.2 Framing. Not less than six full-width crossmembers, including end sills, shall be furnished. Stub crossmembers, as required at the wheel housing to provide strength, shall be furnished. Body sides shall be reinforced for load support.

* 3.5.3 Service doors. The body shall incorporate a service entrance located forward on the curb side and a service exit located behind the rear wheels on the curb side. Inset step wells of safety tread steel or ribbed rubber over steel or fiberglass reinforced plastic shall be furnished at each curb side entrance and exit. Hand rails shall be provided at the curb side service entrance and exit. The service doors shall be of the single, flush type not less than 26 inches wide by 84 inches high extending to the bottom of the step wells. Both of the curb side service doors shall be hung at the front with continuous type hinges covered with neoprene guards, fitted with manufacturer's standard door opening and locking arrangement, furnished with safety glass in the upper section, provided with push rails mounted on the inside, and equipped with an automatic door closer and hold-back device. Doors shall be rubber sealed around all edges to provide a weather tight enclosure. Drip rails shall be installed above the doors.

3.5.4 Driver's door. The manufacturer's standard automotive type cab door shall be installed on the road side. The door shall be fitted with ventilating type, safety glass in the upper section and shall be fitted with standard automotive hardware. The door shall be rubber sealed around all edges to provide a weather tight enclosure. A drip rail shall be provided above the door.

* 3.5.5 Rear window. A rear window shall be provided. The rear window shall be not less than 16 inches by 30 inches overall, fitted with single pane safety glass.

3.5.6 Storage compartment. An exterior storage compartment fitted with a weather tight door, embodying manufacturer's standard locking device, shall be located in the curb side or rear skirt. The exterior compartment shall be divided to house electrical equipment, and to store tools normally supplied with the vehicle.

* 3.5.7 Roof and exterior side panels. Roof and exterior side panels shall be a minimum of 20 gage (0.0359 inch) sheet metal. All body seams and joints shall be dust and weather sealed in accordance with body building industry practice.

* 3.5.8 Skylights. Not less than two skylights shall be installed in the roof. Skylights shall be not less than 14 inches by 14 inches in size, and shall be fitted with translucent white butyrate domes. Skylights, consisting of a raised roof and transom type side windows in the raised portion, may be furnished. Provisions for opening the skylights for ventilation shall be included.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 3.5.9 Composite floor construction. The floor shall be multiple wood and metal construction to provide space for inserting insulating material. An all sheet metal under floor pan shall be an integral part of the flooring. The pan shall be secured to the bottom side of the floor cross sills to provide an insulation retainer and additional weather sealing. Wood floor joists, reinforced with steel channels, not less than 2 inches high, or all aluminum 2 inches by 2 inches by 16 gage aluminum tubing shall be installed on approximate 16 inch centers parallel to chassis cross members. The subfloor shall be all wood construction secured to the floor joists and shall extend the full length and width of load space. The subfloor shall be not less than 0.625 inch thick planking, 0.625 inch laminated exterior grade plywood, or shiplap, and shall be covered with 0.250 inch plywood with a minimum of joints. A vapor barrier of tar paper or metallic foil shall be inserted between the subfloor and plywood. The floor shall be insulated with not less than 2 inches of fiberglass batts or styrofoam.

3.5.10 Exterior wheelhousings. The exterior wheelhousings shall be constructed of not less than 16 gage steel and shall be properly sealed to prevent dust and water seepage. The exterior wheelhousings shall be designed to provide clearance for the dual rear tires under all load conditions.

3.5.11 Interior body dimensions. Inside body dimensions shall be not less than 198 inches long from back of driver's seat to rear interior paneling; 87 inches wide inside of interior paneling exclusive of wheelhousings; and 84 inches high from floor to ceiling, at center of body.

* 3.5.12 Interior body construction. The interior body sides and rear shall be paneled with 0.250 inch finished plywood or aluminum of color and decoration to match shelving. Exposed sides shall be free from defects and sanded smooth. The ceiling shall be lined with sheet metal not less than 20 gage (0.0359 inch) thick. Body sides, rear and roof shall be insulated with not less than 2 inches of fiberglass batts or styrofoam. Inside wheelhousings shall be of square wood or curved metal construction, sealed against dust and moisture, and fully insulated.

* 3.5.13 Driver's cab interior. Cab headliner shall be sheet metal, 0.125 inch tempered masonite, 0.250 inch finished plywood with the exposed side free from defects and sanded smooth, or a one-piece fiberglass liner providing a smooth finished surface. Cab roof, floor, and cowl shall be insulated with not less than 1 inch thick fiberglass batts or styrofoam. Cab side walls shall be carpeted. The cab shall be furnished with a fully adjustable, bucket type driver's seat mounted on a swivel base. Seat shall be capable of being locked in standard driving position, or revolved 360 degrees for use at the front service and loan desk. The seat shall have combination pelvic and upper torso restraint seat belts.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 3.5.14 Floor covering and cove base. The floor shall be covered with high quality commercial grade linoleum or vinyl tile. Linoleum shall be installed over not less than 14 pound felt base. Molding shall be provided at the base of shelving, desks, lockers, wheelboxes, and other projections. Pattern and colors furnished shall be as specified by the procuring activity from selection samples furnished, after award and prior to production, to TACOM, AMSTA-UED.

3.5.15 Interior compartments. A clothes closet shall be installed on the left side of the vehicle, behind and adjacent to the front service and loan desks. Outside dimensions of the closet shall be not less than 10.500 inches deep, 24 inches wide, and 77 inches high. A locker shall be furnished with a full length door fitted with lock and slam type catch, equipped with a shelf at the top, and provided with a hanger bar. Adjoining the clothes locker, an auxiliary compartment, with space for a vacuum insulated jug of 5 gallons capacity shall be installed. The compartment shall provide for storage of drinking cups and miscellaneous items.

3.5.16 Shelving. Shelving shall be manufacturer's current standard, adjustable bookmobile type and shall be computed at the rate of 8 to 10 books per foot of shelf length. A bank of shelves shall be furnished on each, left and right side, of the vehicle; and provided on each end of reference desk at the rear of the vehicle. The banks of shelves on each side of the vehicle shall be sloped 15 degrees; and the banks of shelves at the rear of the vehicle shall be sloped 20 degrees. The shelves shall be not less than 7 inches deep and 10.500 inches clear height; shall be fitted with 90 degree backing strips to enable books to stand squarely and resist unnecessary wear; and shall be supported by a pair of surface mounted pilaster standards at each end. The shelves and standards shall be built of kiln dried 0.750 inch finished lumber; or constructed of 0.750 inch finished plywood with the exposed surfaces free of defects and sanded smooth; or fabricated of sheet metal. No rubber matting shall be applied on the shelves.

3.5.17 Magazine racks. Two magazine racks shall be furnished. One rack shall be provided on each end of the bank of bookshelves adjacent to the entrance and exit service doors.

3.5.18 Bulletin board. One bulletin board, constructed of 0.250 inch sheet cork mounted on a plywood base and framed, shall be furnished; and shall be mounted above the rear window and reference desk.

3.5.19 Desks. The vehicle shall be furnished with a loan desk located behind the driver's seat and shall be provided with a reference desk located below the rear window and between bookshelves in either corner. Both of the desks shall be constructed of sheet metal or not less than 0.750 inch finished lumber or 0.750 inch finished plywood with exposed surfaces free from defects and sanded smooth. The top of each desk shall be covered with Formica of a color and pattern to match the decor of the interior of the

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

vehicle. The top of the loan desk shall be not less than 18 inches deep by 48 inches wide and shall be approximately 35 inches above the floor. The loan desk shall be furnished with a drawer not less than 3 inches deep and shall be provided with a storage compartment for miscellaneous library supplies. The top of the reference desk shall be not less than 15 inches deep by 48 inches wide and shall be approximately 39 inches above the floor. The underneath section of the reference desk shall be a storage cabinet for records, films and other miscellaneous items. The reference desk storage cabinet shall be provided with adjustable shelves and shall be equipped with double doors fitted with locks, handles and catches.

* 3.5.20 Interior lighting and service outlets. The interior of the body shall be equipped with 2 continuous rows of 120-volt, instant starting type fluorescent fixtures, 25 watt 24 inch tubes, and plastic shades. The fluorescent fixtures shall be mounted flush against the ceiling and approximately 15 inches from each bank of side shelving. Control switches for the lights shall be mounted near the loan service desk. A duplex convenience receptacle shall be provided near the front loan service desk. A similar convenience receptacle shall be furnished above the rear reference desk.

* 3.5.21 Heating. The vehicle shall be furnished with three, manufacturer's standard commercial resistance type, 240 volt, electric heaters. Each heater shall be equipped with a circulating fan and an automatic temperature control. The rating per unit of two heaters shall be 13,660 British thermal units (Btu) per hour at 4000 watts, and the capacity of the third unit shall be 5,122 Btu per hour at 1500 watts. One 4000 watt heater shall be mounted underneath the bookshelves and adjacent to the front service entrance. The second 4000 watt heater shall be mounted underneath the bookshelves and adjacent to the rear service exit. The 1500 watt heater shall be mounted underneath the front loan service desk. At the manufacturer's option, strip heaters in the air conditioning units may be used, provided the total Btu and wattage above are met.

3.5.22 Air conditioning. The vehicle shall be provided with two, manufactuer's standard commercial type, air conditioners. The rating of each unit shall be 1 hp at 120 volts, and the capacity per unit shall be not less than 9,700 Btu per hour. One air conditioning unit shall be installed at ceiling height above and toward the front of the bank of bookshelves on the left side of the vehicle. The second unit shall be installed at ceiling height above and toward the rear of the bank of bookshelves on the left side of the vehicle. Both air conditioners shall be equipped with thermostats for automatic temperature control.

* 3.5.23 Electrical power systems. The interior of the body shall be wired in accordance with the requirements of the National Electrical Code, NFPA No. 70-1978, for mobile homes, and electrical wiring code of the state in which the vehicle is to operate. Five, 120-volt power circuits shall be

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

installed. Each row of lights shall be on a separate circuit, each air conditioner shall be on an individual circuit, and both of the receptacles shall be on the same circuit. Three 240-volt power circuits shall be installed. Each heater shall be provided with a separate circuit. Each individual circuit shall be protected with ground fault circuit interrupters of applicable rating. The breaker panel for both panel systems, 120-volt and 240-volt, shall be mounted in the cab above the driver's door. The wiring for both systems shall be installed in flexible or rigid conduit as applicable conditions may warrant. The vehicle shall be furnished with two weather proof shoreline receptacles for power. One outside entry receptacle shall be mounted on the left side of body; and the other entry receptacle shall be installed in the reel compartment. Provision shall be made to disconnect either receptacle when not in use. Not less than 100 feet of No. 8, three conductor, neoprene covered extension cable shall be furnished on a reel in the skirt compartment.

* 3.5.24 Public address system. The vehicle shall be furnished with the audio components specified in 3.5.24.1 through 3.5.24.3. All components and assemblies shall be compatible with each other and operate on 120-volt power.

* 3.5.24.1 Combination AM/FM stereo receiver and amplifier, record player, compact disc (cd) player and cassette player. The unit furnished shall have AM/FM tuning with FM muting to silence noise between stations while tuning. The audio amplifier section shall have a frequency response of not less than 40 to 20,000 Hz at plus or minus 3 decibels (dB) and not less than 30 watts audio output per channel. The compact disc player shall have provisions for auto-search and bidirectional audible search. The cassette player shall include controls for record, start stop, fast forward, fast reverse, pause and end-of-tape auto-stop to protect cassettes. The equipment shall have provisions for a microphone. All components shall be mounted in a suitable location for accessibility. Shock mounts shall be furnished to withstand road shocks and vibrations.

* 3.5.24.2 Microphone. The microphone shall be of the unidirectional (cardioid) dynamic type. A desk stand, cable, plug and on/off switch shall be furnished.

* 3.5.24.3 Speakers. Two weatherproof, outdoor type speakers shall be furnished. The speakers shall have a power rating sufficient to handle the output of the amplifier. Power rating is determined by using equipment that delivers up to the stated (RMS) continuous power per channel, driven to clipping 10% of the time, or normal source material. The frequency response shall be not less than 100 to 20,000 Hz. Speakers shall be mounted horizontally on the forward and rear sections of the bookmobile so as to project maximum sound in the forward and rear direction of the bookmobile while in motion. A suitable metallic guard shall be provided for the purpose of protecting the speakers from damage due to engagement with overhanging branches or other obstacles encountered while in travel.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 3.5.25 Clock. The vehicle shall be furnished with a battery powered, quartz type wall mounted type clock. The clock shall be located near the rear reference desk and securely fastened to the wall.

* 3.5.26 Fire extinguisher. A 10-pound dry chemical type fire extinguisher, conforming to Federal Motor Carrier Safety Regulation 393.95(a), shall be mounted convenient to the driver. The fire extinguisher shall have an Underwriter's Laboratory rating of 2A:40B:C or more, shall include a metal safety pin and wire, and shall conform to type I, class 1, size 5 of A-A-393. The fire extinguisher shall permit visual determination as to whether it is fully charged.

* 3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of engine and brake systems; filling and charging of batteries; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations is an acceptable practice to

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

ascertain conformance to requirements, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

* 4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformity with the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and the distribution of the curb weight on the front and rear axles. The total imposed loads on the front and rear axles shall be computed by the contractor and verified by the Government using the curb weight, the operator weight at 175 pounds, and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle shall be examined and road tested (without payload) by the contractor to assure that the vehicle will operate in accordance with the contract requirements.

4.3.3 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.4 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, ensure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

requirements specified herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 has been accomplished.

5. PREPARATION FOR DELIVERY

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. Bookmobiles covered by this specification are intended to provide library service to off-post sites; to be operated by a male or female librarian over improved or unimproved roads and highways, under all conditions of weather and climate encountered within the continental limits of the United States and at various altitudes and grades which may be encountered on the main roads, highways and access roads within the continental limits of the United States.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
* (b) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(c) Identification of the appropriate military service for painting (see 3.1.1.1).
* (d) Identification of the appropriate military service for marking (see 3.1.1.2).
* (e) Concealed markings, if required (see 3.1.1.2).
(f) Rustproofing, if required (see 3.1.1.3).
* (g) Tropical rustproofing, if required (see 3.1.1.3).
* (h) Gasoline engine, if required (see 3.4.1.2).
* (i) Silicone rubber hoses, if required (see 3.4.1.7).
* (j) Power plant heaters and fuel warmer, if required (see 3.4.1.8).
* (k) A fuel fired engine preheater, if required for a diesel engine driven vehicle (see 3.4.1.9).
* (l) Alternator capacity, if other than as specified, (see 3.4.2.3).
* (m) Disc type wheels, if required (see 3.4.10).
(n) Carrier for spare tire, if required (see 3.4.10.3).
(o) A spare wheel or rim, if required (see 3.4.10.4).
(p) A spare tire, if required (see 3.4.10.5).
(q) Tools, if required (see 3.4.15).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

* 6.3 Performance prediction. SAE Truck Ability Prediction Procedure computations and computation for low speed and maximum geared speed will be required by the contract. The SAE Work Sheet Item 1 should include vehicle model number, engine model number and vehicle type. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature and still, dry air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1	- Tire Factor. This factor must relate to the size of tire furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.173
Table 5	- Velocity Factor. 250.0
Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use vehicle GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

* 6.4 Subject term (key word) listing.

Library
Public address system
Service doors
Shelving
Skylight
Wheelhousing.

* 6.5 Changes from previous issue. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT

Preparing activity:
Army - AT

Project No. 2320-A457

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-45305C(AT) TRUCK: BOOKMOBILE, DIESEL OR GASOLINE ENGINE DRIVEN, 16,000 POUNDS GVW, 4x2, MODIFIED COMMERCIAL

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 78 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:40Z
Check the source to verify that this is the current version before use.