
DETAIL SPECIFICATION SHEET

FILTER ELEMENTS, FLUID PRESSURE, HYDRAULIC LINE, 14-MICRON (C) AND 6-MICRON (C), TYPE II SYSTEMS, 3,000 PSI, -65 °F TO 275°F

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32746.



DRAWING NOTES:

1. Dimensions in inches unless otherwise specified.
2. Tolerances, decimals +/- 0.010, angles +/-5°.
3. Finish all over 100% except as noted. Surface texture in accordance with ASME B46.1 (ANSI) only to machined surfaces.
4. Drawing symbols per ASME Y14.5.
5. Weight of the filter element is 2.00 lbs dry max.
6. Rated flow is 15.0 gpm.
7. O-ring (P/N M83461/1-027) to be supplied with the filter element.

FIGURE 1. Filter element dimensions

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:42Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Pressure Drop: The pre-cold start pressure drop across the element at 100°F, 15-gpm shall not be greater than 15 psid.

Degree of Filtration: Filter elements provided under this military specification sheet shall meet the following minimum performance requirements at 6-microns(c) at 150 psid terminal pressure across the test element. See paragraph 4.6.7 of the base specification:

Grand average (α 6(c)): 200
AFR (High to Low 6(c)): 150
AFR (Low to High 6(c)): 150
Retained Capacity: 33 grams
Where (c) signifies particle sizes per ISO 11171

Element Collapse: The filter element shall withstand a differential pressure of 5,250 psid in accordance with ISO 2941. See Paragraph 4.6.11, of the base specification.

Cold Start: The filter elements shall withstand 3,500 psid differential pressure across the element for the 10 flow cycles and fluid temperature as specified in the base specification. See Paragraph 4.6.6 of the base specification.

Flow Fatigue: The filter element shall withstand the following flow fatigue pressure cycles at a cycling rate of 100 cycles per minute maximum:

90,000 cycles at 20-psid pressure drop
8,000 cycles at 50-psid pressure drop
2,000 cycles at 100-psid pressure drop
500 cycles at 3,000 psid pressure drop

Part Number: The part number consists of the basic number of this specification sheet and a slash number. The format is as follows, using 4 for example: MIL-DTL-32746/4.

Intended Use: The filter element covered by this specification sheet is intended for use as specified in paragraph 6.1 of the base document and specifically for use on all Aviation Ground Power Units (AGPU) to service US Army helicopters.

Referenced Documents: In addition to MIL-DTL-32746, this specification sheet references the following documents:

ASME B46.1 ASME Y14.5 ISO 11171
ISO 2941

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:42Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – AV
Air Force – 11

Preparing Activity:
Army – AV
(Project 1650-2025-006)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:42Z
Check the source to verify that this is the current version before use.