METRIC
MIL-PRF-32731(GL)
23 August 2023

PERFORMANCE SPECIFICATION

AUTHORIZED STOCKAGE LIST MOBILITY SYSTEM VERSION 3 (ASLMS V3)

Comments, suggestions, or questions on this document should be addressed to: Product Manager Force Sustainment Systems, U.S. Army Natick Soldier Systems Center, General Greene Avenue, Natick, MA 01760 or emailed to usarmy.natick.devcom-sc.mbx.nati-sfae-css-e2-f@army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 8145

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH PAGE

1 SCOPE 1
1.1 Scope 1
1.2 Types 1
2 APPLICABLE DOCUMENTS 1
2.1 General 1
2.2 Government documents 1
2.2.1 Government specifications, standards, and handbooks 1
2.2.2 Other government documents, drawings, and publications 2
2.3 Non-government publications 2
2.4 Order of precedence 3
3 REQUIREMENTS 3
3.1 Acceptance Inspection and Test (AI&T) 3
3.1.1 First Article Testing (FAT) 3
3.1.2 Lot Acceptance Inspection/Testing (LAIT) 3
3.1.3 FAT and LAIT Acceptance and Inspection Table 3
3.2 Materials and construction 3
3.2.1 Dissimilar metals 4
3.2.2 Recycled, recovered, environmentally preferable, or biobased materials 4
3.2.3 List of prohibited materials and exceptions 4
3.2.4 Additive manufacturing 4
3.3 Design characteristics 4
3.3.1 ASLMS V3 container 4
3.3.2 Weight 5
3.3.3 Safety 5
3.3.4 Forklift access 5
3.3.5 Bulk/Parts storage system transport durability 5
3.3.6 Parts and bulk storage concept and locking 6
3.3.7 Internal storage devices 6
3.3.8 Roof access 6
3.3.9 Replaceability 6
3.4 Standardization 6
3.4.1 No specialized tools 6
3.5 Workmanship 7
3.5.1 Cleanliness 7
3.5.2 Sharp edges 7
3.5.3 Rubber/gasketing 7
3.6 Changes 7
3.7 Welding 7
3.8 Finish, color, and markings 7
3.8.1 Deterioration prevention and control 7
3.8.2 Corrosion control performance 7
3.8.3 Treatment and painting 8
3.8.4 Interior finish and color 8

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.8.5 Markings 8
3.9 Data plates 8
3.9.1 Shipping data plate 8
3.9.2 Convention for Safe Containers (CSC) plate 8
3.9.3 Manufacturer's data plate 9
3.9.4 Item Unique Identification (IUID) visibility 9
3.10 Security 9
3.10.1 Physical security 9
3.10.2 High security storage 9
3.11 Leveling 9
3.12 Internal storage configurations based on ASLMS V3 Types 9
3.12.1 Internal load stability 10
3.13 Parts storage features 10
3.13.1 Internal parts modules 10
3.13.2 Side-opening bulk storage access doors 10
3.13.3 Parts module drawers 10
3.13.4 Parts sliding/adjustable shelves 10
3.13.5 Parts racks 10
3.13.6 Parts internal storage 10
3.14 Bulk storage features 11
3.14.1 Bulk storage modules 11
3.14.2 Side-opening bulk storage access doors 11
3.14.3 Removeable pallets/rack system 11
3.14.4 Bulk module drawers 11
3.14.5 Bulk sliding/adjustable shelves 11
3.14.6 Adjustable rack storage 11
3.14.7 Storage locations 11
3.15 General system performance 11
3.15.1 Capabilities 11
3.15.2 Deployability 11
3.16 Reliability and maintainability 12
3.16.1 Set up and take down 12
3.16.2 Subsystem reliability 12
3.16.3 Maintainability 13
3.17 Transportability 13
3.17.1 Air transportability 13
3.17.2 Ground transportability 13
3.17.3 Marine transportability 14
3.17.4 Rail transportability 14
3.17.5 Lifting and tiedown provisions 15
3.17.6 Drop shock test 15
3.18 Environmental 15
3.18.1 High temperature (storage and operation) 15
3.18.2 Low temperature (storage and operation) 15
3.18.3 Altitude 15
3.18.4 Solar radiation 15
3.18.5 Rain 15
3.18.6 Fungus 15

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.18.7 Salt fog 15
3.18.8 Sand and dust 16
3.18.9 Climatic access 16
3.19 Weaponized environmental exposure 16
3.19.1 Chemical, biological, radiological, and nuclear (CBRN) environment 16
3.19.2 Mission-oriented protective posture (MOPP) IV access 16
3.19.3 High altitude electromagnetic pusle (HEMP) 16
3.20 Human factors engineering (HFE) 16
4 VERIFICATION 16
4.1 Acceptance inspection and test (AI&T) 16
4.1.1 First Article Testing (FAT) and Lot Acceptance Testing (LAT) 16
4.2 Materials and construction 18
4.2.1 Dissimilar metals 18
4.2.2 Recycled, recovered, environmentally preferable, or biobased materials 18
4.2.3 List of prohibited materials and exceptions 18
4.2.4 Additive manufacturing 18
4.3 Design characteristics 19
4.3.1 ASLMS V3 container 19
4.3.2 Weight 19
4.3.3 Safety 19
4.3.4 Forklift access 19
4.3.5 Bulk/Parts storage system transport durability 19
4.3.6 Parts and bulk storage concept and locking 20
4.3.7 Internal storage devices 20
4.3.8 Roof access 20
4.3.9 Replaceability 20
4.4 Standardization 20
4.4.1 No specialized tools 20
4.5 Workmanship 20
4.5.1 Cleanliness 20
4.5.2 Sharp edges 20
4.5.3 Rubber/gasketing 20
4.6 Changes 20
4.7 Welding 20
4.8 Finish, color, and markings 20
4.8.1 Deterioration prevention and control 20
4.8.2 Corrosion control performance 21
4.8.3 Treatment and painting 21
4.8.4 Interior finish and color 21
4.8.5 Markings 21
4.9 Data plates 21
4.9.1 Shipping data plate 21
4.9.2 Convention for Safe Containers (CSC) plate 21
4.9.3 Manufacturer’s data plate 21
4.9.4 Item Unique Identification (IUID) visibility 21
4.10 Security 21
4.10.1 Physical security 21
4.10.2 High security storage 21

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.11 Leveling 22
4.12 Internal storage configurations based on ASLMS V3 Types 22
4.12.1 Internal load stability 22
4.13 Parts storage features 22
4.13.1 Internal parts modules 22
4.13.2 Side-opening bulk storage access doors 22
4.13.3 Parts module drawers 22
4.13.4 Parts sliding/adjustable shelves 22
4.13.5 Parts racks 22
4.13.6 Parts internal storage 22
4.14 Bulk storage features 22
4.14.1 Bulk storage modules 22
4.14.2 Side-opening bulk storage access doors 22
4.14.3 Removeable pallets/rack system 22
4.14.4 Bulk module drawers 22
4.14.5 Bulk sliding/adjustable shelves 23
4.14.6 Adjustable rack storage 23
4.14.7 Storage locations 23
4.15 General system performance 23
4.15.1 Capabilities 23
4.15.2 Deployability 23
4.16 Reliability and maintainability 23
4.16.1 Set up and take down 23
4.16.2 Subsystem reliability 23
4.16.3 Maintainability 24
4.17 Transportability 24
4.17.1 Air transportability 24
4.17.2 Ground transportability 24
4.17.3 Marine transportability 24
4.17.4 Rail transportability 24
4.17.5 Lifting and tiedown provisions 25
4.17.6 Drop shock test 25
4.18 Environmental 25
4.18.1 High temperature (storage and operation) 25
4.18.2 Low temperature (storage and operation) 25
4.18.3 Altitude 25
4.18.4 Solar radiation 26
4.18.5 Rain 26
4.18.6 Fungus 26
4.18.7 Salt fog 26
4.18.8 Sand and dust 27
4.19 Weaponized environmental environment 27
4.19.1 Chemical, biological, radiological, and nuclear (CBRN) environment 27
4.19.2 Mission-oriented protective posture (MOPP) IV access 27
4.19.3 Cold climate access 27
4.20 Human factors engineering (HFE) 27
5 PACKAGING 27
5.1 Packaging 27

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

6 NOTES 28
6.1 Intended use 28
6.2 Ordering data 28
6.3 First articles 28
6.4 Definitions 28

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

1 SCOPE

1.1 Scope. This performance specification covers the overall performance, environmental, and safety requirements of the Authorized Stockage List Mobility System Version V3 (ASLMS V3). The ASLMS V3 consists of a certified International Organization for Standardization (ISO) container with internal modular storage devices configured to meet individual Supply Support Activity (SSA) storage needs. ASLMS V3 will provide containerized storage for both part and bulk items through the use of modular internal storage devices and be equipped with adjustable rack storage systems, and hazardous material (HAZMAT) spill containment devices. The ASLMS V3 systems will have the capability to operate in garrison and field environments and only be accessed while downloaded on level ground from the transportation asset. Systems being transported via Heavy Expanded Mobility Tactical Truck Load Handling System (HEMTT LHS), Palletized Load System (PLS) trailer, or other ground-based mode will be downloaded prior to accessing for safety reasons. Each ASLMS V3 configuration type will be customizable by an SSA to fit its individual needs. All ASLMS V3 components must be configured and packed for transport within an ISO container and designed to withstand the rigors of transport across sea, air and land (on and off road) modes of travel.

1.2 Types. The Authorized Stockage List Mobility System V3 is comprised of 5 Types/Variants, each heretofore referred to as "ASLMS V3" as follows:

Type 1 – 100% Bulk Storage
Type 2 – 100% Bulk Storage
Type 3 – 70% Parts and 30% Bulk Storage
Type 4 – 70% Parts and 30% Bulk Storage
Type 5 – 70% Parts and 30% Bulk Storage

For a more detailed description please see 3.12

2 APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned they must meet all specified requirements and verification documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Government specifications, standards, and handbooks. The following drawings, specifications, standards, and other publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-53072	-	Chemical Agent Resistant Coating System Application Procedures and Quality Control Inspection

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-129	-	Military Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property
MIL-STD-209	-	Interface Standard for Lifting and Tiedown Provisions

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

MIL-STD-461	-	Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment
MIL-STD-464	-	Electromagnetic Environmental Effects Requirements for Systems
MIL-STD-810	-	Environmental Engineering Considerations and Laboratory Tests
MIL-STD-814	-	Requirements for Tiedown, Suspension and Extraction Provisions on Military Material for Airdrop
MIL-STD-882	-	Standard Practice System Safety
MIL-STD-913	-	Requirements for the Certification of Sling Loaded Military Equipment for External Transportation by Department of Defense Helicopters
MIL-STD-1366	-	Interface Standard for Transportability Criteria
MIL-STD-1472	-	Human Engineering

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION (ISO)

ISO 668	-	Series 1 Freight Containers – Classification, Dimensions and Ratings (DoD Adopted)
ISO 1161	-	Series 1 Freight Containers - Corner Fittings - Specification (DoD Adopted)
ISO 1496/1	-	Series 1 Freight Containers - Specification and Testing - Part 1: General Cargo Containers for General Purposes Amendment 1: 1C Containers (DoD Adopted)
ISO 6346	-	Freight Containers - Coding, Identification and Marking

(Copies of these documents are available from https://quicksearch.dla.mil.)

2.2.2 Other government documents, drawings, and publications. The following other government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

FIELD MANUAL AND ARMY TECHNICAL MANUALS

FM 3-11	-	Chemical, Biological, Radiological, and Nuclear Operations

(Copies of this document are available online at https://armypubs.army.mil/.)

2.3 Non-government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E1925	-	Specification for Engineering and Design Criteria for Rigid Wall Relocatable Structures

(Copies of this document are available online at https://www.astm.org.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY (AWS)

AWS D1.1	-	Structural Welding Code – Steel (DoD Adopted)
AWS D1.2	-	Structural Welding Code – Aluminum (DoD Adopted)
AWS D1.3	-	Structural Welding Code – Sheet Steel (DoD Adopted)
AWS D1.6	-	Structural Welding Code – Stainless Steel (DoD Adopted)

(Copies of these documents are available online at https://www.aws.org.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE) INTERNATIONAL

SAE AMS-STD-595	-	Colors Used in government Procurement

(Copies of this document are available online at https://www.sae.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained/authorized.

3 REQUIREMENTS

3.1 Acceptance Inspection and Test (AI&T). All ASLMS V3 production units shall be subjected to AI&T to ensure production items meet the requirements contained herein prior to acceptance by the government. The contractor shall submit a Certificate of Conformance (CoC).

3.1.1 First Article Testing (FAT). Unless otherwise specified in the contract or purchase order, the ASLMS V3 supplier is responsible for conducting all FAT/FATs to ensure design compliance with performance requirements. The government reserves the right to perform any of the testing set forth in this specification where such tests are deemed necessary to ensure supplies and services conform to prescribed requirements. When a FAT is required, it includes all of the requirements and verifications listed in 4.1.1 Table IV that production units shall undergo. FAT necessitates that design/construction is subjected to AI&T to ensure production items meet the requirements contained herein prior to acceptance by the government. The contractor shall submit a FAT Plan which shall be approved by the government prior to the start of any FAT testing. At the completion of testing, all requisite date shall be submitted along with any additional/supplemental information (such as Certificate of Conformance (CoC) etc.) and incorporated in the FAT Report. The government also reserved the right to conduct any additional testing as they see fit.

3.1.2 Lot Acceptance Inspection/Testing (LAIT). All ASLMS V3 production units shall be subjected to periodic inspections/testing/evaluation to ensure the systems retain their integrity/quality throughout each production run. Supplier shall coordinate with their local DCMA Office in order to administer routine inspection in accordance with their pre-established Quality Assurance Surveillance Plan (QASP). The contractor shall submit a Certificate of Conformance (CoC) for any non-testable items or inspections/evaluations occurring off site at a subcontractor's/vendor's facility.

3.1.3 FAT and LAIT Acceptance and Inspection Table. Summary checklist for 3.1.1 and 3.1.2 items.

3.2 Materials and construction. Materials and construction methods are the choice and responsibility of the contractor and shall be capable of meeting all of the requirements specified herein. Materials shall be free from defects which adversely affect finish, performance, serviceability or lifespan of the final product. Materials and construction methods shall be designed to be inherently reliable and durable, withstanding the rigors of military transport and all environmental conditions/evaluations specified per

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

MIL STD 810 H and as otherwise identified in this specification. Utmost care shall be taken during fabrication to ensure quality workmanship and safety of the service person (operators/maintainers etc.) using the item. Manufacturing practices shall be capable of consistently yielding quality product that conforms to all requirements in this specification and any internally referenced specifications. Continual improvement shall also be a constant focus of the manufacturing practices. All component materials shall be properly marked and identified, and also protected properly during storage. Materials shall be produced and integrated to extend durability and provide consistency of appearance throughout system's life. All components to be assembled shall be thoroughly cleaned of all foreign matter (dust/dirt/filings/grease etc.) prior to assembly. In any case of material, process, or equipment change desired to be made by the contractor, the written consent of the government shall be obtained before making the change. Any areas specifically requested to be free of paint/finish shall be per the governments instruction via requirements/verification or otherwise stated in the contract. Additional testing may be required prior to implementation of any product changes to verify product performance.

3.2.1 Dissimilar metals. The ASLMS V3 shall not use dissimilar metals in intimate contact with each other unless otherwise protected against galvanic corrosion per MIL-STD-889. Paint by itself shall not be considered protection against galvanic corrosion.

3.2.2 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. Used, rebuilt or remanufactured components, pieces and parts (or otherwise compromised components) shall not be incorporated in the ASLMS V3.

3.2.3 List of prohibited materials and exceptions. The following are prohibited materials: asbestos, beryllium, Class I and Class II Ozone Depleting Substances (ODS), hexavalent chromium, cadmium, mercury, lead, radioactive materials, and other Group 1 Agents classified as "carcinogenic to humans" by the International Agency for Research on Cancer (IARC) Monographs. The following exceptions are allowed without prior approval from the government:

a. Products listed under "Priming" and "Topcoating" in MIL-DTL-53072, Table I
b. Silica used in adhesives and sealants
c. Steel containing up to 0.35 % lead by weight
d. Aluminum containing up to 0.4 % lead by weight
e. Copper and Brass alloys containing up to 4 % lead by weight
f. Trace amounts of identified restricted materials contained in base materials and/or alloys. (Trace amounts are defined as <0.1% by weight for carcinogens and <1% by weight for all other materials.)

3.2.4 Additive manufacturing. Additive manufacturing shall be utilized for system fabrication wherever practical to improve reliability and overall system quality/reproducibility/durability.

3.3 Design characteristics.

3.3.1 ASLMS V3 container. The ASLMS V3 container shall meet the design/test requirements of a 20-foot ISO container (1C) and shall be subjected to all the tests as described in ISO 1496-1 and all other requirements specified herein. Of the ISO 1496-1 tests required for certification, the weather proofness portion shall be conducted last to ensure that no permanent deformation has occurred to allow for rain/water intrusion into the ASLMS V3.

3.3.1.1 ASLMS V3 container storage classes. TheClass I, II, III(P), IV, VII, VIII, IX and MTOE items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.3.1.2 ASLMS V3 container stacking. The ASLMS V3 container shall be certified for stacking and tested in accordance with ISO 1496-1 for a Type 1C container.

3.3.1.3 ASLMS V3 ISO container doors. The ASLMS V3 shall be designed such that ISO container doors allow two-way access (along both long sides of the container) to both parts and bulk storage portions of the ASLMS V3. Container doors shall also be equipped with a means of safely securing in the open position during use and in wind conditions.

3.3.1.4 Venting. Packaged (enclosed) components of the ASLMS V3 and container shall have a passive venting capability allowing for pressure equalization for airlift operations per Air transportability section, prevent water/precipitation/sand/dust intrusion, and allow for proper HAZMAT venting and minimization during both storage and regular system operation. Venting system shall be equipped with whatever means necessary (baffling/filters/waterproof design/low profile design/multiple smaller vents etc.) in order to allow the system to successfully meet all MIL-STD 810 H requirements for Blowing Sand/Dust, Blowing Rain and other environmental testing/evaluations as specified herein.

3.3.2 Weight.

3.3.2.1 Container tare weight. Tare weight of an ASLMS V3 container shall not exceed the Tare weight for each ASLMS Type as listed below:

TABLE I: Tare Weights by ASLMS V3 Type

Type I	Type II	Type III	Type IV	Type V
13,356.01	12,547.46	16,405.84	17,787.07	17,636.69

3.3.2.2 Max gross weight. All ASLMS V3 variants shall be capable of at least 37,000 pounds of max gross weight.

3.3.3 Safety. The ASLMS V3 shall be constructed with the safety of the operator and maintainer in mind in accordance with MIL-STD-882 and prevent/mitigate all hazards (pinch/crush/falling cargo etc.) to the maximum extent possible. All ISO/Container doors shall be designed to prevent pinch/crush hazards from occurring.

3.3.4 Forklift access. The ASLMS V3 container shall allow forklift access to bulk/repair parts in all storage locations once it has been properly/safely downloaded and placed in a level location as indicated by leveling indicator. Internal fasteners and lock-down devices shall secure ASL items within their storage locations. ASLMS V3 shall be two way forkliftable and allow for movement of both loaded and unloaded configurations utilizing two sets of forkpockets accounting for load and center of gravity variation.

3.3.5 Bulk/Parts storage system transport durability. All ASLMS V3 bulk and parts storage modules, framing, rack systems, pallets, drawers, locking devices etc. shall be fully capable of all mobility operations and tested IAW MIL STD 810 H, and as otherwise specified/required herein. Storage/retention devices shall not exhibit damage while properly restraining/retaining all bulk and part storage components. ASLMS V3 will be regularly transported by rail, land (including over unimproved terrain) and sea and shall be robustly designed for all rigors of transport.

3.3.5.1 Cycling life of ASLMS V3 subsystems/components ASLMS V3 shall be capable of the following performance cycling characteristics:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.3.5.1.1 Cycling life of LHS interface ASLMS V3 shall be capable of cycling 100 times per year for a total of at least 2,000 cycles over the system life utilizing the LHS interface without sustaining system damage/deformation.

3.3.5.1.2 Cycling life of modules Internal modules shall be capable of cycling (removed from and reinserted/locked in the container) 100 times per year for a total of at least 2,000 cycles over the system life. Intrinsic design shall make these modules easy to place, easy to lock into/secure in the ISO structure and allow for rapid changeout to support specific mission needs.

3.3.5.1.3 Cycling life of ISO doors ISO container doors shall be capable of cycling 300 times per year over the life cycle of the system for a total of at least 6,000 cycles without sustaining damage/deformation for allowing full access to both parts and bulk storage areas.

3.3.5.1.4 Cycling life of removeable pallets Removeable pallets shall be capable of cycling 300 times per year over the life cycle of the system for a total of at least 6,000 cycles without sustaining damage/deformation.

3.3.5.1.5 Cycling life of drawers/sliding shelves All drawers/sliding shelves shall be capable of cycling 600 times per year over the life cycle of the system for a total of at least 12,000 cycles without sustaining damage/deformation.

3.3.6 Parts and bulk storage concept and locking. The ASLMS V3 system shall have expandable, or side-opening, parts storage containers providing modularized bin, shelf, cabinet, drawer, and high security storage for small repair parts. ASLMS V3 shall allow for variable internal configurations using interchangeable components, modular storage devices, and adjustable internal dividers for each drawer. Shelves and drawers shall contain internal provisions/mechanisms to allow for locking in place in both the closed and open position. Locking bars shall be furnished for both security purposes and also to inhibit accidental/unintentional opening during transit and/or storage. All modular storage devices shall also be equipped with forkliftable locking provisions in order to accommodate rapid load out/change out and are capable of being securely locked in place inside of the ISO container. Modules/racks/drawers shelving shall be designed so that they maximize the available storage. These design of systems shall allow for at least 42 inches of storage depth along each long side of the container or overall of 84 inches across both long sides (available storage area across the 8’ overall ISO container dimension).

3.3.7 Internal storage devices. Internal storage devices shall provide a range of 400 to 1000 operator-adjusted, repair parts storage locations and be interchangeable between parts storage containers. Identification labels and labeling areas shall be furnished with the containers in such a manner as to be able to readily identify the contents of a particular container/storage device.

3.3.8 Roof access. The ASLMS V3 shall be equipped with a safe means to egress the roof of the system. All climbing provisions shall lock into place and be fully contained within the standard ISO dimensions when not in use and not subject to accidental opening during transit.

3.3.9 Replaceability. The ASLMS V3 shall have components that are expected to exhibit significant wear/tear over the course of it’s life due to loading operations/drawer cycling/pallet loading/door closings etc. to be designed to be easily replaceable/repairable.

3.4 Standardization. The ASLMS V3 shall have mechanical hardware (e.g., nuts, bolts, fasteners), opening hardware (e.g., hinges, handles, latches, locking mechanisms), and removable components which are uniform for common functions and interchangeable between one ALSMS V3 and another.

3.4.1 No specialized tools. Only tools found in the Automotive Mechanic's Tool Kit (SATS),

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

NSN: 5180-01-649-0856 or General Mechanics Tool Kit NSN: 5180-01-548-7634 shall be required to perform maintenance and repairs to the ASLMS V3 removable components.

3.5 Workmanship. The ASLMS V3 shall be designed/constructed in accordance with (IAW) the quality of product established by this performance specification and IAW with QASP and internal quality control system. Utmost care shall be taken during fabrication to ensure quality workmanship and safety of the service person using the item. Manufacturing practices shall be capable of consistently yielding quality product that conforms to all requirements in this specification and any internally referenced specifications. Continual improvement shall also be a constant focus of the manufacturing practices. Materials shall be produced and integrated to extend durability and provide consistency of appearance throughout the product's life. Finished surfaces are expected to be smooth aside from non-slip surfaces/areas to mitigate personnel hazards and facilitate easy cleaning.

3.5.1 Cleanliness. All components to be assembled shall be thoroughly cleaned of all foreign matter. The ASLMS V3 shall be easily cleaned and disinfected using customary cleaning supplies. Pockets, voids, joints, pitted surfaces etc. inhibiting access for cleaning shall be limited/minimized. All finishes shall be capable of being cleaned without damaging finish/topcoat etc. All surfaces shall be fully degreased/cleaned in preparation of final finishing/painting operations.

3.5.2 Sharp edges. The ASLMS V3 container and its components shall not have sharp edges or burrs presenting a hazard to personnel during cleaning, set up, take down, operation, maintenance or transport. There shall be no presence of burrs/sharp edges that restrict and/or hinder operations in any way or require the use of added force in order to properly install/operate the ASLMS V3 or subject the user to any added hazards or require any additional protective measures.

3.5.3 Rubber/gasketing. The ASLMS V3 container and its components shall not have gaps in rubber seals/gaskets etc. across the entire perimeter allowing for sand/dust/rain or other environmental intrusion, premature failure or allowing for chemical, biological, radiological, and nuclear (CBRN) agent intrusion/penetration into the ASLMS V3 or associated components. Rubber seals/gasketing etc. shall not have any bent and/or creased edges or contain any paint/finish overspray. All door seals and gasketing materials shall be capable of passing MIL-STD-810 H test evaluations at all temperatures and conditions as specified. Gasketing/seals shall be capable of repair and replacement and shall be common across all ASLMS V3 Types to the maximum extent possible.

3.6 Changes. Material, process, or equipment changes made by the contractor shall obtain the written consent of the government prior to making any change. (Additional testing may be required prior to implementation of the change to verify product performance.)

3.7 Welding. All welding shall be in accordance with (IAW) AWS D1.1, AWS D1.2, AWS D1.3, and AWS D1.6.

3.8 Finish, color, and markings.

3.8.1 Deterioration prevention and control. The ASLMS V3 shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against corrosion and deterioration during storage and operational conditions experienced.

3.8.2 Corrosion control performance. The ASLMS V3 shall operate without corrosion affecting form, fit, or function during a 20-year service life. Service life can include varying or extended periods in corrosive environments involving one or more of the following: high humidity, salt spray, road deicing agents, gravel impingement, atmospheric contamination, and temperature extremes. During the 20-year service life, surface corrosion, which may include red, black, and/or white corrosion products, shall be a

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

maximum of 1% of the surface. The loss of the original thickness of the base metal shall be no greater than 2% or 0.001 inch, whichever is less.

3.8.3 Treatment and painting. Unless otherwise specified (see 6.2), exterior finish and color of the ASLMS V3, regardless of the material selected, shall have a finish coat of the Chemical Agent Resistant Coating (CARC), applied in accordance with MIL-DTL-53072 to provide proper corrosion and CBRN system performance. Adhesion testing shall be conducted IAW MIL-DTL-53072 to ensure quality/integrity of the final finish. The color shall be either Green 383, chip number 34094 or Tan 686A, chip number 33446 in accordance with SAE AMS-STD-595 or as specified in the contract. Identification plates shall be installed following application of the final finish coat.

3.8.3.1 Paint free areas. The ASLMS V3 shall keep the following areas free from paint/overspray:

a. fabrics,
b. plastic,
c. rubber,
d. seals,
e. glass,
f. machined surfaces,
g. any location where paint interferes with component function/door/drawer operation etc.

3.8.4 Interior finish and color. The interior surfaces of the ASLMS V3 shall have finish and color in accordance with MIL-T-704 and SAE-AMS-STD-595. The interior color shall be either Green 383, chip number 34094 or Tan 686A, chip number 33446 in accordance with SAE AMS-STD-595 or as specified in the contract. Interior floor shall have a non-slip texture in accordance with Type I of A-A-59166.

3.8.5 Markings. All markings on the ASLMS V3 shall be in accordance with ISO 6346, MIL-STD-129, MIL-STD-130, and MIL-STD-1472.

3.8.5.1 Government-owned container identification. Government-owned containers shall be marked with the identifier "USAU" or "USAX" (as specified in the contract) in accordance with ISO 6346 and registered in the DOD ISO registry within Joint Container Management System (JCMS).

3.8.5.2 Stencils. Unless otherwise specified, the ASLMS V3 shall have stencils in accordance with MIL-T-704 and MIL-DTL-53039, Black, chip number 37030 in accordance with SAE-AMS-STD-595.

3.9 Data plates.

3.9.1 Shipping data plate. Each ASLMS V3 container, shall be furnished with a shipping data plate. The shipping data plate shall show a silhouette of the container indicating the dimensions, weight, center of gravity and the location and capacity of the lifting and tie-down provisions. The plate shall be permanently attached in a location that is visible and accessible but protected from damage during movement and handling.

3.9.2 Convention for Safe Containers (CSC) plate. The CSC plate shall contain at a minimum: "CSC SAFETY APPROVAL", date of container manufacture, specifically the month and year, must be evident. As must the manufacturer's container identification number or, in the case of an existing container without a manufacturer number, the Container Operator's operational number (using a "BIC Code") or the number allotted by the Administration. The container's maximum weight-carrying capability (usually referred to as "Payload" or "max net mass") in both kilograms and pounds must be inscribed, along with the stacking and racking test load values.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.9.3 Manufacturer's data plate. The manufacturer's data plates shall identify at a minimum: specification number, design activity code, manufacturer and CAGE, contract number, date of manufacture, item nomenclature, serial number, National Stock Number (NSN), technical manual number, and US military property identification.

3.9.3.1 Manufacturer's data plate location. The manufacturer's data plate shall be located visibly at the exterior ends of each container. Each container shall have a Field Pack-Up (FPU) unique data plate.

3.9.4 Item Unique Identification (IUID) visibility. The ASLMS V3 shall have IUID and nameplate in accordance with MIL-STD-129 and MIL-STD-130. The ASLMS V3 in transport mode shall have the ability to host smart Radio Frequency Identification Devices (RFID).

3.10 Security. The ASLMS shall possess security features.

3.10.1 Physical security. The ASLMS V3 shall have provisions for securing openings, folding or expanding components, and removable components to prevent unauthorized access, expansion, or removal from the exterior of the ASLMS V3. Primary door will allow exit from inside the ASLMS V3 container when locked from the outside or be equipped with an escape hatch that is internally operational as an alternate.

3.10.2 High security storage. High security storage compartments shall have double-lock security and the compartments shall be easily interchangeable as entire units between storage containers.

3.11 Leveling. The ASLMS V3 shall be equipped with visual leveling indicators to show when the ground surface is sufficiently level to allow for proper operation and mitigate door swing hazards.

3.12 Internal storage configurations based on ASLMS V3 Types. Internal storage configurations shall provide the following bulk vs part breakdown/composition:

TABLE II: Bulk vs Parts Storage Percentages

	Type I	Type II	Type III	Type IV	Type V
Bulk Storage (42" Depth)					
Open Floor with 8 Tie Down Rings	30%		30%		
Forkliftable Bulk Modular Shelving/Open Drawer Unit	40%				
Non-Modular Vertical Frame with Forkliftable Palletized Shelving Accommodates 48" and 30" pallet width	30%	60%		30%	30%
Non-Modular Vertical Frame with Forkliftable Palletized Accommodates Large 67" pallet width		40%			
Total Bulk Percent	100%	100%	30%	30%	30%
Part Storage (42" Depth)					

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

Forkliftable Modular Parts Storage **10 Drawer Cabinet 35" Width			10%	10%	10%
Forkliftable Modular Parts Storage **8 Drawer Cabinet 35" Width			10%	20%	10%
Forkliftable Modular Parts Storage Deep **4 or 5 Drawer Cabinet 35" Width			20%	10%	20%
Non-Modular Parts Storage Deep **Drawers. Combination of 48" and 30" drawer widths.			30%	30%	30%
Total Parts Percent	0%	0%	70%	70%	70%

*Percentages correspond with the available internal volume of an 8'x8'x20' ISO with full side opening access.

** All drawers shall container dividers to allow for customization based on mission purposes.

3.12.1 Internal load stability. Internal fasteners, lock-down/retention devices, doors, or equivalent devices shall be provided to secure all ASLMS V3 items (both bulk and parts storage systems) within all storage compartments. Storage compartment designs shall allow operator access to repair parts along the depth of each compartment. Stability devices shall fully/safely secure all cargo storage and prevent damage to any system component or transportation assets during all modes of transportation described in 3.17.

3.13 Parts storage features. All parts storage modules, doors, sliding/adjustable shelves, rack systems, drawers etc. shall remain fully operational/functional throughout all environmental and post mobility operations. Parts storage devices shall be IAW 3.12 Table II.

3.13.1 Internal parts modules. ASLMS V3 intrinsic design shall contain modular system components /features. Removeable part modules shall be easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs.

3.13.2 Side-opening bulk storage access doors. The ASLMS V3 shall have side-opening parts storage ISO container access on a minimum of two opposing sides to facilitate easy removal of parts storage modules/racks/drawers etc.

3.13.3 Parts module drawers. ASLMS V3 modules shall contain drawers that are robustly designed to meet rigors of transport and furnished with dividers/separators to further customize each drawer.

3.13.4 Parts sliding/adjustable shelves. ASLMS V3 shall be equipped with sliding shelves and adjustable shelving features.

3.13.5 Parts racks. ASLMS V3 shall be equipped with racks supporting parts storage requirements.

3.13.6 Parts internal storage. Internal storage configurations in parts storage containers shall provide no more than 15 percent (minimum), 10 percent (desirable) unusable storage area in a closed configuration and unrestricted cargo access to repair parts when the container is expanded or opened.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.14 Bulk storage features. All bulk storage modules, doors, sliding/adjustable shelves, removeable pallets, rack systems, drawers etc. shall remain fully operational/functional throughout all environmental and post mobility operations. Bulk storage devices shall be IAW 3.12 Table II.

3.14.1 Bulk storage modules. ASLMS V3 intrinsic design shall contain modular system components /features. Removeable bulk modules shall be easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs.

3.14.2 Side-opening bulk storage access doors. The ASLMS V3 shall have side-opening bulk storage ISO container access on a minimum of two opposing sides and provide rack and hazardous material (HAZMAT) storage for large and palletized repair parts.

3.14.3 Removeable pallets/rack system. ASLMS V3 shall be equipped with removeable pallets that interface with a racking system. Removeable pallets shall be easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs. Rack system shall be robustly designed to mitigate damage potential.

3.14.4 Bulk module drawers. ASLMS V3 bulk modules shall contain drawers that are robustly designed to meet rigors of transport and furnished with dividers/separators to further customize each drawer.

3.14.5 Bulk sliding/adjustable shelves. ASLMS V3 shall be equipped with sliding shelves and adjustable shelving features.

3.14.6 Adjustable rack storage. Bulk storage containers shall have adjustable rack storage systems that maximize the usable storage space and allow for operator to make adjustments to the dimensions and number of bulk storage locations per container.

3.14.7 Storage locations. Within the bulk storage containers container, there shall be a minimum of ten and a maximum of 40 bulk storage locations.

a. Ten (10) percent of these storage locations shall provide HAZMAT spill containment which can be easily moved between containers.
b. Location labels shall be affixed to the containers in such a manner as to be able to readily identify the contents of a particular container.
c. Reusable pallets maximizing the length and width dimensions of all possible bulk storage location configurations shall be fielded with each container.
    1) Reusable pallets shall allow location labels to be affixed and viewed from the outside of the bulk storage container.
    2) The number of pallets fielded shall equal the maximum number of storage location allowed by each container. No more than 10 percent (minimum) and 5 percent (desirable) unusable storage space area shall be provided with any storage configuration.
d. The HAZMAT storage areas shall have adequate spill containment and ventilation devices to store all types of hazardous materials stocked in Class IX ASLs.

3.15 General system performance.

3.15.1 Capabilities. The ASLMS V3 system shall support the criteria outlined in the operational mode summary/mission profile (OMS/MP).

3.15.2 Deployability. All ASLMS V3 containers shall be strategically deployable by sea, rail, highway, and air (to include both internal and external air transport modes) to· include all current and

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

developmental medium and heavy transport in both military and civilian military aircraft (lift class range of aircraft starting with the C-130).

3.15.2.1 Stacking of containers. The ASLMS V3 shall be capable of stacking requirements per ISO 1496-1 for a 1C container.

3.15.2.2 Container organization. A container shall be packed so a majority of items in each container can be accessible and removable without prior removal of other items.

3.15.2.3 Container consolidation. Components and bulk materials shall be consolidated together in reusable crates. Standard Practice for Military Packaging. When practical, the crates shall contain only components of like description. Also, when practical, each kit shall be packed in a single crate or securely palletized.

3.16 Reliability and maintainability.

3.16.1 Set up and take down. The set up and take down time for the ASLMS V3 shall be not greater than the values listed below inclusive of leveling time. No special tools shall be required for set up or take down. A small 5k forklift can be utilized to place/changeout modular components. Timeframes listed below shall include one download or upload cycle for the HEMTT LHS, all necessary door openings/closures, and all requisite modular changeouts/offloads. Values listed below are given based on operational condition/posture:

Standard Operation Values

a. 17 minutes with 4 personnel in garrison.
b. 20 minutes with 4 personnel in a driver accommodation.
c. 23 minutes with 4 personnel in a rifleman accommodation.

Values with MOPP/Cold Weather Gear

a. 22 minutes with 4 personnel in garrison.
b. 26 minutes with 4 personnel in a driver accommodation.
c. 30 minutes with 4 personnel in a rifleman accommodation.

3.16.2 Subsystem reliability. The ASLMS V3 LHS interface, modules, doors, pallets, shelving and drawers shall be cycled in order to demonstrate reliability performance during FAT. Testing shall consist of cycling each component 29% (~3.5 months duration) of its yearly estimated value distributed throughout all transportability, environmental, and other related system evaluations.

3.16.2.1 LHS interface reliability. Across all testing conducted, the ASLMS V3 shall be cycled with the LHS once for each test inspection interval for a total of at least 29 lift/drop cycles.

3.16.2.2 Module reliability. Across all testing conducted, Modules shall be cycled once for each test inspection interval for a total of at least 29 install/uninstall cycles.

3.16.2.3 Door reliability. Across all testing conducted, the ISO doors shall be cycled at least three time for each test inspection interval for a total of at least 87 open/close cycles.

3.16.2.4 Removeable pallet reliability. Across all tests conducted, each pallet shall be cycled at least three time for each test inspection interval for a total of at least 87 remove/reinstall cycles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.16.2.5 Drawer/sliding shelve reliability. Across all testing conducted, each drawer/sliding shelf shall be cycled at least six time for each test inspection interval for a total of at least 174 open/close cycles.

3.16.3 Maintainability

3.16.3.1 Maintenance (EUMD). The ASLMS V3 shall not exceed 1 hour for all Essential Unscheduled Maintenance Demands (EUMD).

3.16.3.1.1 Mean time to repair (MeanTTR). The ASLMS V3 MeanTTR shall be 30 minutes.

3.16.3.1.2 Maximum time to repair (MaxTTR). The ASLMS V3 MaxTTR shall not exceed 1.5 hours for 90 percent of all EUMD (T=O).

3.17 Transportability. The ASLMS V3 shall meet all military and commercial test/transportability requirements both empty and when fully loaded with ASL items/cargo. The ASLMS V3 shall be capable of all modes of transportation described herein without damage or degradation to the ASLMS V3, its transportation asset, and without damage to or failure of internal retaining/fastening devices (e.g., tie-down/anchoring provisions, bolts/rivet nuts, shelving, palletized locking mechanisms, modules, drawers, bulk storage provisions, surrounding metal/composites etc.) or cargo. ASLMS V3 shall meet all transportability testing requirements per MIL STD 810 H.

3.17.1 Air transportability.

3.17.1.1 Airlift certificate for fixed wing aircraft. Each Type of container (see 1.2) shall have a current Airlift Certificate issued by the approved authority, US Air Force, ATTN: ASC/ENFC (ATTLA), 2530 Loop Road West, Wright Patterson AFB, OH 45433-7101. The ASLMS V3 shall be air transportable via C-130 and larger Air Mobility Command (AMC) aircraft, and sealift transportable by support watercraft. Air transportability requires that the ASLMS V3 shall comply with all applicable safety, load ability, and tiedown restraint guidelines and capable of properly interfacing with the K-Loader to support air operations. MIL-STD-209K and MIL-STD-1366 shall be used as guides. The ASLMS V3 shall incorporate a pressure equalization device to preclude damage that would endanger the aircraft or personnel due to pressure differential which may be encountered during rapid inflight decompression of as much as 8.3 psi within a 15 second interval.

3.17.1.2 Helicopter sling load (HSL). The ASLMS V3 and container, when fully loaded for transport, shall be externally transportable by CH-47 in accordance with MIL STD 209 and MIL-STD-913. The ASLMS V3 shall be capable of being externally transported (sling loadable) by a DoD rotary wing aircraft to include, but not limited to, CH-47D and CH-53 helicopters. The ASLMS V3 shall be transportable for a minimum mission for 30 nautical miles at a maximum weight of 23,396 pounds based on an elevation of 2,000 feet at an ambient temperature of 70°F. The ASLMS V3 shall be structurally capable, inspected and tested for conformance in meeting the requirements of interface standard MIL-STD-209 and shall show no signs of damage or degradation as a result of aerial transportation. Tie down provisions of MIL-STD 209, design criteria of MIL-STD-913 and helicopter lift limits of MIL-STD-1366 shall be used. For certification Static and Proof load testing is required and it will be up to the certification agency if an actual flight test is required based upon system design and similarity with prior systems.

3.17.2 Ground transportability. The ASLMS V3 shall be furnished with an integral HEMTT LHS and PLS compatible handling system featuring an integral bale bar, rails, and other devices built into the system to allow for safe and efficient handling with the HEMTT LHS, the Palletized Loading System (PLS) vehicle and the PLS-Trailer (PLS-T). The ASLMS V3 shall function properly in all operational and mobility scenarios.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.17.2.1 Highway transportability. The ASLMS V3 when packed for transport on military or commercial vehicles, shall be capable of unrestricted highway transport in accordance with MIL-STD-1366 for all U.S. states and North Atlantic Treaty Organization (NATO) member countries. ASLMS V3 shall be compliant with NATO Standardization Agreement (STANAG) No. 2413 concerning demountable load carrying platforms (DLCP).

3.17.2.2 Ground mobility. The ASLMS V3, when transported, shall have mobility not less than as described in Table I. The ASLMS V3, when mounted on a prime mover (prime mover is to be defined as any military or commercial asset that may be utilized to transport the ASLMS V3 as described in this document), shall be capable of transportation over primary roads, secondary roads, and cross-country terrain as specified below. It shall also be compatible with all standard military flat rack systems/handling devices utilized by the HEMTT LHS and PLS. The ASLMS V3 shall be capable of operating properly during and after each ground mobility test. The ASLMS V3 shall have ground mobility characteristics to withstand the shocks and vibrations encountered in ground transportation and operate properly without damage or degradation to the overall system or internal components during military operations. The fully loaded ASLMS V3, when mounted on the M871, HEMTT-LHS, PLS and the PLS Trailer (PLS-T), shall survive testing to include the Perryman Road Test, Munson Gravel Road Test, Munson Belgian Block Course, 2-inch washboard course and radial washboard course, 2" to 4" waves. The ASLMS V3 shall meet the requirements of MIL-STD-810 H Method 514.8. Note that the fully loaded configuration, for each prime mover, refers to the maximum allowable weight that can be lifted and/or transported by respective prime movers.

TABLE III. ASLMS V3 mobility terrain.

Terrain	Description	Speed (miles per hour)
Primary Roads	High quality paved	65
	Secondary pavement	50
	Rough pavement degraded	25
Secondary Roads	Loose surface	30
	Washboard & potholes	25
Trail	Belgian block	10
Cross Country	Up to 27% slope	5
* 50% of 2ndary, Trail and Cross Country shall be conducted on PLS Trailer.		
** A total of 29 lift/drop cycles shall be performed with the LHS over the course of all FAT test events.		

3.17.3 Marine transportability. The ASLMS V3 when packed for transport, shall be transportable by all modes of military water transportation described in MIL-STD-1366, commercial ships and commercial barges.

3.17.4 Rail transportability. The ASLMS V3 when packed for transport, shall be rail transportable in the U.S. and NATO member countries without restriction. The ASLMS V3, shall have a dimensional profile within the Gabarit International de Chargement (GIC) outline diagram in accordance with MIL-STD-1366 when loaded aboard a 51-inch high rail car deck.

3.17.4.1 Rail impact. The ASLMS V3 shall be capable of withstanding shock loads resulting from Association of American Railroads (AAR) requirements for rail shipment/railroad car impacts as described in MIL-STD-810 H, Method 526.2 (Rail Impact). There shall be no damage or displacement of internal storage systems/modules/cradles/provisions and no damage to the interior of the ASLMS V3 or any associated door hardware upon opening/closing the system post impact. No hazards shall be generated

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

as a result of ASLMS V3 testing. Hardware anchoring the modules/drawers/shelving to the wall/floor/ceiling/structure shall be intact, fully functional and exhibit no damage to the surrounding anchor points, provisions or base materials/structure.

3.17.5 Lifting and tiedown provisions. The ASLMS V3, fully loaded for transport, shall including lifting and tiedown provisions in accordance with MIL-STD-209 to safely and effectively transport equipment/cargo/bulk items without damage.

3.17.6 Drop shock test. The ASLMS V3, fully loaded for transport, shall be subjected to Drop Shock Testing per ASTM 1925-10 Specification for Engineering and Design Criteria for Rigid Wall Relocatable Structures Section 10.29 (All RWRS Without Skids) — for both flat and rotational drops. There shall be no permanent deformation, buckling, delamination, seal separation, or structural failures of any part of the RWRS after each test, and the doors, modules, drawers, locking pallets etc. shall open and close to their full extent without binding.

3.18 Environmental. The ASLMS V3 shall withstand both common and extreme environmental conditions and shall not degrade in any way when exposed to the conditions as delineated below.

3.18.1 High temperature (storage and operation). The ASLMS V3 system shall not be damaged by storage in ambient temperature of 160° F. The ASLMS V3 shall operate and be fully mission capable as specified at ambient temperatures up to 120° F. Operational force measurements shall be recorded and compared to the acceptable limits provided in MIL-STD-1472G. Testing shall be IAW MIL-STD-810 H, Method 501.7, Procedure I - Storage and Procedure II – Operation for a Hot-Dry (A1) environment per AR 70-38.

3.18.2 Low temperature (storage and operation). The ASLMS V3 shall not be damaged by storage in ambient temperature of -50° F. The ASLMS V3 shall operate as specified at ambient temperature of -25° F. Operational force measurements shall be recorded and compared to the acceptable limits provided in MIL-STD-1472G. Testing shall be IAW MIL-STD-810 H, Method 502.7, Procedure I - Storage and Procedure II – Operation for a Basic Cold (C1) environment per AR 70-38. Following the storage exposure, and returning to ambient, the ASLMS V3 shall be fully functional.

3.18.3 Altitude. The ASLMS V3 system, in its storage configuration, shall withstand the low-pressure environment and meet all 3.17.1 requirements for air transport and associated transitions occurring during critical decompression.

3.18.4 Solar radiation. The ASLMS V3 shall perform as specified with up to 355 British thermal units per square foot (Btu/ft^2) per hour of solar radiation per MIL-STD-810 H, Test Method 505.7.

3.18.5 Rain. The ASLMS V3 shall perform as specified herein when subjected to a blowing rain environment of up to 4 in/hr and prevent water intrusion into the main floor area of the container. Testing shall be conducted per MIL-STD-810 H, Test Method 506.6, Procedure I. Before testing, the rainfall rate at the test site was set to 4 in./hr and verified using a calibrated rain gauge

3.18.6 Fungus. The ASLMS V3 system shall be exposed fungus growth and subjected to MIL-STD-810 H Test Method 508.8. If not practical to subject the entire ASLMS V3 to fungus testing, representative material samples shall be provided for evaluation for each surface exposed to demonstrate that no fungus sustaining materials/nutrients are present in ASLMS V3.

3.18.7 Salt fog. Salt fog testing on the ASLMS V3 shall be performed in accordance with MIL-STD-810 H, Test Method 509.7. If not practical to subject the entire ASLMS V3 to salt fog testing, representative material samples shall be provided for evaluation for each surface exposed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

3.18.8 Sand and dust. The ASLMS V3 container shall be exposed to a blowing sand and dust environment per MIL-STD-810 H, Test Method 510.7, Procedure I – Blowing Dust and Procedure II - Blowing Sand and prevent sand/dust intrusion. Procedure II shall be conducted prior to Procedure I.

3.18.9 Climatic access. The ASLMS V3 and container shall be operable and maintainable both day and night by soldiers in appropriate protective clothing during all low and high temperature operational periods.

3.19 Weaponized environmental exposure. The ASLMS V3 in storage mode shall be survivable and operable under the following conditions.

3.19.1 Chemical, biological, radiological, and nuclear (CBRN) environment. The ASLMS V3 in stored mode with all venting closed, shall be capable of CBRN decontamination without damage to the ASLMS V3 or any of its contents. All rubber seals/gasketing etc. materials shall be designed/selected such that no CBRN agents can enter the container and decontamination operations do not result in damage/degradation to any of these materials.

3.19.2 Mission-oriented protective posture (MOPP) IV access. The user of the containers shall be able to gain access to the ASLMS V3 contents of the containers while wearing MOPP IV gear.

3.19.3 High altitude electromagnetic pusle (HEMP). The ASLMS V3 shall be fully survivable and not adversely affected by a HEMP event.

3.20 Human factors engineering (HFE). The ASLMS V3 shall be capable of being operated by the Military Operational Specialty (MOS) personnel 92A and maintained by 92J while: in garrison, driver accommodated (T) Rifleman accommodated (O), wearing gloves, arctic mittens, and equipped with Mission Orientated Protective Posture (MOPP) IV gear. MIL-STD-1472 and MIL-STD-1474 shall be used as the human engineering design criteria.

4 VERIFICATION

4.1 Acceptance inspection and test (AI&T). Nonconformance to any requirement herein, or failure of any required test or examination, or submittal of a CoC shall be cause for rejection by the (see 6.2). government

4.1.1 First Article Testing (FAT) and Lot Acceptance Testing (LAT). TABLE IV. Requirements and verifications

CHARACTERISTICS	REQUIREMENT SECTION	VERIFICATION SECTION	FIRST ARTICLE TESTING (FAT)	LOT ACCEPT-ANCE TESTING (LAT)
Acceptance testing and inspection (AT&I)	**3.1**	**4.1**		
First article testing (FAT)	3.1.1	4.1.1	X	CoC
Lot acceptance testing	3.1.2	4.1.2	NA	X*
Materials and construction	**3.2**	**4.2**		
Dissimilar metals	3.2.1	4.2.1	X	CoC
Prohibited materials	3.2.3	4.2.3	CoC	CoC
Design characteristics	**3.3**	**4.3**		
CSC stacking/certification/venting	3.3.1	4.3.3	X	CoC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

Weight	3.3.2	4.3.2	X	X*
Safety	3.3.3	4.3.3	X	X*
Forklift access	3.3.4	4.3.4	X	X*
Parts/Bulk storage durability	3.3.5	4.3.5	X	X*
Parts/Bulk storage/locking concepts	3.3.6	4.3.6	X	X*
Internal storage devices	3.3.7	4.3.7	X	X*
Roof Access	3.3.8	4.3.8	X	X*
Replaceability	3.3.9	4.3.9	X	X*
Standardization	3.4	4.4		
Commonality/No special tools	3.4.1	4.4.1	X	NA
Workmanship	**3.5**	**4.5**		
Cleanliness	3.5.1	4.5.1	X	X*
Sharp edges	3.5.2	4.5.2	X	X*
Rubber seals/gasketing quality	3.5.3	4.5.3	X	X*
Field Agent Resistance	3.5.4	4.5.4	X	CoC
Welding	**3.7**	**4.7**		
Quality/AWS standards	3.7	4.7	X	X*
Finish, color and markings	**3.8**	**4.8**		
Deterioration/corrosion control	3.8.1-2	4.8.1-2	X	CoC
Treatment, painting, finish, & color	3.8.3-4	4.8.3-4	X	X*
Markings	3.8.5	4.8.5	X	X*
Data plates	**3.9**	**4.9**		
All plates present/correct	3.9.1-3	4.9.1-3	X	X*
IUID visibility	3.9.4	4.9.4	X	X*
Physical security	**3.10**	**4.10**		
Locking/escape	3.10.1-2	4.10.1-2	X	X*
Leveling	**3.11**	**4.11**		
Leveling provisions	3.11	4.11	X	X*
Internal storage configurations	**3.12**	**4.12**		
Overall IAW 3.12 Table II	3.12	4.12	X	NA
Parts storage container performance	3.13	4.13		
Parts requirements	3.13.1-6	4.13.1-6	X	NA
Bulk storage container performance	**3.14**	**4.14**		
Bulk requirements	3.14.1-7	4.14.1-7	X	CoC
General system performance	**3.15**	**4.15**		
Capabilities	3.15.1	4.15.1	X	NA
Deployability	3.15.2	4.15.2	X	NA
Reliability and maintainability	**3.16**	**4.16**		
Set up and take down	3.16.1	4.16.1	X	NA
Subsystem reliability	3.16.2	4.16.2	X	NA
Maintainability	3.16.3	4.16.3	X	NA

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

Transportability	**3.17**	**4.17**		
Air/fixed wing/HSL	3.17.1	4.17.1	X	NA
Ground	3.17.2	4.17.2	X	NA
Marine	3.17.3	4.17.3	X	NA
Rail/Rail Impact	3.17.4	4.17.4	X	NA
Lifting and tiedown	3.17.5	4.17.5	X	NA
Drop shock	3.17.6	4.17.6	X	NA
Environmental	**3.18**	**4.18**		
High temperature	3.18.1	4.18.1	X	NA
Low temperature	3.18.2	4.18.2	X	NA
Altitude	3.18.3	4.18.3	X	NA
Solar radiation	3.18.4	4.18.4		
Rain	3.18.5	4.18.5		
Fungus	3.18.6	4.18.6	X	NA
Salt fog	3.18.7	4.18.7	X	NA
Sand and dust	3.18.8	4.18.8	X	NA
Climatic access	3.18.9	4.18.9	X	NA
Weaponized environment	**3.19**	**4.19**		
CBRN/MOPP/HEMP	3.19.1-3	4.19.1-3	X	NA
Human factors	**3.20**	**4.20**		
IAW 3.12 Table II	3.20	4.20	X	NA

Notes: Recycled, recovered, environmentally preferable, or biobased materials preferred.

Materials which do not meet or exceed the operational and maintenance requirements, or does not promote economically advantageous life cycle costs, or the use of used, rebuilt or remanufactured components, pieces and parts shall be cause for rejection.

1. CoC - certificate of conformance to include data
2. X* - test or inspection to be performed at vendor facility
3. NA - not applicable

**Government may elect to perform any testing of their choosing at their discretion throughout FAT/LAT.

4.2 Materials and construction. Materials and construction methods not meeting the durability/safety/quality/reliability etc. requirements shall be rejected.

4.2.1 Dissimilar metals. ASLMS V3 with dissimilar metals in intimate contact shall be rejected.

4.2.2 Recycled, recovered, environmentally preferable, or biobased materials. Assess/analyze levels of rebuilt/remanufactured/recycled components, pieces and parts in the ASLMS V3.

4.2.3 List of prohibited materials and exceptions. Verification shall be by examination of the bill of materials (BOM). The use of prohibited materials (to include cadmium or hexavalent-chromium etc. used on common fasteners) shall be cause for rejection.

4.2.4 Additive manufacturing. Verify level of additive manufacturing and overall quality improvements as a result.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.3 Design characteristics.

4.3.1 ASLMS V3 container. Nonconformance to any specified requirement, the failure of any test, in accordance with ISO 1496-1 for 1C containers or the presence of one or more defects shall be cause for rejection.

4.3.1.1 ASLMS V3 container storage classes. Failure of theClass I, II, III(P), IV, VII, VIII, IX and MTOE items shall be grounds for rejection.

4.3.1.2 ASLMS V3 container stacking. Failure to stack and successfully pass testing IAW ISO 1496-1 for a Type 1C container shall be cause for rejection.

4.3.1.3 Venting. Failure to equalize pressure or properly vent/minimize HAZMAT or allow intrusion of water, precipitation or dust shall be cause for rejection.

4.3.2 Weight.

4.3.2.1 Tare weight. Each Type of ASLMS V3 shall not exceed the TABLE I weights listed therein or shall be cause for rejection.

4.3.2.2 Max gross weight. Verify that the ASLMS V3 and is capable of a minimum gross weight of at least 37,000 pounds or this shall be cause for rejection.

4.3.3 Safety. Verified by analysis/demonstration to determine the system meets the safety requirements IAW MIL-STD-882 and minimizes/eliminates safety hazards (pinch/crush etc.) based upon design/construction.

4.3.4 Forklift access. Verified through examination and test to determine safe forklift access to interior components using a variety of forklifts, to include all terrain, ranging from 4k to 20k and allowing for movement of both loaded and unloaded configurations. Confirm presence of two sets of fork pockets to accommodate load variation.

4.3.5 Bulk/Parts storage system transport durability. Verify during the design phase through analysis of the technical data and product support analysis. Verify during the test phase through demonstration that system can successfully meet security/mobility requirements without damage while properly restraining product load. Verify durability of modules, ISO doors, drawers, removeable pallets and overall system racks during reliability testing conducted during FAT and assessing transportability, environmental and other related parameters.

4.3.5.1 Cycling life of system components ASLMS V3 shall be capable of the following performance characteristics:

4.3.5.1.1 Cycling life of LHS interface ASLMS V3 shall be capable of cycling 100 times per year utilizing the LHS interface without sustaining system damage/deformation.

4.3.5.1.2 Cycling life of modules Modules shall be capable of cycling 100 times per year over the life cycle of the system without sustaining damage/deformation.

4.3.5.1.3 Cycling life of doors ISO container doors shall be capable of cycling 300 times per year over the life cycle of the system without sustaining damage/deformation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.3.5.1.4 Cycling life of removeable pallets Removeable pallets shall be capable of cycling 300 times per year over the life cycle of the system without sustaining damage/deformation.

4.3.5.1.5 Cycling life of drawers/sliding shelves All drawers/sliding shelves shall be capable of cycling 600 times per year over the life cycle of the system without sustaining damage/deformation.

4.3.6 Parts and bulk storage concept and locking. Verify during the design phase through analysis of the technical data and product support data that modularity and storage elements are built into the ASLMS V3. Verify during the test phase through demonstration that system can successfully meet interchangeability/security/mobility requirements without damage while restraining product load. Demonstrate that modules are easily forkliftable and can rapidly be changed out and locked into the ISO container.

4.3.7 Internal storage devices. Verify during the design phase through analysis of the technical data and product support analysis. Verify during the test phase through demonstration that storage devices are interchangeable, can rapidly be changed out and are content identifiable.

4.3.8 Roof access. Demonstrate that the ASLMS V3 is equipped with a safe means to egress the roof of the system. Ensure climbing provisions lock into place and are fully contained within the standard ISO dimensions when not in use.

4.3.9 Replaceability. Confirm via analyses of bill of materials/technical manual/RPSTL/EDFP etc. that components that are expected to exhibit significant wear/tear are easily replaceable/repairable.

4.4 Standardization. Verify during the design phase through analysis of the technical data and product support analysis. Verify during the test phase through demonstration of interchangeability/commonality of components.

4.4.1 No specialized tools. Verify during the test phase through demonstration of maintenance functions that special tools are not required.

4.5 Workmanship. Examine the ASLMS V3 for proper workmanship, consistency and quality across the product line.

4.5.1 Cleanliness. Examine the ASLMS V3 components are cleaned and free of foreign matter/grease/dust/dirt etc.

4.5.2 Sharp edges. Ensure no sharp/rough edges are present on system/system components.

4.5.3 Rubber/gasketing. Confirm by design/TM analysis that gaskets/seals etc. are replaceable/common. Confirm that there are no gaps/bends/creases or lack of sealing capability. Confirm by testing that no environmental penetration is observed.

4.6 Changes. The contractor shall provide government approval documentation if any changes were made and request approval in advance of making any system changes.

4.7 Welding. Examine the ASLMS V3 welds for proper workmanship.

4.8 Finish, color, and markings.

4.8.1 Deterioration prevention and control. Analyze and examine the ASLMS V3 to ensure a lusterless corrosion resistance finish is applied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.8.2 Corrosion control performance. Demonstrate through testing that no/minimal corrosion is observed.

4.8.3 Treatment and painting. Examine the ASLMS V3 and associated CoC's to ensure CARC is applied and verify adhesion test results.

4.8.3.1 Paint free areas. Examine the ASLMS V3 to ensure the indicated areas are free of paint. Paint on any indicated areas shall constitute non-conformance.

4.8.4 Interior finish and color. Examine the ASLMS V3 to ensure that all finishes/colors IAW MIL-T-704 and SAE-AMS-STD-595 and colors as specified by contract.

4.8.5 Markings. Examine the ASLMS V3 container to ensure all proper markings are applied per ISO 6346, MIL-STD 129, MIL-STD-130 and MIL-STD-1472.

4.8.5.1 Government-owned container identification. Confirm by inspection that the ASLMS V3 container contains proper "USAU" or "USAX" markings per ISO 6346 and examine documentation to ensure the container is registered within the JCMS.

4.8.5.2 Stencils. Examine the ASLMS V3 to ensure all necessary stencils are applied and legible.

4.9 Data plates.

4.9.1 Shipping data plate. Verified by examination proper shipping/data plates are provided IAW MIL-DTL-15024.

4.9.2 Convention for Safe Containers (CSC) plate. Verified by examination CSC plate is permanently affixed to the container and contains the required information.

4.9.3 Manufacturer's data plate. Examine the Manufacturer's data plate is permanently affixed to the container and contains the required information.

4.9.3.1 Manufacturer's data plate location. Examine the Manufacturer's data plate located properly.

4.9.4 Item Unique Identification (IUID) visibility. Verified by:

a. Analysis showing components requiring IUIDs have been identified, properly marked per most recent version of MIL-STD-129, and MIL-STD-130.
b. Demonstration the human and machine-readable labels can in-fact be read, and
c. Examination to show the information contained within the IUID is complete.

4.10 Security. Verify that the ASLMS V3 possess the following security features.

4.10.1 Physical security. Verify by examination that low security padlocks (sometimes referred to as secondary locks – NSN: 5340-00-421-9382 or equivalent) are used. [Low security padlocks shall be Key-retaining and stamped with "US," (or "US Set", if a padlock set). These padlocks provide only minimal resistance to forced or surreptitious entry and shall not be used to secure classified material. (Key-retaining means the key must be captive (unmovable) in the cylinder when the padlock is unlocked.)]. Confirm by inspection/demonstration that necessary escape features are present.

4.10.2 High security storage. Verify by examination that double lock security measures are used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.11 Leveling. Verify by examination that leveling features are present and can be accomplished by personnel in rifleman encumbrance.

4.12 Internal storage configurations based on ASLMS V3 Types. Confirm by verification that storage configuration for each type of ASLMS V3 are IAW with Table II contained in 3.12.

4.12.1 Internal load stability. Verify by the examination and testing that internal storage/retention provisions properly restrain cargo and prevent damage during all transportation modes.

4.13 Parts storage features. Verify through testing that parts storage drawers, modules, pallets, shelving, rack systems etc. remain fully operational/functional throughout all environmental, mobility and post mobility operations.

4.13.1 Internal parts modules. Verify that ASLMS V3 intrinsic design contain modular system components /features. Verify that modules are easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs.

4.13.2 Side-opening bulk storage access doors. Verify that the ASLMS V3 contains side-opening parts storage ISO container access on a minimum of two opposing sides to facilitate easy removal of parts storage modules/racks/drawers etc.

4.13.3 Parts module drawers. Verify that the ASLMS V3 modules contain drawers that are robustly designed to meet rigors of transport and furnished with dividers/separators to further customize each drawer.

4.13.4 Parts sliding/adjustable shelves. Verify that the ASLMS V3 is equipped with sliding shelves and adjustable shelving features.

4.13.5 Parts racks. Verify that the ASLMS V3 is equipped with racks supporting parts storage requirements.

4.13.6 Parts internal storage. Confirm through analyses/inspection storage percentages and minimized unusable space. Confirm unrestricted cargo access through testing/verification.

4.14 Bulk storage features.

4.14.1 Bulk storage modules. Confirm by analysis/inspection that the ASLMS V3 intrinsic design incorporates modular system components /features. Confirm that bulk modules are easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs.

4.14.2 Side-opening bulk storage access doors. Confirm by analysis/inspection that the ASLMS V3 contains side-opening bulk storage access on a minimum of two opposing sides and provides necessary storage for bulk/HAZMAT items.

4.14.3 Removeable pallets/rack system. Confirm by analysis/inspection that the ASLMS V3 is equipped with removeable pallets that interface with a racking system. Confirm that removeable pallets are easy to place, easy to lock into the ISO structure and allow for rapid changeout to support specific mission needs. Confirm by analysis/inspection that rack system are robustly designed to mitigate damage potential.

4.14.4 Bulk module drawers. Confirm that ASLMS V3 bulk modules contain drawers that are robustly designed to meet rigors of transport and furnished with dividers/separators to further customize each drawer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.14.5 Bulk sliding/adjustable shelves. Confirm by analysis/inspection that the ASLMS V3 is equipped with sliding shelves and adjustable shelving features.

4.14.6 Adjustable rack storage. Demonstrate that bulk storage provisions have adjustable rack and storage systems to maximize usable space/customization.

4.14.7 Storage locations. Confirm by analyses/inspection that bulk storage locations provide sufficient storage area and are affixed with proper labelling/identification. Verify that HAZMAT storage and ventilation system provide necessary capabilities.

4.15 General system performance.

4.15.1 Capabilities. Demonstrate the ASLMS V3 system can operate as outlined in the operational mode summary/mission profile (OMS/MP) via analysis/testing/demonstration.

4.15.2 Deployability. Analyze deployability based on test performance for all transportability modes

4.15.2.1 Stacking of containers. Verify by testing that the ASLMS V3 is capable of stacking requirements per ISO 1496-1 for a 1C container and submit supporting CoC.

4.15.2.2 Container organization. Verify that majority of items in each container can be accessible and removable without prior removal of other items.

4.15.2.3 Container consolidation. Analyze to determine if components and bulk materials can be consolidated together in reusable crates. Standard Practice for Military Packaging. Verify that the crates contain only components of like description. Also confirm that, when practical, each kit is packed in a single crate or securely palletized.

4.16 Reliability and maintainability.

4.16.1 Set up and take down. Verify by testing, 4 personnel can set up/take down the ASLMS V3 in the allotted time and with equipment as specified.

4.16.2 Subsystem reliability. Verify that the ASLMS V3 LHS interface, modules, doors, pallets, shelving, drawers, sliding shelves etc. properly operate following a 3.5 month representative cycling interval. Cycling conducted throughout all transportability, environmental, and other related system evaluations shall be the basis for this data.

4.16.2.1 LHS interface reliability. Verify that the ASLMS V3 is capable of at least 29 HEMTT LHS lift/drop cycles.

4.16.2.2 Module reliability. Verify ASLMS V3 ability to successfully remove/replace modules for a total of at least 29 install/uninstall cycles.

4.16.2.3 Door reliability. Verify ASLMS V3 ability to successfully cycle doors for at least 87 open/close cycles.

4.16.2.4 Removeable pallet reliability. Verify ASLMS V3 ability to successfully conduct at least 87 remove/reinstall cycles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.16.2.5 Drawer/sliding shelve reliability. Verify ASLMS V3 ability to successfully cycle each drawer/sliding shelf at least six time for each test inspection interval for a total of at least 174 open/close cycles.

4.16.3 Maintainability.

4.16.3.1 Maintenance EUMD. Verify that the ASLMS V3 does not exceed 1 hour for all Essential Unscheduled Maintenance Demands (EUMD).

4.16.3.1.1 Mean time to repair (MeanTTR). Verify that the ASLMS V3 MeanTTR is 30 minutes.

4.16.3.1.2 Maximum time to repair (MaxTTR). Verify that the ASLMS V3 MaxTTR does not exceed 1.5 hours for 90 percent of all EUMD (T=O).

4.17 Transportability.

4.17.1 Air transportability.

4.17.1.1 Airlift certificate for fixed wing aircraft. All ASLMS V3 Types shall pass all requisite analyses/testing to achieve an unrestricted Airlift Certificate (see 1.2) of container. Any certificate less then unrestricted constitutes failure.

4.17.1.2 Helicopter sling load (HSL). Verify by analysis/demonstration, the ASLMS V3 and container, when fully loaded for transport, can be externally transportable by CH-47 in accordance with MIL STD 209 and MIL-STD-913. Inability to pass testing constitutes failure.

4.17.2 Ground transportability. Verify that the ASLMS V3 is furnished with an integral HEMTT LHS and PLS compatible handling system that can safely and efficiently interface and function properly with the HEMTT LHS, the Palletized Loading System (PLS) vehicle and the PLS-Tralier (PLS-T) in all operational and mobility scenarios. ASLMS V3 shall successfully pass all transportability evaluations. Any packed component breaking free or showing any sign of permanent deformation or reduction of performance, or generation of any safety hazards as a result of the impact test series shall constitute failure. The contractor shall provide all test documentation and relevant CoCs.

4.17.2.1 Highway transportability. Verify that the ASLMS V3 when packed for transport on military or commercial vehicles, shall be successful and capable of unrestricted highway transport in accordance with MIL-STD-1366 for all U.S. states and North Atlantic Treaty Organization (NATO) member countries. Inability to obtain unrestricted highway transport constitutes failure.

4.17.2.2 Ground mobility. Verify through testing that the ASLMS V3, when transported, shall have mobility not less than as described in Table III when transported via prime mover. Failure to pass testing constitutes failure.

4.17.3 Marine transportability. The contractor shall verify by successful testing/demonstration and provide a CoC upon passing test results. Failure to test/demonstrate this constitutes failure.

4.17.4 Rail transportability. The contractor shall verify by successful testing/demonstration and provide a CoC upon passing test results. Failure to meet all rail transportability requirements constitutes failure.

4.17.4.1 Rail impact. Confirm by testing that the ASLMS V3 can successfully pass MIL-STD-810 H, Method 526.2 (Rail Impact) evaluation when mounted on a rail car in its packed shipment configuration and stacked only one level high. Any packed component breaking free or showing any sign of permanent

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

deformation, reduction of performance, or generation of any safety hazards as a result of the impact test series shall constitute failure. The contractor shall provide all test documentation. Inability to pass Rail Impact evaluation constitutes failure.

4.17.5 Lifting and tiedown provisions. ASLMS V3 shall successfully perform IAW MIL-STD-209 lifting/tiedown assessment. Any packed component breaking free or showing any sign of permanent deformation or reduction of performance or generation of any safety hazard as a result of the impact test series shall constitute failure. The contractor shall provide all test documentation. Inability to properly restrain with lifting/tiedown provisions constitutes failure.

4.17.6 Drop shock test. The ASLMS V3, fully loaded for transport, shall be subjected to Drop Shock Testing per ASTM 1925-10 Specification for Engineering and Design Criteria for Rigid Wall Relocatable Structures Section 10.29 (All RWRS Without Skids) — for both flat and rotational drops. There shall be no permanent deformation, buckling, delamination, sealer separation, or structural failures of any part of the RWRS after each test, and the doors and covers shall open and close to their full extent without binding.

4.18 Environmental.

4.18.1 High temperature (storage and operation). The ASLMS V3 system shall be verified by examination and tested in accordance with the following:

a. The ASLMS V3 shall be consecutively tested IAW Procedure I (Storage) and then Procedure II (Operation) of MIL-STD-810 H, Method 501.7.
b. During Procedure I (Storage), the ASLMS V3 components shall be in their storage configuration during testing.
c. The test temperatures shall be as specified in 3.18.1.
d. During Procedure I (Storage) the test duration shall be seven (7) 24-hour cycles.
e. During Procedure II (Operation) the test shall be of constant temperature exposure and the components shall be operated for a minimum of 4 hours.
f. Failure of the components to operate as specified, or any damage or degradation of performance as a result of exposure to the temperature extremes, shall result in failure of this test.

4.18.2 Low temperature (storage and operation). The ASLMS V3 system shall be verified by examination and test in accordance with the following:

a. The ASLMS V3 shall be consecutively tested IAW Procedure I (Storage), Procedure II (Operation) and Procedure III (Manipulation) of MIL-STD-810 H, Method 502.7.
b. During Procedure I (Storage), the ASLMS V3 components shall be in their storage configuration during testing.
c. For Procedure II (Operation) and Procedure III (Manipulation), the components and container shall be in their operational configurations.
d. The test temperatures shall be as specified in 3.18.2.
e. During Procedure I (Storage) the test duration shall be seven (7) 24-hour cycles.
f. During Procedure II (Operation) and Procedure III (Manipulation), the test shall be of constant temperature exposure and the components shall be operated for a minimum of 4 hours. Manipulation shall include all set-up and installation tasks of components with cold weather gear and gloves used by the personnel.
g. Failure of the components to operate as specified, or any damage or degradation of performance as a result of exposure to the temperature extremes, shall result in failure of this test.

4.18.3 Altitude. The ASLMS V3 system, in its storage configuration, shall be tested IAW

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

MIL-STD-810 H, Method 500.6, Procedure I (Storage/Air Transport). Procedure I, shall be conducted on each significantly different pack configuration for a 1-hour storage period at an altitude of not less than 15,000 feet above sea level. Any damage as a result of exposure to the altitude extremes, shall result in failure of this test.

4.18.4 Solar radiation. Verify by test and examination as follows:

a. The ASLMS V3 system shall be tested IAW MIL-STD-810 H, Method 505.7, Procedure I Cycling using up to 355 British thermal units per square foot per hour (Btu/ft^2) of solar radiation.
b. Test duration shall be not less than 5 cycles of 24 hours each.
c. Operate the ASLMS V3 doors, draws, and bulk storage containers for a minimum of 10 minutes during the peak response temperature of the final 24-hour cycle.
d. Upon completion of this test the ASLMS V3 shall be examined for damage and the doors, draws, and storage containers shall operate normally for not less than 30 minutes.
e. Failure of the ASLMS V3 to operate as specified shall result in failure of this test.

4.18.5 Rain. Verify by test and examination as follows:

a. The ASLMS V3 container and each component (may be done simultaneously), shall be tested IAW MIL-STD-810 H, Method 506.6, Procedure I (Rain and Blowing Rain). The water distribution device shall deliver water for a 30-minute period per side. A rainfall rate of up to 4 inch per hour impinging on the system at angles from the vertical up to 45 degrees shall be used.
b. Test item temperature shall be a minimum of 20 °F higher than the rain temperature at the beginning of each exposure period.
c. At the conclusion of this test, the ASLMS V3 doors, draws, and bulk storage containers shall be operated for not less than 30 minutes.
d. Failure of the ASLMS V3 to operate as specified shall result in failure of this test.
e. Surfaces shall shed water and moisture regardless of incline. No pooling of water in or on components shall be evident.
f. If an intrusion/door berm is present, no water/moisture shall pass beyond this point or this constitutes a failure.

4.18.6 Fungus. Verify by test and examination as follows:

a. Two separate ASLMS V3 container doors with seals, each type of securing device, each type of drawer/bulk storage container and each type of packed component (test specimens), shall be tested IAW MIL-STD-810 H, Method 508.8 (Fungus). One set of test specimens inoculated with Fungus Sources Identification Numbers - USDA QM 380, the other set of test specimens USDA QM 474 for a period of not less than 85.
b. Test item temperature shall be test ambient temperatures of not less than 70 °F and not greater than 104 °F and ambient relative humidity of not less than 70%.
c. Evidence of pitting, delamination, intrusion into interior of packaged components, failure of seals, loss of securing device material (>5%) or impairment in the function of components shall constitute a failure of this test.

4.18.7 Salt fog. Verify by test and examination as follows:

a. The ASLMS V3 shall be tested IAW MIL-STD-810 H, Method 509.7 (Salt Fog).
b. The ASLMS V3 shall subjected to salt fog for four (4) 24-hour periods (two wet and two dry).
c. Upon completion of the test, the ASLMS V3 shall be examined for corrosion of any metal parts (red or white rust), or impairment of function of components.
d. Any evidence of corrosion or impairment in the function of components shall result in failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

4.18.8 Sand and dust. Verify by test and examination as follows:

a. The ASLMS V3 container shall be tested IAW MIL-STD-810 H, Method 510.7, Procedure II (Blowing Sand) with a combination of particle sizes of <150 µm (50% ±5%) and 150 to 850 µm (50% ±5%) in diameter.
b. The ASLMS V3 container shall be placed on the ground and each side exposed to blowing sand/dust for a minimum of not less than 6 hours (repeat for each side not including roof).
c. At the conclusion of this test, and prior to step "d." operate moving parts for a minimum of hour.
d. The ASLMS V3 container shall be inspected for:

    1) Abrasion and erosion of surfaces exposing bare metal shall constitute a failure.
    2) Penetration of door seals shall constitute a failure.
    3) Obstruction/clogging of openings (vents).
    4) Physical interference with mating parts. Degrading performance, effectiveness, reliability, and maintainability shall constitute a failure.
    5) Fouling/interference of moving parts. Degrading performance, effectiveness, reliability, and maintainability shall constitute a failure.
    6) Wear (increased fretting due to imbedding between mating surfaces). Wear >5% shall constitute a failure.

4.19 Weaponized environmental environment. Confirm the ASLMS V3's survivability in storage mode and post exposure operation under the following conditions.

4.19.1 Chemical, biological, radiological, and nuclear (CBRN) environment. Analyze/verify operational characteristics in a CBRN environment of a closed ASLMS V3 container in accordance with FM-3-11. Determine if the ASLMS V3 container is capable of being successfully decontaminated or it shall be considered a test failure. Any intrusion of environmental precipitation/sand/dust shall provide evidence that system is not adequately sealed for CBRN exposure in the closed configuration

4.19.2 Mission-oriented protective posture (MOPP) IV access. Confirm operability of ASLMS V3 through demonstration from the 5th percentile female through 95 percentile male wearing MOPP IV and in the rifleman encumbrance. Inability to access a container and its contents by any one of the selected shall be considered a failure.

4.19.3 Cold climate access. Confirm operability of ASLMS V3 through demonstration from the 5th percentile female through 95 percentile male wearing artic clothing and in the rifleman encumbrance. Inability to access a container and its contents by any one of the selected shall be considered a failure.

4.20 Human factors engineering (HFE). Confirm operability of ASLMS V3 through demonstration by the Military Operational Specialty (MOS) personnel 92A while: in garrison, driver accommodated (T) Rifleman accommodated (O), wearing gloves, arctic mittens, and equipped with Mission Orientated Protective Posture (MOPP) IV gear shall constitute failure. Inability of complying with MIL-STD-1472 and MIL-STD-1474 shall constitute failure. Confirm maintainability of ASLMS V3 by 91J personnel.

5 PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department or Defense Agency's

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

automated packaging files, CD-ROM products, or by contacting the responsible packaging activity at DLA https://www.dla.mil/Information-Operations/Services/Applications/WebFLIS/ .

6 NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The ASLMS V3 is intended to meet unit SSA/ASL needs. These requirements are military unique since the commercial market does not meet the military requirements for CBRN environment survivability, or have the durability requirements and mobility for tactical movement usage.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.0)
c. If first article is required (see 3.1).
d. If painting procedure and color is other than specified (see 3.11.1).
e. Information to be shown on identification plates (see 3.10).
f. Packaging required (see 5.1).
g. If 100K WSDS should be ordered with or without the Split Ops Kit (see 3.4.6).
h. Color of collapsible storage tanks (see 3.4.1.2)
i. Color of TRICONs (see 3.5)

6.3 First articles. When a first article inspection is required, the item(s) should be a first article production unit(s). The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article examination results, and disposition of the first article(s).

6.4 Definitions.

a. Acceptance inspection & test (AI&T) – Inspections and tests performed by Quality Assurance Representatives (QAR) prior to government acceptance of system delivery.
b. Ambient temperature - is the average air temperature surrounding something whether inside or outside.

6.5 Subject Terms/Key Words.

ALSMSV3
CARC - Chemical Agent Resistant Coating
CBRN - Chemical, biological, radiological, and nuclear environment
CoC - Certificate of Conformance
CSC – Convention for Safe Containers
EUMD - Essential Unscheduled Maintenance Demands
FAT – First Article Testing
HEMP - High altitude electromagnetic pulse
HEMTT LHS - Heavy Expanded Mobility Tactical Truck Load Handling System
HFE - Human factors engineering
IUID - Item Unique Identification
Laden Weight - System's fully loaded weight
MaxTTR - Maximum time to repair

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.

MeanTTR - Mean time to repair
MOPP - Mission-oriented protective posture
NATO STANAG - NATO Standardization Agreement
NSN - National Stock Number
ODS – Ozone Depleting Substances
PLS - Palletized Load System
PLS-T - Palletized Load System Trailer
QASP - Quality Assurance Surveillance Plan
RWRS - Rigid Wall Relocatable Structures
SAE – Society of Automotive Engineers
SSA - Supply Support Activity
Tare Weight – System's empty weight

Custodian:
Army – GL

Preparing activity:
Army - GL
Project # 8145-2022-001

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:40Z
Check the source to verify that this is the current version before use.