FED. SUP CLASS
5110



MANUFACTURER'S NAME OR TRADE MARK AND MS PART NO. SHALL BE PERMANENTLY MARKED ON EITHER RING.

MS PART NO. (c)	FINISH	BORE B		D OUTSIDE DIA.		WIDTH V		MAX CORNER RADIUS	(d) B RADIUS	CAPACITY (a) Co	CAPACITY (b) C	LIMIT CONTINUOUS RPM (c)
		M. M.	INCH	M. M.	INCH	M. M.	INCH					
MS17107-1		10	.3937	30	1.1811	9	.3543	.030	.025	620	805	10,000
MS17107-2		12	.4724	32	1.2598	10	.3937	.030	.025	535	1050	10,000
MS17107-3		15	.5906	35	1.3780	11	.4331	.030	.025	620	1180	10,000
MS17107-4		17	.6693	40	1.5748	12	.4724	.080	.025	765	1250	10,000
MS17107-5		20	.7874	47	1.8504	14	.5512	.060	.030	1370	2210	10,000
MS17107-6		25	.9843	52	2.0472	15	.5906	.060	.030	1560	2470	10,000
MS17107-7		30	1.1811	62	2.4409	16	.6299	.060	.030	2730	3350	10,000
MS17107-8		35	1.3780	72	2.8346	17	.6693	.060	.030	3050	3450	10,000

CLEARANCES FOR CLEARING IN .0001 INCH

INNER RING								OUTER RING							
BORE DIA M. M.		d		V	PARALLELISM OF SIDES	SIDE FACE -OUT WITH BORE	GROOVE PARALLELISM WITH SIDE	RADIAL RUNOUT MAX.	D OUTSIDE DIA M. M.		O. D. TOL		V	PARALLELISM OF SIDES	O.D. SQUARE WITH SIDE RUNOUT	GROOVE PARALLELISM WITH SIDE	RADIAL RUNOUT MAX.
OVER	INCL	MIN	MAX						OVER	INCL	MIN	MAX					
0	50	-9	+0	+0 -50	2	3	3	2	30	50	-2	+0	+0 -50	2	3	3	2
									50	80	-3	+0				4	3

RADIAL INTERNAL CLEARANCE (NOM. LIMITS)	
BORE (B) M. M.	RADIAL PLAY .0001 IN.
10 - 17	5 - 9
18 - 29	6 - 10
30 - 50	7 - 12

(a) BASIC STATIC LOAD RATING IN POUNDS = THAT STATIC LOAD WHICH CORRESPONDS TO A TOTAL PERMANENT DEFORMATION OF BALL AND RACE AT THE MOST HEAVILY LOADED CONTACT OF 0.0001 OF THE BALL DIAMETER.

(b) RADIAL DYNAMIC LOAD IN POUNDS AT 33-1/3 RPM YIELDS 10^6 REVOLUTIONS B10 LIFE; AT OTHER SPEEDS INVERSE CUBE ROOT OF SPEED RATIO.

(c) RATED LOADS AND LIMIT RPM ARE BASED UPON GREASE LUBRICATION AND UPON BEARING OPERATING TEMPERATURE NOT EXCEEDING 325°F.

(d) B = MAXIMUM FILLET RADIUS FOR BEARING, OR OF SHAFT WHICH BEARING RADIUS WILL CLEAR.

(e) MS PART NUMBER -1 THRU -4 SHALL HAVE PASSIVATED STEEL RETAINERS. MS PART NUMBERS -5 THRU -8 SHALL HAVE PHENOLIC RETAINERS.

MATERIALS: RINGS STEEL, AISI 52100 PER QQ-S-666. BALLS STEEL, AISI 1020 PER QQ-S-666.

BREAK ALL SHARP EDGES .005/.005 UNLESS OTHERWISE SPECIFIED.

LUBRICATION: PACK 30/40 PERCENT WITH GREASE SPECIFICATION MIL-G-81322. (A)

NOTE: THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

APPROVED 23 October 1999 REVISED (A) 25 Apr 90

THE ACTIVITIES RESPONSIBLE FOR THE PREPARATION OF THIS DOCUMENT HAVE ELECTED NOT TO USE METRIC UNITS IN THIS DOCUMENT. THE INCH-POUND VALUES ARE THE GOVERNING STANDARD.

P.A. AIR FORCE-11 (A)	TITLE	MILITARY STANDARD
Other Cust ARMY- AT Navy- AS	BEARING, BALL, ANNULAR, PREMIUM PCD AIRCRAFT ENGINE-GEARBOX, TYPE I	MS17107
PROCUREMENT SPECIFICATION MIL-B-22277	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (Coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:03Z
Check the source to verify that this is the current version before use.