MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

BATTERIES

TO ALL HOLDERS OF MIL-STD-35-39(MI)

1. The following pages of MIL-STD-35-39(MI) have been revised and supersede the pages listed:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	31 December 1974	v	18 June 1974
vi	31 December 1974	vi	18 June 1974
vii	31 December 1974	vii	18 June 1974
viii	31 December 1974	viii and ix	18 June 1974
3	31 December 1974	3	18 June 1974
4	31 December 1974	4	18 June 1974
5	31 December 1974	5	18 June 1974
6	31 December 1974	6	18 June 1974
7	31 December 1974	7	18 June 1974
8	31 December 1974	8 through 24	18 June 1974
25	31 December 1974	25 and 26	18 June 1974
69	18 June 1974	Reprinted without change	
70	31 December 1974	70 through 76	18 June 1974
77	31 December 1974	77	18 June 1974
78	18 June 1974	Reprinted without change	
155	31 December 1974	155 through 166	18 June 1974
167	31 December 1974	167 and 168	18 June 1974
171	31 December 1974	171	18 June 1974
172	31 December 1974	172 through 188	18 June 1974
215	31 December 1974	215 through 219	18 June 1974

2. The following pages have been added.

NEW PAGE	DATE
4a and 4b	31 December 1974

3. Retain this notice page and insert before the Table of Contents.

4. Holders of MIL-STD-35-39(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-A077

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
1.0	Batteries	1
1.1	Specification Title Index	3
1.2	Specification Requirements Instructions	5
1.2.1	General	5
1.2.2	Approved Item Name Code	6
1.2.3	Figure Number	6
1.2.4	Dimensions	6
1.2.5	Tabulation	6
1.2.6	Deleted	
1.2.7	Deleted	
1.2.8	Deleted	
1.2.9	Applicable Documents	8
	NOTE: Paragraphs 1.2.10 through 1.2.21 have been deleted.	
1.2.22	Design and Construction	25
1.2.23	Open Circuit Voltage	28
1.2.24	Closed Circuit Voltage	29
1.2.25	Capacity Discharge	29
1.2.26	Filled Discharge Capacity	30
1.2.27	Full Charge Capacity	31
1.2.28	Full Capacity Discharge	32
1.2.29	Overcharge Cycle	33

Supersedes page v of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.30	Retention of Charge	34
1.2.31	High Rate Discharge	34
1.2.32	Life Cycle Capacity	35
1.2.33	Internal Dry Insulation Resistance	36
1.2.34	Electrical Breakdown of Containers	37
1.2.35	Electrolyte Leakage	37
1.2.36	Sealing Compound Test	38
1.2.37	Waterproofing of Jacket	39
1.2.38	Bulge Resistance	40
1.2.39	Impact Resistance	41
1.2.40	Drop Test	42
1.2.41	Mechanical Shock	42
1.2.42	Internal Air Pressure	44
1.2.43	Explosive Atmosphere	45
1.2.44	Low Temperature Performance	45
1.2.45	Altitude	46
1.2.46	Sunshine	47
1.2.47	Rain	48
1.2.48	High Temperature	49
1.2.49	Low Temperature	50
1.2.50	Alkali Absorption Resistance	50

Supersedes page vi of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.51	Acid Absorption Resistance	51
1.2.52	Hydrogen Evolution (Gassing)	52
1.2.53	Magnetic Effect	53
1.2.54	Terminal Strength	54
1.2.55	Potassium Carbonate	55
1.2.56	Temperature Rise	56
1.2.57	Inversion	57
1.2.58	Heater Performance (Internally Heated Batteries)	58
1.2.59	Heater Endurance (Internally Heated Batteries)	59
1.2.60	Thermoswitch Cycling (Internally Heated Batteries)	60
1.2.61	Thermal Shock	61
1.2.62	Fungus	62
1.2.63	Salt Spray	63
1.2.64	Immersion (Leakage)	64
1.2.65	Insulation Resistance	65
1.2.66	Random Vibration	66
1.2.67	High Frequency Vibration	67
1.2.68	Low Frequency Vibration	68
1.2.69	Shock (High Impact)	69

Supersedes page vii of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
	Specification Requirements	77
	Tables	167
1.3	Configuration and Drawings	189
1.3.1	Figure Titles vs Figure Numbers	191
1.3.2	Legend Index	193
	Figures 302-01-1 through 302-05-1	197-213

Supersedes pages viii and ix of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.1

SPECIFICATION TITLE INDEX

Specification Title Code	Specification Title	Applicable Document
302001	Batteries, Primary, Dry	MIL-B-18 MIL-B-13136 MIL-B-25356 MIL-B-49030 MIL-B-49041 MIL-B-55252 MIL-B-55679 W-B-101
302002	Batteries, Primary, Water Activated	MIL-B-10154 MIL-B-17402 MIL-B-55290 MIL-B-83771
302006	Batteries, Primary, Wet	MIL-B-17482 MIL-B-23394 MIL-B-55150
302004	Batteries, Storage, Acid	MIL-B-6428 MIL-B-6429 MIL-B-9225 MIL-B-11188 MIL-B-15072 MIL-B-24200 MIL-B-55166 MIL-B-62141 MIL-B-83769 MS-16974 MS-35000 MS-35002 MS-35004 MS-35005 MS-52152 MS-75047 MS-90448 MS-90901 MS-90903

Supersedes page 3 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.1

SPECIFICATION TITLE INDEX (CONT)

Specification Title Code	Specification Title	Applicable Document
		MS-90904
		MS-91310
		MS-91311
		MS-91314
		MS-91315
		MS-91318
		MS-91319
		MS-91320
		MS-91321
		MS-91322
		MS-91323
		MS-91324
		MS-91325
		MS-91326
		MS-91327
		MS-50051
302005	Batteries, Storage, Acid/ Alkaline	MIL-B-8565
		MS-3491
		MS-15367
		MS-18045
		MS-18093
		MS-90365
		MS-90377
		MS-90378
		MS-90379
302003	Batteries, Storage, Alkaline Nickel-Cadmium	MIL-B-11453
		MIL-B-21442
		MIL-B-23272
		MIL-B-26026
		MIL-B-26220
		MIL-B-55118
		MIL-B-55130
		MIL-B-55363
		MIL-B-83424
		MS-3319
		MS-3337
		MS-3346
		MS-3375
		MS-3489
		MS-17334

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.1

SPECIFICATION TITLE INDEX (CONT)

Specification Title	Specification Title	Applicable Document
		MS-24496
		MS-24497
		MS-24498
		MS-24511
		MS-27546
		MS-53073
		MS-53074
		MS-75026
		MS-75030
		MS-75031
		MS-75032
		MS-75033
		MS-75034
		MS-75035
		MS-75039
		MS-75048
		MS-90447
	Nickel-Iron	MIL-B-52730
		W-B-137
	Silver-Zinc	MIL-B-11814
		MIL-B-18855
		MIL-B-24207
		MIL-B-24353
		MIL-B-24409
		MIL-B-81502
		MIL-B-82117
		MIL-B-83764
		MS-3487
		MS-18122
		MS-90449

New Page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these instructions is to establish the procedures to be followed, and the format to be used, for submission of requirements to obtain a computer generated procurement document.

The requester will find it impossible to complete an SRS using only this dash numbered part of MIL-STD-35. Information which is standard for all generic families has been included in the master document at the issuance of MIL-STD-35C. This information is not repeated for each dash numbered part. The following list contains the subjects which are pertinent to every family unless otherwise excepted.

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-Item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables A through S

Source: https://assist.dla.mil -- Downloaded: 2024-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for a battery, to be entered on the SRS with Code 1007, is selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Battery, Dry	00012
Battery, Storage	00013
Battery, Water Activated	00725
Unapproved Name	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3. Where it may be necessary to show more than one figure to describe an item, the figure numbers must be in correct sequence and as in the following example: "1ØØ93Ø2-Ø2-1 AND 3Ø2-Ø4-1#".

1.2.4 Dimensions

MIL-STD-35 must be used in conjunction with this dash numbered part to completely delineate the dimensions for a battery.

The figures and corresponding legends, representing different configurations of batteries, are located in the rear of this document. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009. The figure legends in this document (AA, AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimensioning batteries are in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation are found in MIL-STD-35. Candidates for tabulation for this part are the dimensional codes shown in Table A of MIL-STD-35 and the following:

Supersedes page 6 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026Ø10-23T20:56Z
Check the source to verify that this is the current version before use.

TABULATION CANDIDATES FOR BATTERIES

Characteristic Code	Parameter
	Rated Voltage
1562	Nominal
1564	Minimum
1566	Maximum
	Battery Capacity
1568	Ampere-Hours
1570	Hour-Rate
	Socket Configuration
1608	Style (Number)
1610	Figure (Number)
1612	Number of Cells
	Energy Density
1616	Watt-Hours per Cubic Inch
1618	Watt-Hours per Pound
1630, 1632, 1634 or 1636	Charge Condition for Shipment
	Shelf Life
1662	Days
1664	Months
1666	Years
	Weight
1700	Grams
1702	Ounces
1704	Pounds

Supersedes page 7 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

NOTE: Paragraphs 1.2.6, 1.2.7, and 1.2.8 have been deleted.

1.2.9 Applicable Documents

In addition to the documents contained in the Applicable Document List of MIL-STD-35, the documents that follow shall be entered on the SRS with appropriate codes from Table B of MIL-STD-35:

Documents	Codes or Other Conditions
MIL-STD-130	Mandatory
MIL-STD-202	When a characteristic code specifying a test method in MIL-STD-202 is entered on the SRS.
MIL-STD-810	When a characteristic code specifying a test method in MIL-STD-810 is entered on the SRS.
FED-STD-601	2104 (Bulge Resistance) or 2134 (Inpact Resistance)
Document from MSE Title Index	1006 and whenever a test or requirement specifies a document from the MSE Title Index

NOTE: Paragraphs 1.2.10 through 1.2.21 have been deleted.

Supersedes pages 8 through 24 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the currentversion before use.

1.2.22 Design and Construction

To specify the nominal rated voltage of the battery, enter Code 1562 on the SRS followed by the value in volts. To specify a range for the rated voltage, enter Codes 1564 and 1566 on the SRS followed by the minimum and the maximum values, respectively, in volts.

To specify the battery capacity, enter Code 1568 on the SRS followed by the value in ampere-hours. If Code 1568 is used, it is mandatory to enter Code 1570 on the SRS followed by the hour rate in hours.

To specify the operating temperature range, it is mandatory to enter Codes 1580 and 1582 on the SRS followed by the minimum and the maximum values, respectively, in degrees C.

To specify the storage temperature range, it is mandatory to enter Codes 1584 and 1586 on the SRS followed by the minimum and the maximum values, respectively, in degrees C.

To specify the battery type, class, grade, style and/or size (dry cell only), enter Code 1590, 1592, 1594, 1596 and/or 1598, respectively, on the SRS followed by the appropriate value.

To specify the terminal configuration in accordance with Table III, the Terminal Configuration Table, enter the appropriate codes from the appropriate columns of Table III on the SRS followed with the desired data to fill these columns. The fills (desired data) for each of these columns should be limited as follows:

Marking - 28 spaces
Terminal Style Figure - 9 spaces
Terminal Style - 5 spaces

If more than the allotted spaces are filled-in, the computer will print the information on additional lines in the allotted column.

An example of the use of codes from these columns of Table III is as follows:

CHAR CODE 13 14 15 16	VALUE 20 25 30 35 40
4001	1#
4002	30 2-04-2#
4003	9#

Supersedes pages 25 and 26 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

followed by an "X". To specify any suitable mounting method or normal mounting method, enter Code 1478 or 1479, respectively, on the SRS followed by an "X". To specify mounting in accordance with an existing document, enter Code 1480 on the SRS followed by the number of the document. To specify that the battery is to be discharged, it is mandatory to enter Codes 1481 and 1482 on the SRS followed by the current in amperes and the duration in hours, respectively. To specify the statement shown with Code 1483 in the SRL, enter Code 1483 on the SRS followed by an "X".

If the requirement shown in the document referenced by using Code 1006 is sufficient, enter Code 1484 on the SRS followed by an "X".

If it is desired to modify the requirement shown in the document referenced by using Code 1006, enter Code 1485 on the SRS and complete the sentence shown with Code 1485 in the SRL, using 189 characters or less including punctuation and spaces.

To specify one or both of the requirements shown with Code 1486 and 1487 in the SRL, enter the appropriate code(s) on the SRS followed by an "X". To specify the battery capacity, enter Code 1488 on the SRS followed by the minimum value in ampere-hours. To specify the open circuit voltage, enter Code 1489 on the SRS followed by the nominal value in volts. To specify the closed circuit voltage, enter Code 1490 on the SRS followed by the nominal value in volts.

1.2.69 Shock (High Impact)

If the test procedure shown in the document referenced by using Code 1006 is sufficient, enter Code 1494 on the SRS followed by an "X".

If it is desired to take exception to the test procedure shown in the document referenced by using Code 1006, enter Code 1495 on the SRS and complete the sentence shown with Code 1495 in the SRL, using 189 characters or less including punctuation and spaces.

To specify that testing shall be in accordance with MIL-STD-202, Method 207, enter Code 1496 on the SRS followed by an "X". If Code 1496 is used, enter MIL-STD-202 on the SRS with an appropriate code from Appendix B (see 1.2.9). If Code 1496 is used, it is possible to specify additional test conditions. To specify the mounting fixture in accordance with one of the figures shown with Method 207 in MIL-STD-202, enter Code 1497 on the SRS followed by the figure number. To specify any suitable

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

mounting fixture, enter Code 1498 on the SRS followed by an "X". To specify the electrical load, enter Code 1499 on the SRS followed by the value in ohms. To specify external resilient mountings, enter Code 1500 or Code 1501 on the SRS followed by, respectively, the federal stock number or the commercial designation of the mounting. To specify the statement shown with Code 1502 in the SRL, enter Code 1502 on the SRS followed by an "X".

If the requirement shown in the document referenced with Code 1006 is sufficient, enter Code 1504 on the SRS followed by an "X".

If it is desired to modify the requirement shown in the document referenced by with Code 1006, enter Code 1505 on the SRS and complete the sentence shown with Code 1505 in the SRL, using 189 characters or less including punctuation and spaces.

To specify that during testing the cell shall deliver constant current, enter Code 1506 on the SRS followed by the hour rate. To specify measurement of the closed circuit voltage at intervals between shock blows, enter Code 1507 on the SRS followed by the value in minutes. To specify the voltage to which each cell is to be discharged, enter Code 1508 on the SRS followed by the value in volts. To specify the requirement shown with Code 1509 in the SRL, enter Code 1509 on the SRS followed by an "X".

Custodians:
Army-MI

User Activity:
Army-MU

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

Preparing Activity:
Army-MI
Project EDS-A077

Supersedes pages 70 through 76 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
	NOTE: This note applies to all contractors of the U.S. Army Materiel Command (AMC), major subordinate commands, AMC Project Product managers, separate installations and activities reporting to Headquarters AMC. AMCR 700-83 will be complied with prior to submitting a Specification Requirements Sheet (SRS) on batteries.	
1.2.1	Enter on SRS, requirements from MIL-STD-35.	
	NOTE: Reference paragraphs 1.2.12 through 1.2.21 have been deleted. These characteristic names and codes are now contained in MIL-STD-35.	

Supersedes page 77 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF. PARA.	CHARACTERISTIC NAME	CODE
1.2.22	Design and Construction	
	Rated Voltage (volts)	
	Nominal	1562
	Minimum	1564
	*Maximum	1566
	Battery Capacity	
	Ampere-Hours	1568
	*Hour-Rate (hours)	1570
	Temperature (Degrees C)	
	Operating	
	*Minimum	1580
	*Maximum	1582
	Storage	
	*Minimum	1584
	*Maximum	1586

*INDICATES MANDATORY REQUIREMENTS

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC	
	NAME	CODE
1.2.69 Cont	Measure closed circuit voltage at _____ minute intervals between shock blows.	1507
	Discharge to test end voltage of _____ volts per cell.	1508
	There shall be no damage that will affect form, fit, or function.	1509

Supersedes pages 155 through 166 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE I. DELETED

TABLE II. DELETED

Supersedes pages 167 and 168 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

APPENDIX A

DIMENSION CHARACTERISTICS

NOTE: The Dimension Characteristic Table now appears as Table A in MIL-STD-35.

Supersedes page 171 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:56Z
Check the source to verify that this is the current version before use.

APPENDIX B

APPLICABLE DOCUMENTS

NOTE: The Applicable Documents Table now appears as Table B in MIL-STD-35.

Supersedes pages 172 through 188 of 18 June 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY

LEFT BLANK

Supersedes pages 215 through 219 of 18 June 1974

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-126/857

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.