INCH-POUND

MIL-STD-656D
12 January 2021
SUPERSEDING
MIL-STD-656C
18 July 1990

DEPARTMENT OF DEFENSE
STANDARD PRACTICE

PROVISIONS FOR EVALUATING QUALITY

OF SLACKS, WOMEN'S

AMSC N/A FSC 8410

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

FOREWORD

1. This standard is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. This standard is intended to provide standard practice for quality inspections of women's slacks. This standard provides the following information:

- A standard method for visually inspecting and evaluating the quality of slacks
- Standard descriptions for slacks defects
- Standardized examination requirements for slacks

3. Slacks covered by this document are designated as Dress, Semi-Dress and Utility. Semi-dress slacks are sometimes referred to as "Service Uniform" slacks. If an end-item specification includes a list of defects or exceptions to this standard, the end-item specification will prevail. For provisions for evaluating quality of men's trousers MIL-STD-1488 should be used.

4. Comments, suggestions, or questions on this document should be addressed to: Attn: DLA Troop Support, 700 Robbins Street, Philadelphia, PA 19111-5096. Since contact information can change, you may want to verify the currency of this address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
	FOREWORD	ii
1.	SCOPE	1
1.1	Scope	1
1.2	Purpose	1
1.3	Applicability	1
1.4	Classification	1
2.	APPLICABLE DOCUMENTS	1
2.1	General	1
2.2	Government documents	1
2.3	Non-Government publications	1
2.4	Order of precedence	2
3.	DEFINITIONS	2
3.1	Defective button	2
3.2	End-item	2
3.3	Fabric defects	2
3.4	Inside and outside	2
3.5	Knots and slubs	2
3.6	Major defect	2
3.7	Minor defect	2
3.8	Puckering	3
3.9	Quality assurance terms and procedures	3
3.10	Raw edge	3
3.11	Seams and stitching	3
3.11.1	Open seam	3
3.12	Slacks	3
4.	GENERAL REQUIREMENTS	3
4.1	General	3
4.2	Normal viewing conditions	3
5.	DETAILED REQUIREMENTS	3
5.1	Sampling and acceptance criteria	3
5.2	End-item dimensional examination	4
5.3	End-item visual examination	4
5.4	Shade variation examination	18
5.4.1	Shade match and appearance examination	18

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH			PAGE
6.	NOTES	.....	18
6.1		Intended use	18
6.2		Acquisition requirements	18
6.3		Subject term (key word) listing	18
6.4		Changes from previous issue	18
TABLE I.		End-item defect	5-17

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard covers the inspection provision requirements for slacks worn by female members of the military.

1.2 Purpose. The purpose of this document is to provide standardized examination provisions for evaluating the quality of slacks. It is intended to, in a single document, list defects irrespective of fabrics used.

1.3 Applicability. This standard is applicable to contracts by reference in the appropriate slacks specifications.

1.4 Classification. The slacks will be of the following types:

Dress
Semi-Dress
Utility

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4 or 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4 and 5 of this standard, whether or not they are listed.

2.2 Government documents. No Government documents are currently specified in this standard.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS

68373A: AATCC Photographic Seam Smoothness Scales

(Scales are available at https://www.aatcc.org)

AMERICAN SOCIETY FOR QUALITY

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://www.asq.org.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

ASTM INTERNATIONAL

ASTM D3990 - Standard Terminology Relating to Fabric Defects
ASTM D6193 - Standard Practice for Stitches and Seams

(Copies of these documents are available online at https://www.astm.org.)

Fabric Defect Replica Scales

(For information on obtaining copies of the Fabric Defect Replica Scales please contact U.S. Army Combat Capabilities Development Command (CCDC), Soldier Center, ATTN: FCDD-SCD-PD, 10 General Greene Avenue, Natick, MA 01760-5019.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document or end-item specific documents, however, supersedes applicable laws and regulations, unless a specific exemption has been obtained.

3. DEFINITIONS

3.1 Defective button. A button will be considered defective when it is broken or cracked; has sharp, rough or split edges; has scratches or dents, blemishes or foreign matter embedded or is unevenly shaded. Additional button defects may be found in the defects tables in section 5 of this standard or in applicable button specifications.

3.2 End-item. End-item refers to finished slacks ready for inspection and acceptance.

3.3 Fabric defects. Fabric defects specified in Table I are defined in ASTM D3990. Fabric defects not specified in Table I are specified in the appropriate fabric specification.

3.4 Inside and outside. The term “inside” refers to any part of the slacks that are not visible when completely closed and fastened, while the term “outside” refers to any part of the slacks that are visible when the completely closed and fastened.

3.5 Knots and slubs. Only knots and slubs on the outside of the slacks that exceed the limits in the basic cloth specification will be scored as defects in evaluating quality of the finished slacks. Knots and slubs are rated using Fabric Defect Replica Scales (see 2.3).

3.6 Major defect. A departure of a quality characteristic from its intended level of the specification that occurs with a severity sufficient that is likely to result in a failure, or to reduce considerably the usability of the slacks for its intended purpose.

3.7 Minor defect. A departure of a quality characteristic from its intended level of the specification but the slacks are still considered serviceable. (Multiple minor defects may render slacks or production lot unserviceable).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

3.8 Puckering. Refers to the gathering of a seam/stitches during sewing, after sewing and after laundering causing unacceptable seam appearance when compared to the 68373A; AATCC Photographic Seam Smoothness Scales (see 2.3). Puckering on major portions of the suspected seam that has a rating less than "4" will be scored as a puckered seam.

3.9 Quality assurance terms and procedures. Definitions of quality assurance terms and procedures, where applicable, will be in accordance with ASQ/ANSI Z1.4.

3.10 Raw edge. Raw edge is defined as any fabric edge not serged or otherwise finished to prevent raveling.

3.11 Seams and stitching. Unless otherwise specified, seams and stitching will be as defined in ASTM D6193. Open seam defects will be as defined in 3.11.1.

3.11.1 Open seam. A seam will be considered open when stitching joining the seam areas are broken, skipped or missing stitches. (Seams with multiple rows of stitching are considered open when any of the criteria in this section are met by any one or more of the rows.)

3.12 Slacks. The term "slacks" refers to "an outer garment covering the body from the waist to the ankles, with a separate part for each leg".

4. GENERAL REQUIREMENTS

4.1 General. This standard contains provisions and terminology for end-item inspection of dress, semi-dress and utility slacks. If there are any inconsistencies between the requirements of the appropriate end-item specification and the provisions of this standard, the end-item specification shall govern.

4.2 Normal viewing conditions. Normal viewing conditions for the inspection of slacks is three (3) feet from the surface being examined. Unless otherwise specified, slacks shall be examined while laid flat on a suitable table using the following illumination criteria. The overhead direct lighting source shall be parallel to the viewing surface so as to illuminate with direct perpendicular impinging light rays. The surface illumination level shall be a minimum of 1075 lux (100 foot candles). The lights shall be cool white preheat rapid start fluorescent lamps with white reflectors and without baffles or glass.

5. DETAILED REQUIREMENTS

5.1 Sampling and acceptance criteria. The sample unit shall be one pair of finished slacks and lot size shall be expressed in the number of sample units. The sample size and Acceptance Quality Limits (AQLs) shall be as specified in the contract or purchase order. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 – Sampling Procedures and Tables for Inspection by Attributes. Sampling shall represent all types, classes, and styles included in the production lot, and shall include samples from the beginning, middle and end of production of the end-item specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

5.2 End-item dimensional examination. Finished slacks shall be measured for conformance to the finished measurements as stated in the end item specification. The sample size for end item dimensional examination shall be as specified in the contract or purchase order.

5.3 End-item visual examination. The slacks shall be examined for the defects stated in Table I of this document. Defects are assigned as “Major” or “Minor”. The sample unit shall be one pair of finished slacks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects.

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
I. MATERIAL DEFECT AND DAMAGE						
Any hole, cut, tear, smash, burn, drill hole, scorched area and/or multiple float:						
- Up to ¼-inch, inclusive	101		101			201
- More than ¼-inch in any direction	102		102		101	
Any knot and/or slub 1/		201		201		202
Misweave, area of no dye penetration, dye, streak, missing yarn, broken yarn, visible mend, thin place, shade bar and barre		202		202		203
Loose yarn, snag and/or coarse yarn more than ½-inch in any direction on outside	103			203		204
Woven in debris and/or waste on outside visible at 3-feet		203		204		205
II. SHADED PARTS						
Variation and shade within a part and/or between parts	104		103			206
III. STITCHING AND SEAM DEFECTS						
Needle chew:						
- Up to ¼-inch, inclusive, in any direction		204		205		207
- More than ¼-inch in any direction	105		104		102	
Seam allowance not as specified		205		206		208
Raw edge of fabric not as specified (except where pinking is required)		206		207		209
Seams irregular, twisted, wavy and/or pleated	106			208		210
Wrong seam and/or stitch type	107		105		103	
Any line of stitching omitted	108		106		104	
Any line of stitching not starting and/or ending where specified		207		209		211

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
III. STITCHING AND SEAM DEFECTS (continued)						
Basting stitch visible on outside of the finished slacks		208		210		212
Gauge irregular and/or not within range specified (score only when condition exists on more than ½-inch the length of the seam)		209		211		213
Stitches per inch incorrect		210		212		214
Loose stitch tension:						
- Up to ½-inch inclusive		211		213		215
- More than ¾-inch	109		107		105	
Tight stitch tension (all seams)	110		108		106	
Seam puckered 2/ (score only on major portion of seam)	111		109			216
Any part of slacks caught in an unrelated operation and/or stitching	112		110		107	
End of stitching, when not caught in another seam, not backstitched as specified		212		214		217
Thread break not repaired by backstitching at least ½-inch		213		215		218
Ends of a continuous line of stitching not overlapped by at least ½-inch		214		216		219
Open seam (see 3.11.1) or runoff:						
- Up to and including ½-inch		215		217		220
- Greater than ½-inch	113		111		108	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
III. STITCHING AND SEAM DEFECTS (continued)						
Inseam and/or outseam not lapped as specified	114			218		221
Ends of inseams staggered at crotch more than ½-inch (center to center)	115			219		222
Pleated and/or twisted at base of pocket and/or placket opening	116			220	--	--
Front and seat seams not joined in one continuous operation (when applicable)		216		221		223
Seat seam outlet omitted		217		222		224
IV. COMPONENTS						
Any component omitted and/or part not as specified and/or twisted, unless otherwise specified below	117		112		109	
Thread/gimp						
Thread/gimp color not as specified	118		113			225
Button						
Button not as specified, broken, cracked, bent		218		223		226
Snap fastener						
Not as specified	--	--	114		110	
Non-functioning, broken, cracked, bent	--	--	115		111	
Hook and eye/bar fastener						
Not as specified	119		116		112	
Non-functioning (broken, bent, cracked)	120		117		113	
Hook and loop fastener						
Not as specified	--	--	--	--	114	
Non-functioning	--	--	--	--	115	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
IV. COMPONENTS (continued)						
Slide fastener						
Not as specified	121		118		116	
Cut, hole and/or tear in tape	122		119		117	
Slider does not operate smoothly (binds, catches and/or sticks)		219		224		227
Drawcord(s)						
Not as specified	--	--	--	--		228
End(s) not finished as specified	--	--	--	--		229
Binding						
Material type and/or color not as specified		220		225		230
Not cut as specified (e.g., on the bias)		221		226		231
Width of finished binding not as specified		222		227		232
Waistband						
Waistband gripper tape not as specified		223		228		233
Label						
Not as specified (material)		224		229		234
Missing, incorrect and/or illegible information	123		121		118	
Braid/cord						
Braid/cord/stripes not as specified	124		122		--	--
Fusing material						
Not as specified	125		123		--	--
V. CONSTRUCTION						
Unless otherwise specified, items intended to be equal in length and/or in alignment that differ by more than ½-inch and ⅛-inch respectively.	126		124		119	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Any component part not cut and/or sewn in accordance with specified directional lines, twill lines and/or fabric grain not parallel between parts	127		125		120	
Excessive bulging, twisting, pulling and/or puckering at closures when fasteners and/or closure devices are properly positioned according to marks on patterns	128		126		121	
Notch exposed at pocket opening	129		127		122	
Top of pocketing not securely inserted under waistband causing bulge and distortion on the outside	130		128		123	
Pocketing caught in unrelated stitching	131		129		124	
Buttonhole						
Not as specified, location, omitted, added, not finished as specified	132		130		125	
Gimp omitted, uncut buttonhole, incomplete stitching	133		131		126	
Two (2) or more skipped and/or loose stitches		225		230		235
Button						
Misplaced, missing, insecurely sewn		226		231		236
Location not as specified		227		232		237
Number of buttons not as specified		228		233		238
Snap fastener						
Not attached as specified, missing	--	--	132		127	
Male and female sides misaligned by more than ⅛-inch when slacks are properly oriented	--	--		234		239
Hook and eye/bar fastener						
Not attached as specified	134		133		128	
Not positioned as specified causing bulging, puckering, twisting and/or pulling	135		134		129	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Hook and eye/bar fastener (continued)						
Hook and eye sides misaligned:						
- Misaligned by ≥ ¼-inch	136		135		130	
Hook and loop fastener						
Not attached as specified	--	--	--	--	131	
Hook and loop sides misaligned:						
- Misaligned by ≥ ¾-inch	--	--	--	--	132	
Bartack or tack						
Missing, insecure, misplaced, not serving intended purpose and/or not specified size and/or type:						
- Bartack for attachment	137		136		133	
- Bartack for reinforcement		229		235		240
Incorrect number of stitches		230		236		241
Loose and/or tight stitch tension		231		237		242
Waist adjustment strap or tab						
Not attached and/or finished as specified, missing	--	--	137		134	
Slide fastener						
Not attached as specified	138		138		135	
Opening greater than ⅛-inch at top when fully secured		232		238		243
Uneven at top by more than ¼-inch	139		139		136	
Bottom stop not positioned within ⅜-inch of front seam		233		239	137	
Stitching too close to chain not permitting slider to pass freely	140		140		138	
Slide fastener thong missing and/or incorrectly attached	--	--	--	--		244
Bottom stop not securely stapled	141		141		139	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Slide fastener thong						
Length of thong not as specified	--	--		240		245
End of thong not finished as specified	--	--		241		246
Drawcord(s)						
Finished length not as specified		234		242		247
Eyelet misplaced and/or not positioned as specified		235		243		248
Stay stitch omitted		236		244		249
Drawcord does not move freely		237		245		250
Binding						
Not attached and/or finished as specified	142		142		140	
Tight and/or twisted, causing puckering and/or pleating		238		246		251
More splices than specified		239		247		252
Waistband						
Width of finished waistband and linings not as specified		240		248		253
Waistband not uniformly stitched to top of slacks causing waviness, pleats, twist of waistband, lining visible on outside	143		143		141	
Joining seam (center back) not aligned with seat seam by ⅛-inch or more	144		144			254
Bottom edges of waistband extensions not in line with waistband joining seam by more than ¼-inch, when slacks are buttoned		241		249		255
Waistband extension not specified distance from fold and/or welt to point of tab and/or underside exposed by ⅛-inch.		242		250		256
Linings not as specified and exposed on outside		243		251	--	--
Non-slip tape as specified	145		--	--	--	--
Waistband interlining/fusing not as specified, bubbling, delamination	146		--	--	--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Waistband (continued)						
Waist adjustment strap and/or tab missing	--	--	--	--	142	
Belt loops						
Belt loops, missing and/or incorrect number	147		145		143	
Finished width and length not as specified		244		252		257
Not attached and/or finished as specified		245		253		258
Placement more than ¼-inch from specified location		246		254		259
Opening differs from specified by more than ⅛-inch		247		255		260
Center back loop not centered on seat seam by more than ¼-inch		248		256		261
Bartacks not as specified		249		257		262
Darts						
Darts stitched with twists and/or puckers, and/or not properly tapered and stitched closed to the very end of the folded edge, resulting in noticeable indentation and/or fullness on the outside of slacks	148		146			263
Length of darts differs by more than ¼-inch	149		147			264
Front opening						
Opening orientation incorrect	150		148		144	
J stitch not as specified		250		258		265
Left fly facing exposed when slide fastener is closed	151		149			266
Right fly facing exposed when slide fastener is closed		251		259		267
Fly attachment seam visible on outside of slacks	152		150			268
Slide fastener tapes show when the slacks are fully closed	153		151			269
Fly tab not positioned as specified		252		260		270

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Pockets or flap:						
General pocket information:						
Pocket and/or flap out of alignment from each other by more than ½-inch when intended to be in corresponding locations	154		152		145	
Poor pocket construction causing fullness and/or distortion	155		153		--	--
Pocket openings uneven in length up to ¼-inch		253		261		271
Raw edge of pocket opening exposed	156			262		272
Pocket flap not as specified, crooked, poorly shaped and/or constructed, not covering pocket opening	157		154			273
Pocket bag material not as specified		254		263		274
Depth of pocket not as specified by more than ½-inch	158		155		146	
Pocket bag improperly sewn, causing fullness, twisting or bunching	159			264		275
Pocket bag material caught in an unrelated operation	160			265		276
Welt pocket information:						
Pocket opening welt not as specified	161		156		--	--
Poorly shaped and/or not uniform in shape or size	162		157		--	--
Irregular in-width by more than $^{3}/_{16}$-inch	163		158		--	--
Welts out of horizontal alignment with waistband when measured from bottom of waistband to top corners of welt up to ¼-inch	164		159		--	--
Finish depth and width of welt not as specified	165		160		--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Welt pocket information (continued)						
Welts out of alignment from each other when measured from the bottom waistband straight down to top edge of outside and inside end of welt by ¼-inch	166		161		--	--
Hip pocket information:						
Cord and/or welt not as specified width	--	--		266		277
Hip pocket cord and/or bearer not caught in the edge stitching of pocketing	--	--		267		278
Side pocket or hanging type pocket information:						
Pocketing facing too tight and/or loose causing edge of pocket opening to be wavy		255		268	--	--
Facing and/or bearer not caught in bartack at each end of opening; facing and/or bearer not extending below bottom bartack and above top bartack	167		162			279
Pocketing notched more than ¼-inch beyond width of outseam allowance on the underside		256		269		280
Bartack extends beyond outseam, no more than ⅛-inch	--	--		270		281
Cargo pocket information:						
Shape not as specified	--	--	--	--	147	
Pleats not as specified	--	--	--	--	148	
Center of button out of alignment with eyelet of buttonhole in flap causing distortion when buttoned.	--	--	--	--		282
Bellows shape and/or size not as specified	--	--	--	--	149	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Cargo pocket information (continued):						
Cargo pockets do not align (right and left leg)	--	--	--	--		283
Drawcord lock/toggle missing and/or not functioning	--	--	--	--	150	
Eyelets omitted	--	--	--	--	151	
Eyelets not as specified	--	--	--	--	152	
Fabric inside of eyelet not completely cut and/or removed	--	--	--	--		284
Eyelet stitches not securely caught in fabric	--	--	--	--	153	
Shin/lower leg pocket						
Shape not as specified	--	--	--	--	154	
Center of button out of alignment with buttonhole in flap causing distortion, bunching or twisting when buttoned.	--	--	--	--	--	285
Bellow shape and/or size not as specified	--	--	--	--	155	
Eyelets not as specified	--	--	--	--	156	
Drawcord lock/toggle missing and/or not functioning	--	--	--	--	157	
Pockets do not align (right and left leg)	--	--	--	--		286
Seat patch						
Missing, not properly placed and/or aligned	--	--	--	--	158	
Knee patch						
Misplaced (i.e. not serving intended purpose)	--	--	--	--		287
Omitted and/or not securely caught in either inseam/outseam	--	--	--	--	159	
Hem/leg bottom						
Not finished as specified		257		271		288

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Hem/leg bottom (continued)						
Unhemmed bottoms uneven by more than ½-inch at inseams and outseams		258		272	--	--
Width of hem not as specified and/or irregular by more than ¼-inch	--	--	--	--		289
Leg tie tape						
Length not as specified	--	--	--	--		290
Ends not finished as specified	--	--	--	--		291
Not attached as specified	--	--	--	--		292
Label						
Not as specified, missing, incorrect and/or illegible	168		163		160	
Braid/stripes (when required)						
Not as specified, missing	169		164		--	--
Not completely caught in waistband seam	170		165		--	--
Twisted, bulging, bunched and/or puckered	171		166		--	--
Stripes not centered over outseam and not even with edge of side pocket						
VI. PRESSING AND CLEANING EFFECTS						
Pressing omitted and/or poorly pressed, and/or exhibiting a double crease line:						
- On permanent crease and/or durable press	172		167		161	
- On other than permanent crease and/or durable press	173			273		293

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
VI. PRESSING AND CLEANING EFFECTS (continued)						
Pressing not seam on seam by more than ½-inch:						
- On permanent crease and/or durable press	174			274		294
- On other than permanent crease and/or durable press		259		275		295
Permanent crease line not ending within specified limits	176		169			397
Permanent crease omitted:						
- ≤1-inch	175		168			296
Seam allowance not pressed open		260		276	--	--
Burned and/or scorched in pressing	177		170		--	--
Gloss and/or impressions not removed		261		277	--	--
Any spot and/or stain that cannot be completely removed with a clean cloth moistened with water:						
- 1/16 to ⅜-inch, inclusive		262		278		398
- >⅜-inch up to and including ¾-inch	178		171			399
Three (3) or more thread ends on the outside greater than or equal to ½-inch		263		279		300
Re-sewn and/or re-stitched seams not cleaned	179		172			301
Thread end caught in a line of stitching on the outside for more than ¼-inch		264		280		302

1/ Knots and slubs shall be rated in accordance with the Fabric Defect Replica Scales.
2/ Puckering shall be rated in accordance with the AATCC Photographic Seam Smoothness Scales (see 2.3). Puckering on major portions of the suspected seam that has a rating less than "4" shall be scored as a puckered seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

5.4 Shade variation examination. During the examination, each pair of slacks in the sample shall be examined for shade variation. Any slacks in the sample containing uneven shade or shade variation, within a part or between parts, shall be cause for rejection of entire lot represented by the sample.

5.4.1 Shade match and appearance examination. The shade match and appearance examination shall be conducted as specified in the material specification, contract or purchase order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. To provide a standardized examination procedure for evaluating quality of women's slacks that are worn by members of the military as part of dress, semi-dress and utility uniforms. These defects are typical of those included in quality inspections of slacks.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this standard
b. Type of material defects allowed.
c. The specific issue of individual documents referenced (see 2.3)
d. Acceptance Quality Levels (AQLs)
e. Sample size

6.3 Subject term (key word) listing.

Defect
Dress uniform
Examination
Inspection
Semi-Dress uniform
Utility uniform

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.

Custodians:
Army - GL
Navy - NU
Air Force - 11

Preparing activity:
DLA - CT

Review activities:
Navy - MC

(Project: 8410-2021-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:20Z
Check the source to verify that this is the current version before use.