INCH-POUND


MS21367G
W/AMENDMENT 1
15 July 2022
SUPERSEDING
MS21367G
2 July 2007

MILITARY SPECIFICATION SHEET

COILS, RADIO FREQUENCY, ENCAPSULATED, FIXED, MICRO-MINIATURE, SHIELDED (IRON CORE) TYPES LT10K354 TO LT10K383 INCL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification and MIL-PRF-15305.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Coils are held rigidly by the body during vibration and mechanical shock testing.
4. The “G” dimension is not applicable within one-sixteenth of the body of the coil.

FIGURE 1. Dimensions and configuration.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	Dimensions in inches with metric equivalents (mm) in parentheses
	Minimum	Maximum
A	.090 (2.29)	.110 (2.79)
B	---	.065 (1.65)
C	.210 (5.33)	---
D	.350 (8.89) REF	.350 (8.89) REF
E	.080 (2.03)	.110 (2.79)
F	.010 (0.25)	.014 (0.36)
G	.002 (0.05)	.003 (0.08)
H	.005 (0.13) NOM	.005 (0.13) NOM

FIGURE 1. Dimensions and configuration - Continued

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Style: LT10.

Grade: 1.
Class: A.

Core material: Powdered iron.

Lead material: Beryllium copper with an electro-tin plating .0001 to .0002 inch thickness composed of 60 percent tin minimum and 40 percent lead maximum.

Weight: .03 gram, maximum.

Operating temperature range: -55°C to +105°C.

Ambient temperature: 90°C maximum.

Temperature rise: 15°C maximum.

Power dissipation: 20.5 mW, maximum. Maximum power is the wattage dissipated by the coil when rated dc current produces a 15°C temperature rise at 90°C ambient.

Terminal pull: 227 grams minimum.

Terminal bend: 2 operations minimum.

Terminal twist: Not applicable.

Altitude: 70,000 feet.

Shock, specified pulse: MIL-STD-202-213, test condition I, is applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage:

At sea level: MIL-STD-202-301, test voltage 140 V rms minimum.

At reduced barometric pressure: MIL-STD-202-105, test condition C, test voltage 50 V rms minimum.

Percent coupling: 3 percent maximum.

Resistance to soldering heat: MIL-STD-202-210, test condition A, is applicable.

Electrical characteristics: See table I, table II, and table III.

Inductance: See table I.

Q values: See table I.

Self-resonant frequency (SRF): See table I.

DC resistance (DCR): See table I.

Part or Identifying Number (PIN): MS21367 - (dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial).

Dash number 1/	Type designation	Nominal Inductance (μH)	Q (min)	Test frequency (MHz)	SRF min (MHz)	DC resistance (ohms) at 25°C (max)	Rated dc current (mA)
-1	LT10K354	.015 ±30%	40	50	250	.065	492
-2	LT10K355	.022 ±30%	40	50	250	.090	418
-3	LT10K356	.033 ±30%	40	50	250	.115	370
-4	LT10K357	.047 ±30%	40	50	250	.120	360
-5	LT10K358	.068 ±30%	40	50	250	.150	324
-6	LT10K359	.100 ±30%	40	50	250	.170	304
-7	LT10K360	.120 ±20%	35	25	250	.140	335
-8	LT10K361	.150 ±20%	40	25	250	.160	313
-9	LT10K362	.180 ±20%	40	25	250	.190	287
-10	LT10K363	.220 ±20%	40	25	250	.210	274
-11	LT10K364	.270 ±20%	40	25	250	.240	256
-12	LT10K365	.330 ±20%	40	25	250	.250	251
-13	LT10K366	.390 ±20%	40	25	200	.280	237
-14	LT10K367	.470 ±20%	40	25	175	.310	225
-15	LT10K368	.560 ±20%	40	25	170	.450	185
-16	LT10K369	.680 ±20%	40	25	165	.620	159
-17	LT10K370	.820 ±20%	35	25	160	.650	155
-18	LT10K371	1.00 ±20%	35	25	135	.730	145
-19	LT10K372	1.20 ±10%	35	7.9	120	1.00	125
-20	LT10K373	1.50 ±10%	32	7.9	110	1.20	114
-21	LT10K374	1.80 ±10%	32	7.9	95	1.50	102
-22	LT10K375	2.20 ±10%	35	7.9	80	1.70	96
-23	LT10K376	2.70 ±10%	35	7.9	70	2.00	89
-24	LT10K377	3.30 ±10%	37	7.9	65	2.20	84
-25	LT10K378	3.90 ±10%	37	7.9	60	2.80	75
-26	LT10K379	4.70 ±10%	40	7.9	55	3.10	71
-27	LT10K380	5.60 ±10%	40	7.9	50	3.30	69
-28	LT10K381	6.80 ±10%	40	7.9	45	3.80	64
-29	LT10K382	8.20 ±10%	40	7.9	43	5.00	56
-30	LT10K383	10.0 ±10%	40	7.9	40	5.60	53

1/ The dash number added to MS military standard number constitutes the MS PIN; for example MS21367-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final). (For .015 µH through 1.0 µH) 1/

Inspection group	Allowable variation from Initial measurement	Allowable variation from Initial measurement	Allowable percent from specified minimum value in electrical characteristics (initial) table	Allowable percent from specified minimum value in electrical characteristics (initial) table
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±5	---	---	-10
Group III	±10	±(3% +.001 ohm)	-10	-15
Group IV	±5	±(2% +.001 ohm)	-10	-10
Conformance inspection group C				
Subgroup I	±5	---	---	-10
Subgroup II	±5	±(2% +.001 ohm)	-10	-10
Subgroup III	±10	±(3% +.001 ohm)	-10	-15

TABLE III. Electrical characteristics (final). (For 1.2 µH through 10 µH) 1/


Inspection group	Allowable variation from Initial measurement	Allowable variation from Initial measurement	Allowable percent from specified minimum value in electrical characteristics (initial) table	Allowable percent from specified minimum value in electrical characteristics (initial) table
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±2	---	---	-10
Group III	±5	±(3% +.001 ohm)	-8	-10
Group IV	±2	±(2% +.001 ohm)	-10	-10
Conformance inspection group C				
Subgroup I	±2	---	---	-10
Subgroup II	±2	±(2% +.001 ohm)	-10	-10
Subgroup III	±5	±(3% +.001 ohm)	-8	-10

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

1/ The test fixture in the diagram below or its equivalent shall be used for electrical measurements. Inductance values are effective inductance as indicated on a HP260A or equivalent, Q meter, when tested in the test fixture. Inductance of 10 µH or less are corrected for residual meter and test fixture inductance which is typically .050 µH.

NOTES:

1. Polarization during moisture resistance test is not applicable.
2. The percent coupling between two radio frequency coils is to be determined by measuring the voltage induced in a coil when a voltage is applied to an adjacent coil. Percent coupling is not to be measured for parts with nominal inductances of less than 1.0 µH. The measurement is to be performed at 10 kHz for nominal inductance values from 1.0 µH through 100 µH and at 1 kHz for nominal inductance values greater than 100 µH. The measurement circuit is shown in the figure below.



Equipment for 1 kHz and 10 kHz consists of General Radio Audio Oscillator and Power Amplifier type 1308-A, or equivalent and Model 400 vacuum tube voltmeter, or equivalent.

The coils to be tested shall be taped or otherwise secured such that the bodies of the coils are kept parallel and in contact with each other to ensure maximum coupling as shown in the figure below.



The voltage levels shall be as low as possible to permit reliable readings of V_2. The inductance shall be measured with .02 volt injection voltage on a Hewlett-Packard model 260A Q-meter or equivalent.

The percent coupling is to be calculated using the equation:

$$\text{Percent coupling} = \sqrt{\frac{L_1}{L_2}} \times \frac{V_2}{V_1} \times 100$$

where: L_1 = effective inductance of primary coil (measured at standard Q-meter test frequency)
L_2 = effective inductance of secondary coil (measured at standard Q-meter test frequency)
V_1 = voltage measured across primary
V_2 = voltage measured across secondary

3. For dielectric withstanding voltage, barometric pressure and insulation resistance units shall be placed on flat metal plate with leads insulated from surface. Measurement of dielectric withstanding voltage, barometric pressure and insulation resistance shall be between the leads of the coil connected together and the metal plate.

4. The marking shall be as specified in MIL-PRF-15305 except that the marking shall be on the unit package or container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.

FIGURE 1. Typical coil test fixture.




FIGURE 1. Typical coil test fixture - Continued.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-15305, this document references the following:

MIL-STD-202-105 MIL-STD-202-210 MIL-STD-202-213 MIL-STD-202-301

Custodians:
Air Force – 85
DLA - CC

Preparing activity:
DLA – CC

(Project 5950-2022-050)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:37Z
Check the source to verify that this is the current version before use.