
FED SUP CLASS
5306






TABLE I

NOMINAL SIZE		.250			.3125			.375			.500		
THREADS PER INCH		20	28		18	24		16	24		13	20	
D BODY DIAMETER	MAX	.250			.3125			.375			.500		
	MIN	.245			.3065			.369			.493		
F ACROSS FLATS	MAX	.500			.562			.625			.812		
	MIN	.489			.551			.612			.798		
G ACROSS CORNERS	MAX	.577			.650			.722			.936		
	MIN	.557			.628			.698			.910		
H HEAD HEIGHT	MAX	.135			.198			.260			.327		
	MIN	.125			.188			.250			.312		
M THREAD LENGTH	REF	.750			.875			1.000			1.250		
N UNTHREADED* LENGTH-MAX		.125	.089		.139	.104		.156	.104		.192	.125	

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
.750	CAD PHOS	1201 1202	1223 1224			1245 1246	1267 1268			1289 1290	1311 1312			1395 1396	1425 1426		
.875	CAD PHOS	1203 1204	1225 1226		.125	1247 1248	1269 1270			1291 1292	1313 1314			1397 1398	1427 1428		
1.000	CAD PHOS	1205 1206	1227 1228		.250	1249 1250	1271 1272			1293 1294	1315 1316			1399 1400	1429 1430		
1.250	CAD PHOS	1207 1208	1229 1230	.100	.500	1251 1252	1273 1274		.375	1295 1296	1317 1318		.250	1401 1402	1431 1432		
1.500	CAD PHOS	1209 1210	1231 1232	.350	.750	1253 1254	1275 1276	.208	.625	1297 1298	1319 1320	.062	.500	1403 1404	1433 1434		.250
1.750	CAD PHOS	1211 1212	1233 1234	.600	1.000	1255 1256	1277 1278	.458	.875	1299 1300	1321 1322	.312	.750	1405 1406	1435 1436	.019	.500
2.000	CAD PHOS					1257 1258	1279 1280	.708	1.125	1301 1302	1323 1324	.562	1.000	1407 1408	1437 1438	.269	.750
2.250	CAD PHOS					1259 1260	1281 1282	.958	1.375	1303 1304	1325 1326	.812	1.250	1409 1410	1439 1440	.519	1.000
2.500	CAD PHOS									1305 1306	1327 1328	1.062	1.500	1411 1412	1441 1442	.769	1.250
2.750	CAD PHOS									1307 1308	1329 1330	1.312	1.750	1413 1414	1443 1444	1.019	1.500
3.000	CAD PHOS													1415 1416	1445 1446	1.269	1.750
3.250	CAD PHOS													1417 1418	1447 1448	1.519	2.000
3.500	CAD PHOS													1419 1420	1449 1450	1.769	2.250
3.750	CAD PHOS													1421 1422	1451 1452	2.019	2.500

* SEE NOTE 6.

(E) ENTIRE STANDARD REVISED

REVIEWER: AT, AV, MA, GL, MS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) 29 DEC 1975

PA: MC; Other Cust: 82	TITLE: BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS35764
PROCUREMENT SPECIFICATION: MIL-B-[illegible]12	SUPERSEDES: BAN11 thru BAN11.1	SHEET 1 OF 7

DD FORM 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

FED SUP CLASS 5306

TABLE I - Continued

NOMINAL SIZE		.625			.750			1.000			1.250		
THREADS PER INCH		11	12		10	16		8	12		7	12	
D BODY DIAMETER	MAX	.625			.750			1.000			1.250		
	MIN	.617			.742			.990			[illegible]		
F ACROSS FLATS	MAX	1.000			1.125			1.500			[illegible]		
	MIN	.963			1.106			1.477			[illegible]		
G ACROSS CORNERS	MAX	1.155			1.299			1.732			2.165		
	MIN	1.121			1.261			1.684			2.060		
H HEAD HEIGHT	MAX	.390			.458			.582			.692		
	MIN	.375			.438			.562			.677		
M THREAD LENGTH	REF	1.500			1.750			2.250			2.750		
N UNTHREADED LENGTH-MAX		.227	.139		.250	.156		.312	.208		.357	.208	

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
1.000	CAD PHOS	1515 1516	1543 1544														
1.250	CAD PHOS	1517 1518	1545 1546			1571 1572	1599 1600										
1.500	CAD PHOS	1519 1520	1547 1548			1573 1574	1601 1602										
1.750	CAD PHOS	1521 1522	1549 1550		.250	1575 1576	1603 1604			1679 1680	1705 1706						
2.000	CAD PHOS	1523 1524	1551 1552		.500	1577 1578	1605 1606		.250	1681 1682	1707 1708			1729 1730	1753 1754		
2.250	CAD PHOS	1525 1526	1553 1554		.750	1579 1580	1607 1608		.500	1683 1684	1709 1710			1731 1732	1755 1756		
2.500	CAD PHOS	1527 1528	1555 1556	.227	1.000	1581 1582	1609 1610		.750	1685 1686	1711 1712			1733 1734	1757 1758		
2.750	CAD PHOS	1529 1530	1557 1558	.477	1.250	1583 1584	1611 1612	.200	1.000	1687 1688	1713 1714		.500	1735 1736	1759 1760		
3.000	CAD PHOS	1531 1532	1559 1560	.727	1.500	1585 1586	1613 1614	.450	1.250	1689 1690	1715 1716		.750	1737 1738	1761 1762		
3.250	CAD PHOS	1533 1534	1561 1562	.977	1.750	1587 1588	1615 1616	.700	1.500	1691 1692	1717 1718	.125	1.000	1739 1740	1763 1764		.500
3.500	CAD PHOS	1535 1536	1563 1564	1.227	2.000	1589 1590	1617 1618	.950	1.750	1693 1694	1719 1720	.375	1.250	1741 1742	1765 1766		.750
3.750	CAD PHOS	1537 1538	1565 1566	1.477	2.250	1591 1592	1619 1620	1.200	2.000	1695 1696	1721 1722	.625	1.500	1743 1744	1767 1768	.071	1.000
4.000	CAD PHOS	1539 1540	1567 1568	1.727	2.500	1593 1594	1621 1622	1.450	2.250	1697 1698	1723 1724	.875	1.750	1745 1746	1769 1770	.321	1.250
4.500	CAD PHOS	1541 1542	1569 1570	2.227	3.000	1595 1596	1623 1624	1.950	2.750	1699 1700	1725 1726	1.375	2.250	1747 1748	1771 1772	.821	1.750
5.000	CAD PHOS									1701 1702	1727 1728	1.875	2.750	1749 1750	1773 1774	1.321	2.250

* SEE NOTE 6.

TABLE II
LENGTH TOLERANCE

NOMINAL SIZE	.250 .3125 .375	.4375 .500	.5625 .625 .750	.875 1.000	1.250
LENGTH	TOLERANCE (+.000)				
THRU 1.000	-.030	-.030	-.030		
OVER 1.000 THRU 2.500	-.040	-.060	-.080	-.100	-.120
OVER 2.500 THRU 4.000	-.060	-.080	-.100	-.140	-.160
OVER 4.000				-.160	-.180

REVIEWER: AT, AV, MU, GL, 19, MSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P A DC Other Cust 82	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS 35764
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES BARX3 thru BARX3.3	SHEET 2 OF 7

DD FORM 672-1 (COORDINATED)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

NOTES:
1. MATERIAL: Steel, SAE Grade 8 in accordance with procurement specification.
2. PROTECTIVE COATING: Cadmium plated in accordance with QQ-P-416, Type II, Class 2. Phosphate coated in accordance with MIL-P-16232, Type 2, Class 2.
3. THREADS: Threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook H28.
4. DIMENSIONS: All dimensions are in inches.
5. HEAD DIMENSIONS: For head dimensions see procurement specification.
*6. UNTHREADED LENGTH: Bolts too short for full thread length shall have threads extending over the full length. The distance from the underside of the head to the first complete (full form) thread, as measured with a ring thread gage, shall not exceed the maximum unthreaded length "N".
7. HEAD MARKING: Heads shall be marked on top with the manufacturer's identification and the number 8 to designate Grade 8 material. Raised markings are preferred.
8. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS35764-1201.
9. Referenced documents shall be of the issue in effect on date of invitations for bid.
10. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
11. This bolt is covered by U.S. Patent Number 3342236 which expires 19 September 1984. The Government does not have a royalty free license under this patent. This bolt is known as a "Place Bolt" under this patent.

TABLE III

GRADE 8 - REFERENCE INFORMATION ONLY				
NOMINAL SIZE	THREADS PER INCH	PROOF LOAD LBS (MIN)	RECOMMENDED AXIAL LOAD (LBS)	*RECOMMENDED TIGHTENING TORQUE (FT - LBS)
.250	20 28	3800 4350	2850 3263	11 14
.3125	18 24	6300 6950	4725 5213	21.5 27
.375	16 24	9300 10550	6975 7913	40.5 55
.500	13 20	17050 19200	12788 14363	102 126
.625	11 18	27100 30700	20325 23025	212 263
.750	10 16	40100 44750	30075 33563	390 464
1.000	8 12	72700 79550	54525 59663	889 1050
1.250	7 12	116300 128750	87225 96563	1956 2253

NOTES:
1. Torque based on 0.2 coefficient of friction.
2. Torque and axial load based upon 75% of proof load value.
3. The self-locking feature of these bolts is full effective when tightened to the torque values shown herein. Lockwashers or locknuts are not needed. (See note 5)
* 4. Torque values are to be shown adjacent the bolt part number callouts upon assembly drawings. They are subject to upward or downward revision by the agency responsible for the assembly drawings when the tightening friction coefficient for specific applications, is found to vary from as shown in note (1), above.
5. Where material, softer than the bolt material, is fastened, plain washer of material as hard as the bolt, of adequate thickness, and larger in diameter than the bolt head, shall be used under bolt head.

REVIEWER: AT, AV, MU, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGE S SEE SHEET 1

1. This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. DC Other Cust. 82	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS 35764
PROCUREMENT SPECIFICATION MIL-B-[illegible]	SUPERSEDES BAB11 thru BAB13.3	SHEET 3 OF [illegible]

DD FORM 672-1 (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

REVIEWER: AT, AV, MU, GL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

TABLE IV

The following former dash numbers of MS35764 are INACTIVE FOR NEW DESIGN AFTER 15 MAY 1973. These inactive dash numbers have smaller "B" and "C" dimensions than the new dash numbers in Table I, and have Type II, Class 3 cadmium plating per QQ-P-416.

NOMINAL SIZE		.250			.3125			.375			.4375		
THREADS PER INCH		20	28		18	24		16	24		14	20	
E BODY DIAMETER	MAX	.250			.3125			.375			.4375		
	MIN	.245			.3065			.369			.4305		
F ACROSS FLATS	MAX	.438			.500			.562			.625		
	MIN	.428			.489			.551			.612		
G ACROSS CORNERS	MAX	.505			.577			.650			.722		
	MIN	.488			.557			.628			.695		
H HEAD HEIGHT	MAX	.135			.196			.260			.293		
	MIN	.125			.186			.250			.283		
M THREAD LENGTH	REF	.750			.875			1.000			1.125		
N UNTHREADED* LENGTH-MAX		.125	.089		.139	.104		.156	.104		.179	.125	

L LENGTH	FINISH	DASH NO.		BODY LOT MIN	GRIP LOT MAX	DASH NO.		BODY LOT MIN	GRIP LOT MAX	DASH NO.		BODY LOT MIN	GRIP LOT MAX	DASH NO.		BODY LOT MIN	GRIP LOT MAX
.750	CAD PHOS	803 203	1003 603			817 217	1017 617			831 231	1031 631			846 246	1046 646		
.875	CAD PHOS	804 204	1004 604		.125	818 218	1018 618			832 232	1032 632			847 247	1047 647		
1.000	CAD PHOS	805 205	1005 605		.250	819 219	1019 619			833 233	1033 633			848 248	1048 648		
1.250	CAD PHOS	807 207	1007 607	.100	.500	821 221	1021 621		.375	835 235	1035 635		.250	850 250	1050 650		
1.500	CAD PHOS	808 208	1008 608	.350	.750	822 222	1022 622	.208	.625	836 236	1036 636	.062	.500	851 251	1051 651		.375
1.750	CAD PHOS	809 209	1009 609	.600	1.000	823 223	1023 623	.458	.875	837 237	1037 637	.312	.750	852 252	1052 652	.161	.625
2.000	CAD PHOS	810 210	1010 610	.850	1.250	824 224	1024 624	.708	1.125	838 238	1038 638	.562	1.000	853 253	1053 653	.411	.875
2.250	CAD PHOS	811 211	1011 611	1.100	1.500	825 225	1025 625	.958	1.375	839 239	1039 639	.812	1.250	854 254	1054 654	.661	1.125
2.500	CAD PHOS	812 212	1012 612	1.350	1.750	826 226	1026 626	1.208	1.625	840 240	1040 640	1.062	1.500	855 255	1055 655	.911	1.375
2.750	CAD PHOS	813 213	1013 613	1.600	2.000	827 227	1027 627	1.458	1.875	841 241	1041 641	1.312	1.750	856 256	1056 656	1.161	1.625
3.000	CAD PHOS	814 214	1014 614	1.850	2.250	828 228	1028 628	1.708	2.125	842 242	1042 642	1.562	2.000	857 257	1057 657	1.411	1.875
3.250	CAD PHOS													858 258	1058 658	1.661	2.125
3.500	CAD PHOS										1044 644	2.062	2.500	859 259	1059 659	1.911	2.375
3.750	CAD PHOS													860 260	1060 660	2.161	2.625
4.000	CAD PHOS													861 261	1061 661	2.411	2.875

* SEE NOTE 6.

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P A	TITLE	MILITARY STANDARD
MC Other Cog: 82	BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MS35764
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES BARI3 thru BARI3.3	SHEET 4 OF 7

DD FORM 672-1 (COORDINATED) *PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

FED SUP CLASS 5306

TABLE IV - Continued

NOMINAL SIZE		.500			.5625			.625			.75		
THREADS PER INCH		13	20		12	16		11	18		10	16	
D BODY DIAMETER	MAX	.500			.5625			.625			.750		
	MIN	.493			.5545			.617			.743		
F ACROSS FLATS	MAX	.750			.812			.875			1.000		
	MIN	.736			.798			.860			.963		
C ACROSS CORNERS	MAX	.866			.936			1.010			1.155		
	MIN	.840			.910			.980			1.121		
H HEAD HEIGHT	MAX	.327			.390			.390			.456		
	MIN	.312			.375			.375			.439		
M THREAD LENGTH	REF	1.250			1.375			1.500			1.750		
N UNTHREADED* LENGTH - MAX		.192	.125		.208	.139		.227	.139		.250	.156	

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
.750	CAD	864	1064			882	1082										
	PHOS	264	664			282	682										
.875	CAD	865	1065			883	1083										
	PHOS	265	665			283	683										
1.000	CAD	866	1066			884	1084			900	1100				1116		
	PHOS	266	666			284	684			300	700				716		
1.250	CAD	868	1068			886	1086			902	1102			918	1118		
	PHOS	268	668			286	686			302	702			318	718		
1.500	CAD	869	1069		.250	887	1087			903	1103			919	1119		
	PHOS	269	669			287	687			303	703			319	719		
1.750	CAD	870	1070	.019	.500	888	1088		.375	904	1104		.250	920	1120		
	PHOS	270	670			288	688			304	704			320	720		
2.000	CAD	871	1071	.269	.750	889	1089		.625	905	1105		.500	921	1121		.250
	PHOS	271	671			289	689			305	705			321	721		
2.250	CAD	872	1072	.519	1.000	890	1090	.125	.875	906	1106		.750	922	1122		.500
	PHOS	272	672			290	690			306	706			322	722		
2.500	CAD	873	1073	.769	1.250	891	1091	.375	1.125	907	1107	.227	1.000	923	1123		.750
	PHOS	273	673			291	691			307	707			323	723		
2.750	CAD	874	1074	1.019	1.500	892	1092	.625	1.375	908	1108	.477	1.250	924	1124	.200	1.000
	PHOS	274	674			292	692			308	708			324	724		
3.000	CAD	875	1075	1.269	1.750	893	1093	.875	1.625	909	1109	.727	1.500	925	1125	.450	1.250
	PHOS	275	675			293	693			309	709			325	725		
3.250	CAD	876	1076	1.519	2.000	894	1094	1.125	1.875	910	1110	.977	1.750	926	1126	.700	1.500
	PHOS	276	676			294	694			310	710			326	726		
3.500	CAD	877	1077	1.769	2.250	895	1095	1.375	2.125	911	1111	1.227	2.000	927	1127	.950	1.750
	PHOS	277	677			295	695			311	711			327	727		
3.750	CAD	878	1078	2.019	2.500	896	1096	1.625	2.375	912	1112	1.447	2.250	928	1128	1.200	2.000
	PHOS	278	678			296	696			312	712			328	728		
4.000	CAD	879	1079	2.269	2.750	897	1097	1.875	2.625	913	1113	1.727	2.500	929	1129	1.450	2.250
	PHOS	279	679			297	697			313	713			329	729		
4.500	CAD									914	1114	2.227	3.000	930	1130	1.950	2.750
	PHOS									314	714			330	730		

* SEE NOTE 6.

REVIEWER: AT, AV, MU, CL, IS, NSA
USER: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 15 MAY 1973 (E) FOR CHANGES SEE SHEET 1

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P A b Other Cust 82	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS35764
PROCUREMENT SPECIFICATION MIL-B-45913	SUPERSEDES BARX3 thru BARX3.3	SHEET 5 OF 7

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

FED SUP CLASS 5306

TABLE IV - DIMENSIONS

NOMINAL SIZE													
THREADS PER INCH													
F BODY DIAMETER	MAX	.573			1.000				1.250				
	MIN	.866			.990				1.234				
F ACROSS FLATS	MAX				1.462								
	MIN				1.298								
G ACROSS CORNERS	MAX	1.299			1.516				1.949				
	MIN	1.261			1.473				1.896				
H HEAD HEIGHT	MAX	.520			.582				.697				
	MIN	.5			.562				.677				
M THREAD LENGTH	REF	2.000			2.250				2.750				
N UNTHREADED LENGTH*	MAX	.276	.179		.312	.205			.357	.206			

L LENGTH	FINISH	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX	DASH NO.		BODY LGT MIN	GRIP LGT MAX
1.250	CAD PHOS		1133 733				1146 746						
1.500	CAD PHOS	934 334	1134 734								1177 777		
1.750	CAD PHOS	935 335	1135 735			950 350	1150 750						
2.000	CAD PHOS	936 336	1136 736			951 351	1151 751			979 379	1179 779		
2.250	CAD PHOS	937 337	1137 737			952 352	1152 752			980 380	1180 780		
2.500	CAD PHOS	938 338	1138 738		.500	953 353	1153 753			981 381	1181 781		
2.750	CAD PHOS	939 339	1139 739		.750	954 354	1154 754		.500	982 382	1182 782		
3.000	CAD PHOS	940 340	1140 740	.167	1.000	955 355	1155 755		.750	983 383	1183 783		
3.250	CAD PHOS	941 341	1141 741	.417	1.250	956 356	1156 756	.125	1.000	984 384	1184 784		.500
3.500	CAD PHOS	942 342	1142 742	.667	1.500	957 357	1157 757	.375	1.250	985 385	1185 785		.750
3.750	CAD PHOS	943 343	1143 743	.917	1.750	958 358	1158 758	.625	1.500	986 386	1186 786	.071	1.000
4.000	CAD PHOS	944 344	1144 744	1.167	2.000	959 359	1159 759	.875	1.750	987 387	1187 787	.321	1.250
4.500	CAD PHOS	945 345	1145 745	1.667	2.500	960 360	1160 760	1.375	2.250	988 388	1188 788	.821	1.750
5.000	CAD PHOS	946 346	1146 746	2.167	3.000	961 361	1161 761	1.875	2.750	989 389	1189 789	1.321	2.250

* SEE NOTE 6.

REVIEWER: AT, AV, MU, GL, IS, NSA
USERS: EL, ME, EA, PA, WV, OS, MC, SH

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 15 MAY 1973 (D) AUG 1979 (E) FOR CHANGES SEE SHEET 1

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

PA bc Other Cust F2	TITLE: BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS35764
PROCUREMENT SPECIFICATION MIL-B-45912	SUPERSEDES BAR13 thru BAR13.3	SHEET 6 OF 7

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5306

TABLE V - INTERCHANGEABILITY TABLE

Cadmium or zinc plated bolts covered by the dash numbers given in the original issue of this standard are canceled after 13 September 19[illegible]. The canceled bolts should be used for maintenance purposes until existing stocks are depleted. Replacement shall be in accordance with this table. The new dash numbers given in this table have been inactivated (see TABLE IV). Use only the dash numbers in Table I for new design and engineering.

DASH NUMBERS									
CANCELLED MS35764	NEW MS35764	CANCELLED MS35764	NEW MS35764	CANCELLED MS35764	NEW MS35764	CANCELLED MS35764	NEW MS35764	CANCELLED MS35764	NEW MS35764
3	603	77	877	152	952	452	1052	527	1127
4	604	78	878	153	953	453	1053	528	1128
[illegible]	[illegible]	[illegible]	[illegible]	154	954	454	1054	529	1129
[illegible]	[illegible]	[illegible]	[illegible]	155	955	455	1055	530	1130
[illegible]	[illegible]	[illegible]	[illegible]	156	956	456	1056	531	1131
6	606	84	884	157	957	457	1057	532	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	158	958	458	1058	533	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	159	959	459	1059	534	[illegible]
[illegible]	[illegible]	86	886	160	960	460	1060	535	[illegible]
13	613	89	889	161	961	461	1061	534	1134
14	614	90	890	170	970	464	1064	535	1135
15	615	91	891	171	971	465	1065	536	1136
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	466	1066	537	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	468	1068	538	[illegible]
[illegible]	[illegible]	94	894	[illegible]	[illegible]	469	1069	540	[illegible]
[illegible]	623	95	895	174	974	470	1070	540	[illegible]
[illegible]	623	96	896	175	975	471	1071	541	[illegible]
[illegible]	[illegible]	97	897	176	976	472	1072	542	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	473	1073	543	[illegible]
30	630	102	902	[illegible]	[illegible]	474	1074	544	[illegible]
[illegible]	[illegible]	103	903	1[illegible]	[illegible]	475	1075	545	[illegible]
[illegible]	626	104	904	403	1003	476	1076	546	[illegible]
31	631	105	905	404	1004	477	1077	547	[illegible]
32	632	106	906	405	1005	478	1078	550	[illegible]
33	633	107	907	407	1007	479	1079	551	[illegible]
34	634	108	908	408	1008	482	1082	552	[illegible]
35	635	109	909	409	1009	483	1083	553	[illegible]
36	636	110	910	410	1010	484	1084	554	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	411	1011	486	1086	555	[illegible]
38	638	112	912	412	1012	487	1087	556	[illegible]
40	640	113	913	413	1013	488	1088	557	[illegible]
41	641	114	914	414	1014	489	1089	558	[illegible]
42	642	115	915	417	1017	490	1090	559	[illegible]
43	643	118	918	418	1018	491	1091	560	[illegible]
44	644	119	919	419	1019	492	1092	562	[illegible]
46	646	121	921	421	1021	493	1093	563	[illegible]
50	650	122	922	422	1022	494	1094	564	[illegible]
51	651	123	923	423	1023	495	1095	565	[illegible]
52	652	124	924	424	1024	496	1096	566	[illegible]
53	653	125	925	425	1025	497	1097	567	[illegible]
54	654	126	926	426	1026	500	1100	568	[illegible]
55	655	127	927	427	1027	502	1102	569	[illegible]
56	656	128	928	428	1028	503	1103	570	[illegible]
57	657	129	929	431	1031	504	1104	571	[illegible]
58	658	130	930	432	1032	505	1105	572	[illegible]
59	659	134	934	433	1033	506	1106	573	[illegible]
60	660	135	935	435	1035	507	1107	574	[illegible]
61	661	136	936	436	1036	508	1108	575	[illegible]
64	664	137	937	437	1037	509	1109	576	[illegible]
65	665	138	938	438	1038	510	1110	577	[illegible]
66	666	139	939	439	1039	511	1111	578	[illegible]
67	667	140	940	440	1040	512	1112	579	[illegible]
68	668	141	941	441	1041	513	1113	580	[illegible]
70	670	142	942	442	1042	514	1114	[illegible]	[illegible]
71	671	143	943	444	1044	516	1116	[illegible]	[illegible]
72	672	144	944	446	1046	518	1118	[illegible]	[illegible]
73	673	145	945	447	1047	519	1119	[illegible]	[illegible]
74	674	146	946	448	1048	520	1120	[illegible]	[illegible]
75	675	150	950	450	1050	521	1121	[illegible]	[illegible]
76	676	151	951	451	1051	522	1122	[illegible]	[illegible]

MAINTAINED BY: AT, AV, MD, GL, IS, NSA
USAR: EL, ME, EA, PA, WV, OS, MC, SH

Military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 16 AUG 1956 REVISED (A) 13 SEP 1966 (B) 19 JUN 1967 (C) 8 AUG 1969 (D) 17 MAY 1973 (E) FOR CHANGES SEE SHEET 1

P.A. NC Other Coop [illegible]	TITLE BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL, GRADE 8, UNC-2A AND UNF-2A	MILITARY STANDARD MS35764
PROCUREMENT SPECIFICATION MIL-B-45913	SUPERSEDES BARX3 thru BARX[illegible]	SHEET [illegible] OF [illegible]

DD FORM 672-1 (Continued) PREVIOUS EDITION OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.